2180

MICROFILMED
JAN 1 1965



Distances from Side Stakes for Cross-Sectioning

Slope 1 to 1. Roadway of Any Width

	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	
0	0.00	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	0
1	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.70	1.80	1.90	1
2	2.00	2.10	2.20	2.30	2.40	2.50	2.60	2.70	2.80	2.90	2
3	3.00	3.10	3.20	3.30	3.40	3.50	3.60	3.70	3.80	3.90	3
4	4.00	4.10	4.20	4.30	4.40	4.50	4.60	4.70	4.80	4.90	4
5	5.00	5.10	5.20	5.30	5.40	5.50	5.60	5.70	5.80	5.90	5
6	6.00	6.10	6.20	6.30	6.40	6.50	6.60	6.70	6.80	6.90	6
7	7.00	7.10	7.20	7.30	7.40	7.50	7.60	7.70	7.80	7.90	7
8	8.00	8.10	8.20	8.30	8.40	8.50	8.60	8.70	8.80	8.90	8
9	9.00	9.10	9.20	9.30	9.40	9.50	9.60	9.70	9.80	9.90	9
10	10.00	10.10	10.20	10.30	10.40	10.50	10.60	10.70	10.80	10.90	10
11	11.00	11.10	11.20	11.30	11.40	11.50	11.60	11.70	11.80	11.90	11
12	12.00	12.10	12.20	12.30	12.40	12.50	12.60	12.70	12.80	12.90	12
13	13.00	13.10	13.20	13.30	13.40	13.50	13.60	13.70	13.80	13.90	13
14	14.00	14.10	14.20	14.30	14.40	14.50	14.60	14.70	14.80	14.90	14
15	15.00	15.10	15.20	15.30	15.40	15.50	15.60	15.70	15.80	15.90	15
16	16.00	16.10	16.20	16.30	16.40	16.50	16.60	16.70	16.80	16.90	16
17	17.00	17.10	17.20	17.30	17.40	17.50	17.60	17.70	17.80	17.90	17
18	18.00	18.10	18.20	18.30	18.40	18.50	18.60	18.70	18.80	18.90	18
19	19.00	19.10	19.20	19.30	19.40	19.50	19.60	19.70	19.80	19.90	19
20	20.00	20.10	20.20	20.30	20.40	20.50	20.60	20.70	20.80	20.90	20
21	21.00	21.10	21.20	21.30	21.40	21.50	21.60	21.70	21.80	21.90	21
22	22.00	22.10	22.20	22.30	22.40	22.50	22.60	22.70	22.80	22.90	22
23	23.00	23.10	23.20	23.30	23.40	23.50	23.60	23.70	23.80	23.90	23
24	24.00	24.10	24.20	24.30	24.40	24.50	24.60	24.70	24.80	24.90	24
25	25.00	25.10	25.20	25.30	25.40	25.50	25.60	25.70	25.80	25.90	25
26	26.00	26.10	26.20	26.30	26.40	26.50	26.60	26.70	26.80	26.90	26
27	27.00	27.10	27.20	27.30	27.40	27.50	27.60	27.70	27.80	27.90	27
28	28.00	28.10	28.20	28.30	28.40	28.50	28.60	28.70	28.80	28.90	28
29	29.00	29.10	29.20	29.30	29.40	29.50	29.60	29.70	29.80	29.90	29
30	30.00	30.10	30.20	30.30	30.40	30.50	30.60	30.70	30.80	30.90	30
31	31.00	31.10	31.20	31.30	31.40	31.50	31.60	31.70	31.80	31.90	31
32	32.00	32.10	32.20	32.30	32.40	32.50	32.60	32.70	32.80	32.90	32
33	33.00	33.10	33.20	33.30	33.40	33.50	33.60	33.70	33.80	33.90	33
34	34.00	34.10	34.20	34.30	34.40	34.50	34.60	34.70	34.80	34.90	34
35	35.00	35.10	35.20	35.30	35.40	35.50	35.60	35.70	35.80	35.90	35
36	36.00	36.10	36.20	36.30	36.40	36.50	36.60	36.70	36.80	36.90	36
37	37.00	37.10	37.20	37.30	37.40	37.50	37.60	37.70	37.80	37.90	37
38	38.00	38.10	38.20	38.30	38.40	38.50	38.60	38.70	38.80	38.90	38
39	39.00	39.10	39.20	39.30	39.40	39.50	39.60	39.70	39.80	39.90	39
40	40.00	40.10	40.20	40.30	40.40	40.50	40.60	40.70	40.80	40.90	40
41	41.00	41.10	41.20	41.30	41.40	41.50	41.60	41.70	41.80	41.90	41
42	42.00	42.10	42.20	42.30	42.40	42.50	42.60	42.70	42.80	42.90	42
43	43.00	43.10	43.20	43.30	43.40	43.50	43.60	43.70	43.80	43.90	43
44	44.00	44.10	44.20	44.30	44.40	44.50	44.60	44.70	44.80	44.90	44
45	45.00	45.10	45.20	45.30	45.40	45.50	45.60	45.70	45.80	45.90	45
46	46.00	46.10	46.20	46.30	46.40	46.50	46.60	46.70	46.80	46.90	46
47	47.00	47.10	47.20	47.30	47.40	47.50	47.60	47.70	47.80	47.90	47
48	48.00	48.10	48.20	48.30	48.40	48.50	48.60	48.70	48.80	48.90	48
49	49.00	49.10	49.20	49.30	49.40	49.50	49.60	49.70	49.80	49.90	49
50	50.00	50.10	50.20	50.30	50.40	50.50	50.60	50.70	50.80	50.90	50

Distance of slope stake from side or shoulder stake for any width roadway, slope 1 to 1. If ground is nearly level, the cut or fill at side stake is located by the double entry method in left column and top row. The number in body of table in same row and column gives distance from side stake to slope stake. If ground is not level estimate the difference in elevation between the side stake and slope stake, lower target by this amount if cut, elevate if fill. Add this amount to cut or fill and find distance in table. Set up rod at this point, and line of sight should cut target. If it does not make the slight adjustment necessary.

TABLE XIII—CORRECTIONS FOR TANGENTS AND EXTERNALS

These corrections are to be added to the approximate values, found by dividing the tangent, or external, for a 1° curve (Table VIII) by the degree of curve, in order to obtain the true tangents, or externals. Intermediate values may be obtained by interpolation.

FOR TANGENTS ADD

Central Angle	DEGREE OF CURVE													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	03	.06	09	13	16	19	.22	.25	.28	.31	34	38	42	.46
15°	04	10	14	19	24	.29	.34	.39	45	.51	.53	58	.63	.68
20°	06	.13	19	26	.32	.39	.45	.51	.58	.65	.72	79	.84	.90
25°	.08	16	24	.33	40	49	.58	67	.75	.83	90	.99	1.06	1.14
30°	10	19	.29	39	49	.59	.69	79	.89	.99	1.09	1.20	1.29	1.39
35°	11	22	.34	47	.58	.69	.70	.81	.92	1.04	1.29	1.42	1.54	1.66
40°	13	.26	.40	.53	.67	.80	.93	1.06	1.20	1.34	1.49	1.64	1.79	1.94
45°	15	.30	44	60	76	91	1.06	1.21	1.37	1.52	1.70	1.87	2.04	2.21
50°	17	.34	.51	.68	.85	1.02	1.19	1.36	1.54	1.72	1.91	2.10	2.29	2.48
55°	19	.38	.57	76	.95	1.14	1.32	1.52	1.72	1.92	2.14	2.35	2.56	2.77
60°	.21	42	.63	.84	1.05	1.27	1.49	1.71	1.94	2.17	2.38	2.60	2.83	3.07
65°	23	46	.69	.93	1.16	1 40	1.64	1.88	2.13	2.38	2.63	2.88	3.13	3.39
70°	.25	.51	76	1.02	1.28	1.54	1.80	2.06	2.33	2.60	2.88	3.16	3.44	3.72
75°	.27	.56	.83	1.12	1.40	1.69	1.98	2.27	2.57	2.87	3.16	3.47	3.78	4.09
80°	30	.61	.91	1.22	1.53	1.84	2.15	2.46	2 78	3.10	3.44	3.78	4.12	4.46
85°	33	66	1.00	1.33	1.68	2.02	2.36	2 70	3.05	3.40	3.77	4.14	4.55	4 89
90°	36	.72	1.09	1.45	1.83	2.20	2.57	2.94	3.32	3.70	4.10	4.50	4.91	5.32
95°	39	79	1.19	1.55	2.00	2.40	2.80	3.20	3.61	4.02	4.40	4.98	5.38	5.83
100°	43	.86	1.30	1.74	2.18	2.62	3.06	3.50	3.95	4.40	4.88	5.37	5.85	6.34
110°	51	1.03	1.56	2.08	2.61	3.14	3.67	4.21	4 76	5.31	5 86	6.43	7 01	7 60
120°	62	1.25	1 93	2.52	3.16	3.81	4 45	5.11	5.77	6 44	7 12	7.80	8.50	9 22

FOR EXTERNALS ADD

Central Angle	DEGREE OF CURVE													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	.001	.003	.004	.006	.007	.008	.009	.011	.012	.014	.015	.017	.018	.020
15°	.003	.007	.010	.014	.018	.023	.027	.029	.032	.035	.039	.043	.047	.051
20°	.006	.011	.017	.022	.028	.034	.038	.045	.051	.057	.063	.070	.076	.083
25°	.009	.018	.027	036	.046	.056	.065	.074	.083	.093	.106	120	127	135
30°	.013	.025	.038	.051	.065	.078	.090	.103	.116	.129	.149	.170	179	.188
35°	.018	.035	.054	.072	.086	.109	.131	.153	.175	.197	.213	.230	.247	.264
40°	.023	.046	.070	.093	.117	.141	.172	.203	.234	.265	.277	.290	.315	.341
45°	.030	.060	.093	.119	.153	.184	.216	.254	.289	.325	.351	.378	.411	.445
50°	.037	.075	.116	.151	.189	.227	.266	.305	.345	.384	.425	.467	.508	.550
55°	.046	.093	.142	.188	.236	.283	.332	.381	.420	.479	.530	.582	.641	.700
60°	.056	.112	.168	.225	.283	.340	.398	.457	.516	.575	.636	.697	.774	.851
65°	.067	.135	.204	.273	.343	.412	.483	.554	.625	.697	.711	.845	.922	1.01
70°	.080	.159	.240	.321	.403	.485	.568	.652	.735	.819	.906	.994	1.08	1.17
75°	.095	.182	.286	.383	.480	.578	.678	.777	.877	.977	1.07	1.18	1.29	1.39
80°	.110	.220	.332	.445	.558	.671	.787	.903	1.02	1.13	1.25	1.38	1.50	1.62
85°	.128	.259	.391	.524	.657	.790	.926	1.06	1.20	1.34	1.47	1.62	1.76	1.91
90°	.149	.299	.450	.603	.756	.910	1.07	1.22	1.38	1.54	1.70	1.87	2.03	2.20
95°	.174	.350	.522	.706	.985	1.06	1.25	1.43	1.62	1.80	1.99	2.18	2.38	2.58
100°	.200	.401	.604	.809	1.01	1.22	1.43	1.64	1.85	2.06	2.28	2.50	2.73	2.96
110°	.268	.536	.806	1.08	1.35	1.63	1.91	2.20	2.48	2.76	3.05	3.35	3.66	3.96
120°	.360	.721	1.08	1.45	1.82	2.19	2.57	2.95	3.33	3.72	4.11	4.50	4.91	5.32

Bay Park Village

notes on Drain - Lister & Frankfort Sts — Pgs 1-4

Alley - Drain Milton & Frankfort to Lister & Galveston — 5-10

X-Sec. Alley Blk 87 " " " — 12-14

Bay Park Village Drain Milton St & Illion St — 15-25

Drain survey - Lot P. Mt View Manor — 26.

"P" Line - "ELECTRIC" - Rosemont to Westbourne — 28

Alley Blk J, Balboa Vista — 43

" " I " — 48

Proposed Storm Drain
Frankfort St.
Milton to Orten

Dec. 7-51
R. Sisson
Garber
Roret
Fritz
W.O. # 20897



Levels Proposed Storm Drain
Frankfort St. Milton to Orton.

				57.59
BM	2+55	57.59 ✓	55.04	o+22 Hub 2067-69 2274.54
0+70		8.5	49.1	
+06		9.4	48.2	
+17		6.6	51.1	
+30		6.2	51.4	
+44.67	△ 50°00 Lt.	7.0	50.6	
+50		6.5	51.1	
+55	2.9 Rt of ℄ = End Cb	6.45	51.14	
+56	1.0 Lt of ℄ = △ Power Pole		#4299	
+89.55 = BC Rt		5.5	52.1	
1+01	1.0 Rt of ℄ = ℄ Power Pole		#2998	
+02.5	Top Curb	5.16	52.43	
"	Gutter	5.77	51.82	
+09.18 = Mid. Point		5.58	52.01	
+28.82 = EC		5.39	52.20	
+50		5.19	52.40	
2+0		4.75	52.84	
"	7' Rt = Gut	5.07	52.52	
"	7' Rt = Cb	4.44	53.15	
2+50		4.86	53.23	
3+0		3.92	53.67	
"	7' Rt = Gutter	4.22	53.37	
"	7' Rt = Curb	3.60	53.99	
+50		3.39	54.20	
4+0		2.99	54.60	
"	7' Rt = Gut	3.24	54.35	
"	7' Rt = Cb.	2.64	54.95	
+50		2.54	55.05	
TP	6.36	61.40 ✓	2.55	55.04 ✓ N.Y.C.R.R. Frankfort & Napier 55.13
+74.23			6.14	55.26
5+0			6.12	55.28
+27			6.17	55.23
"	7' Rt = Gutter		6.48	54.92
"	7' Rt = Curb EC		5.93	55.47
+50			6.10	55.30
6+0			5.93	55.47
"	7' Rt = Gut.		6.28	55.12
"	7' Rt		5.65	55.75

61.40

6+50		5.71	55.69
7+00		5.57	55.83
"	7' Rt = Gutter	5.88	55.52
"	7' Rt = Curb	5.28	56.12
+50		5.46	55.94
8+00		5.18	56.22
"	7' Rt = Gutter in Drive	5.50	55.90
+50		4.95	56.45
+74		4.84	56.56
"	7' Rt = Gutter ∠ 14.5 Conc Drive	5.12	56.28
9+0468 = ℄		4.71	56.69
"	7' Rt = Gutter	5.08	56.32
"	7' Rt = Cb	4.42	56.98
+34		4.58	56.82
"	7' Rt = Gutter = ℄ 9' Conc Dr	4.84	56.56
9+55		4.52	56.88
"	7' Rt = Gutter = ℄ 10.5 Conc Dr.	4.87	56.53
BM		4.45	56.95

BP 7" Cb
Frankfort
1 1/2 Br. Cap
57.06

Reduced By CRL 12-11-51

Proposed Storm Drain Laterals
Morena Blvd. to Chicago St.

W.O. 20897 Dec. 10-51 4
H.S. Isson
Garber
Roger
Fritz

BM	8.19	15.71 ✓	7.52	o/ Hub 1+59.10 Lt. 2067-62
0+0	= 1+07.46 "H"		5.78	9.93 o/ Hub
+05			6.3	9.41
+12			9.0	6.7
+24			9.4	6.3
+32			6.2	9.5
+39.6	= P/L P.C.		6.13	9.58
+49.6			5.86	9.85
+59.2	= P/L P.C.		6.11	9.60
1+0			5.7	10.0
+50			4.9	10.8
2+0			3.9	11.8
+50			2.1	13.6
TP	7.71	22.27 ✓	1.18	14.53 ✓
3+0			1.3	16.0
+21.65	Δ 90°00' Lt.		5.2	17.1
+26			1.3	16.0
+40			5.6	16.7
+54.65			5.8	16.5

Reduced By CRL 12-11-51



Proposed Storm Drain
From Frankfort + Milton
To Lister + Galveston

Sommermeyer
B.C.T.9
R. Sissen
W. Ottman

~~Bay Park Village~~
Alley Blk 87
W.O. 20897
1-3-52

FB 2067-P58-70
FB 2180-P-1

Milton to Lister
Bet. Frankfort & Galveston.

INDEXED
JAN 4 1952

□ denotes Fd. ½ hub
□ denotes set ½ + disk

= End.
4+36.70



2+74.40 = Δ 24° 40' 30" Lt.

2+45.85 = ½ P.O.T.

1+73.00 = ½ P.O.T.

Δ 42° 49' Rt. off back line as shown →

0+00 = 54° Lt. of 23+94 ℄ FB 2067 / 60

For this portion
See FB. 2067-58



Fd. P.O.T. 22+40.54

Station				
0+60				
0+40				
0+16				
0+03				
0+00	4' Lt. = ℄ 24" corr. iron culvert			

W = in wash
B = Top of main bank

T.P.	6.39	65.41 ✓	1.87	59.02 ✓
B.M. #1			8.43	52.46 ✓
	5.85	60.89 ✓	—	55.04

B.L.

0+60: 58.8 / 6.6 / 10 — 58.5 / 6.9 / B — 56.4 / 9.0 / 2 w — 57.2 / 8.2 / 19 w — 59.4 / 6.0 / 23 B

0+40: 58.4 / 7.0 / 10 — 58.1 / 7.3 — 58.2 / 7.2 / 6 B — 56.7 / 8.7 / .7 w — 56.1 / 9.3 / 20 w — 59.0 / 6.4 / 23 B

0+16: 58.3 / 7.1 / 25 — 56.9 / 8.5 / 10 B — 55.7 / 9.7 / 2 w — 54.7 / 10.7 / Gnd. w — 52.7 / 12.7 / I.E. pipe ℄ — 56.1 / 9.3 / 2 w — 56.7 / 8.7 / 10 B — 59.0 / 6.4 / 25

0+03: 57.4 / 8.0 / 25 — 56.1 / 9.3 / 10 w — 55.6 / 9.8 / w — 56.7 / 8.7 / 10 w — 57.8 / 7.6 / 20

0+00: 55.7 / 9.7 / 10 B. — 50.7 / 14.7 / 9 w — 52.0 / 13.4 / 4 I.E. — 52.27 / 13.14 / w — 52.7 / 12.7 / 1 w — 54.9 / 10.5 / 2 B — 56.4 / 9.0 / 14

65.41

Also = 23+94.65 F.B. 2067 p 60
½ - 54.90 south of 0+00 (see sketch) -

Set B.M. = S.W. B.P. Milton + Frankfort.

B.M. = ½ P.O.T. sta 22+40.54 FB 2067 - p 69

4

2+00					
	62.5	57.0	57.0	62.5	
	6.2	11.7	11.7	6.2	
	10	8	W	A	
	B	W		B	
1+95					
	62.5	56.9	57.1	61.7	62.1
	6.2	11.8	11.6	7.0	6.0
	13	11	3	B	10
	B.	W	W		
T.P.	7.79	68.74 ✓	4.46	60.95 ✓	T.P. 2/2 1+73.00
1+35					
	61.1	60.8	56.8	56.6	59.6	60.1	60.6
	4.3	4.6	8.6	8.8	5.8	5.3	4.8
	40	29	28	15	14		10
		B	W	W	B		
0+90							
	59.8	56.2	56.2	59.0	59.4		
	5.6	9.2	9.2	6.4	6.0		
	15	12	2	B	5		
	B	W	W				
0+88							
	59.7	56.2	56.4	58.9			
	5.7	9.2	9.0	6.5			
	13	10	W	2			
	B.	W		B			
0+61							
	58.6	56.4	57.2	57.4			
	6.8	9.0	8.2	6.0			
	1	W	19	23			
	B		W	B.			

65.41 ✓

2+52

2+51

2+40

2+20

2+11

2+05 = Aprox. wly line Galveston

64.0 63.6 57.3 57.5 63.4
4.7 5.1 11.4 11.2 5.3
10 1 W 12 16
B W B

63.6 57.3 57.4 63.4
5.1 11.4 11.3 5.3
B 1 13 17
W W B

63.9 63.3 63.0 57.5 57.1 63.7
4.8 5.4 5.7 11.2 11.6 5.0
10 12 13 22 29
B W W B

63.1 63.3 60.7 57.7 57.2 64.1
5.0 5.4 8.0 11.0 11.5 4.6
10 B 5 7 16 18
W W B

57.6
11.1
W

62.9 57.2 57.0 54.8 62.5
5.8 11.5 11.7 11.8 6.2
7 5 W 5 8
B; W W B

68.74

3+45

65.0 59.7 58.0 64.3 65.3 65.5
3.7 9.0 10.7 4.4 3.4 3.2
26 24 9 5 15
B W W B

3+40

65.0 59.7 57.4 58.3 65.1
3.7 9.0 10.8 10.4 3.6
26 24 15 W 7
B W W B

3+37

65.0 64.7 59.1 58.3 58.5 65.0
3.7 4.1 9.0 10.4 10.2 3.7
30 28 23 W 4 9
B W W

3+35

64.9 63.9 58.0 58.0 58.1 59.7 64.3
3.8 4.8 10.7 10.7 10.6 9.0 2.4
30 6 4 W 5 7 35
B W W B1

3+15

63.8 62.7 57.9 57.8 57.7 64.0
4.9 6.0 10.8 10.8 11.0 3.9
20 6 3 4 9
B W W B

Section on split of Δ
2+74 40 = Δ 24°-40'-30" Lt.

64.1 62.5 57.4 57.45 57.2 62.6
4.6 6.2 11.3 11.29 11.5 5.1
20 9 6 Hub 5 8
B W W B

68.74

	Check		5.32	55.04 ✓ 55.04	Orig. B.M. – P.C
	Check		7.90	52.46 ✓	B.M. #1 – Page 6
	T.P.	1.33	60.36 ✓	6.40 59.03 ✓	
3	T.P.	4.48	65.43 ✓	7.79 60.95 ✓	
	4+73 =	also = Aprox. ℄ ditch from N.E. intersect fence. = Aprox		Lister Nly. line	
3					
	4+50				
3					
	4+47				
3	4+36.70		3.97 Hub	64.77 ✓	
3	4+25				
2	3+95				

Reduced By CRL 1-8-52

℄

67.7 | 60.2 | 60.2 | 61.2 | 66.9
1.0 C B | 8.5 4 W | 8.5 W | 7.5 9 W | 1.8 13 B

60.0
8.7 W
65.2
3.5 B

63.8 | 58.4 | 54.3 | 64.3 | 65.0 | 67.1
4.9 18 B | 9.3 16 W | 9.4 7 W | 4.4 6 B | 3.7 Ord. | 1.6 15

64.1 | 63.1 | 60.9 | 59.3 | 64.1 | 64.7 | 66.7
9.6 35 | 4.8 30 B | 7.8 28 W | 9.4 11 W | 4.6 10 B | 4.0 | 2.0 15

66.7 | 66.7 | 61.6 | 58.7 | 58.6 | 66.8 | 67.1
2.0 25 | 2.0 23 B | 7.1 19 W | 10.0 | 10.1 7 W | 1.9 9 B | 1.6 15

68.74 ✓

Channel Cross Section

Sec FB 2067 / 69 + 2180 / 5 — 1-17-52 C.H.S.

21+10 See below

7.61 | 60.07 | — 52.46

= 0 − 54.90 P-5 this book,
21+40.54 FB 2067. P69

Sta 21+10 (See F.B. 2067 P.69)

B.L. 11

56.1 | 56.0 | 52.6
4.0 | 4.1 | 7.5
50 | 45 | 43

51.2 | 51.4 | 55.3 | 55.3
8.9 | 8.7 | 4.8 | 4.8
38 | 30 | 28 | 25

60.07

S.E. B.P. Milton + Frankfort (Page 6)



Cross Sec. for grade Est.

Alley Blk 87 Bay Park Village
~~Mitton to Lister~~
between Frankfort & Galveston

1-17-51

C.H.S.
B.99
R. Sissan
W. Oltman.

FB. 1502
48

0+00 = Nly line Milton St.

General drainage of block is to S.S.W.

INDEXED
JAN 2 1952

0-54.90 - P5



0+65

0+47

page 5
change profile of drain sec.
washed out Last night.
This was road over + thru. wash

0+43 . in wash

0+38

0+20

0+00 Nly. line Milton

0+00 =

5.89 64.91 ✓ — 59.02

4

57.8	58.8	56.7
7.1	6.1	6.2
10		10
53.4	55.4	53.6
11.5	9.5	11.3
10	~~No wash~~	10
in wash		in wash
52.9	55.2	53.2
12.0	11.7	11.7
10		10
53.0	55.8	56.6
11.9	9.1	9.0 8.3
10	3	10
in wash		
57.1	57.8	58.6
7.8	7.0	6.9
10		10
59.6	59.0	59.3
6.3	5.9	5.6
10		10

64.91 ✓

(= 0-54.90 - P. 5)
½ 5' Lt of 0-17

see orig x-sec. for Lister St.

3+50 = Approx. 51' line Lister

T.P.	10.47	85.87	0.15	75.40
3+00				
T.P	12.38	75.55	1.74	63.17
2+50				
2+00				
1+50				
1+00				

79.3	76.1	75.8	74.7	70.0
6.6	9.8	10.1	11.2	15.9
50	10	85.87 ✓	10	50

69.2	65.2	64.8	64.2	69.4
6.4	10.3	10.8	11.3	7.2
50	10		10	50

75.55 ✓

	62.2	62.2	62.2	
	2.7	2.7	2.7	
	10		10	

58.6	60.1	60.2	60.1	61.4
5.3	4.8	4.7	4.8	3.5
50	10		10	50

58.7	59.0	59.2	
6.2	5.9	5.7	
10		10	

57.3	58.4	58.8	58.8	59.1	
7.6	6.5	6.1	6.1	5.8	
50	10		10	45	

64.91 ✓

Bay Park Village Storm Drain

Milton - Frankfort to Illion St.

Illion Milton to Orten 1-17-52

WO 20897

□ = Fd ¾" hub & tack or disk

● = Fd. disk & tack

□ = set ¾" + disk

× = cut cross } in conc.

↓ = cut arrow }

cuts taken to near side of poles,

" " " " " " " trees

" " " Ctr. of deadman



INDEXED
law
APR 7 1952


Existing Conc. Ct.
R.R. Cross in ct.
El. = 159.08 (Page 25)
72.50
See p. 25 ✱ on ct. face
prop. disk. in drive
R.R. cross in ct.
1+22.9
Arrow on ct. face
"B" line
A.C. Pave
Illion St.
0+67
0+00
29° 55'
73.75'
97° 39' 30"
P.I.
10'
prop. Co't.
20'
8+06.35
3.5' x 7' conc. slab for Telephone booths
9+03.78 E.C.
Δ 90° 03' 30"
R 95'
T 95.09
L 149.93
Ext. 39.40
7+53.85
B.C.
Milton St.
206.1
Prop. Pipe & disk.
10'
12'
90°
Drive 13.6
28.4'
12.5'
Drive 14.4'
45°
Δ 45°
R = 91
T 37.69
L 71.47
11+05.07
10+80.7
10+30.2
10+60.75
P.I.
9+89.28

T.P.	13.21	83.56	0.15	70.35
1+47	10[5] Lt. = 2[5]'			
1+43	10[5] Lt. = 3'			Eucalyptus.
1+39	10[5] Lt. = 8[5]'			Diam.
1+25	8[5] Lt. = 3'			
1+17	10[5] Lt. = 2.6"			
1+09	7[5] Lt. = 4'			
1+00				
0+98	11[5] Lt. = 16" diam			
0+90	11[5] Lt. = 16" diam			Eucalyptus
0+85	7[5] Lt. = 2' diam.			
0+77	11' Lt. = 2' diam.			Eucalyptus
0+65	12' Lt. = 18" diam.			Eucalyptus
0+50	7[5] Lt. = 2' diam			Eucalyptus
	out taken to near side of trees			
0+21	- 12" Lt - 2' diam			Eucalyptus
0+00				
	11.48	70.50	—	59.02

65.6 66.4 66.7

4.9 4.1 3.8

15 15

62.9

7.6

56.9 59.3 59.5

11.6 11.2 11.0

15 70.50 15

B.M. = ½ - 3' Lt. 0+00 = 0-54.90 page 5

EL. = 59.02 page 6

4+40				
T.P.	13.35	122.25	0.51	108.90
4+00				
3+50				
T.P.	13.06	109.41	0.19	96.35
3+00				
T.P.	13.14	96.54	0.16	83.40
2+50				
2+00				
1+80 ± = ½ P.O.T.			8.84	74.72
1+50				

107.0
15.2
20

107.4
14.8
15

112.6
9.6
6

112.6
9.6
122.25

113.6
8.6
15

102.2
7.2
15

106.2
3.2

107.2
2.2
15

98.3
11.1
109.41

87.9
8.6
15

90.0
6.6
96.54

90.1
6.4
15

88.0
1.6

76.3
7.3
15

76.7
6.9

77.0
6.6
15

72.0
11.6
83.56

T.P.	12.58	159.17	0.66	146.59
6+50				
6+00				
T.P.	12.85	147.25	0.25	134.40
5+69.24	20' Ltr. N.E. Prop ½			Hartford Milton +
5+50				
T.P.	12.58	134.65	0.18	122.07
5+00				
4+75				

159.17

14.2
6.0
15

136.2 136.2 132.4 132.2 137.6
11.0 11.0 14.8 15.0 14.6
15 13 7 15

147.25

127.6 130.4 130.0 127.8 128.0 128.6
4.89 4.2 4.6 6.8 6.6 6.1
20 15 10 7 15
on Hub.

125.6 126.0 126.4
9.0 8.7 8.3
15 15

134.65

118.4 118.6 121.6 121.6 122.2
3.8 3.7 0.7 0.6 0.1
15 12 6 15

113.8 113.8 118.2 118.2 119.0
8.5 8.5 4.0 4.0 3.3
15 13 6 15

122.25

it is set at 90° to Illion St.
Conc. base for 2 telephone booths

8+66 - 3.5 RX. = 3.5 N.E. Cor. wide (N+S) × 7' long (E+W)

8+56 3.7 Lt. = Pole # 4599

G

39.40 Lt. = P.I. ½

8+28.81 = Mid curve

T.

5+ 7+91.33 ¼ curve

(Δ = 90°-03'-30" Rt.)

5 7+53.85 = B.C. 95' Rad. Curve

T

P.I. ½		4.40	157.28 ✓	
5 T.P.	8.82	161.68 ✓	—	152.86
7+25.84 = ½ P.O.T.		6.31	152.86 ✓	

4.

7+00

156.49
5.19
3.5
N.E. Cor.

157.28 157.3 157.2 156.9
4.40 4.4 4.5 4.8
39.40 15 15
P.I. ½

156.8 157.0 157.0
4.9 4.7 4.7
15 15

161.7 161.5 155.6 155.3 155.6
0.0 0.2 6.1 6.4 6.1
20 15 6 15

161.68 ✓

157.0
6.2

154.1 154.0 149.6 149.5 150.3
5.1 5.2 9.6 9.7 8.9
15 13 7 15

159.17 ✓

T.P. on B.C.	4.02	152.24 ✓	10.58	148.22 ✓
9+89.28 = ℄ = B.C. Lt.				
9+58				
9+45				
	3.30	158.80 ✓	—	155.50 ✓
9+03.78 = E.C.			6.18 Hub	155.50 ✓
8+74 3' Rt. = deadman				
8+73 9 3 Rt. = pole # 573952				
8+66.29 = 3/4 curve				

148.4 / 148.22 / 147.8
10.4 / 15 — 10.58 Hub — 11.0 / 15

148.8 / 148.8 / 148.0
10.0 / 15 — 10.0 — 10.8 / 15

154.1 / 154.7 / 154.9
4.7 / 15 — A.1 — 3.9 / 15

158.80 ✓

155.4 / 155.6 / 155.5
6.3 / 15 — 6.1 — 6.2 / 15

156.5 / 156.4 / 154.47 / 156.1
5.2 / 15 — 5.3 — 5.21 / 35 on Conc. — 5.6 / 15 Gnd.

161.68

				℄				
	147.37	145.50	144.60	144.26		144.20	144.38	144.63	144.99
	4,87	6.74	7.64	7.98	8.04		7.86	7.61	7.25
	100	65	40	20			30	60	100
Δ 45° Rt. of ℄ drain									
10+80 ℄ along line of Pave									
(Sec. at 90° to ℄) South									
wly edge pave produced from									
10+80 ℄ = cross wly line of general				144.42		144.20		143.85	
				7.82		8.04		8.39	
				15				15	
				144.28		142.74		142.94	
10+65 ℄ = E.C. Radial				7.96		8.50		9.30	
				15				15	
Irreg. curve Aprox. 40-Rad. d.									
along edge of A.C. Pave				144.08		142.59		140.69	
10+30 ℄ Not at 90° to ℄ but is				8.15		9.65		11.35	
				15				15	
						142.59			
10+30 ℄ start A.C. Pave.						9.65			
				144.1		144.1		143.2	
10+25				8.1		8.1		9.0	
				15				15	
				145.9		145.3		144.5	
10+00				6.3		6.9		7.7	
				15				15	
						152.24 ✓			

Illion (B line - P16)

See P. 24 for levels across

3.74 157.62

5.85 155.51 (155.59)

T.P. 10.32 1.61.36 1.20 151.04

Sec. along curb

11+05.1 = top of curb

64' Lt. = Δ in ch. (Δ to west)

Sec. in gutter

11+05.07 = X on Ch. face = end of line

Sec. Along Gutter edge

11+03.8 = wly. edge Conc. Gutter

Marked. El. 157.74

Fd Nail in pole #4599 (Swly Cor Milton + Illion)

Check B.C. 9+03.78

161.36

14+00	13+00	12+00	11+00	10+00	9+00	8+00	7+00	6+00	5+00
14.54	13.54	12.54	11.54	10.54	9.54	8.54	7.54	6.54	5.54
5.70	6.93	7.11	7.32	7.35	7.40	7.42	7.36	6.95	6.79
100	64	50	28	20		27	45	84	102
14.01	13.01	12.01	11.01	10.01	9.01	8.01	7.01	6.01	5.01
6.18	7.40	7.57	7.74	7.75	7.72	7.70	7.67	7.39	7.22
100	64	50	28	20		27	45	84	102
14.00	13.00	12.00	11.00	10.00	9.00	8.00	7.00	6.00	5.00
6.04	7.35	7.56	7.77	7.74	7.73	7.72	7.66	7.26	7.10
98±	62±	50	26±	18±		28±	46±	88±	103±

152.24

"B" line

Cont. P-25 — see sketch P-16

1+23	= top of curb				4.21		
122.9	= gutter at curb				4.69		
1+21.4	= edge conc. gutter				4.58		
0+90			156.4	156.5	4.9	156.6	4.8
			5.0				10
			10				
0+82 - 0.5' Lt.	= Cap over water valve						
0+67	2' Rt. = N.Wly. cor	A.C. Pave	156.7	156.0		156.02	155.82
			4.7	5.4		5.34	5.54
			10			2	10
						Edge Pave	on Pave
0+40	Rt. = Wly edge	existing A.C. Pave	156.6	156.0		154.61	
			4.8	5.4		6.75	
			10			15	
						E. Pave	
0+25			156.4	156.4		154.5	
			5.0	5.0		6.9	
			10			10	
= 0+00 = 9+03.78	See P.16			155.51	5.85		

161.36 From P-23

N. Ely. Return
Milton & Illion

INDEXED
Paid
JAN 22 1952



See P.16

166.25 R.P. Cross Mty. ob. 2.28 159.08

Set B.M.

T 161.3 C

Clark
Shephard
Bruner

W.O. 20766
9-29-52

DATA: FB 1194 f 64/70
DWG: 9162-B

SURVEY TO EXTEND DRAIN
LOT "P" MT. VIEW MANOR - WILSHIRE DR.

INDEXED
SEP Rec'd
1952

Sketch NOT to scale:

Notes; Pg 27



SURVEY - EXTEND DRAIN - LOT "P" WILSHIRE DR.
MT. VIEW MANOR

		Check: 5.60	385.53 = 385.54 = BP	N/W Wilshire & 35'th		
T.P.	11.19	391.13	0.51	379.94	Set Spike	IN Pole # P-5367 5' RT & Inlet
0+75						
0+50						
0+32		3.0 RT & Headman				
0+25						
0+09.06		END EXIST. Pipe				
0+00 = E/y Line Wilshire						
0-05 = Ch Face						
T.P.	0.10	380.45	10.80	380.35		
B.M.	5.61	391.15		385.54 = N/W B.P.	Wilshire & 35'th	

LT.								RT.
			26.5 / 10		25.0		23.0 / 10	
			16.1 / 10		15.5		14.0 / 10	
			8.6 / 10		7.5		6.5 / 10	
0.9 / 10	0.9 / 6	3.85 Ft. Line		1.6 / 3	1.5 / 10			
			0.64 Bk. Walk					
		0.79 TPCB	1.78 G.U.T.	2.71 Ft. Line Inlet				
			380.45					

INDEXED SEP 1952

Clark
Shepherd
Bruner
Presley
W.O. 27526
1-23-53

"P" LINE - ELECTRIC Ry to FAY AVE

Rosemont to Westbourne

Sketch NOT to SCALE.



DATA: Maps 1729
1808
1977
TP 17-36
18

R/S 2079
2907-L
2909-L
2021-L
6702-L
7610-L
7714-L
~~550-56~~
~~1639-58~~
~~820-B~~
~~823-B~~
~~4296~~
4354
4788-B
7211



"P" Line (cont.)

~~Not~~ to Scale:

Loc. of Bldgs to West of "P" Line:





"P" LINE (CONT.)

FAI
1120-56
1424-65
1501-30
1533-42
1424-68
1077-L TOPO
1809-L
1810-L
4788-B
1959-B
1977-B
7169-L
4809-B
1979-B
5736-L

FAI

RUSHVILLE

N'LY LINE

110'

FAI

80' M.R.M.L.

Fd 1/2" I.P.

33'

90°

7'

FAI

20

25+30.73 (CH. IN CURVE) = ∠ RT 6°26'30"

6°26'30" RT

∠ CH. IN CURVE 90°27'

33'

90°

Fd 1-85 AP

MUIRLANDS AVE.

NET FD.

See P. 57 Add'l Notes

Note: due to bldgs, trees etc, impossible to find N'LY LINE OF WESTBOURNE through

Fd. CON MON (T.P. 17-36)

Fd 1" I.P. ON S'LY LINE WESTBOURNE MAP 1729-3

90°14'37"

165.14'

6.10'

Fd 2" I.P. CHISELED X

N'LY LINE WESTBOURNE T.P. 17-36

21+17.61 =

83°30'07"

287.43'

= 01°02'07" DeF. RT. TO CON. MON.

19+01.30 ∠ LT 35°26'40"

2x2

"P" LINE

Clark
Shephard
Bruner
Presley

"P" Line - Levels:
& Profile

1-30-53

T.P.	11.98	138.90	0.37	126.92	
1+50			1.50		125.79
1+00	toe slope		8.56		118.73
0+50			7.85		119.44
0+00 = P.I.	S-Ly 10' Line Rosemont & E Ry R.W. Proj. Ahead		3.73		123.56
0-50			3.04		124.25
T.P.	12.02	127.29	0.25	115.27	127.29 ✓
T.P.	12.10	115.52	0.11	103.42	
T.P.	12.04	103.53	0.27	91.49	
B.M.	7.96	91.76		83.80 S.E. B.R. Rosemont & Electric	

℄ Profile "P" Line (cont.)

6+00			6.25	
5+00			7.56	
4+33.62 4LT 6° 02'			6.04	
T.P.	10.45	194.54	0.69	184.09
4+00			2.77	
T.P	11.09	184.78	0.07	173.69
T.P.	12.23	173.76	0.15	161.53
3+00			2.63	
T.P.	11.81	161.68	0.14	149.87
T.P.	11.96	150.01	0.85	138.05
2+00			3.70	

℄
188.29
186.98
188.50
194.54
182.01
184.78
159.05
161.68
135.20
138.90

℄ Profile "P" Line (cont.)

					℄
9+81	Top Rise			2.98	170.26
9+40	Shoulder			5.90	167.34
T.P.		11.47	173.24	0.15	161.77	173.24
9+00				9.66	152.26
8+72	Bott. Draw			14.6	147.32
T.P.		0.92	161.92	11.71	161.00	161.92
T.P.		0.05	172.71	11.49	172.66	
8+00				7.10	177.05
T.P.		0.91	184.15	11.30	183.24	184.15
7+54.07 = 2x2 = P.O.T. shoulder - begin slope into Draw				4.76	189.78
7+00				3.66	190.88
					194.54

Profile "P" Line (Cont.)

15+00.02 = 2x2 P.O.T Brow			4.47		187.30
T.P	2.64	191.77	0.18	189.13	191.77
14+00			6.30		183.01
13+00			11.11		178.20
T.P.	11.81	189.31	0.65	177.50	189.31
T.P.	12.28	178.15	0.13	165.87	
12+00			0.60		165.40
T.P.	11.70	166.00	0.59	154.30	166.00
11+00			6.57		148.32
T.P.	4.95	154.89	11.83	149.94	154.89
T.P.	0.75	161.77	12.22	161.02	
10+00			5.85		167.39

℄ Profile "P" Line

18+79 Shoulder			3.90		190.01
18+53.97 = 2x2 P.O.T.			1.22		192.69
18+16 Shoulder			1.83		192.08
17+99.87			6.19		187.72
T.P.	11.92	193.91	0.15	181.98 ~~181.91~~	193.71
T.P.	12.13	182.14	0.40	170.01	
17+00			4.82		165.59
16+46 Toe			10.06		160.35
15+97 Toe Slope			11.92		158.49
T.P.	10.51	170.41	9.48	159.90	170.41
T.P.	0.42	169.38	11.09	168.96	
T.P.	0.43	180.05	12.15	179.62	
15+36 Shoulder			10.23		181.54
					191.77

℄ Profile "P" Line

℄

For X-Sections See Pg 37

	Check		8.96	149.01 = 149.29 = ℄ NAIL IN S.W. Ret. Nashville Hwy	
21+16	APPROX. SLINE Westbourne		6.95		151.02
T.P.	5.05	157.97	12.20	152.92	157.97
20+40	tac		10.65		154.47
20+00			3.18		161.94
T.P.	0.86	165.12	12.14	164.26	165.12
T.P.	0.98	176.40	11.75	175.42	
19+01.30 ℄ LT	35°	26' 40"	1.25		195.92
~~18+79~~ BROW	(See preced. Pg.)				~~190.01~~
T.P.	5.25	187.17	11.99	181.92	187.17

Clark
Shephard
Huffman
Acuna
1-31-53
W.O 27526

X-SECTIONS "P" LINE - Electric Ry to Fay Ave

STADIA SECTIONS At 90° ℄ OFF BK TANG. unless otherwise Noted.
For Elev. of ℄ STATIONS (1x1 Studs) See Pgs. 31-36

INDEXED 31

FEB 5 1953

STA	ROD INT.	VERT ∠	COMP. DISTANCE	DIFF Elev.	Elev. □	Elev.
RT	1.48	+10°25' ON 9.0	143'	+26.3 -4.1		145.8
RT	1.04	+10°20' ON 9.0	101'	+18.4		142.0 -137.9
RT.	0.53	+6°20'	52'	+5.8		129.4
LT	0.65	0°0 ON 16.0	65'	-11.1		112.5
LT Toe Ry Fill	0.42	0°0 ON 14.2	42	-9.3		114.3
LT	0.21	0°0 ON 5.25	21'	-0.35		123.2
□ 0+00					4.9=H.I 123.56	
RT.	1.46	+9°30'	142'	+23.8		148.0
RT	1.02	+8°16'	100.	+14.5		138.7
RT	0.60	+11°	57.8	+11.22		135.47
LT Sly C.B. Roadway Easement	0.72	-10°20'	69.7	-12.7		111.55
LT Toe Ry Fill	0.46	0°0 ON 13.7	46'	-9.1		115.15
LT	0.20	0°0 ON 6.6	20'	-2.0		122.25
□ 0-50					H.I=4.6 124.25	

STA	ROD INT.	VERT ∠	COMP. DIST.	DIFF. Elev.	Elev □	Elev.
RT.	1.58	+15°40'	146'	+41.		176.2
RT.	1.11	+15°20'	103'	+28.3		163.5
LT. Wly Toe	1.30	-8°50' ON 16.0	127'	-19.9 -10.7		104.8?
LT Wly Edge Ry Fill Top	0.80	0°0 ON 13.0	80'	-7.7		127.5
LT. Ely Edge Ry Fill Top	0.60	0°0 ON 13.0	60'	-7.7		127.5
LT Ely toe Ry Fill	0.50	-13°50'	47'	-11.6		123.6
□ 2+00					5.3=H.I 135.20	
RT.	1.80	+15°30'	167'	+46.4		165.1
RT.	1.05	+12°10'	100'	+21.6		140.0
LT			85			108.6 (hand-level)
LT. Edge Ry Fill			42			SAME ↓
LT. Ry Fill	0.35	+12°10	33.5.	+7.2		126.0
LT Ely Toe Ry Fill	0.15	0°0 ON 6.0	15'	-0.7		118.0
□ 1+00					H.I=5.3 118.73	

STADIA X-SECTIONS "P" LINE (CONT)

STA	ROD INT.	VERT ∅	COMP. DIST.	DIFF ELEV.	ELEV.	ELEV.	
LT	2.20	-20° 10'	194'	-71.		117.5	
LT W'ly edge of Ry Fill	1.79	-19° 20'	160'	-56.		132.0	
LT. Toe - H:1 Uniform Slope	1.60	-22° 10'	137'	-56.		132.0	
⊡ #33+62 L.T. 06° 02'					5.0=H.I 188.50		
RT Brk	1.33	+18° 30'	120'	+40.		222.0	226.8=Elev {HAND level} 220' RT ℄
RT Uniform slope	1.10	+19° 30'	98'	+34.6		216.6	
LT toe - Flat	2.06	-20° 0'	182'	-66	~~116.0~~	116.0	
LT. W'ly Edge of Ry Fill	1.66	-18° 55'	149'	-51	~~131.0~~	131.0	
LT. Toe - H:1 Uniform Slope	1.48	-21° 50'	127'	-51	~~131.0~~	131.0	
⊡ 4+00					5.2=H.I 182.01		
RT.	1.75	+15° 10'	163'	+49		203.0	
RT "Brook"	1.10	+15° 50'	102'	+28.9		187.9	
LT. E'ly walk - Draper St.	1.94	-16° 25'	178.5'	-52		107.0	
LT. W'ly Edge Ry Fill	1.18	-15° 15'	110'	-29.9		129.0	
LT. toe slope (Uniform)	1.02	-18° 06'	92'	-30.		129.0	
⊡ 3+00					4.9=H.I 159.05		

STA	ROD INT.	VERT. ∅	COMP. DIST.	DIFF Elev.	ELEV. ⊡	ELEV.	
RT Brk - Rim	0.63	+20° 50'	56'	+21.		212.	
LT. Toe - H:11 UNIF. slope	1.82	-17° 30' ON 9.0	166'	-52. + ℄		134.5	
⊡ 7+00					5.2 H.I 190.88		
RT. Flat - Top			194	+1.4 above Rim shot		221.5	(Hand-Level)
RT Flat - Top			154'	+3.0 Above Rim shot		223.0	(Hand-Level)
RT. Rim, or Brow	1.05	+19° 05'	94'	+32.		220.0	
RT Brk	0.64	+20° 15'	57'	+21.		209.0	
LT. Uniform Slope toe H:11	1.92	-17° 50'	174'	-56.		132.0	
⊡ 6+00					5.2=H.I 188.29		
RT Flat Top			170	+6.0 Above Rim-elev.		222	(HAND-Level)
RT Flat Top			100'	+3.0 Above Rim Shot		219	(HAND-Level)
RT. Uniform slope	0.82 Brk - Rim	+22° 50'	70'	+29.0		216.	
LT. toe H:11 Uniform Slope	1.70	-20° 15'	150'	-55.		132.0	
⊡ 5+00					5.2=H.I 186.98		
RT Uniform slope Brk - Rim, tp.	0.97	+19° 45'	86'	+30.8	188.50	219.3	222.0 Elev 186 Rt ℄ {HAND Level}

STADIA X-Sections "P" Line (Cont.)

STA.	Rod INT.	Vert. ∅	Comp. Dist.	Diff. Elev.	Elev. □	Elev.	
Shoulder, Ridge E. of Draw RT	2.88	+10° 50'	278	+53.5		201	
RT Toe-Hill EAST of draw	1.68	+5° 58'	166			164.6	
RT IN Draw	0.86	+7° 25'	84.5	+11.		158.0	
LT FLAT	0.93	0° 0 ON 7.5	93'	-2.5		144.8	
LT	0.56	0° 0 ON 5.8	56'	-0.8		146.5	
8+72 □ Batt. Draw					4.1=5.0 147.32		
Shoulder on Slope EAST of Draw. Draw Lies to SOUTH RT	3.48	+5° 50'	344'	+35.		212.	
RT. BRK	1.54	2° 35' ON 10.0	154'	+6.9 -5.0		179.	163 (HAND Level) / 195 RTE = Batt. Draw
LT toe	1.43	-13° 25'	139'	-32		145.	
LT BRK	0.47	0° 0 ON 12.3	47'	-7.3		169.7	
8+00 □					5.0=H.I 177.05		
RT	0.99	+8° 30' ON 11.0	97'	+14.6 -5.7		199.	197.5 / 150 RTE = BRK (HAND Level) INTO DRAW
LT Even slope. Toe-hill	1.65	-17° 40'	150'	-47.7		142.	
T+54.07 □ 2×2 Pot.					5.3=H.I 189.78		
RT.	0.96 BRK	+19° 40 ON 11.0	85'	+30. -6.0		215.	214.0 / 150 RTE = BRK (HAND Level)
					5.1=H.I 190.88		begin slope EASTward into Draw

STA	Rod. INT.	Vert. ∅	comp. Dist.	Diff Elev.	Elev. □	Elev.	
RT BRK	1.45	+8° 35'	142.	+22.		192	
RT BRK	0.49	+6° 45'	48.4	+5.8		176.	
LT Toe hill	1.42	-10° 04' ON 9.0		-24. -3.6		143.	
LT BRK	0.50	0° 0 ON 18.2	50'	-12.8		157.5	
9+81 Tp. Ridge & Beg. Slope into Draw Ahead					5.4=H.I 170.26		
Shoulder of E. Ridge RT.	2.88	+8° 12' ON 9.0	282	+41 -3.8		204.5	
RT. BRK	0.85	+9° 02'	83.	+13		180.	
LT ON FLAT	1.50	-10° 45	145.	-27.5		140.	
LT Toe	1.18	-12° 24'	113.	-25		142	
LT BRK	0.88	-10° 59'	85.	-16.5		151.	
9+40 □ Shoulder					5.2=H.I 167.34		
RT. toe of Ridge to EAST	1.62	+9° 58 ON 9.0	157.	+27. -3.6		~~179.~~ 176.	
RT. BRK	0.77	+9° 30'	75'	+13		165.0	
LT Toe	1.04	0° 0 ON 14.6	104'	-9.2		143.0	
LT	0.70	0° 0 ON 13.8	70'	-8.4		143.8	
9700 □ Toe Slope					5.4=H.I 152.26		

STADIA X-SECTIONS "P" LINE (Cont.)

STA.		ROD INT.	VERT ∅	COMP. DIST.	DIFF ELEV.	ELEV.	ELEV.	
Bk. Shoulder	RT	0.56	#11°24'	54.	+9.7		188.	
on FLAT At toe cut	LT			118'	-29		143	(hand-Level)
Tp. Rim of Cut to west	LT	1.22	-13°25	116.	-27.		151	
Bk	LT	0.71	-12°05	68'	-14.		164.	
13+00						5.3=H.I 178.20		
Shoulder Ridge to East.	RT	3.11	+6°04	307.5	+32.5		197.9	
North Draw Runn. Ely	RT	1.73	+4°32' ON 11.0	172.	+13.4 -5.8		173.0	
Bk	RT	0.65	+5°09	64.5'	+6.		171.	
toe hill uniform	LT	1.40	-10°	136.	-24		141.	
12+00 Shoulder Ridge						5.2=H.I 165.40		
Shoulder of Ridge to East	RT	3.20	+9°12	312'	+51.		199.	
in Draw At toe slope to East.	RT	1.02	+5°12'	101.	+9.		157.	
Bottom Draw in Line with toe Bk Ahead	LT	1.34	0°0 ON 12.7	1.34'	-7.5		140.8	
11+00 Bott. Draw						5.2=H.I 148.32		
E Ely Head of Draw Running N West	RT			175		170.26	199.	(hand-Level)

STA		ROD INT.	VERT ∅	COMP. DIST.	DIFF ELEV.	ELEV.	ELEV.	
	RT.	3.30	+1° ON 11.0	330'	+5.8 -5.6		187.5	
Bk	RT	1.49	0°0 ON 7.3	149'	-2		185	
Bk	RT	0.45	0°0 ON 1:8	45'	+3.6		191.	
Toe cut on Flat	LT			87			147.3	with Level
Top. Rim of cut	LT	0.81	-15°54'	75'	-21.		166.	
Bk	LT	0.41	0°0 ON 14.5	41'	-9		178.	
15+00 Draw						5.4=H.I 187.30		
Flat	RT			280'	+20		203	(Hand-Level)
	RT.	2.31	+5°31 ON 10.0	229.'	+22 -5		200	
	RT	1.62	+4°35'	161'	+12.		195.	
Shoulder	RT	0.66	+7°49'	65'	+9.		191.	
on Flat, toe cut	LT			102'	-36.		147.	Hand-Level
Tp. Rim along cut to west	LT	1.02	-14°14'	96'	-24.		159	
14+00						5.1=H.I 183.01		
Flat	RT			243'	+25.6		204.	(hand-Level)
	RT.	1.45	+7°23' ON 11.0	142.5	+19.	5.3=H.I 178.20	197.	

STADIA SECTIONS "P" LINE (CONT.)

STA	ROD INT.	VERT. ∅	COMP. DIST.	DIFF ELEV.	ELEV. □	ELEV.	
Toe cut LT at Flat			45'			154.4 on Flat (with Level)	
Top Rim LT of Cut	0.30	0°0 ON 7.8	30'	-2.6		163	
P 17+00					5.2 H.I 165.59		
RT Shoulder Ridge East	4.30	+6°31' ON 10.0	425'	+48.5 -5		203.8	
RT Brk	3.20,	+6°23' ON 10.0	316'	+35 -5		190.	
RT Brk	2.22	+5°15'	220'	+20.		180,	
RT Brk	1.02	+3°46'	102'	+6.6		167.	
LT Toe	0.80	0°0 ON 15.2	80'	-10		150.	
LT Brk	0.62	0°0 ON 8.9	62'	-3.7		156.6	
P 16+46					5.2 H.I 160.35		
RT Toe-Ridge to N.E	3.30	+5° ON 16.0	328	+28 -11		175.	
RT Brk	1.08	+6°40' ON 11.0	107.	+12 -6		164.	
RT Brk	0.70	+9°44' ON 10.0	68'	+11.6 -5		165.	
LT Mouth Draw	0.88	0°0 ON 14.8	88'	-9.8		148.	
LT Brk	0.70	0°0 ON 9.2	70'	-4.2		154.	
15+97 Toe Slope + Beg. Draw.					5.0 H.I 158.49		

STA	ROD INT.	VERT. ∅	COMP DIST.	DIFF ELEV.	ELEV □	ELEV.	
FLAT RT	1.79	+2°44'	179'	+8.5		198.5	
RT Brk	0.82	+3°18'	82'	+1.6		193	
ON FLAT LT			90'			152.2	(with Level)
Toe cut LT			76'			154.5	(with Level)
Rim - Top of Cut LT	0.65	-11°19'	62'	-13		177.	
□ 18+79 Shoulder					5.2 H.I 190.01		
FLAT RT	2.41	+2°10'	241'	+9		201	
FLAT RT	1.01	0°0 ON 2.2	101'	+2.9		195.	
Toe cut LT on FLAT			66'			154.4 on FLAT, (with Level)	
Rim, Top of Cut LT	0.46	0°0 ON 13.2	46'	-8.		186.	
□ 18+16 Brow					5.1 = H.I 192.08		
Shoulder Ridge E'LY RT	2.84	+6°45'	280	+32.6		198	
RT	1.45	+7°22'	143'	+19		184.	
					5.2 H.I 165.59		

STADIA Sections "P" Line (Cont.)

STA	Rod INT.	Vert ∅	Comp Dist.	Diff Elev.	Elev. □	Elev	
RT IN DRAW	1.20	+3°38 ON 17.0	120'	+7.5° -12.		157.4	
Toe Slope RT & Bott. Draw	0.26	0°0 ON 10.5	26'	-5.4		156.5	
Toe — LT — CUT ON FLAT			46			152.5	(with Level)
Rim, LT tp CUT	0.35	0°0 on 1.6	35'	+3.5		165.4	
□ 20+00					5.1 H.I. 161.94		
Toe Slope RT At Bot. Draw Ahead	2.80	-2°47' ON 11.0	279'	-13.50 -6.		166.4	
LT □ 19+01.30	(Shot AT 90° to Forward TANG.)						
FLAT RT	2.10	+3°32'	209'	+12.9		199.	
FLAT RT	1.02	+3°24'	102'	+6.		192	
ON FLAT LT			83			152.5	(" ")
Toe CUT LT			78			155	(with Level)
Rim LT tp CUT	0.71	0°0 on 17.0	71'	-12		174.	
L. LT. □ 19+01.30					5.1 H.I. 185.92		

STA.	Rod INT.	Vert ∅	Comp Dist.	Diff Elev.	Elev. □	Elev.	
Top Bank. RT N'Ely	1.26	+8°33'	123'	+18.4		172.9	
IN DRAW RT AT Toe N'Ely Bank	0.78	+3°	78'	+4.10		155.1	
FLAT LT ON Cold-Lay	0.41	0°0 ON 2.5	41'	+1.8		152.8	
Approx S.L. WESTBOURNE 21+16 ± (AT 90° BK TANG.)					4.3 = H.I. 151.02		
Toe N'Ely RT Bank	1.05	+2°53 ON 7.0	105'	+5 -1.7		157.8	
LT ON Cold-LAY FAT	0.54	0°0 ON 7.2	54'	-1.9		152.6	
LT. Mouth Draw	0.20	0°0 ON 5.5	20'	-.2		154.2	
□ 20+40 Toe Slope & Bott. Draw					5.3 = H.I. 154.47		

Roberts
Cota
Moore
Moralez
Aug. 19, 1953
W.O. #31973

X-Section Alley Block "J", Balboa Vista

So. line of Balboa Vista to Laurel

see FB 2165 pg 1



Contd From Page 43

Lt | ℄ | Rt

		282.3	276.8	281.8	277.0	279.6	282.7	282.6	282.5	284.8	287.2	286.5	280.9
	9.8' Lt. Begin of Conc. Block wall	5.3	10.8	5.8	8.6	8.0	4.9	5.0	5.1	2.8	0.4	+1.1	+6.7
0+50	10.2' Lt. End of conc. Block Wall	9½ Top	9½ Foot	10 Top	10 Foot	10 GRD	4		8	10	14	26	33
0+49	8.1' Rt to center P. Pole #5845554												
0+25	9.0' Rt. to deadman												
		280.0	281.9	285.6	285.5	285.6	287.2	286.9	284.1	279.2			
0+10		7.6	5.7	2.0	2.1	2.0	+0.4	+0.7	+3.5	+8.4			
		12	10	5		6	8	10	23	34			
						279.9	279.2	282.2					
0+01	12.9' Lt begin conc. Block Wall (No steel Not Rebt.)					7.7	8.4	5.4					
						12.9 GRD	12.9 Foot	12.9 Top					
		280.2	280.1	284.6	285.7	285.3	284.88	285.7	287.1	286.8	284.1		
0+00	South Line of Balboa Vista	7.4	7.5	3.0	1.9	2.1	2.69	1.9	0.5	+1.1	+3.5		
		29	13	10	8	on Ground	on Hub	3	5	10	19		

287.57 ⊼

T.P.	6.99	287.57 ⊼	0.60	280.58	
T.P.	11.02	281.18	5.65	270.16	on Hub 44 ^ 3469.
T.P.	4.73	275.81	8.56	271.08	
BM	1.75	279.64		277.89	SEBP in Paving. 54th E

Blackton Drive
(Biloxi Street Now!)

Cont'd From Page 44

T.P.	1.51	277.62 ℄	11.4	276.11
2+01	10'	Lt Begin conc block Wall		
2+00				
1+50				
1+49	10' Rt to center T. Pole			
1+01	9' Lt East End E & W conc Block Wall			
1+00				
0+88	9' Lt End conc Block Wall			

287.57 ℄

Lt ℄ Rt

277.9 274.5 275.7
7.7 13.1 11.9
10' 10' 10'
Top Foot GRD

279.2 275.6 276.0 276.5 280.2 283.6
13.4 12.0 11.6 11.1 9.4 4.0
30 10 10 16 28

273.5 275.0 276.2 276.4 276.8 278.7 280.3 286.0
14.1 12.6 11.4 11.2 10.8 8.9 7.3 1.6
30 10 3 8 10 12 29

281.8 275.6 277.4
5.8 12.0 10.2
9' 9' 9'
Top Foot GRD

276.4 277.8 278.6 278.6 280.8 285.3 285.6
11.2 9.8 9.0 9.0 6.7 2.3 +2.0
30 10 7 10 17 33

282.1 276.8 278.5
5.5 10.8 9.0
9' 9' 9'
Top Foot GRD

287.57 ℄

		Lt	℄	Rt
4+00		269.8 / 7.8 / 20	270.1 / 7.5 / 10	270.2 / 7.4
		270.6 / 7.0 / 10	272.4 / 5.2 / 12	275.3 / 2.3 / 22
3+50		269.6 / 8.0 / 30	270.1 / 6.9 / 10	271.1 / 6.5
		271.2 / 6.4 / 10	273.8 / 3.8 / 13	277.1 / 0.5 / 25
3+02	10± Rt to center T. Pole # 48#557H			
3+00		272.2 / 5.4 / 30	272.7 / 4.9 / 10	273.2 / 4.4
		273.3 / 4.3 / 10	275.5 / 1.7 / 15	276.0 / +1.6 / 26
2+51	10' Lt End Conc block wall	275.6 / +2.0 / 10' Top	274.3 / 3.3 / 10' Foot	275.3 / 2.3 / 10' GRD
2+50		275.3 / 2.3 / 10	275.4 / 2.2	275.7 / 1.9 / 10
		276.6 / +1.0 / 16	274.6 / +3.6 / 26	
2+33	10.6' Lt center 10.5' gate in wall	275.11 / 2.51 / 23.6 Garage Floor	275.41 / 2.21 / 18.6 Conc	

277.62 ↑

277.62 ↑

Rt

℄

2t

Reduced
R E Boyd
28 Aug 53

℄ Laurel Street

South Line plus sixteen feet

South Line plus nine feet

4+34.69 South Line of Laurel

Sections taken Parallel to Laurel

2t		℄		Rt
		271.4	272.7	274.8
		6.2	4.9	2.8
		47		50
	271.7	272.9		274.8
	5.9	4.7		2.8
	42			50
270.3	271.9	271.9	273.6	275.4
7.3	5.7	5.7	4.0	2.2
40		13	21	50
270.0	271.0	271.5	272.3	274.0	275.6
7.6	6.6	6.1	5.3	3.6	2.0
37	102	on GRP	102	19	50
		271.6			
		7.6			
		on Hub			

277.62 ℄

277.62 ℄

Roberts
Cota
Moore
Morales
8-19-53
W.O. #31973

X-Section Alley Block I, Balboa Vista

Laurel to Biloxi

See F.B. 2142 pg 28





Cont'd from Page 48

0+63	10' Lt begin conc. block wall			
T.P.	12.00	291.73 ℄	0.18	279.73
0+50	Property owner on Lt. Intends to build Garage			
0+35	9' Rt to center T. Pole #584559H			
0+34	10' Lt End picket fence			
0+00	10± Left on St. Line begin Picket fence North Line Laurel Street			
	North Line Laurel minus seventeen feet.			
	North Line Laurel minus twenty-five feet.			
TBM	9.75	279.91 ℄	270.16.00 Hub See	page 44

Sections taken parallel to Laurel Street

Lt ℄ Rt

285.3 280.7 280.1
6.4 11.2 11.6
10± 10± 10±
Top Foot GRD
& stake at ℄

291.73 ℄

279.8 279.8 278.8 278.3 278.3 278.2 277.3 278.0 279.0 278.8
0.1 0.1 1.1 1.6 1.6 1.7 2.6 1.9 1.9 1.1
20 14 10 8 5 7 8 10 20

272.6 274.0 273.3 273.2 273.3 272.6 273.7 273.7 276.8
7.3 5.9 6.6 6.7 6.6 7.3 6.3 6.3 3.1
50 10± 10 5 8 10 10± 50

270.1 271.7 274.0
9.8 8.2 5.9
50 50

270.9 272.6 274.9
9.0 7.3 50
50 50

279.91 ℄

1+84.5 92' Rt to center TPK # 584560H

1+75

1+50

1+36

1+35

1+00 [Back yards on Left are pretty well terraced.]

0+84.5 10' Lt End conc. block wall

	288.5	288.5	288.7	288.6	288.1	289.2	289.2	287.3
	3.2	3.2	3.0	3.1	3.6	2.5	2.5	2.6
	20	10		4	6	7	10	20

	288.0	287.2	286.7	286.6	286.6	286.0	286.7	286.9	287.6
	3.7	4.5	5.0	5.1	5.1	5.7	5.0	4.8	4.1
	20	10	9		4	6	8	10	20

	287.7	287.9	285.5	285.4	285.4	284.7	285.4	285.7	286.5
	4.0	3.8	6.2	6.3	6.3	7.0	6.3	6.0	5.2
	20	14	10		4	6	8	10	20

	284.1	284.3	285.3	285.3	285.3	284.6	285.3	285.6	286.4
	7.6	7.4	6.4	6.4	6.4	7.1	6.4	6.1	5.3
	20	12	10		4	6	8	10	20

	283.8	283.8	282.5	282.5	282.3	281.6	282.6	282.8	283.2
	7.9	7.9	9.2	9.2	9.4	10.1	9.3	8.9	8.5
	20	10	9		5	7	8	10	20

	285.4	280.4	280.7
	6.3	11.3	11.0
	10'	10'	10'
	Top	Foot	GRD

29173A

29173A

Contd From Page 50

					Lt				℄		Rt		
					288.3	288.7	290.3	290.9	290.8	291.0	290.3	291.1	291.5
2+71.90 Midpoint					5.3	4.9	3.3	2.7	2.8	2.6	3.3	2.5	2.1
					25	12	10	8		7	10	11	20
					289.6	289.2	290.9	290.8	290.8	290.3	291.0	291.1	
2+55.21 BC.					4.0	4.4	2.7	2.8	2.8	3.3	2.6	2.5	
					25	10	8		7	9	10	20	
					289.0	289.5	290.9	290.8	290.7	289.9	291.0	291.0	291.0
2+36					4.6	4.1	2.7	2.8	2.9	3.7	2.6	2.6	2.6
					20	12	10		5	7	8	10	20
					292.1	290.4	290.6						
2+35	10' Lt. End conc. block wall				+0.4	3.2	3.0						
					10	10	10						
					Top	Foot	GRD						
T.P.	2.63	293.60 ℄	0.76	290.97					293.60				
					290.9	290.1	290.1	290.0	289.4	290.2	290.2	290.0	
2+00					Also Yard of yard → 0.8		1.6	1.6	1.7	2.3	1.5	1.5	1.7
					10	9.5			4	6	8	10	20
					Top footing								
					294.9	289.8	289.3						
1+85	9.6' Lt begin conc. block wall				+3.2	1.9	2.4						
					9.6	9.6	9.6						
					Top	Foot	GRD						
		291.73 ℄							291.73 ℄				

Lt ℄ Rt

3+85 $28^{\pm}$ Rt to center T. Pole # 5845614

3+76.30 Mid point $8^{\pm}$ Lt to fence

286.6	287.1	286.8	286.5	286.8	286.5	286.2	287.3	288.8	290.0
7.0	6.5	6.8	7.1	6.8	7.1	7.4	6.3	4.8	3.6
20	10	8		9	10	11	12	17	25

3+45 ± $10^{\pm}$ Lt begin, board fence ~~built on Straight Line~~

$10^{\pm}$ Lt End conc. block wall

295.9	289.6	289.0	288.9	288.9	288.6	289.0	290.0	290.4
+2.3	5.0	4.6	4.7	4.7	5.3	4.6	3.6	3.2
$10^{\pm}$	$10^{\pm}$	10		6	8	10	14	20
Top	Foot	GRD						

3+31.13 P.R.C.

295.8	289.3	289.8	289.7	289.7	289.3	290.5	291.0
+2.2	4.3	3.8	3.9	3.9	4.3	3.1	2.6
10	10	10		6	8	10	20
Top	Foot	GRD					

3+09.86 Mid point ~ $10^{\pm}$ Lt begin conc. block wall.

295.8	290.3	290.6	290.7	290.9	290.1	291.1	291.1	291.6
+2.2	3.3	3.0	2.9	2.7	3.5	2.5	2.5	2.0
$10^{\pm}$	$10^{\pm}$	10		4	7	8	10	20
Top	Foot							

2+88.59 P.R.C. $10^{\pm}$ Lt. to fence

291.6	290.8	290.9	291.0	289.9	291.1	291.5		
yard Level → 2.0	2.8	2.9	2.6	3.7	2.5	2.1		
11	10		6	8	10	20		

2+82 $10^{\pm}$ Lt begin board fence

293.60 ℄

293.60 ℄

Contd From Page 52

check		6.44	277.89 = 277.89	
T.P.	3.56	284.33	12.83	280.77

℄ Biloxi Street

South Line of Biloxi plus six feet

4+57.99? South Line of Biloxi Street

Sections taken Parallel to Biloxi

4+33.90 E.C.

4+21.48 P.R.C.

3+93.5 95' Lt End board fence

293.60 ℄

See page 44

Reduced 25' Aug 53 [illegible]

Lt. ℄ Rt.

		279.8		280.8			282.4	
		13.8		12.8			11.2	
		50		50			50	
	279.8			281.3			282.5	
	13.8			12.3			11.1	
	50			50			50	
281.2	280.5	281.2	281.5	281.6	281.7	285.0	286.8	
12.4	13.1	12.4	12.1	12.0	11.9	8.6	7.2	
50	30	10		10	18	27	50	
283.4	283.6	282.4	282.5	282.6	282.3	283.6	285.9	287.0
10.2	10.0	11.2	11.1	11.0	11.3	10.0	7.7	6.6
25	14	10		7	9	10	16	25
284.1	284.6	283.3	283.3	283.3	282.9	283.9	286.4	287.2
9.5	9.0	10.3	10.3	10.3	10.7	9.7	7.2	6.4
20	10	8		7	9	10	17	25

293.60 ℄

INDEXED
ER
AUG 21 1953

SURVEY

PROPOSED OPENING
LOS ALTUS ROAD
NO 27622

Deed
250.0

Map #1618

Walker
Pope
Oltman
Olon
1-22-54

○ = Fd. city Pipe & Disc.
□ = Set 2" x 2" Hub & Disc.
● = Fd city Mon
▭ = Proposed Opening

INDEXED
JER
JAN 25 1954

Note: See Drg. No. 5222-B for adjusted traverse. R.E.C. 2-1-54

P.L. Cor Pipe RE 4847

T.P. 27/17

City Mon. T.P. 27/19

Pueblo Line

This Sec. Detail — Sketch D-55

Los Altos Road

Fd. 3/4" Iron Pipe L.S. 2317

Fd. 3/4" Iron Pipe L.S. 2201

Fd. city Pipe & Disc

Los Altos Rd.

Set Hub & Disc

Fd. City Mon L.S. 1880

Fd. Iron P.P. checks for line

Fd. Pipe L.S. 2317

Fd 3/4" Iron Pipe R.O.S Map 1195

EASEMENT

Turned 72°22'15"

Radial Bisector

R=1576.40'
137.09
P.T.
Δ=5°20'
Arc 42.23'
T=21.12
R=1556.40
T=137.09
Δ=4°40'
R=1536.64'
R=1531.4
124.73
R=15' Δ=117°39'05" T=28.78
R=50 Δ=77°
R=15' Δ=64°52'46" T=9.52
R=103' Δ=5°
L=82.17
L=171.81
L=42.49
L=56.08
L=35.53
L=30'
L=146'
L=124'
L=163.16'
L=139.98'
L=206'
L=12.80'
L=39.38'
L=68.19'
L=127.5'
L=186.79 Meas.
L=387.33' Meas.
L=387.31' R.O.S.
L=2.80'
L=46.00'
L=43.43'
Δ=6°04'50" L=46.09'
107°37'30" Turned
P.55
40'
5'
5'

Detail - Ties
To opening line
Los Altos Road.



See Drg. No.
5222-B

3-9-54

Stamper
Hoffman
Nordahl
Sherry

Ref Map No 2306
F.B. 1704/3

ENCROACHMENT CHECK LOT No 1151 OF
TALMADGE PARK ESTATES No 2 W.O. 20006

LEGEND

● = Lead & Tacks 3' offset @ 90° to P.L.
Found Set in Sidewalk

INDEXED
MAR 0 1 1954
INDEXED
MAR 10 1954



D. Smith
J. Rorer
R. Taylor
B. Fish

INDEXED
JUL 2 1954

57

X Sec Fay St "P" Line
Westbourne St to Rushville

Wo #27526
7-1-54

Match LINE
Pg 59 Bottom




Rushville St
5' parking
5' walk
10' sidewalk
15'
15'
14
26'
26'
14
5' parking
5' walk
27182.93
66 PK nail
Fd L+T on 7' Line
NOT FD
213.86
Ex. 6" Sch. Woods Cor. bleachers with 8' conc. fence on line
Ex. 6" Pine Line
NOT FD
Fd L+T on 7' Line
FD. 1-85 LP
NOT FD
Ed. chisel (S)
S 25+30.73
L 87°26'30"
trg 59. top
2" Muir rods @


14'
26'
5' parking
5' walk
Cont. From bottom pg. 58.
NOT FD.
Fd obiss (1/2") L.RT 6°26'30"
FD 1-85' BP
25+30.73
edge conc gutter
25'
2540
6' CG&S walk comb
34'
73'
73'
128'
118.5'
91'
17.5'
Fay St extended Sly
24+00
14.6' C
48'
5' high wood picket fence
Sly of Schabbs conc block ext with 8' cyclone fence on top
Sly of Fay St extended
180'
40
4" conc block wall
10' wide conc drive
conc block wall
10' wide conc drive
conc block wall
20+41
40'
21.0
75'
Match Line
pg 57 top
6' comb CG&S walk
34'
23+00
35'
conc block House
1 Story stucco garage
E Muirlands Dr.

"X" Sec "P" Line
Sta – 21+00 through 22+82.93

Lt. Wly "P" Line Rt. Ely

TP2 11.65 + 164.81 5.02 153.16

22+50

18.6 Rt. & 18" Eucalyptus tree

22+45 3.0 Lt. & 8" Tel Pole 5190547H

22+43 77 Rt. end 2.5 picket fence planting

22+00

21+60 39.6 Lt. & 14" P Pole # 7002

21+49 13.7 Lt. & 14" P Pole # JP 7001

21+48 8.7 Rt. & 8" tree

21+47 4.6 Lt. Begin 2.5 Picket Fence planting

21+46 { 5.7 Rt. & 12" P Pole # JP 9/10
{ 4.0 Lt. & E deadman

21+32 { 80.0 Lt. CB inlet 10' throat with a 4x2.3 gate @ Sly end. 144.7 147.63
{ 3.4 Rt. inlet 36" RCP

21+00

TP1 5.35 + 158.18 5.98 152.83

BM 9.80 158.81 149.01 – P936 –

Bench Rock (149.29) La Nail SW Return CB Rushville & Fay

+ 158.18

25+130.23 L. Rt 6°26'30" taken @ 90° to tangent ahead

25+122± ℄ crosses edge Sly cor par Fay. St

25+00

24+60 4.9 Lt ℄ 16" P Pole # 7088

24+50

24+00

23+82 12.5 Rt ℄ 8" Tel Pole # 5190 53 H

23+50

23+12 22° Lt ℄ 12" P Pole # 7042

23+00

Lt-Wly

152.94	152.8	152.45	153.16	Lines	153.27	153.32	153.3	153.93	155.3	168.21				
11.87	12.01	12.34	11.65		11.54	11.49	11.50	10.88	9.51	43.2				
40	26	26	13			13	26	40	66	95				
CS		Gut												
153.7	152.9	153.2	153.5		153.4	154.3	155.4	157.0	159.7					
11.10	11.9	11.6	11.3		11.4	10.5	9.4	7.8	5.10					
37	37	15			18	35	50	75	100					
CS	Gut													
153.45	152.9	153.3	153.5		153.7	154.8	153.9	160.5	161.2	162.2	163.9			
11.36	11.9	11.5	11.3		11.4	10.0	10.2	4.3	3.6	2.6	1.0			
43	43	20			15	23	27	42	50	70	100			
CS	Gut													
153.37	152.7	157.1	153.5		153.6	154.1	160.1	162.4	165.3	169.3				
11.44	12.1	7.7	11.3		11.2	10.2	4.7	2.4	+0.5	+4.5				
47	47	30	15		13	25	35	50	75	100				
CS	Gut													
153.27	152.7	153.3	153.5		153.3	154.1	158.9	161.4	164.8	166.8				
11.54	12.1	11.5	11.3		11.5	10.2	5.9	3.4	0.8	+2.0				
50	55	30	15		15	28	50	80	100					
CS	Gut													
153.08	152.6	155.1	153.2	153.1		153.3	154.0	159.8	161.3	161.6	163.0	164.8	166.0	
11.73	12.2	11.1	11.6	11.7		11.5	10.8	5.0	3.5	3.2	1.8	0.8	+1.2	
60	60	45	30	15		16	28	42	70	72	85	100		
CS	Gut													

T 164.81

Rt-Ely

BM start 1960		9.42	149.03 +0.02
27782.93			
27740			
27700			
26784	140' RE double garage cor floor		
26750			
TP 3	6.80	1.58.45	13.16 151.65
26700			
25750			

Lt = Wly "P" Rt = Ely

146.29	148.02	147.62	148.42		148.69	148.63	148.6	149.12	149.18	150.5	159.7			
10.16	10.43	10.83	10.00	9.76	9.82	9.85	9.33	9.27	8.6	+1.2				
40	26 cc	26 gut	13		13	26 gut	26 cc	36 w/k	40	53				
146.65	148.37	148.96	149.27		149.20	149.13	149.67	149.75	151.45	162.1				
9.80	10.08	9.49	9.18		9.25	9.32	8.78	8.70	7.0	+3.6				
40	26	13			13	26 gut	26 cc	36 w/k	40	50				
149.8	149.53	149.10	149.85		150.05	150.03	149.93	150.47	150.56	153.15	163.5			
8.2	8.92	9.35	8.60	8.40		8.42	8.52	7.98	7.89	5.3	+4.8			
40	26 cc	26 gut	13			13	26 gut	26 cc	36 w/k	40	50			
							150.92	151.28	151.57		161.57			
							7.53	7.17	6.88		+3.8 roof			
							36 w/k	37	40 floor		40			
150.63	150.48	150.10	150.82		151.11		151.00	150.91	151.46	151.65	154.05	166.55		
7.82	7.97	8.35	7.62	7.34		7.45	7.54	6.99	6.80	4.4	+8.4			
40	26 cc	26 gut	13			13	24 gut	26 cc	36 w/k	40	50			
154.6	154.54	154.12	152.09	152.21		152.09	151.99	152.55	152.71	153.51	163.2			
13.20	13.27	13.69	12.72	12.60		12.72	12.83	12.26	12.0	11.3	+1.6			
40	26 cc	26 gut	13			13	26 gut	26 cc	36 w/k	40	50			
152.69	152.53	152.21	152.87	153.13		153.28	153.03	153.66	153.90	154.0	162.1			
12.12	12.28	12.29	11.94	11.68		11.63	11.78	11.20	10.21	10.8	+2.1			
40	26 cc	26 gut	13			13	26	39 39 gut	39 cc	40	50			

↑ 158.45

↑ 164.81


1+00
L+43.84 = P.K. = ℄ old Conc. Pave
℄ for Sections
= ℄ Conc. strip.
℄ 10'
Conc. Pave
5
3/4" Pipe LS 2416
15'
3/4" Pipe - Ld. + c.t.
0+00
10'
5
Fd. old orig. Hub. + ct.
0.53'
3/4" Pipe Ld. + c.t.
0.20
1488
3.84
0+85 = Hub. P.O.T.
Conc. Mon.
82.39
R.O. Ramage
90° 03'
13
14
15
16
Lot 9
Lot 10
Miramar Terrace
Map. 750
Sub Line
15' Lt.
0+01.84 = Pipe - LS 2416
15'
0+00 = Hub.
Lot 17
Lot 18
Fay Ave.

Beg. Levels along ℄ of Prop. Drive in Lot 17 - Miramar Terrace - sketch - P. 63

W.O. 27526 - 11-21-55 7.0.

Lt. ℄ Rt. 64

INDEXED MER NOV 25 1955

0+31.7 - 9' Lt. = ℄ 3/4" Hose Bib

0+31.5 3' Rt. = ℄ 2" Citrus

0+30.7 - 9.6' Rt. = Ang. in fence

0+24 - 6.7' Lt. = ℄ 2" Tree - Dead.

0+21 - 9.5' Rt. = Ang. in fence + 15.5 Lt. = Wire fence

0+19.5 - 13.5' Lt. = Beg ℄ of Row of Shubs - 5' cc.

0+17.5 - 13.9' Rt. = Cor. of Conc. Patio - Rock Border.

0+16.8 - 0.4' Lt. = ℄ 6.3 side of 6.3 x 9.3' Play House (movable)

0+16.2 - 12.4' Rt. = Ang. in fence

0+15.2 - 14.2' Rt. = Cor. of House + Beg. Redwood stave fence

0+11 - 12.8' Lt. = ℄ shrub.

0+09.5 - 12.7' Rt. = Cor. of chimney

0+04.5 - 12.7' Rt. = Cor. of Brick chimney

0+01.8 - 14.8' Lt. = Cor. of fence - goes N.

0+01 - 12.6' Lt. = ℄ shrub.

0+00

69.1 / 15 — 69.2 — 69.7 / 11.5 — 71.4 / 12.5 in Planting — 71.43 / 13.8 on Top Conc. wall Patio — 69.94 — 70.03 / 25

67.54 / 12.7 on Conc. Footing

66.3 / 15 — 66.70 on Hub — 66.4 / 14.5 = By House

0-00.9 = Cross Rough Redwood stave fence - 14.5' Rt. = Cor. of House + 14.8' Lt. = Cor. of Fence

BM. = S.W. Nail - Rushville + Fay 149.01 p. 36, p. 60

100' Frg. Not Noted.

	Lt.	℄	Rt.
Ely. of Rock wall along walk below - To S.			
0+75 - 14' Rt. = Nly. of Rough 2' Conc. walk to E. ←			77.41 14 walk; 77.75 16 Top wall; 78.05 30.8 Top wall; 73.7 ground To S.
Joins walk to W.			
0+72.5 - 14' Rt. = ℄ of Nly. of 3.5 Sloping Conc. walk to S.			77.24 14 walk; 74.16 26 walk - Bottom
0+65 - Cont.			75.19 31 Top wall; 73.5 ground to S.
0+65 - 1.6' Rt. = ℄ 3" Dead Citrus	76.59 15 Top of wall & ground	76.4	76.4 13; 75.68 15.5 walk; 75.73 17.5; 75.2 18
0+58.3 - 8.5' Lt. = ℄ 2" Citrus			
0+55.4 - 10.4' Lt. = ℄ 2.5' Conc. walk - Thru shrubs	75.12 21.5 By House Conc.	75.30 15 Top wall; 75.08 10.4 walk	
0+50 - 2' Rt. = ℄ 3" dead Tree			
0+48.2 - 14.9' Lt. = Beg. Sly. of 8" Brick Top - To Conc. Block wall - 6"	75.25 14.9 Top wall		
0+40 - Cont.			73.02 31.2 Top wall; 69.2 on Lawn
0+40 - 13.7' Rt. = end Nly. of Landing of 2" Conc. walk + 15' Rt. = Beg. Nly.	72.5 15	73.0	72.90 13.7 Cor. Conc.; 72.84 15 walk To E.; 72.88 17; 72.6 25
0+39.8 - 7.5' Lt. = ℄ 3" Citrus			
0+36.8 - 13.7' Rt. = N.ly. of Top of steps.			72.80 13.7 Top of steps; 72.70 17.2
0+35 - 12.2' Rt. = Cor. of fence - goes S.	71.5 15	71.6	71.8 11; 72.00 14.5 Top wall; 70.05 on Conc. Patio; 70.11 25
0+32.1 - 14.5' Rt. = wall + Cor. of Conc. Patio — wrong line			
Beg. Nly. of 3.5' Conc. steps.			

1+43.84 = ℄ Conc. Pave

1+37.5 - 14' Rt. = ℄ Traffic Sign

1+32 = edge of Conc. - AC Top

1+15

1+02.8 - 16.8 Lt. = ℄ 18" Euc. Tree

1+01.8 - 19' Lt. = Cor. of wall - goes N.

0+91.3 - 19' Lt. = ℄ 3' walk thru. wall

0+97.5 - 12' Lt. = ℄ shrub.

0+90.5 - 12' Lt. = end ℄ of Row of shrubs. - Large

0+86 - 7' Lt. = ℄ 2" Dead Tree

0+85 = Sub. Line

- 14.7' Lt. = end wall = Cor - goes N. 4.3 - 19' Lt. = wall to E.

0+83.8 - 13.5' Rt. = end N'ly of 2" walk
end of Low 6" - Raises in jogs.

0+78 - 14.9' Lt. = Beg. 4' High 8" Conc. Block wall

0+77 - 15' Lt. = ℄ ½ Hose bib.

0+76.4 - 13' Rt. = ℄ 2" dead Tree

Lt.		℄		Rt.		
85.88	85.49	87.78	89.69	91.28	91.1	88.3
Top cb	46.5 gut.	20	on PK.	17 edge	29	40
85.95		87.78	89.55	89.3	85.8	86.8
40		20 ℄	edge of Pave	11	27	50
86.63	87.0	84.7	82.7	83.0	83.5	
32 edge Conc. Pave	25	15		15	25	
82.97	80.6	80.3	80.4	81.3	81.2	
Top wall	19 ground	15		15	25	
78.79						
19 = walk						
		78.2	78.45	79.1	79.0	
		15	on Hub.	15	25	
				78.80	78.75	
				13.5	15.5	
					end walk	
81.64		78.09				
Top wall to E.		14.9 = wall to Top. W.				

Beg. Levels for profile along ℄ of 20' Conc. Strip in W. Murlands Drive

0+00 = 100' N.W.ly. along ℄ from Sta. 1+43.84 on ℄ of Drive

	Lt.		℄	Rt.		
1+50 = end.	92.07	91.57	93.23	93.98		94.1
	Top	23.3 gut.		10 edge		25 - Lawn
1+42 - 18' Rt. = end ℄ Hedge	90.46	89.99	91.64	92.21	91.1	87.9
	Top	23.6 gut.		10 edge	18	25
1+25.						
1+19 - 18' Rt. = Beg. ℄ of Shrub Hedge	88.98	88.48	89.69	90.16	89.2	84.5
	Top	23.6 gut.		10 edge	17	25 Toe
1+00 = 1+43.84 on Dr. Sta.						
0+73 - 13' Rt. = end Rail fence	87.16	86.68	87.64	87.86	87.3	81.2
	Top	23.2 gut.		10 edge	13	24 Toe
0+75						
0+58.5 - 20.6 Rt. = ℄ 5" Pine on Dr. Notes.						
0+53 - 22.5 Rt. = N'ly. of 8' Block wall - See S. and				83.17		
				22.5 = Top wall		
0+50	85.04	85.59		85.84	85.7	80.65
	23.4 gut. in Dr.			10 edge	13	24.4 Top wall
0+25 - 13.5' Rt. = Rail fence - Heavy Tree planting behind	83.68	83.21	83.50	83.50		
	Top	23 gut.		10 edge		
0+00	81.95	81.51	81.51	81.44		
	Top cb.	22 gut.		10 edge Conc.		

25·1 30.73
252 20
2782.93

NG.

9	
.35	0
.85	1
.35	2
.85	3
.35	4
.85	5
.35	6
.85	7
.35	8
.85	9
.35	10
.85	11
.35	12
.85	13
.35	14
.85	15
.35	16
.85	17
.35	18
.85	19
.35	20
.85	21
.35	22
.85	23
.35	24
.85	25
.35	26
.85	27
.35	28
.85	29
.35	30
.85	31
.35	32
.85	33
.35	34
.85	35
.35	36
.85	37
.35	38
.85	39
.35	40
.85	41
.35	42
.85	43
.35	44
.85	45
.35	46
.85	47
.35	48
.85	49
.35	50



DISTANCES FROM SIDE STAKES FOR CROSS-SECTIONING.

SLOPE 1½ TO 1. ROADWAY OF ANY WIDTH.

	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	
0	0.00	0.15	0.30	0.45	0.60	0.75	0.90	1.05	1.20	1.35	0
1	1.50	1.65	1.80	1.95	2.10	2.25	2.40	2.55	2.70	2.85	1
2	3.00	3.15	3.30	3.45	3.60	3.75	3.90	4.05	4.20	4.35	2
3	4.50	4.65	4.80	4.95	5.10	5.25	5.40	5.55	5.70	5.85	3
4	6.00	6.15	6.30	6.45	6.60	6.75	6.90	7.05	7.20	7.35	4
5	7.50	7.65	7.80	7.95	8.10	8.25	8.40	8.55	8.70	8.85	5
6	9.00	9.15	9.30	9.45	9.60	9.75	9.90	10.05	10.20	10.35	6
7	10.50	10.65	10.80	10.95	11.10	11.25	11.40	11.55	11.70	11.85	7
8	12.00	12.15	12.30	12.45	12.60	12.75	12.90	13.05	13.20	13.35	8
9	13.50	13.65	13.80	13.95	14.10	14.25	14.40	14.55	14.70	14.85	9
10	15.00	15.15	15.30	15.45	15.60	15.75	15.90	16.05	16.20	16.35	10
11	16.50	16.65	16.80	16.95	17.10	17.25	17.40	17.55	17.70	17.85	11
12	18.00	18.15	18.30	18.45	18.60	18.75	18.90	19.05	19.20	19.35	12
13	19.50	19.65	19.80	19.95	20.10	20.25	20.40	20.55	20.70	20.85	13
14	21.00	21.15	21.30	21.45	21.60	21.75	21.90	22.05	22.20	22.35	14
15	22.50	22.65	22.80	22.95	23.10	23.25	23.40	23.55	23.70	23.85	15
16	24.00	24.15	24.30	24.45	24.60	24.75	24.90	25.05	25.20	25.35	16
17	25.50	25.65	25.80	25.95	26.10	26.25	26.40	26.55	26.70	26.85	17
18	27.00	27.15	27.30	27.45	27.60	27.75	27.90	28.05	28.20	28.35	18
19	28.50	28.65	28.80	28.95	29.10	29.25	29.40	29.55	29.70	29.85	19
20	30.00	30.15	30.30	30.45	30.60	30.75	30.90	31.05	31.20	31.35	20
21	31.50	31.65	31.80	31.95	32.10	32.25	32.40	32.55	32.70	32.85	21
22	33.00	33.15	33.30	33.45	33.60	33.75	33.90	34.05	34.20	34.35	22
23	34.50	34.65	34.80	34.95	35.10	35.25	35.40	35.55	35.70	35.85	23
24	36.00	36.15	36.30	36.45	36.60	36.75	36.90	37.05	37.20	37.35	24
25	37.50	37.65	37.80	37.95	38.10	38.25	38.40	38.55	38.70	38.85	25
26	39.00	39.15	39.30	39.45	39.60	39.75	39.90	40.05	40.20	40.35	26
27	40.50	40.65	40.80	40.95	41.10	41.25	41.40	41.55	41.70	41.85	27
28	42.00	42.15	42.30	42.45	42.60	42.75	42.90	43.05	43.20	43.35	28
29	43.50	43.65	43.80	43.95	44.10	44.25	44.40	44.55	44.70	44.85	29
30	45.00	45.15	45.30	45.45	45.60	45.75	45.90	46.05	46.20	46.35	30
31	46.50	46.65	46.80	46.95	47.10	47.25	47.40	47.55	47.70	47.85	31
32	48.00	48.15	48.30	48.45	48.60	48.75	48.90	49.05	49.20	49.35	32
33	49.50	49.65	49.80	49.95	50.10	50.25	50.40	50.55	50.70	50.85	33
34	51.00	51.15	51.30	51.45	51.60	51.75	51.90	52.05	52.20	52.35	34
35	52.50	52.65	52.80	52.95	53.10	53.25	53.40	53.55	53.70	53.85	35
36	54.00	54.15	54.30	54.45	54.60	54.75	54.90	55.05	55.20	55.35	36
37	55.50	55.65	55.80	55.95	56.10	56.25	56.40	56.55	56.70	56.85	37
38	57.00	57.15	57.30	57.45	57.60	57.75	57.90	58.05	58.20	58.35	38
39	58.50	58.65	58.80	58.95	59.10	59.25	59.40	59.55	59.70	59.85	39
40	60.00	60.15	60.30	60.45	60.60	60.75	60.90	61.05	61.20	61.35	40
41	61.50	61.65	61.80	61.95	62.10	62.25	62.40	62.55	62.70	62.85	41
42	63.00	63.15	63.30	63.45	63.60	63.75	63.90	64.05	64.20	64.35	42
43	64.50	64.65	64.80	64.95	65.10	65.25	65.40	65.55	65.70	65.85	43
44	66.00	66.15	66.30	66.45	66.60	66.75	66.90	67.05	67.20	67.35	44
45	67.50	67.65	67.80	67.95	68.10	68.25	68.40	68.55	68.70	68.85	45
46	69.00	69.15	69.30	69.45	69.60	69.75	69.90	70.05	70.20	70.35	46
47	70.50	70.65	70.80	70.95	71.10	71.20	71.40	71.55	71.70	71.85	47
48	72.00	72.15	72.30	72.45	72.60	72.75	72.90	73.05	73.20	73.35	48
49	73.50	73.65	73.80	73.95	74.10	74.25	74.40	74.55	74.70	74.85	49
50	75.00	75.15	75.30	75.45	75.60	75.75	75.90	76.05	76.20	76.35	50

THE NATIONAL BLANK BOOK COMPANY
HOLYOKE MASSACHUSETTS
NEW YORK CHICAGO BOSTON SAN FRANCISCO