
WI
40

MICROFILMED
JAN 6 1965

INDEX.

	Page
Triangulation on axis of Morena dam to establish points	1
Levels on wagon road near Green's house	2-3
Levels for trolley bench on north side dam ; also notes	4-5
Points for entrance to tunnel at upper end	6
Levels over tunnel line	7
Setting point in north trolley bench and triangulating same; also checking on point E on axis of dam above trolley bench	8
Levels for road from elbow of new wagon road into north trolley pit	9
Check levels on B. M. on tunnel line	10
Grades for commencement of tunnel	11-16
Levels for north trolley bench up to stream alongside of road for supply of water	17-19
Levels from south trolley bench to find elevation of reservoir above trolley bench	20
Levels over line for flume to water ram dam above Chewings to blacksmith shop	21-24
Grades for flume line from Chewings to opp. Camp	25-27
Grades and cetntres for tunnel	28
Tunnel line on top	29-30
Measurement across canon from hub on w s to hub on e s	31
Notes for deriick guys; measurement across canon for stationary cable	32
Grades and centres in tunnel	33
Levels from Words reservoir to south bench	34-35
Derrick No. 2; notes for guys, etc.	36
Foundation for trestle work, south bench	37
Measurements of cement wall east side	38
Drawing north trolley bench	39
Measurement of loose rock on head	39 ½
Levels to give 150 ft contour on axis of dam	40
Levels to give height for building cribbing for cement wall	41
Levels on pipe line from south trolley bench towards Wards reservoir to find air bound places	42-43
Derrick No. 3	44
Extending line between JnO. Ward's place and E. S. Babcock's property	45
Meander of Ward's fence line	46-48
Measurements for line of tunnel and intersection with axis of dam	49

Notes on opposite page are Triangulation on Axis of Morena Dam to establish points on Same -

Base line for Triangulation taken about the 200' Contour at Right angles to axis of Dam - Eastwards Base line 147' -

One angle (40° 40') taken on base of 125' -

Measurement from M to Intersection of Tunnel line 60' approximately

July 15. 1897

Axis of Dam

Angle to A = 82° 49'

" B = 82 38'

" C = 82 19'

" D = 81 56

Do Pt. E = 81 35 ✓ 993.5

" F = 81 16 957.0

" G = 80 53 916.0

above Cattle Pt H = 80 28 875.3

Big Rock = 79 08 ✓ 765.7

I = 77 48 approximately.

J = 76 36 617.0

150' Contour K = 74° 53 ✓ 544.2

TUNNEL LINE Intersection = approximate = 167.0

on Rock M = 40° 40 ✓ 107.4

Hub on Axis of Dam on = 125 / 147'

137.5

241.1

260.3

V

Levels on Wagon Road

Near Evans House for Change of Road

July 16, 1897

Station	B.S.	Int.	F.S.	H.I.	Elev.	Grade	Cut or Fill	
B.M.	5.43			105.43	100.			assumed Elev.
0		14.40			91.03	91.0	0.0	
+25		12.40			93.03	94.4	- 1.4	
+50		6.80			98.63	97.8	+ 0.9	
+75		2.60			102.83	101.2	+ 1.6	
Peg on Stone			0.53		104.90			
	11.92			116.82				
1.00		9.90			106.92	104.6	+2.3	
1+25		6.00			110.82	108.0	+2.8	
1+50		4.05			112.77	111.4	+1.4	
1+75		2.85			113.97	114.8	- 0.8	
Peg			1.87		114.95			
	12.26			127.21				
2.00		10.20			117.01	118.2	- 1.2	
on Root			1.20		126.01			
	8.46			134.47				
2+25		14.00			120.47	121.6	- 1.1	
2+47		7.30			127.17	124.8	+2.5	
2+55		5.30			129.17	125.1	+4.0	
2+75		2			131.95	128.8		
on Stone								

Levels on Wagon Road Near Grimes House Continued

Sta.	B.S.	Int.	F.S.	H.I.	Elev.	Grade	Cut or Fill	
	11.32			143.78	132.46			
3.00		8.50			135.28	132.2	+3.0	
+25		7.47			136.31	135.0	+1.3	
+50		5.50			138.28	138.0	+0.3	
+75		4.40			139.38	139.0	+0.4	
4.00		3.85			139.93	139.6	+0.3	
+25		3.25			140.53	140.2	+0.3	
+50		1.50			142.28	142.2	0.0	
Peg.			1.93		141.85			
	10.45			152.30				
+75		7.27			145.03	144.0	+1.0	
5.00		6.00			146.30	146.	+0.3	
+25		4.85			147.45	148.	-0.5	
on Rock.			3.56		146.74			
		3.90			148.40			Grade of Road off 5.25

Levels for Trolley Bench on North Side Morena Dam. July 17. 1897

Sta	B.S.	Ht.	T.S.	H.I.		
	5.00			305.00	300.00	Assumed Elevation of Trolley Bench South side
Peg-			0.0		305.00	
	11.77			316.77		
Peg on Rock			.57		316.20	
	10.97			327.17		
		2.17			325.00	Hub for Elev. of Bench. North side
		2.17			"	" " "
		2.17			"	Point on Rock
		2.17			"	Hub for Elev. "
		2.17			"	" " "
		2.17			"	" " on Earth point
			2.17		325.00	Point on Rock.
	6.34			331.34		
			6.34		325.00	Hub and B.M.

Note:-
Elevation of Trolley Bench on North side 6" is 25 feet above Trolley Bench on South side - See notation given by Mr Budd

Feby 17th 1897

Notes for Bench North Side Morena Dam.

Axis of Dam

Line at Right angles to axis of dam near Face of Trolley Bench

July 22 - 1897

Giving points for entrance to tunnel at upper end -

Line A. = Supposed centre line of Concrete Wall at Toe of Slope

B = point where wall will connect with Solid Rock. -

Angle from Tunnel entrance to B = 62°30' distance 55 ft approximately

Hub R.P. opposite side of creek about 800 ft -



Levels over Tunnel Line

Feby 22-97

B.M.	5.06			41.99	36.93
		11.99			30. = 30' Contour point from
			0.17		41.82
	9.38			51.20	
			0.98		50.22
	11.47			61.69	
0.0		1.60			60.09 Hub at entrance to Tunnel
	10.87		0.83	71.73	60.86
+25		6.80			64.93
+50		6.80			64.93
+75		3.50			68.23
+90	9.39		0.37	80.75	71.36 Solid Rock on Rock boulder
1+00		8.20			72.55
1+10		6.60			74.15
+20		4.60			76.15 Cross axis of dam
+50		1.70			79.05
Pig	7.60		0.94	87.41	79.81 on Boulder
1+80		5.50			81.91
2+00		7.20			80.21
2+50		3.20			84.21
3+00					82.01

Feby 23 99

Setting point in North Trolley Bench and Triangulating
& Same also checking on point E on axis of dam above Trolley Bench -

{Old point on axis of dam Top of Hill = Same as (E) 78°.31' 994.3
{Former measurment made this 993.5

Hub in Trolley pit North side at Grade 75°.56' 806.2

Hub on axis of dam about 200' Contour Turned Rt angle for Base line 202'



9

Levels for Wagon Road leading from North Trolley pit

Hand Level

	0.0	8.80			108.80	100.00		
	+25		2.40			106.40		
	+50		2.60			106.20		
Rg.				0.60		108.20		
		12.20						
	+75		10.00			110.4		
	1.00		1.30			119.1		
				0.50		119.90		
		8.00			127.90			
	1+25		0.80			127.1		
	1+50		7.00			120.9		
	1+80		6.30			121.6		
	2.00		3.30			124.6		
Rg on Stone		7.70		0.10	135.50	127.80		
	2+20		0.50			135.0		
	2+50		1.20			134.3		
Rg.		12.50		11.70	136.30	123.80		
				0.60		135.70		
		11.30			147.00			
	3+00							
	3+30					145.50		
	3+5					480		
						60		

elbow of new wagon Road into

Feby 25. 1897

Corr

100.2	- 0.2	
104.0	+2.4	
8.0	0.0	Stake moved 1.8 up hill
		" " 1.6
112.00	0.0	Stake moved 1.6 up hill
116.00	+3.1	
118.00	+9.1	
120.0	+0.9	
121.6	0.0	
124.0	+0.6	
127.0	+9.0	
131.0	+3.3	
		on High point of Rock — not part in —
143.0	+2.5	Foot of Rock point
		Trolley pit

Check levels on B.M.° on tunnel line

			33.67
7.82	41.49		
		4.56	36.93
		7.02	34.47
0.39	34.86		
		1.49	33.37
		6.11	28.75
		7.76	27.10

levels to establish roof of tunnel - lower end

			27.10
14.67	37.77		
		8.17	29.60
		0.67	37.10

levels to set grades on face of trolley foundations 340°

			325.00
11.34	33		

March 13th 1897

ele of signal B.M. north side of creek

B.M. at up stream end (chuck)

B.M. at down stream end (33.27 signal ele) dif 0.10

T.P. on rock at entrance of spillway down stream end

new B.M. on bid rock down stream end

March 13th 1897

New B.M. at down stream end

Grade

Roof of tunnel

North side. March 12th 1897

in hub set by J.H. Sykes.

11

29th March

Grades for Commencement of Tunnel -

Sta	B.S.	Int.	F.S.	H.I.	Elv
B.M.	6.26			33.86	27.10
			3.76		29.60

Grade of Tunnel. Rod Reading.

29.6 | 3.76.

No Rock. Mouth of Tunnel
Points given at Entrance of Tunnel -



⊙ Hole drilled in Rock in front of Tunnel

Hole drilled ⊙ in Rock in front of Tunnel

March 30. 1894



12

Sta	B.S.	Int.	F.S.	H.I.	Elev
on N. Bench	12.00			356.00	344.0
on Rock			2.0		356.00
	12.30			368.3	
on Rock			0		368.3
	12.40			380.7	
on Rock			0.1		380.6
	12.30			392.9	
	5.00				
on Rock			1.5	396.4	391.4
	8.0		4.4	401.0	392.0
	4.0		8.0	397.0	392.0
391.0	-2.0				395
390.	0				399.
394	+ 5.2				406.
392.2	1.00				406.
391.0	1+50				400.
Sta. 2.	391.4			392.7	392.0
	1.3				
	392.7 H.I.		0.7		
	6.0				
	386.7				
	4.6				
2+50.	391.3 H.I.		5.3		386.0
	1.6				
	389.7				
	12.0				
3.00					1.0



Set stakes in Cameron's place for fence line above 175' Centers March 30 1897.

Levels to Reestablish 30 m 150' Centers

B.S.		F.S.		33.67
9.95			43.62	
	11.4			32.2
		0.05		43.57
11.85			55.42	
	4.90			50.52
		0.05		55.37
11.98			67.35	
		0.17		67.18
11.84			79.02	
		0.28		78.74
11.54			90.28	
		0.09		90.19
12.22			102.41	
		0.16		102.25
10.50			112.75	
				112.7

March 30th 1897

B.M. on North side creek above toe wall

Set stake on South side above wall

B.M. On Boulder near Cement House

				122.93	
	11.71		134.64		
		0.32		134.32	
	11.82		146.14		
		0.08		146.06	B.M. On Rock in old trail near Blacksmith Shop
	9.97		156.03		
		6.05		149.98	Set hub beside old trail

Sta		chist	dep	
1st	1	15.00	0.37	
	2	30.	1.14	
	3	45.	1.51	1.47 for 45'
	4	60.	2.28	
2nd	1	15	0.36.6	
	2	30	1.13.2	
	3	45	1.49.8	
	4	60	2.26.4	
3rd	1		0.38.8	
	2		1.10.6	
	3		1.46	
	4		2.7.1	
4th	1		0.34.5	
	2		1.09	
	3		1.43.5	
	4		2.18	

Inside Track for South Scally Branch

" " " "

8°.15

Second Track

8°.09

7°.57

7°.41

16

Grades for Tunnel

5.60		32.70	27.10
	3.10		

Abs Centre given

Grades for Tunnel

5.98		33.08	27.10
	3.48		

Grade for Tunnel
April 12.97

6.32		33.42	27.10
	3.82		
7.02		34.12	2710
	4.52		
6.91		34.01	27.10
apl 15.	1.76		32.25
2.71		34.96	
apl 17.			27.10

Grade

april 5. 1897

29.60

Plug in Roof for angle
is 4" above Roof grade } angle 38°.28.L

29.6 Plug in Roof for angle is 4" high

29.6

29.6

5.36

29.6 Plug [illegible] Grade

B.M.

Levels from North Trolley Bench up to stream alongside of Wagon Road for supply of water

Sta	BS	Int	FS	H.I	Elev	
	12.00			357.00	345.00	Level of North Trolley Bench
Pig			0.35		356.65	on path
	11.95			368.60		
			2.90		365.70	On Big Rock
	10.33			376.03		
			0.90		375.13	on Rock
	7.45			382.58		
			12.10		370.48	
	6.70			377.18		
			0.30		376.88	
	12.28			389.16		
			0.95		388.21	
	12.36			400.57		
			0.18		400.39	
	9.77			410.16		
			0.09		410.07	
	12.10			422.17		
		4.67			417.50	
		6.67	6.67		415.50	Water Elev in Creek above Inv
		14.47			407.70	Water " " below Inv
	94.94		24.44			
	24.0					
	70					

Levels from

0	5.97			421.47	415.50	at upper Res.
+50		10.70			410.8	lower "
+72		13.70			407.8	lower.
1+00		19.00			402.5	
1+50		19.00			402.5	
2.00		16.50			405.0	
	3.22		9.00	416.69	413.47	
2+50					395	in gully about 10' below 2.00
3.		13.00			403.7	
3+50		10.00			406.7	
4.		12.60			404.1	
Pvg			11.94		404.75	
	1.61			405.36		
4+50		3.46			401.9	} crosses Road
5		9.80			395.6	
5+50		14.00			391.4	
Pvg			12.02		394.34	
	0.50			394.84		
6.		7.15			386.7	
6+50		10.80			383.0	
7		10.90			383.0	
7+50					383.4	
Pvg					388.46	

Sta	B.S.		F.S.		
	10.33			393.79	383.46
8		11.1			382.7
+50		11.3			382.5
9		10.5			383.3
+50		5.6			388.2
10		9.50			384.3
+50		9.50			384.3
11		14.1			379.7
Tp.			11.04		382.75
	0.50			388.25	
11+50		5.40			377.8
12		9.60			373.6
-50		8.00			375.2
13		8.80			374.4
+50		10.00			373.2
14		9.40			374.8
+50		8.60			375.6
15		7.20			376.0
+50		2.90			380.3
16		5.30			378.0
+50		7.75	7.75		376.50
	5.0			380.52	
17					373.1
					369.7
					366.0

amongst big Rocks

30.27
15.85
14.42

Top of Ridge

Levels from South Trolley above Trolley Bench

11.27			311.27	300.00
		0.47		310.80
10.55			321.35	
		0.09		321.26
11.87			333.13	
		0.11		333.02
12.20			345.22	
		0.12		345.10
11.49			356.59	
		0.12		356.47
11.38			367.85	
		0.00		367.85
10.82			378.67	
	4.20			374.47
	12.35			366.12
		0.05		378.62
79.58		.96		
96				
78.62				

Bench to find Elevation of Reservoir

April 16. 1897

Elev. South Trolley Bench =

looking across just strikes North Trolley B.

on Big Stone Top of Reservoir West side

bottom of Reservoir

B.M. on Big Rock North side of Reservoir

Levels over Line for dam above Chennings

Flume to Water Ram to Blacksmith shop.

April 16. 1896.

	7.43			40.08	32.65	B.M. on peg near Chennings House at edge of Water
0+0		3.68			36.40	Notch at top next to dam = grade
+50		3.70			36.38	36.32 +0.06
1.00		4.68			35.40	36.24 - 0.84
+50		5.30			34.78	36.16 - 1.38
1.95		3.10			36.98	36.08 +0.90 point of R.
2.00		3.30			36.78	36.08 +0.70
2+50		4.81			35.27	36.00 +0 - 0.73
3.		4.97			35.11	35.92 - 0.81
3+50		5.27			34.81	35.84 - 1.03
4.		6.10			33.98	35.76 - 1.78
+35		4.78			35.30	35.70 - 0.40 point of R.
Tp.			2.42		37.66	
	2.89			40.25		
B.M.		1.98			38.27	
4+50		5.30			34.95	35.68 - 0.73
5.00		5.22			35.03	35.60 - 0.57
5+50		6.60			33.65	35.52 - 1.87 R
6.00		5.83			34.42	35.44 - 1.02
6+50		6.80			33.45	35.36 - 1.91
Peg in Stump			5.30		34.95	R
	3.[illegible]			38.76		
7.					36.81	35.28
7					34.16	35.[illegible]

	13.83		7.72					
7+88		1.87		38.76	36.89	35.14	+ 1.75	point R
8.00		3.47			35.29	35.12	+ 0.17	
+50		3.30			35.46	35.04	+ 0.42	
9.00		3.62			35.14	34.96	+ 0.18	
+50		4.05			34.71	34.88	-0.17	
10.		4.15			34.61	34.80	-0.19	
Peg on Slope			4.24		34.52			
	4.12			38.64				
10+25		3.57			35.17	34.76	+ 0.41	point R
+50		3.40			35.24	34.72	+ 0.52	
11.		3.30			35.34	34.64	+ 0.70	
+50		7.20			31.44	34.56	-3.12	
+80		3.12			35.52	34.51	+ 1.01	point R.
+97		2.50			36.14	34.48	+ 1.66	" "
12.50		8.30			30.34	34.40	-4.06	
			6.71		31.93			
	9.16			41.09				
13.00		5.58			35.51	34.32	+ 1.19	R
+50		4.63			36.46	34.24	+ 2.22	
14.		5.20			35.89	34.16	+ 1.73	
+50		6.33			34.76	34.08	+ 0.68	R
15		6.28			34.81	34.00	+ 0.81	
					36.77			

Sta.	0.23			37.00	36.77			
15+50		3.03			33.97	33.92	+0.05	
16.		3.63			33.37	33.84		-0.47
+50		4.20			32.80	33.76		-0.96
17.		3.30			33.70	33.68	+0.02	
+06		2.85			34.15	33.67	+0.48	
+50		2.76			34.24	33.60	+0.64	
18.		3.55			33.45	33.52		-0.07
Sig-			3.03		33.97			
	2.45			36.42				
18+50		5.90			30.52	33.44	-2.92	
19		6.57			29.85	33.36		-3.51
+50		7.58			28.84	33.28		-4.44
20		6.00			30.42	33.20	✓	-2.78
+50		11.80			24.62	33.12		-8.50
+80		2.75			33.67	33.07	+0.60	
+78		2.12	2.12		34.30	33.07	+1.23	
	2.62			36.92				
21		4.72			32.20	33.04		-0.84
+50		4.60			32.32	32.96		-0.64
22		5.45			31.47	32.88		-1.41
+50		5.60			31.32	32.80		-1.48
23					30.12	32.72		
Sig					32.30	✓		

17
16
102
12
2.72

3640
272
33.68

33.28
28.84
5.44

36.40
3.20
33.20

Highest part of R

9.77
5.30
4.47

24

	3.68			35.98	32.30
23+50		4.95			31.03
24		3.60			32.38
+50		6.40			29.58
25		5.40			30.58
+50		6.53			29.45
26.		6.90			29.08
Jog.			2.20		33.78
	0.0			33.78	
26+40		3.00			30.78
26.80		5.20			30.78
Inn			11.21		22.57
	3.55			26.12	
27		6.90			20.22
+22		10.40			15.72
27+62		7.60			18.52
28.00		5.90			20.22
		10.40			15.72
28+22		8.30			17.82
+50		9.90			16.22
29.		7.75			18.37
+40		9.47			16.65
					25.46
					32.42
					43.57
					0.21

In Inn

32.64	- 1.61
32.56	- 0.18
32.48	- 2.90
32.40 ✓	- 1.82
32.32	- 2.87

25
16
150
25
400

3600

Rock point — 32.40 − 30.78 = 1.62

" 3, R

" Columnrid

on Rock in place — 30.78 − 16.65 = 14.13

on big Rock " " R

" bed of Run 27+72

X on Stone by Road.

34.74 − 16.81 = 17.91

26.40 − 16.65 = 19.75

✓ B

Grades for flume line

Sta	F. S.	Int.	F. S.	H. I	Elev.
	2.42			38.82	36.40
+ 0.50		2.50			36.32
1.00		3.40			35.41
1.50		4.01			34.81
1+95		1.83		~~36.99~~	36.99
2.		2.11			36.71
2+50		3.52			35.30
3.		3.71			35.11
3+50		4.06	4.06		34.76
	4.98			39.74	
4.		5.68			34.06
+18		6.14			33.60
+35		2.39			37.35
4+50		4.42			35.32
5.		4.69			35.05
+50		6.08			33.66
6.			5.50		34.24
	4.04			38.28	
+50		4.87			33.41
7.		4.09			34.19
+50		4.52			33.76
+88			5.21		33.07
	5.68			38.75	
8.					34.11
+5					34.96

for Chevrings to opp. Camp

Grade		
36.40		Bottom of flume at dam.
36.32		
36.24	-0.82	
36.16	-1.35	
36.09	+0.90	Earth — angle R
36.08	+0.63	Rock.
36.60	-0.70	
35.92	-0.81	
35.84	-1.08	
35.76	-1.70	
35.73	-2.13	— angle R
35.70	+1.65	
35.68	-0.36	
35.60	-0.55	
35.52	-1.86	
35.44	-1.20	
35.36	-1.95	angle R
35.28	-1.09	
35.20	-1.44	
35.15	-2.08	angle R
35.12		
35.		

Sta	B.S.	Int.	F.S.		
9.		3.72		38.75	35.03
+50		4.57			34.18
+80.		4.35			34.51
+82		4.67			34.08
10.		5.03			33.72
+50		5.25			33.50
11.			5.18		33.57
	1.21			34.78	
+50		4.00			30.78
12.0		3.01			31.77
+22		6.35	6.35		28.43
	10.35			38.78	
+29		4.06			34.72
12+50		9.22			29.56
13.		8.61			30.17
+50			6.28		32.50
	7.74			40.24	
14		7.98			32.26
+50		6.92			33.32
15.		5.29			34.95
+50		6.18			34.06
16.		6.88	6.88		33.36
	5.61			38.97	
+50					32.82

34.96	+0.07		
34.88		-0.70	
34.80			B.M.
34.83		-0.75	angle L
34.80		-1.08	
34.72		-1.28	-1.22
34.64		-1.07	
34.56		-3.78	
34.48		-2.71	
34.45		-6.02	angle R
			angle
34.43			point R.
34.40		-4.84	
34.32		-4.15	
34.24		-1.74	
34.16			
34.16		-1.90	
34.08		-0.66	
34.00	+0.95		
33.92	+0.14		
33.84		-0.48	
33.76			

17.00		4.61		38.97	34.36	33.68	+0.68		
+50		4.67			34.30	33.60	+0.70		
18.		4.85			34.12	33.52	+0.60		
+50			7.93		31.04	33.44		-2.40	angle R
	4.48			35.52					
~~19+00~~		5.50			30.02	33.36		-3.34	
19+50		6.95			28.57	33.28		-4.71	
20.00		5.16			30.36	33.20		-2.84	angle L
+50		10.88			24.64	33.12		-8.48	
BM.		1.30			34.32	33.07			
20+80		2.84			32.68	33.07		-0.39	angle R
	2.80			35.48					
21.		4.50			30.98	33.04		-2.06	
+50		3.00			32.48	32.96		-0.48	
22		2.84			32.64	32.88		-0.28	angle L
+50		2.85	2.85		32.63	32.80		-0.17	" L
	3.68			36.31					
23.		5.35			30.96	32.72		-1.76	
+50		5.72			30.59	32.64		-2.05	
24.		4.87			31.44	32.56		-1.12	
+37		5.16		~~1.15~~	31.15	32.50		-1.45	angle L
+50		6.01			30.30	32.48		-2.18	
25.					30.71	32.40			
					34.81				

Grades & Centres for Tunnel

3.28		34.91	31.63
	5.31		
3.35		34.98	31.63
	5.38		
3.48		35.10	31.63
	5.50		
3.73		35.36	31.63
	5.66		
3.51		35.14	31.63
	5.44		
3.63		35.26	31.63
	5.56		
3.56		35.19	31.63

April 17. 1897

B.M.
29.60 = grade
Centres given

April 20.

96

29.60 — 1° high in both in 44 feet.

29.60 — O.K. apl 22
26 ft in from angle 38°.

29.70 — O.K. Centre & grade apl 24
32' beyond angle & 54'
22

29.70 — in 36' beyond angle all apl 27 97
Grades & cen

May 1st 1897

29.70 + centre — 44 ft beyond angle

May 4th

29.70 — beyond angle

29

Tunnel Line on

S/a.

Hub. 0

+45

+95

1+12.5 old axis

Hub. 1+36.5

1+60 New axis

Hub. 1+77.6

209

Hub. 268.2

Hub. 3.372 42°.30' R.

360.0

top.

Flag

April 23 1897

Point on Rock.

Flag

8.5 up hill from old S/a 0. 8.1 of Tunnel Line

8.6

Plug in Rock

1+77.6

1+36.5

old axis draw

1+12.5

Entrance to Tunnel

1+60

Point on Rock


7 log
7 log 150 Contour
1 1/3 to 1
.110
7 log 40/60
1 1/2 to 1
80/120 7 log
.70
.30 Contour
0.0
-10
240'

Measurement across Canon

May 5. 1899

S	80°.42'	80.42
	161.23	80.41.20
	242.04	80.41.20
	322.47	80.41.45
	403.30	80.42
	43.	

80°.41 3/4 = 976.6

80°.41' 3/4 = 976.6.

	976.6
From A to Centre of outside track S. Branch	8.4
" B " " " " N. "	5.0
	990.0

From Hub on W.S. to Hub on E.S.





32

Notes for Derrick Guys

			Rod	Vert.	dist.
No 1 =	A	0.0	2.84	7°30'	281
No 2 =	B.	49°40'	2.38	10°00	232
No 3 -	C	105°15'	3.28	3°40	328
No 4 -	D	165°10	1.99	16°30	184.
No 5	E	205°45'	1.47	30°00	111.
No 6	F	270°30	1.73	24°20	145.



Measurements across Canyon for Stationary Cable

Sta.	1			
	2	0.32	-	11.70 -
"	3			
	4	0.35 -	-	11.65 -

35 ft below Newaxis - in line with back truck of North Trolley - and on Solid Rock back of South Trolley bench -

Grades & Centres in Tunnel

3.71	5.64	35.34	31.63
3.67	5.60	35.30	31.63
3.71	5.64	35.34	31.63
3.67	5.60	35.30	31.63
3.70	5.63	35.33	31.63
3.60	5.53	35.23	31.63
3.65	5.58	35.28	31.63
3.66	5.59	35.34	31.63

June 16. 1897 Grade 29.80 3.71 35.34 31.63 5.54

May 7. 1897

in 55 ft from angle

29.70

grade & centre O.K.

May 11.97

29.70 in 64 ft from angle

Centres given May 14th 97

29.70 — 4" high in Roof

May 21. 1897 ft = 101

29.70 Centres &c

May 28. 1897

Centres given

29.70 116 ft in

May 31.

29.70 Grade given

Bottom 3" high — Centres given

29.70 June 10. 128 in from angle - 148 full

1897 - + centres

29.70

29.80 centres

Levels from Woods

Reservoir to South Bench

Sta					
	4.66			284.66	280.00
		8.66			276.00
Peg.			11.79		272.87
	0.48			273.35	
Peg			11.95		261.40
	0.14			261.54	
Peg on Big R.			11.93		249.61
	1.03			250.64	
Peg on Stm			11.36		239.28
	0.68			239.96	
			11.51		228.45
	0.21			228.66	
			0.94		227.72
	12.50			239.72	
Peg on Stm			0.67		239.05
	11.25			250.30	
			0.32		249.98
	10.68			260.66	
			0.04		260.62
	11.37			271.99	
Peg on Stm			0.57		271.42
	12.12			283.54	
			0.6		283.48
	64.[illegible]				

Approximate Elev Woods Reservoir
1st Instrument inside of Woods Fence 80' fr Res.

on Road near Parodise flat

North side of Road West of P flat

Levels from Woods Reservoir

Continued

6.45			289.93	283.48	✓
		1.63		288.30	on point near Trolley B.
8.66			296.96		
		10.73		286.23	on Point of Rock near Trolley B.
5.59			291.82		
	9.82	~~9.82~~		282.00	B.M on Rock 20 ft East of Pipe –
	11.82			280.00	Mark on Rock = Elev Woods Reservoir
		0.47		291.35	Near pipe
11.26			302.61		
	2.71			299.90	on South Trolley Bench.

36

Derrick No 2.
Notes for Guys &c

May 17

			Vert. ° ′			
No 1	A	00	7.10	- 3.20	720	- 41
No 2.	B.	48°.00	8.58	- 1.50	865	- 27
No 3.	C.	122.62	3.40	+ 12° 30′	300	+ 63
No 4.	D.	172.10	1.92	+ 31°.20	141	+ 85
No 5	E	242.35	1.50	+ 34°.10	120	+ 20 + 75
No 6.	F	284.40	1.36	+ 14.40	388	+ 33 } less 8′ back 12′ to R and 14′ down
+		1°.0 R.	+ 2.67	+ 4.0		

37

Foundation for Trestle work South Bench.

Elevations for Trestle on South Bench

		Rod
Top of Rail		2.17
Height of Rail		0.30
		2.47
Tie	5½	
Str	15½	
Cap	11½	
	32½ =	2.71
		5.18

Frost heart in Centre of bent 9.93 = 4.75 =

Second heart 13.03 = 7.85 =



2.17
.30
2.71
4.75
9.93

2.17
3
2.71
5.18

9.93
3.21½
6.71½
6.31½
13.03
5.18
7.85

Tie 6.
Str 16
Cap 12/34 =

Rod 3.95
2.85
6.80
Rod 6.80

9.93
3.21½
6.71½
6.31½
13.03

6.31½

⊙+2.25 ⊙+2.25
⊙+2.35 ⊙+2.30

⊙+2.15 ⊙+2.30
⊙+2.15 ⊙+2.35

⊙ ⊙
+2.5

4.11.9

7.10¼



38

(N. O. Centre Grade Hubs 20 ft.)

← W. ---

← To old axis 107.0" →

Back of wall

Front of wall

Stream



Measurements Taken on Cement Wall E. Side
June 11, 1897

From Old axis
To back of wall 107' to
Hub on Rock.





Measurement of Loose Rock on Head

Trolley Car — June 8th 1897.

9.3 × 14. × 5.4	=	703.08	
16 × 3 × 5.8	=	278.40	
9.5 × 16 × 5.8	=	881.60	= 1863.08
3 × 5 × 2 1/2	=		37.00
			1900.08
Less 6 × 3 × 4	= 72		144.
" 6 × 3 × 4	= 72		
		Cubfut	1756.08

1756 Cf = 65 Cyds. = 97 Tons.

Levels to give 150' Centers on Axis of dam

11.76			161.76	150.00
	.0	0.46		161.30
12.50			173.80	
		0.98		172.82
7.50			180.32	
		11.40		168.92
0.65			169.57	
		12.35		157.22
0.10			157.32	
		12.6		144.7
0.0			144.7	
0.7		12.1	133.3	132.6
0.2		11.7	121.8	121.6
0.2		11.8	110.2	111.0
0.0		5.0	105.2	105.2
0.6		12.4	93.4	92.8
0.8		12.4	81.8	81.0
0.3		11.8	70.3	70.0
0.0		11.7	58.6	58.6
0.0		11.4	47.2	47.2
		10.3		37.0

Levels taken from B.M. on peg on trail 0/s/o. B. Shop, on Rock

7.3 - Sore 150' ⊙ 10' W. Side Center

45'
15
60
10
70.

1½-1

1½-1

= -40 ⊙ 70' 110' ⊙ Flag S. Side

Flag N Side - 105' - ⊙ 70' - 45'.

17.6 ⊙ Pinnacle line 1' low, and 4' south of Center.

41

Levels to give heights for building Cribbing for Cement wall –

B.S.	Int	F.S.		
0.20			33.87	33.67
		8.04		25.83
1.27			27.10	
	9.80			17.30
	8.04			19.06
0.40			34.07	33.67
	9.07			25.00
0.54			34.21	33.67
	9.21			
	9.40			
0.42		11.95	22.68	22.26
0.58		11.88	11.38	10.80

B.M on big boulder Original B.M.

Top of 2nd post of Cribbing – 30.00
" 17.30
12.8½ = 12.70

= Height given for Elev. top of wall at grade of asphalt.

34.07
25.00
9.07

34.21
25.
9.21

on edge of board – 0.19

30.
19.06
10.94

30
17.30
12.70

12.8½

Levels on Pipe Line from South Drainage Beach towards Wards Reservoir to find air. bound places.

	5.60			287.80	282.	B.M. on Rock near water pipe on Line from Wards Res.
	0.46		11.71	276.35	275.89	
32+10		9.00			267.35	No.1 Corner where pipe turns down hill
			9.62		266.73	In
	3.21			269.94		
~~1+30~~ 30+30		3.20			266.74	No 2. around point of Rock
200' 29+60			1.25		268.79	No 3. opposite big boulder
	6.16			274.95		
260' 29-		7.25			267.70	No 4- in bend-
~~300~~ 28+60		6.00			269.	No 5 "
~~550~~ 26+35			1.40		273.55	No 6. in bend-
	3.63			277.18		
~~600~~ 25+00		6.25			270.93	271. No 7 on smooth Rock face opp. Bath House
~~640~~ 24+70		5.25			271.93	No 8 " " "
Sun 24+15			7.95		269.23	No 9 " " "
	2.61			271.84		
23+50		3.35			268.50	No 10 " " "
22+50		0.30			271.5	No 11 in bend beyond "
~~H 21~~ 20+95			1.27		270.57	No 12 Near big R beyond Sawyers tent
	4.47			275.04		
19+60		4.7	~~4.70~~		270.3	No 13
18+30			4.52		270.52	No 14 on point West of Paradise Flat-
	6.37			276.84		
			11.94		264.90	

16

Assume 276 as water Elev. in Reservoir—

	1.14			266.04	264.90	
15+80		4.54			261.5	No 15-
15+03			10.32		255.72	No 16 at angle where pipe turns down Green Bank
Paradise	0.34			256.06		
Flats 14+05			11.87		244.19	14+55 Taps No 17 Near big Rock below 2 tents
	0.16			244.30		
			10.63		233.67	hey and P. F
	1.22			234.69		
			11.04		223.64	
	4.17			227.81		
11-		5.9			221.9	No 18: East of Paradise Flat.
10+40		5.			222.8	No 19
9+60		9.			218.8	No 20 Near Fence East of Paradise Flat
Pigeon Rock			3.65-		224.16	
	10.13			234.29		
			0.07		234.22	on Flat Rock near Road to Wards
	11.93			246.15		
			0.04		246.11	
	6.92			253.03		
5+60		1.1			251.9	No 21 Near Wards House
	9.85		1.07	261.86	262.01	
3+25	11.73		0:38	272.26	261.53	No 22
1.50	10.72		0.16	282.82	272.10	No 23
		8.7			274.1	No 24 at Shortcut to Wards Near Wards
					278.52	Water

Derrick No 3

2.84

	Angle	Rod	Vert.	dist.	
No 1	00	2.84	+ 8°.00	290	On Sawn Rock as Guy No 1 Derrick No 1 } ~~add 3'~~
" 2	83°.30	1.72	+30°.20	138	north end of Rock when ⊙ is " 2'
" 3	163.00	2.75	+7°.40	280	add 3'
" 4	218°.00	3.85	10°.40'	355	on Rock with ⊙ above Tunnel add 2'
" 5	253°.10	2.86	16°.20'	275	on boulder NEar Flag (110) alt " 1
" 6	295.00	3.12	12°.00'	315	on boulder as Guy No 6 Derrick No 1

45

Extending Line between Jno Wards place and E. A. Babcocks property

West Line of Jno Wards

2640
1636
1604

1200'

70°

425'

820

2648

Blk Stub

2640

Field

2177

1836

1636

278

68

405'

Wards old House

1358

1320

369

9890

271

718

1320

693

229'

1 mile

Wards East Line

Wards House

43° 47'

Big Rock 745'

681

Hub 667

W. Ire fence

600

Swing

573

560

Jap

535

29.4

533 Hub

Small tent

Large tent

450 pg

55'

302

Barn

248 = 180 Contra

Monument No 1

7.00
4.23
2.77
1358
1636
700
430
470

85
163
54
302
573
145
718

7.00
3.32
3 68
700
160
540
163½
2177
471
2648

365
85
45°

163
85
248

46 Meander of Woods Fence line

△	1201		R.				2.7	1201
				N. 74° E	N. 75 17 E			113
	1088	9° 41'	R.	P			1.0	1088
	1084							4
	1037				N. 66.05 E		0.6	1084
	970			N. 64½ E				47
⊙	951.6	107°.54	R				⊙ 0.0	1037
	828						1.0	67
								970
	771				N. 41°.51 W		2.0	18.4
	719			N. 43¼ W.				951.6
⊙	676	33°.37	L				5.0	12 3.6
	586				N. 8°.14 W			828
△	508	78°.29	L	N. 9½ W.			74	51
	505							771
				N. 69½ E	N 70°.15 E		7.8 ⊙	57
△	336	23°.25	L					719
	275						@3.5 ⊙	43
	198				S 86°.20 E		2.0	676
	149			N. 87½ E				90
△	128	8°.40	L				at fork 3.0 ⊙	586
	77							78
	+20			S. 78° E	S. 77.40 E			508
667	= 0 =	64°.30	L				1.0	
				S. 13° E	S. 13°.05 E		3.5	172
								336
							29.0	61
								275
							16.0	77
								198
							5.0	149
								49
							2.3	21
								128
							1.5 ⊙	
							18 ⊙	
							In line of section ⊙ 15' ⊙ ⊙ Offset to fence	

And meanding around fence line
Commencing at point 667 feet South of ½ Corner on West line land

47

N. 13° W.

△ 1419.0 56°.0' R.

N. 69 3/4° W N 68.46 W

△ 1210.6 35°.40' R.

S. 75°.34 W

1069 62°.35' L

⊙ 1034 N. 41.5° W

Return to Stub Sta 95°1.6 ▽ Center back Tangent

~~2186~~
2141

1941 92°.55' to Woods Chimney 92.92

1908

1717

1661

1561 1°.23' L

1861

N. 76 1/2 E N 77.30

1201 2°.16' R.

To Connection with Land Line ⊙ at 50' South of Monument

1941
247
2188

1661
247
1908

14190
208.4
12106
141.6
1069
35
10340
82.4
95°1.6

13'.

Woods Line

10'.

1.8

92°.58'

2'.0

86°.40'

Woods House

Angle 86°.40' from Back Tang.

1.6

2.4

2.7

1941
280
1661
1717
1661
100
1561
2000
1361
160
1201

4.87
1.60-
3.22

A = 5.85
B. 6.70
1.65-

B. 4.87
A- 3.22

Measurements taken on ground July 11 97

For Line of tunnel and intersection with axis of dam

N.B. Supposed corner of Wall - Not certain



1 Miners Inch of water = 9 Gals per Minute
1 " " = 1440 Gals per day
1 " " = 192 Cub ft per day -

2 Caps 12×12 – 22
4 Sills 7×16 – 24
2 Posts 12×12 – 10
2 " " 6
2 Braces 3×12 22
2 " " 10
for Trestle work South Bench

24
99
36

Fittings

2 90° Ells.

1-16×12 C.I. reducer
1-12" vitrified elbow 10°
1-16" " " "
16" C.I. gate valve ?

6-10" Suction Pipe
23'
1 90° Ell flanged.
Holes in side bell will take 8"55 ? in diameter

1 check valve 10" gate valve
2 45° Ells



TRAVERSE TABLE FOR TRANSIT BOOK.

From 1° to 90° for a distance of 100.

Degrees.	DEGREES.		¼ DEGREE.		½ DEGREE.		¾ DEGREE.		Degrees.
	Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	
0			100.00	0.44	100.00	0.87	99.99	1.31	89
1	99.98	1.75	99.98	2.18	99.97	2.62	99.95	3.05	88
2	99.94	3.49	99.92	3.93	99.91	4.36	99.88	4.80	87
3	99.86	5.23	99.84	5.67	99.81	6.10	99.79	6.54	86
4	99.76	6.98	99.73	7.41	99.69	7.85	99.66	8.28	85
5	99.62	8.72	99.58	9.15	99.54	9.58	99.50	10.02	84
6	99.45	10.45	99.41	10.89	99.36	11.32	99.31	11.75	83
7	99.25	12.19	99.20	12.62	99.14	13.05	99.09	13.49	82
8	99.03	13.92	98.97	14.35	98.90	14.78	98.84	15.21	81
9	98.77	15.64	98.70	16.07	98.63	16.50	98.56	16.93	80
10	98.48	17.36	98.40	17.79	98.33	18.22	98.25	18.65	79
11	98.16	19.08	98.08	19.51					
12	97.81	20.79	97.72	21.22	97.99	19.94	97.90	20.36	78
13	97.44	22.50	97.34	22.92	97.63	21.64	97.53	22.07	77
14	97.03	24.19	96.92	24.62	97.24	23.34	97.13	23.77	76
15	96.59	25.88	96.48	26.30	96.81	25.04	96.70	25.46	75
16	96.13	27.56	96.00	27.98	96.36	26.72	96.25	27.14	74
17	95.63	29.24	95.50	29.65	95.88	28.40	95.76	28.82	73
18	95.11	30.90	94.97	31.32	95.37	30.07	95.24	30.49	72
19	94.55	32.56	94.41	32.97	94.83	31.73	94.69	32.14	71
20	93.97	34.20	93.82	34.61	94.26	33.38	94.12	33.79	70
21	93.36	35.84	93.20	36.24	93.67	35.02	93.51	35.43	69
22	92.72	37.46	92.55	37.86	93.04	36.65	92.88	37.06	68
23	92.05	39.07	91.88	39.47	92.39	38.27	92.22	38.67	67
24	91.35	40.67	91.18	41.07	91.71	39.87	91.53	40.27	66
25	90.63	42.26	90.45	42.66	91.00	41.47	90 81	41.87	65
26	89.88	43.84	89.69	44.23	90.26	43.05	90.07	43.44	64
27	89.10	45.40	88.90	45.79	89.49	44.62	89.30	45.01	63
28	88.29	46.95	88.09	47.33	88.70	46.17	88.50	46.56	62
29	87.46	48.48	87.25	48.86	87.88	47.72	87.67	48.10	61
30	86.60	50.00	86.38	50.38	87.04	49.24	86.82	49.62	60
31	85.72	51.50	85.49	51.88	86.16	50.75	85.94	51.13	59
32	84.80	52.99	84.57	53.36	85.26	52.25	85.04	52.62	58
33	83.87	54.46	83.63	54.83	84.34	53.73	84.10	54.10	57
34	82.90	55.92	82.66	56.28	83.39	55.19	83.15	55.56	56
35	81.92	57.36	81.66	57.71	82.41	56.64	82.16	57.00	55
36	80.90	58.78	80.64	59.13	81.41	58.07	81.16	58.42	54
37	79.86	60.18	79.60	60.53	80.39	59.48	80.13	59.83	53
38	78.80	61.57	78.53	61.91	79.34	60.88	79.07	61.22	52
39	77.71	62.93	77.44	63.27	78.26	62.25	77.99	62.59	51
40	76.60	64.28	76.32	64.61	77.16	63.61	76.88	63.94	50
41	75.47	65.61	75.18	65.93	76.04	64.94	75.76	65.28	49
42	74.31	66.91	74.02	67.24	74.90	66.26	74.61	66.59	48
43	73.14	68.20	72.84	68.52	73.73	67.56	73.43	67.88	47
44	71.93	69.47	71.63	69.78	72.54	68.84	72.24	69.15	46
45	70.71	70.71			71.33	70.09	71.02	70.40	45
Degrees.	Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Degrees.
	DEGREES.		¾ DEGREE.		½ DEGREE.		¼ DEGREE.		

Published by H. S. Crocker & Co., Stationers, Drawing Materials, Mathematical Instruments, etc., San Francisco.