
W233
DAST
233
JEWEL BOOK
No. 889

#233

MICROFILMED

Our Leather Bound Engineers Note Books are carried in the following rulings:

No. 380 LEVEL BOOK. Left and Right Hand Page the same as Left Hand Page of this Book.

No. 382 FIELD BOOK. Left Hand Page as in this Book, Right Hand Page 4 x 4 to the inch, Center Line Red.

No. 384 MINING TRANSIT BOOK. Left Hand Page as in this Book, Right Hand Page 8x8 to the inch, Center Line Red.

No. 385 FIELD BOOK. Left Hand Page as in this Book, Right Hand Page 8 vertical and 4 horizontal lines to the inch, Center Line Red.

We also carry the Note Books listed above, bound in extra strong Fabri-Hide (otherwise the same quality of book), which can be furnished at a somewhat lower price.

In ordering Fabri-Hide covered books, add the letter *"F"* to catalog number.

THE FREDERICK POST CO.

ENGINEERING and DRAFTING SUPPLIES

IRVING PARK STATION

CHICAGO, ILL.

92 FIFTH ST.
PORTLAND, ORE.

79 NEW MONTGOMERY ST.
SAN FRANCISCO, CAL.

AGENTS FOR

"BERGER" TRANSITS and LEVELS
"GURLEY" SURVEYING and HYDRAULIC INSTRUMENTS
"CHICAGO" STEEL TAPES, etc.

Levels and Slope Stake Cross Sections of Road from Lower Otay Dam along south side to upper end of Lake.

Surveyed by REWard - 1927.

Pages - 2 - to 63.

List of Drainage Pipe for Construction — Page - 78

Septic Tank + Sewer 65-67
Settling Tank - Fish Tables 68

(2) Levels on "A" Line Road Survey at Lower Otay Dam to E. end Lake.

+	H.I.	−	Elev.
			492.20 Elev.

Elev. = Roadway on Top Lower Otay Dam.

8.00	500.20		
		4.44	495.76 TP.
7.21	502.97		
		0.38	502.59 B.M.

B.M. - Spk. in Fence Cor. 6' Rt. 0+00 - E. End Bridge.

12.78	515.37		

Sta.	Grade	End Area Cut Sec.	Lt.	℄	Rt.
0+00	502.10		0.0	0.0 13.3	0.0
+50	504.4	(6.6)		FO 5 11.5	CO 2 10.0
1+00	506.7	(5.8)		FO 2 8.9	CO 3 3.0 C1 5 10 C1 6 10.8
+25	507.8	(11.1)	0.0 7.0	CO 4 7.2	CO 5 5 C1 9 10 C2 2 11.1
+50	509.00	(6.7)	0.0 2.5	CO 3 6.1	CO 6 7 C1 1 10 C2 1 11.1
2+00	510.0	(22.5)	0.0 6.0	C1 4 4.0	C1 8 3 C1 8 10 C2 0 11.0
+44	510.9	(27.3)	0.0 2.0	C1 6 2.9	C2 5 4 C2 7 10 C2 8 11.4
+50	511.0	(21.8)	0.0 0.5	CO 4.3	C2 0 2.5 C2 6 10 C2 6 11.3

+4.6 0/0

+2.0 0/0

= 0 - 92 0

498.2
17.2
West End Bridge

515.37 H.I.

East End Bridge
502.1
503.9
506.5
508.2
509.3
511.4
512.5
511.1

Nov. - 9 - '27
Ward - Notes
Duermit - Inst
Mc Bain - Rod

③	+	H.I.	−	Elev.
		515.37 ✓		
+85			3.5	
3+00			3.7	
3+39.35 △			2.7	
+50			2.6	
			0.30	515.07 TP.
	8.53	523.60 ✓		
4+00			7.2	
+50			5.1	
4+81.11 △			~~6.0~~	
+75				
5+00			~~4.3~~	
+30			4.4	
+50			2.2	
6+00			1.4	
+25			0.6	

℄ Grade		Lt	℄ 515.37 H.I.	Rt
511.7	(4.2)	0.0 1.0	CO2 3.5 (511.9)	CO2 CO1 10 10.4
512.0	(0.8)		FO3 3.7 (511.7)	0.0 C0.3 CO1 5.0 10 10.2
	(0.0)	+20 = 0.0 − 10 Rt.		
512.8 Ex+12.8 Lt.		FO1 5	FO1 2.7 (512.1)	FO2 10
513.00 Lt set 8'	(0.0)	FO1 4	FO2 2.6 (512.8)	0.0 10.0
			523.60 H.I. ✓	
515.0	(48.2)	0.0 C1.2 10.0 6	C1+ 7.2 (516.4)	C1.8 C4.8 C5.2 C6.4 4 8 10 13.2
517.0	(38.2)	0.0 C1.2 9.0 6	C1.5 5.1 (518.5)	C2.5 C4.6 C5.5 6 10 12.8
518.2	(22.4)	0.0 9.0	CO.6 (519.2)	CO1 C3.2 C3.7 C4.2 4 6 10 12.0
519.00	(31.8)	0.0 8.0	CO1 4	C2.4 C3.8 C4.7 4 10 12.2
519.8	(24.5)		FO.4 4.4 (519.4)	0.0 C1.2 C3.5 C4.3 0.5 1 10 12.2
520.3	(26.2)	0.0 1.0	C1.1 2.2 (521.4)	C3.4 C3.8 10 11.9
521.5	(24.7)	0.0 2.5	CO1 CO1 1.4 (522.2)	C1.8 C3.6 C4.2 5 10 12.1
522.1	(24.7)	0.0 1.0	CO2 0.6 (523.0)	C3.3 C4.2 10 12.0

+2.0 %

+4.0 %

+2.5-4.5 %

④	+	H.I.	−	Elev.
		523.60 ✓		
+50			1.7	
			0.80	522.80 ✓ T.P.
	3.70	526.50 ✓		
7+00			2.1	
+50			1.2	
+75			1.1	
8+00			2.7	
+50			3.7	
9+00			8.1	
+20			9.2	
+50			12.9	
10+00			16.5	
+25			17.1	
+50			15.0	

+2.54.5 % ℄ Grade

522.8 (16.5)

+25 524.73

524.1 (8.1)

525.1 (11.7)

100' V.C.

524.9 (16.4)

524.1 (10.0)

+75 522.75

521.1 (33.0)

−6.50 %

517.9 (13.2)

516.6 (20.4)

514.6 (0.1) =0.0

+75 513.00

50' V.C.

512.0

512.30

+3.70 %

513.2 (0.0)

LT

CO⁸ 8.4 | CO⁸ 8

0.0 3.0

0.0 1.0

0.0 4.0

0.0 2.5

F4⁵ 14.7 | F3³ 8

℄ RT

523.60 H.I.

FO⁹ 1.7 (521.9) 0.0 2.0 | C1⁴ 4 | C2⁸ 10 | C3⁶ 11.8

526.50 H.I.

CO³ 2.1 (524.4) | CO⁵ 7 | C1.8 10 | C2³ 11.1

CO² 1.2 (525.3) 0.0 1.0 | C1³ 5 | C1⁶ 10 | C1⁶ 10.8

CO⁵ 1.1 (525.4) | C2⁰ 8 | C2² 10 | C2² 11.1

FO³ 2.7 (523.8) 0.0 2.0 | C2² 10 | C2⁴ 11.1

C1⁷ 3.7 (522.8) | C2⁵ 10 | C2⁸ 11.4

CO⁵ 8.1 (518.4) | C2⁶ 10 | C3⁰ 11.5

CO² 9.2 (517.3) 0.0 2.5 | C2⁸ 10 | C2⁸ 11.4

F1⁰ 12.9 (513.6) 0.0 9.0 | CO² 10 | CO² 10.1

F2⁰ 16.5 (510.0) | F1⁵ 8 | F1³ 10.0

F2⁹ 17.1 (509.4)

F1⁷ 15.0 (511.5) 0.0 13.0

⑤	+	H.I.	−	Elev.
		526.50 ✓		
+90			9.3	
11+00			9.0	
"A" 11+28.17	P.O.T.		9.5	
"B" 0+00	△			
+50			9.4	
			10.79	515.71 ✓ B.M. #2

+3.70% — 50' V. C.

B.M. on Hub at Property Fence 30' Lt. 11+28.17

2.99 518.70

+7.0			4.1	
12+00			5.8	
+50			8.1	
13+00			9.6	
+25			8.8	
+50			10.4	
+80			10.2	

100' V. C.

Grade		Lt		℄		Rt	
				526.50 H.I.			
514.7	(49.3)	C1 9 / 10.5	C1 4 / 10	C2 5	517.2 9.3	C3.0 / 10	C2 5 / 11.3
515.07	(49.1)	C2 0 / 11.0	C2 2 / 10	C2 4	517.5 9.0	C2 5 / 10	C2 5 / 11.3
515.5	(28.4)	CO 7 / 10.4	CO 7 / 10	C1 5	517.0 9.5	C1 8 / 10	C1 8 / 10.9
515.08	(34.6)	0.0 / 12.0	CO 7 / 10	C2 2	517.1 9.4	C2 7 / 10	C2 7 / 11.1
				518.70 H.I.			
514.4	(3.3)	0.0 / 2.0	CO 2	514.6 4.1		CO 4 / 10	CO 5 / 10.3
513.3	(1.3)	FO 5 / 10	FO 4	512.9 5.8		0.0 / 6.0	CO 9 / 10 — CO 6 / 10.3
511.4	(2.2)		FO 8	510.6 8.1		0.0 / 3.0	CO 6 / 10 — CO 6 / 10.3
509.58	(2.5)		FO 5	509.1 9.6		0.0 / 4.0	CO 8 / 10 — CO 9 / 10.4
509.3	(12.7)	0.0 / 1.5	CO 6	509.9 8.8		C1 7 / 10	C1 8 / 10.9
509.1	(1.1)		FO 8	508.3 10.4		0.0 / 7.0	CO 7 / 10 — CO 8 / 10.4
	(0.0) +60						
510.0			FI 5	508.5 10.2		+60 = 0.0 − 10 Rt.	

⑥	+	H.I. 518.70 ✓	−	Elev.	
+83			11.4		
Drain					
+87			11.2		
+92			10.1		
14+00			9.6		
+20			7.6		
+50			4.6		
		✓	0.57	518.13	T.P. ✓
	11.78	529.91 ✓			
15+00			9.7		
+20			8.0		
+50			6.6		
16+00			3.1		
+50			2.0		
+80			2.7		

100' V. C.

+ 7.0 %

+75 100' V. C. +75

Grade	Lt	℄	Rt
		518.70 H.I.	
510.1		F2⁸ 11.4 507.3	
510.4		F2⁹ 11.2 507.5	
510.8	F2⁷ 12.6	F2⁷ 9 F2³ 10.1 508.6	F3⁷ 7 F3¹ 9 F2⁶ 13.0
511.25		F2² 9.6 509.1	
512.7		F1⁶ 7.6 511.1	
514.8 (0.0)		0.0 10.0 F0² 4.6 514.1	
		529.91 H.I.	
518.3 (38.1)	C2² 11.1	C2² 10 C1² 9.7 520.2	C1³ 10 C1² 10.6
519.7 (43.4)	C2⁹ 11.2	C2⁷ 10 C2³ 8.0 521.9	C1⁵ 10 C1⁴ 10.7
521.8 (34.1)	C2² 11.1	C2² 10 C1⁵ 6.6 523.3	C1³ 10 C1² 10.6
523.50			
524.9 (38.7)	C2¹ 11.1	C2¹ 10 C1⁹ 3.1 526.8	C1⁵ 10 C1⁵ 10.8
525.4 (53.8)	C2⁴ 11.2	C2⁴ 10 C2⁵ 2.0 527.9	C2⁷ 10 C2⁸ 11.4
524.50			
524.3 (62.4)	C2² 11.1	C2³ 10 C2⁹ 2.7 527.2	C3⁵ 10 C3⁶ 11.8

Nov. 28 - '27
Ward - Notes
Duermit - Rod
McBain - Chn
Slope Stakes

(7)	+	H.I.	−	Elev.
		529.91 ✓		
17+00			5.6	
17+26.47 Δ			10.0	
			9.95	519.96 TP. on P.I.
	2.67	522.63 ✓		
+50			~~3.5~~	
+70			~~4.1~~	
17+79.03 E.C.				
17+84.30 P.O.T.				
18+00			3.5	
+50			5.1	
19+00			7.4	
+25			8.4	
+50			8.2	
20+00			7.0	
+50			5.5	
			10.43	512.20 ✓ B.M. #3
B.M.-Spk. in Hub 25' Lt. 20+58				
	10.84 ✓	523.04		

Curve Run in.

℄ Grade	Lt	℄	Rt
		529.91 H.I.	
	(31.5)		
523.3		0.0 C0 5 ~~C0 6~~ 5.6 C1 4 C2 6 C2 8 (524.3)	
		11.0 10 ℄ 10 11.4	
522.0	(11.1)	~~F0 1~~ 10.0 0.0 C2 0 C2 1 (519.9)	
		℄ 10 11.1	
		522.63 H.I.	
520.8	(3.7)	~~F1 7~~ 3.5 F1 2 0.0 C1 3 C1 4 (519.1)	
		℄ 5.0 10 10.7	
519.8	(2.5)	F1 4 4.1 0.0 C1 0 C1 2 (~~518.6~~)	
519.50		℄ 5.5 10 10.6	
518.7	(15.1)	0.0 C0 4 3.5 C2 2 C2 5 (519.1)	
		2.0 10 11.3	
516.8	(25.1)	0.0 C0 7 5.1 C3 3 C3 5 (517.6)	
		4.0 10 11.8	
515.83			
515.1	(12.3)	0.0 C0 4 7.4 C2 1 C2 6 (515.2)	
		1.0 10 11.2	
514.7	(12.2)	F0 5 8.4 0.0 C2 6 C2 8 (514.2)	
		2.0 10 11.4	
514.6	(9.0)	F0 2 8.2 0.0 C1 8 C2 0 (514.4)	
		1.0 10 11.0	
515.0			
515.5	(11.7)	0.0 C0 4 7.0 C2 2 C2 4 (515.6)	
		1.0 10 11.2	
516.5	(20.1)	2.0 C0 6 5.5 C2 8 C3 2 (517.1)	
		3.0 10 11.6	

+75 −3.87 4% 100' V.C. +75 +2.0 %

24.73 Dist.

⑧	+	H.I. 523.04 ✓	−	Elev.
21+00			5.3	
+50			4.4	
22+00			5.4	
+50			8.9	
23+00			9.0	
+50			8.8	
+75			8.0	
24+00			7.2	
			8.19	514.85 T.P.
	3.94	518.79 ✓		
+25			2.7	
+50			3.0	
25+00			5.0	
+25			5.7	

+2.0%
+25 sag
+75
−3.0%
+1.0%
100' V. C.
−6.0%

Grade	Lt.	℄ 523.04 H.I.		Rt
517.5	(13.3)	0.0 CO² 5.3 (517.7) C2²	C2⁴	C2⁴ 11.2
518.00		1.0	10	
518.2	(17.2)	0.0 CO² 4.4 (518.6) C2⁶	C2⁸	
517.75		2.0	10	11.4
517.0	(17.5)	0.0 CO⁶ 5.4 (517.6) C2⁴	C2⁶	
		3.0	10	11.3
515.5	(2.1)	F1⁴ 8.9 (514.1) 0.0	CO⁹	C1¹
			6.0	10 10.6
514.00	(9.3)	0.0 9.0 (514.0) C1⁷	C1⁹	
			10	11.0
514.5	(6.7)	F0² 8.8 (514.2) 0.0	C1⁵	C1⁷
			2.0 10	10.9
514.8	(10.0)	0.0 CO² 8.0 (515.0) C1⁶	C1⁶	
		4.0	10	10.8
515.00	(8.8)	0.0 CO² 7.2 (515.2) C1⁴	C1⁶	
		2.0	10	10.8
		518.79 H.I.		
515.0	(20.7)	0.0 C1¹ 2.7 (516.1) C1²	C1³	
		7.0	10	10.7
514.6	(27.7)	0.0 C1² 3.0 (515.8) C3⁰	C3³	
		7.0	10	11.7
512.50	(29.3)	0.0 C1³ 5.0 (513.8) C3³	C3.7	
		5.0	10	11.9
511.00	(18.5)	0.0 C2¹ 5.7 (513.1) C4⁴	C5⁰	
		10.0	10	12.5

⑨	+	H.I. 518.79	−	Elev.
+50			8.2	
+85			15.1	
Drain				
+90			12.3	
26+00			9.3	
+15			6.9	
+50			1.7	
+60			1.1	
27+00			1.7	
+25			3.0	
+50			3.3	
			6.64	512.15 T.P. on P.I.
	10.87	523.02		
+75			7.4	
28+00			7.6	

100' V.C.

+25

+6.0%

50' V.C.

+1.0%

℄ Grade		Lt	℄	Rt
			518.79 H.I.	
509.9	(22.0)		0.0 CO⁷ 8.2 510.6 C3⁰ 10	C3⁴ 11.7
	(0.0)	+60	503.1 +60 = 0.0–10.0 Rt.	
509.6		F6⁶ 17.9	F5⁹ 15.1	F4⁴ 14.6
509.7			F3² 12.3 506.5	
	(0.0)	+95	509.5 +95 = 0.0–10.0 Rt	
509.9	(5.7)		F0² 9.3	0.0 3.0 C1⁴ 10 C2⁴ 11.2
510.5	(38.2)		0.0 C1⁴ 6.9 511.9 10.0	C4.0 10 C4⁷ 12.1
511.00				
512.50	(99.8)	C1⁸ 10.9	C2² 10 C4⁶ 1.7 517.1	C6.2 10 C7⁰ 13.5
513.0	(103.9)	C2³ 11.2	C2⁴ 10 C4⁷ 1.1 517.7	C6⁷ 10 C6⁰ 13.0
514.25	(59.8)		0.0 12.0 C2⁸ 1.7 517.1	C4⁶ 10 C5² 12.6
514.5	(35.7)		0.0 7.0 C1³ 3.0 515.8	C4⁰ 10 C4⁶ 12.3
514.8	(19.6)		0.0 3.0 CO⁷ 3.3 515.5	C2⁶ 10 C3¹ 11.6
			523.02 H.I.	
515.0	(17.6)		0.0 3.0 CO⁶ 7.4 515.6	C2⁴ 10 C2⁸ 11.4
515.3	(9.8)		0.0 1.0 CO¹ 7.6 515.4	C1⁷ 10 C2⁰ 11.0

(10)

	+	H.I. 523.02	−	Elev.
+25			7.6	
+50			5.8	
29+00			5.8	
+25			4.5	
+50			6.1	
+80			5.8	
30+00			6.1	
+25			7.1	
+50			6.2	
+60			3.9	
+80			2.9	
31+00			1.8	
+35			3.1	

℄ Grade	Lt		Δ 523.02 H.I.		Rt	
515.5	(10.0)		F0+ 7.6 (515.4)	0.0 0.5	C1 9 10	C2 0 11.0
515.8	(28.5)	0.0 5.0	C1+ 5.8 (517.2)		C3 1 10	C3 2 11.6
516.3	(24.8)	0.0 3.0	C0 2 5.8 (517.2)		C3 2 10	C3 5 11.8
516.5	(40.0)	0.0 8.0	C2- 4.5 (518.5)		C3 7 10	C3 8 11.9
516.8	(18.2)	0.0 0.5	C0- 6.1 (516.9)		C3 0 10	C3 4 11.7
517.1	(16.7)	0.0 0.2	C0- 5.8 (517.2)		C2 8 10	C3 2 11.6
517.3	(9.1)		F0+ 6.1 (516.9)	0.0 2.0	C2 0 10	C2 2 11.1
517.5	(5.7)		F1- 7.1 (515.9)	0.0 5.0	C1 9 10	C2 2 11.1
517.8	(17.9)		F1 0 6.2 (516.8)	0.0 2.2	C3 7 10	C3 8 11.9
517.9	(39.5)	0.0 3.0	C1 2 3.9 (519.1)		C5 0 10	C5 4 12.7
518.1	(56.6)	0.0 8.0	C2 0 2.9 (520.1)		C5 8 10	C6 6 13.3
518.3	(70.1)	0.0 10.0	C2 9 1.8 (521.2)		C6 0 10	C7 2 13.7
518.6	(41.5)	0.0 3.0	C1 3 3.1 (519.9)		C5 0 10	C6 4 13.2

(11)

	+	H.I. 523.02	−	Elev.	
+50			2.0		
			11.15	511.87	B.M. #4
B.M. – Top of Boulder			33' Lt	30+88	
	11.56	523.43			
32+00			3.4		
+50			4.7		
+70			4.9		
+90			2.6		
33+00			2.9		
+30			6.1		
+50			7.0		
+75			7.6		
34+00			8.3		
+08			8.8		

℄ Grade	Lt	℄ 523.02 H.I.	Rt
518.75	(48.6) 0.0 6.0	C2 2.0 (521.0) C4.8 10	C5.8 12.9
		523.43 H.I.	
518.1	(56.2) 0.0 5.0	C1.2 3.4 (520.0) C6.0 10	C8.2 14.0
517.50	(33.4) 0.0 5.0	C1.2 4.7 (518.7) C4.0 10	C4.5 12.2
516.5	(50.0) 0.0 6.0	C2.0 4.9 (518.5) C5.6 10	C6.5 13.2
515.5	(121.0) 0.0 14.0	C2.0 C5.3 2.6 (520.8) C7.5 10	C8.8 14.4
515.0	(126.5) C1.2 10.6	C1.3 10 C5.5 2.9 (520.5) C8.5 10	C10.4 15.2
513.5	(109.2) 0.0 10.0	C4.0 6.1 (517.3) C8.7 10	C11.7 15.9
512.5	(88.4) 0.0 8.5	C3.9 7.0 (516.4) C8.2 10	C9.6 14.8
511.3	(122.1) 0.0 10.5	C4.5 7.6 (515.8) C9.5 10	C12.0 16.0
510.0	(124.8) 0.0 9.0	C5.1 8.3 (515.1) C9.3 10	C12.7 16.4
509.6	(110.5) 0.0 8.5	C4.8 5 C5.0 8.8 (514.6) C7.3 10	C8.8 14.4

Slope Stks Not. -29-27
Ward - Notes
Dvernit - Rod
MC Bain - Che

(12)

	+	H.I. 523.43	−	Elev.
+22			17.8	
+32			19.0	
+50			15.4	
+66			9.8	
+85			11.7	
35+00			10.7	
+10			12.1	
			6.95	516.48 B.M. #5
B.M. – On Top Boulder			30' Rt.	35+25
	0.30	516.78		
+25			10.9	
35+34.66 E.C.			16.9	
+50			25.5	
+52			27.4	

Edge Water (10/8/27)
Level used on Channel Soundings
At time of Running ℄.
= Water Level that date.

5% Grade
−5.0
+75
50' V.C.
Level
Level

	Lt	℄ 523.43 H.I.	Rt
508.9	(1.4)	505.6 F33 17.8 0.0 8.0	C1.2 10 C1.7 10.7
508.4	(1.0)	504.4 F42 19.0 0.0 8.0	C0.8 10 C1.1 10.6
507.5	(40.3)	508.0 0.0 0.5 C0.5 15.4	C5.5 10 C7.4 13.7
506.7	(159.0)	513.6 0.0 9.0 C6.2 9.8	C11.2 10 C14.0 17.0
506.25			
505.9	(163.4)	511.7 0.0 12.0 C1.2 10 C5.8 11.7	C11.3 10 C15.2 17.6
505.3	(178.6)	512.7 0.0 12.0 C7.1 10.7	C11.5 10 C13.8 16.9
505.2	(149.3)	511.3 0.0 11.0 C6.1 12.1	C10.4 10 C12.7 16.4
		516.78 H.I.	
505.00	(36.5)	505.9 0.0 2.5 C0.2 10.9	C3.3 8 C6.0 10 C6.2 13.1
	(0.0) +30	499.9 16.9	499.9 +30 = 0.0 − 10 Rt.
		491.3 25.5	
		489.4 27.4	

<Water is 0.8 Higher at time of Levels than at running ℄.>

(13)

	+	H.I. 516.78	−	Elev
35+63			35.4	
+66			42.4	
+82			57.4	
+92			62.4	
36+04			59.4	
+12			55.4	
+14			51.4	
+32			41.4	
+37			34.4	
+45			32.4	
36+55 Edge Water 10/8/27			27.4	

These Elevations were obtained by Soundings from Boat.

Across Arm of Lake.

H.	+	516.78 H.I.	−	Elev
		35.4	481.4	
		42.4	474.4	
		57.4	459.4	
		62.4	454.4	
		59.4	457.4	
		55.4	461.4	
		51.4	465.4	
		41.4	475.4	
		34.4	482.4	
		32.4	484.4	
		27.4	489.4	

(14)

+	H.I.	−	Elev.	
B.M.-on top Boulder 30' Rt. 35+25, 516.48 B.M. #5				
1.96	518.44			
		10.25	508.19	BM #6
B.M. - On top Boulder 40' Rt. 37+00				
11.67	519.86			
36+70		23.5		
+92		16.7		
37+00		14.5		
+10		12.1		
+50		6.7		
38+00		4.4		
+20		2.9		
+50		1.9		
38+65.87 Δ Rt.		0.7		
39+00		3.2		
+50		5.9		

Nov. 14-'27
Ward - Notes
Duermit - Inst.
McBain - Rod

519.86 H.I.

| | Lt. | | | |

(15)	+	H.I.	−	Elev.	
		519.86			
40+00			4.2		
+50			2.4		
			5.85	514.01	T.P.
	5.66	519.67			
41+00			3.3		
+10			2.9		
+35			3.0		
+50			3.5		
+70			5.2		
42+00			6.5		
+20			6.2		
+50			6.7		
43+00			7.2		
+15			7.4		

− 1.50 ℄

+75 — 50' V.C. — +25

℄ Grade	Lt.				℄ 519.86 H.I.		Rt
516.75	(7.1)	C2 2 / 11.1	C2 0 / 10	0.0 / 4.0	Fl 4.2	515.7	
516.0	(32.9)	C4 2 / 12.1	C3 7 / 10	C1 5	2.4	517.5	0.0 / 4.0
					519.67 H.I.		
515.3	(39.1)	C6 4 / 13.2	C4 8 / 10	C1 1	3.3	516.4	0.0 / 3.5
515.1	(54.7)	C7 6 / 13.8	C6 2 / 10	C1 3	2.9	516.8	0.0 / 9.0
514.7	(51.7)	C6 2 / 13.1	C5 3 / 10	C2 0	3.0	516.7	0.0 / 7.0
514.5	(44.3)	C5 5 / 12.8	C4 8 / 10	C1 7	3.5	516.2	0.0 / 6.0
514.2	(17.2)	C3 0 / 11.5	C2 7 / 10	CO 3	5.2	514.5	0.0 / 1.0
513.8	(6.8)	C1 8 / 10.9	C1 7 / 10	0.0 / 3.0	Fo 6	513.2	6.5
513.5	(9.3)	C1 9 / 11.0	C1 7 / 10	0.0 ℄	6.2	513.5	
513.0	(11.2)	C2 4 / 11.2	C2 0 / 10	0.0 ℄	6.7	513.0	
512.62							
512.0	(13.8)	C2 0 / 11.0	C1 9 / 10	CO 5	7.2	512.5	0.0 / 3.0
511.3	(18.2)	C2 0 / 11.0	C2 0 / 10	C1 0	7.4	512.3	0.0 / 4.5
510.88							

(16)

	+	H.I. 519.67	−	Elev.	
+50			8.8		
			8.93	510.74	T.P. on △ Hub
	1.24	511.98			
+70			1.4		
44+00			3.1		
+25			5.6		
+50			8.9		
+75			12.0		
45+00			11.5		
+50			9.8		
			9.98	502.00	T.P.
	8.12	510.12			
46+00			6.9		
+20			6.2		
+50			6.8		

− 5.50 %

100' V.C.

+1.68 %

	Lt					Grade		Rt
							519.67 H.I.	
							510.9	
509.5	(27.6)	C2 6 11.3	C2 4 10	C1 +	8.8		0.0 10.0	
							511.98 H.I.	
							510.6	
508.4	(44.6)	C3 2 11.6	C3 0 10	C2 2	1.4	C1 0 10	C1 0 10.5	
							508.9	
506.8	(41.5)	C2 6 11.3	C2 5 10	C2 1	3.1	C1 2 10	C1 3 10.6	
							506.A	
505.4	(19.0)	C1 2 10.6	C1 2 10	C1 0	5.6	CO 5 10	CO 4 10.2	
	(0.0)	+37					503.1	+37 = 0.0 sec. both sides
504.00				F0 9	8.9			
							500.0	
502.9		F2 0 11.0	F2 3 8	F2 9	12.0	F3 4 8	F4 0 14.0	
							500.5	
502.2				F1 7	11.5			
	(0.0)	+23 = 0.0 − 10' Lt.						
							502.N	
502.09	(4.2)	CO 7 10.4	CO 7 10	CO 1	9.8		0.0 1.0	
							510.12 H.I.	
							503.N	
502.9	(6.9)	CO 9 10.5	CO 9 10	CO 3	6.9		0.0 4.5	
							503.9	
503.2	(13.8)	C1 0 10.5	C1 0 10	CO 7	6.2	CO 3 10	CO 3 10.2	
							503.3	
503.7	(1.0)	CO 3 10.2	CO 3 10	D.O 4.0	FO 4	6.8		

(17)

	+	H.I. 510.12	−	Elev.
47+00			5.5	
+50			4.8	
+75			4.8	
48+00			3.6	
+20			3.3	
+50			0.7	
			0.69	509.43 TT
	4.83	514.26		
+85			3.7	
49+00			3.8	
49+17.40	△ Rt.		4.2	
+50			7.3	
50+00			10.9	
			8.48	505.78 BM #7

B.M. – Spk. in Hub 40' Lt. 50+00
5.62 511.40

+75 ℄ 50' V.C. +25 ℄ — 3.0 ℄ + 1.688 ℄

℄ Grade		Lt.		℄ 510.12 H.I.		Rt
504.6	(3.6)	CO 7 10.4	CO 7 10	0.0 ℄	5.5	504.6
505.4	(4.2)	C1 0 10.5	CO 9 10	0.0 1.0	F0 1 4.8	505.3
505.8	(2.9)	C1 0 10.5	CO 2 10	0.0 4.0	F0 5 4.8	505.3
506.3	(8.1)	C1 3 10.7	C1 3 10	CO 2 3.6	0.0 1.0	506.5
506.6	(11.1)	C1 9 11.0	C1 8 10	CO 2 3.3	0.0 2.0	506.8
507.2	(47.9)	C4 3 12.2	C3 9 10	C2 2 0.7	CO 9 10 0.0 11.5	509.4

514.26 H.I.

507.58								
507.7 Offset 3' Rt.	(48.4)	C4 2 12.1	C4 0 10	C2 9	3.7	C2 2 ℄	0.0 12.0	510.6
507.7 Offset 6'	(42.0)	C3 5 11.8	C3 3 10	C2 8	3.8	C1 9 ℄	CO 5 10 0.0 12.0	510.5
507.25								
507.4 Ext. 10'±		⟨Not needed⟩		C2 7	4.2			510.1
506.5 Offset 4'	(5.8)	C1 1 10.6	C1 0 10	C0 5	7.3	CO 1 ℄	0.0 0.5	507.0
	(0.0)	+80 = 0.0 – 10' Lt.						503.4
505.0		F1 0 9.5	F1 2 8	F1 6	10.9	F1 7 8	F1 8 10.6	

(18)

	+	H.I. 511.40	−	Elev.	
					−3.0%
+50			8.4		
51+00			9.3		
+50			9.7		
+65			10.5		
+85			9.5		+1.33%
52+00			10.2		
+25			8.6		
+50			8.0		
+80			5.9		
53+00			6.6		+3.555%
+30			4.1		
+50			4.1		
+60			4.4		

℄ Grade		Lt	℄ 511.40 H.I.		Rt
503.5	(0.0)		0.0 / 10.0	8.4 FO5 ℄ (503.0)	FO7 / 9.0
502.00	(3.8)	CO6 / 10.3	CO6 / 10	9.3 CO1 ℄ (502.1)	0.0 / 4.0
	(2.0)	+2.0 = 0.0 − 10' Lt.			
502.7			F1⁰ / 9.5	9.7 F1⁰ ℄ (501.7)	F1⁶ / 10.4
502.9			F1⁶ / 10.4	10.5 F2⁰ ℄ (500.9)	F2³ / 11.5
503.1				9.5 F1³ ℄ (501.9)	
503.3			F1³ / 10.0	10.2 F2¹ ℄ (501.2)	F2⁴ / 11.6
503.7			FO7 / 9.0	8.6 FO9 ℄ (502.8)	FO4 / 8.6
504.00	(0.0)		0.0 / 10.0	8.0 FO6 ℄ (503.4)	F1⁰ / 9.5
505.1	(6.1)	CO7 / 10.4	CO6 / 10	5.9 CO4 ℄ (505.5)	0.0 / 5.0
505.8	(0.1)	CO2 CO2 / 10.1 10	0.0 / 9.0	6.6 F1⁰ ℄ (504.8)	F2⁰ / 11.0
506.9	(7.8)	CO8 / 10.4	CO8 / 10	7.1 CO4 ℄ (507.3)	0.0 / 8.0
507.6	(1.6)	CO6 CO6 / 10.3 10	0.0 / 5.0	4.1 FO3 ℄ (507.3)	F1¹ / 9.7
508.0	(0.0)		0.0 / 10.0	4.4 F1⁰ ℄ (507.0)	F1⁷ / 10.5

(19)

	+	H.I. 511.40	−	Elev.	
+75			3.0		
54+00			1.9		
			1.16	510.24	T.P. Top 54+00
	13.00	523.24			
+20			13.0		
+35			12.9		
+50			12.3		
+65			11.1		
+80			11.5		
55+00			10.0		
+25			8.3		
+50			7.0		
+75			3.9		
56+00			1.5		

+3.555 @ 0

50' V.C.

+8.0 @ 0

℄ Grade		Lt	℄ 511.40 H.I.	Rt
508.4	(2.0)	CO 4 / 10.2 CO 4 / 10	508.4 3.0 0.0 ℄	0.0 / 5.0
509.3	(7.0)	CI 2 / 10.6 CI 1 / 10	509.5 1.9 CO 2 ℄	0.0 / 2.5
			523.24 H.I.	
510.0	(5.0)	CO 7 / 10.4 CO 7 / 10	510.2 13.0 CO 2 ℄	0.0 / 4.0
510.6	(0.8)	CO 3 / 10.2 CO 3 / 10	510.3 0.0 / 5.0 12.9 FO 3 ℄	
511.1	(2.5)	CO 6 / 10.3 CO 6 / 10	510.9 0.0 / 2.0 12.3 FO 2 ℄	
511.8	(6.0)	CI 0 / 10.5 CO 8 / 10	512.1 11.1 CO 3 ℄	0.0 / 2.0
512.5	(0.0)		511.7 0.0 / 10.0 11.5 FO 8 ℄	
514.00			513.2 0.0 / 10.0 10.0 FO 8 ℄	FI 0 / 9.5
516.0			514.7 0.0 / 11.5 8.3 FI ℄	
518.0			516.2 FO 7 / 9.0 7.0 FI 8 ℄	F2 7 / 12.0
	(0.0)	+ 70 = 0.0 − 10'44.		
520.0	(1.5)	CO 8 / 10.4 CO 7 / 10	519.3 0.0 / 6.0 3.9 FO 7 ℄	
522.0	(4.6)	CI 4 / 10.7 CI 2 / 10	521.7 0.0 / 3.0 1.5 FO 3 ℄	

(20)

	+	H.I.	−	Elev.	
		523.24			
			1.70	521.54	TP.
	12.61	534.15			
+50			6.1		
+75			3.3		
57+00			2.1		
			0.73	533.42	TP. on P.O.T.
	12.17	545.59			
+50			10.7		
58+00			8.3		
+50			5.5		
			1.98	543.61	B.M. #8.

B.M. – Spk. in Telephone Pole 14' Lt. 58+50

	11.36	554.97		
59+00			12.8	
+25			10.8	
+50			11.6	
60+00			8.0	

+8.0%

+5.0%

+8.0%

% Grade	Lt	℄	Rt
		534.15 H.I.	
526.0	(46.5)	C4.3 C4.0 6.1 C2.1 ℄ (528.1)	0.0 11.0
528.0	(59.3)	C4.0 C3.7 3.3 C2.8 ℄ (530.8)	C1.7 C1.5 10 10.7
530.0	(46.7)	C3.4 C3.3 2.1 C2.1 ℄ (532.1)	C1.2 C1.1 10 10.6
		545.59 H.I.	
534.00	(20.1)	C2.4 C2.3 10.7 C0.2 ℄ (534.9)	0.0 6.0
536.5	(21.9)	C3.1 C2.8 8.3 C0.2 ℄ (537.3)	0.0 4.0
539.0	(25.8)	C3.4 C3.0 5.5 C1.1 ℄ (540.1)	0.0 5.0
		554.97 H.I.	
541.5	(22.0)	C3.2 C3.0 12.8 C0.7 ℄ (542.2)	0.0 3.0
542.8	(25.8)	C3.2 C3.0 10.8 C1.4 ℄ (544.2)	0.0 2.4
544.00	(12.5)	C2.5 C2.3 C1.7 0.0 11.3 10 6 2.5 FO.6 ℄ (543.4)	0.0 0.0 3.0 10.0
548.0	(2.4)	C0.2 C0.2 0.0 8.0 F1.2 ℄ (547.0)	FO.3 8.5

(21)

	+	H.I.	−	Elev.	
		554.97			
+50			4.5		
			1.20	553.77	T.P.
	12.08	565.85			
61+00			10.6		
+50			4.8		
62+00			0.7		
			0.91	564.94	T.P.
	12.58	577.52			
+50			7.8		
63+00			4.6		
+50			2.7		
64+00			2.0		
+50			1.8		
			1.96	575.56	T.P.
	3.63	579.19			
65+00			3.3		

+8.0 to 100' Lt. Level

Grade		Lt.	℄	Rt
			554.97 H.I.	
552.0	(2.8)	C1 0 / 10.5 C1 0 / 10	0 / 5 — 550.5 — 4.5 F1 5 ℄	F0 7 / 8
			565.85 H.I.	
556.0	(9.4)	C2 3 / 11 C2 2 / 10	0 / 3 — 555.3 — 10.6 F0 7 ℄	0 / 2 — 0 / 10.8
560.0	(35.4)	C3 8 / 11.9 C3 5 / 10	561.1 — 4.8 C1 L ℄	C0 7 / 10 — C0 7 / 10.1
564.0	(25.2)	C2 4 / 11 C2 4 / 10	566.2 — 0.7 C1 2 ℄	C0 9 / 10 — C1 0 / 10.5
			577.52 H.I.	
568.0	(45.5)	C2 2 / 11.1 C2 2 / 10	569.7 — 7.8 C1 7 ℄	C1 2 / 1 C1 2 / 6 C1 2 / 10 C1 L / 10.6
572.00	(9.2)	C1 L / 10.6 C1 0 / 10	572.9 — 4.6 C0 9 ℄	C0 9 / 10 C0 9 / 10.5
575.0	(0.5)	F0 2 / 8.3	574.8 — 2.7 F0 2 ℄	0.0 / 5.5 C0 2 / 10 C0 2 / 10.1
		+70 = 0.0 − 10' Rt.		
576.00		F0 7 / 9.0	575.5 — 2.0 F0 5 ℄	F0 3 / 8.5
576.0		F1 0 / 9.5	575.7 — 1.8 F0 3 ℄	0.0 / 10.0
			579.19 H.I.	
		+75 = 0.0 − 10 Rt.		
576.00	(1.9)	F0 5 / 8.7	575.9 — 3.3 F0 L ℄	0.0 / 1.0 C0 4 / 10 C0 4 / 10.2

(22)

	+	H.I. 579.19	−	Elev.	
+25			2.8		
+50			3.2		
+85			3.2		
66+00			3.9		
+20			4.6		
+50			4.6		
66+67.93	Δ		4.75		On Rail Cattle Guard
+80			4.6		
67+00			5.8		
+25			7.3		
+50			7.7		
+75			7.5		
68+00			7.9		

1.0 %

1.0 %

℄ Grade	Lt	℄ 579.19 H.I.	Rt
575.8	(12.9) 0.0 9.0	576.4 2.8 CO6 ℄	C1 1 8 · C1 6 10 · C1 7 10.9
575.5	(10.1) 0.0 9.0	576.0 3.2 CO5 ℄	C1 0 10 · C1 1 10.6
575.2	(15.6) 0.0 9.0	CO4 7 · 576.0 3.2 CO8 ℄	C1 0 6 · C1 5 10 · C1 6 10.8
575.0	(7.1) 0.0 6.0	575.3 3.9 CO3 ℄	CO9 10 · C1 0 10.5
574.8		574.6 4.6 FO2 ℄	0.0 10.0
574.5	(0.5) 0.0 4.5	574.6 4.6 CO1 ℄	0.0 6.0
		574.4 4.75 ↑ On Top Cattle Guard	
574.2	(2.4) 0.0 6.5. +92 = 0.0 ℄ − 0.0 2.4.	574.6 4.6 CO4 ℄	0.0 5.5
574.0		573.4 5.8 FO6 ℄	
573.8		571.9 7.3 F1 2 ℄	
573.5		F2 4 11.6 · 571.5 7.7 F2 0 ℄	F1 7 10.5
573.2		571.7 7.5 F1 5 ℄	
573.0		571.3 7.9 F1 7 ℄	

(23)

	+	H.I.	−	Elev.	
		579.19			
+20 Sm. Drain			8.2		−1.0%
			8.01	571.18	T.P.
	5.18	576.36			
+50			4.8		
69+00			4.1		
+50			4.8		
70+00			4.5		+0.40%
+50 Sm. Drain			4.0		
			3.72	572.64	B.M. #9

BM – Spt. in Tel. Pole 14' Lt 70+45

	4.20	576.84			
71+00			3.1		
+25			2.3		
+50			2.3		−1.75%
72+00			4.9		

Grade	Lt	℄	Rt
		579.19 H.I.	
572.8		571.0 F2 7 / 12.0 — 8.2 — F2 8 ℄	F2 3 / 11.5
		576.36 H.I.	
572.5		571.6 4.8 FO 9 ℄	FO 9 / 8.6
	+75 = 0.0 / 10 Lt.	572.3 — 0.0 / 10 Rt.	
572.00	(11.6)	0.0 / 10.0 — 4.1 — CO 3 ℄	C1 6 / 10 — C1 6 / 10.8
572.2	(0.7)	571.6 4.8 FO 6 ℄	0.0 / 5.5 — CO 3 / 10 — CO 3 / 10.2
572.4	(1.2)	571.9 4.5 FO 5 ℄	0.0 / 5.5 — CO 5 / 10 — CO 5 / 10.3
572.6	(1.4)	572.4 4.0 FO 2 ℄	0.0 / 5.5 — CO 6 / 10 — CO 6 / 10.3
		576.84 H.I.	
572.8	(22.4)	CO 8 / 10.4 — CO 8 / 10 — 573.7 3.1 CO 9 ℄	C1 7 / 10 — C1 8 / 10.9
572.9	(37.9)	C1 5 / 10.8 — C1 5 / 10 — 574.5 2.3 C1 6 ℄	C1 9 / 5 — C2 6 / 10 — C2 7 / 11.4
573.00	(34.8)	C1 3 / 10.7 — C1 4 / 10 — 574.5 2.3 C1 5 ℄	C2 7 / 10 — C2 3 / 11.2
572.1	(1.6)	571.9 4.9 FO 2 ℄	0.0 / 4.0 — CO 5 / 10 — CO 6 / 10.3

(24)

	+	H.I. 576,84	−	Elev.
+50			6.4	
73+00 Sm. Drain			7.6	
+50			6.8	
74+00			6.5	
+50			7.8	
			7.41	569.43 T.T.
	4.11	573.54		
75+00			6.8	
+50 Sm. Drain			7.5	
76+00			6.4	
+50			5.9	
77+00			4.1	
+50			2.8	
78+00			3.0	

−1.75 %

+1.81 %

Grade	Ht.			576.84 H.I.		
571.3	(0.3)			6.4 FO$^{9}_{E}$	0.0 7.0	CO$^{2}_{}$ 10.1
	765 = 0.0 − 10 Rt.			569.2		
570.4		F1$^{4}_{}$ 10.1		7.6 F1$^{2}_{E}$ 570.0	FO$^{7}_{}$ 9.0	
569.5	(17.4)	0.0 11.0		6.8 CO$^{5}_{E}$ 570.3	CO$^{8}_{}$ 5	C1$^{5}_{}$ 10 C1$^{6}_{}$ 10.8
568.6	(32.9)	CO$^{8}_{}$ 10.4 C1$^{2}_{}$ 10	C1$^{5}_{}$ 7.5	6.5 C1$^{7}_{E}$ 569.0	C2$^{2}_{}$ 5	C2$^{6}_{}$ 10 C2$^{8}_{}$ 11.4
567.8	(28.0)	CO$^{9}_{}$ 10.5	C1$^{2}_{}$ 10	7.8 C1$^{2}_{E}$	C1$^{2}_{}$ 5	C2$^{2}_{}$ 10 C2$^{3}_{}$ 11.1
				573.54 H.I.		
566.9	(1.3)			6.8 FO$^{2}_{E}$ 566.1	0.0 6	CO$^{6}_{}$ 10 CO$^{6}_{}$ 10.3
566.00	(2.6)	0.0 5.0		7.5 0.0 566.0	CO$^{5}_{}$ 10	CO$^{5}_{}$ 10.3
566.9	(6.4)	0.0 7.0		6.4 CO$^{2}_{E}$ 567.1	CO$^{9}_{}$ 10	C1$^{2}_{}$ 10.5
567.8	(3.6)			5.9 FO$^{2}_{E}$ 567.6	0.0 3.5	C1$^{2}_{}$ 10 C1$^{1}_{}$ 10.6
568.7	(15.5)	CO$^{2}_{}$ 10.1		4.1 CO$^{7}_{E}$ 569.4	C1.$^{9}_{}$ 10	C2$^{2}_{}$ 11.0
569.6	(20.8)	CO$^{1}_{}$ 10.2	CO$^{9}_{}$ 10	2.8 C1$^{1}_{E}$ 570.7	C1$^{3}_{}$ 8	C1$^{7}_{}$ 10 C1$^{8}_{}$ 10.9
570.5	(1.8)		0.0 4.0	3.0 0.0 570.5	CO$^{1}_{}$ 6	CO$^{6}_{}$ 10 CO$^{7}_{}$ 10.4
	+25 = 0.0 − 10 Rt.					

(25)

	+	H.I. 573.54	−	Elev.
+50			3.0	
79+00			2.0	
+50			0.4	
			0.62	572.92 BM.#10

BM. - Spk. in Tel. Pole 10' Lt. 79+45

	5.23	578.15		
80+00			4.3	
+50			2.8	
81+00			3.2	
+50			3.3	
+60			3.5	
82+00			5.7	
+50			8.0	
83+00			9.6	

Nov. 15 - '27
Ward - Notes
Duermit - Inst
Mc Bain - Rod

	Grade	Lt	℄ 573.54 H.I.	Rt.
	571.5		570.5 3.0 F1⁰ ℄	F0⁷ 9.0
	572.4		571.5 2.0 F0⁹ ℄	0.0 9.5
	573.3	(2.6)	573.1 0.4 F0² ℄	0.0 C0⁸ C0⁸ 4.0 10 10.4
			'578.15 H.I.	
	574.2	(0.8)	573.9 4.3 F0³ ℄	0.0 C0⁵ C0⁵ 7.0 10 10.3
	575.09	(6.3)	575.4 2.8 C0³ ℄	0.0 C0⁵ C0⁷ C0⁸ 8.0 8 10 10.4
	575.3	(2.0)	575.0 3.2 F0³ ℄	F0⁸ 9.2 0.0 C0⁵ C0⁶ 6.5 10 10.3
	574.125	(15.4)	574.9 3.3 C0⁸ ℄	0.0 C1³ C1⁸ C2⁼ 7.5 8 10 11.0
	573.8	(19.0)	574.7 3.5 C0⁹ ℄	0.0 C1⁴ C2² C2³ 9.5 7 10 11.2
	572.25	(7.5)	572.5 5.7 C0² ℄	0.0 C1⁻ C1² 7.0 10 10.6
	570.4	(3.1)	570.2 8.0 F0² ℄	0.0 C0⁵ C1⁻ C1⁻ 6.5 3.5 8 10 10.6
	568.50	(3.8)	569.6 9.6 C0⁻ ℄	0.0 C0⁴ C0² C1² 5.0 8 10 10.5

100' V.C. - 3.75 %
+1.81 %

(26)

	+	H.I. 578.15	−	Elev.
+50			9.8	
+75			9.9	
84+00			9.8	
+50			9.4	
+75			9.2	
85+00			9.8	
			9.20	568.95 T.P.
	2.01	570.96		
+50			2.7	
86+00			4.0	
+50			4.6	
86+74.61 E.C. / 86+74.99 P.O.T. (34.62 Dist.)				
+85			5.3	
87+00			6.1	
+50			7.7	

Grade — Level — +1.0% — 50' V.C. — −2.50% — −2.76% — +25

Lt			℄ 578.15 H.I.		RH		
568.5	(0.3)		0.0 / 7.0	9.8 FO 1 ℄	568.4	0.0 CO 3 / 8.5	CO 3 / 10.2
568.5	(0.3)		FO 6 / 8.9	9.9 FO 2 ℄	568.3	0.0 CO 3 / 8.5	CO 3 / 10.2
568.50	(1.5)		FI 2 / 9.5	9.8 FO 1 ℄	568.4	0.0 CO 2 / 3.0	CO 7 CO 8 / 8 10 10.4
569.0			FO 7 / 8.6	9.4 FO 2 ℄	568.8	0.0 / 9.0	0.0 / 10
569.25			FO 5 / 8.7	9.2 FO 3 ℄	569.0	0.0 / 10	
569.3			FI 3 / 10.0	9.8 FO 2 ℄	568.4	FO 5 / 8.7	
			570.96 H.I.				
568.88		+30=0.0 − 10 RH.					
568.3	(0.5)		FO 4 / 8.6	2.7 00 ℄	568.3	0.0 CO 3 / 7.0	CO 4 / 10.2
567.0	(0.6)			4.0 0.0 ℄	567.0	0.0 CO 4 / 7.0	CO 4 / 10.2
565.75	(3.9)	CO 3 / 10.2	CO 3 / 10	4.6 CO 6 ℄	566.4	CO 7 / 5	C1 5 / 10 C1 5 / 10.8
564.8 (34.62)	(19.7)	CO 5 / 10.3	CO 5 / 10	5.3 CO 1 ℄	565.7	C1 5 / 10	C1 5 / 10.3
564.4	(16.4)	0.0 / 9.0	CO 7 / 8	6.1 CO 5 ℄	564.9	C1 2 / 5	C1 7 / 10 C1 7 / 10.9
563.0	(3.8)		0.0 / 7.0	7.7 CO 3 ℄	563.3	0.0 / 6.5	CO 9 / 10 CO 9 / 10.5

(27)

	+	H.I.	−	Elev.	
		570.96			
88+00			9.5		
+35			10.8		
+50			11.8		
			12.16	558.80	T.P.
	3.13	561.93			
+80			6.4		
89+00			7.7		
+25			8.1		
+50			8.0		
+75			9.3		
90+00			10.4		
			6.09	555.84	B.M. #11

B.M. - Spk. in Tel. Pole 16' Rt 90+00

	0.89	556.73	
+50			

+1.66 %

−6.0 %

Grade	Lt		℄		Rt		
			570.96 H.I.				
			561.5				
560.7	(17.8)	CO 7 / 10.4	CO 7 / 10	9.5	CO 8 / ℄	CO 6 / 6	C1 9 / 10	C1 9 / 11.0
			560.2				
559.0	(27.4)	C1 2 / 10.6	C1 2 / 10	10.8	C1 2 / ℄	C1 8 / 10	C2 0 / 11.0	
			559.2				
558.3	(19.2)	CO 5 / 10.3	CO 6 / 10	11.8	CO 9 / ℄	C1 4 / 4	C1 5 / 10	C1 6 / 10.8
			561.93 H.I.				
		+65 = 0.0 / 10 Lt		— 0.0 / 10 Rt.				
			555.5				
556.9		F1 7 / 10.5		6.4	F1 4 / ℄	F0 6 / 8.9		
			554.2				
556.0		F4 0 / 14.0		7.7	F1 8 / ℄	F1 0 / 9.5		
		+15 = 0.0 — 10 Rt.						
			553.8					
554.5	(3.1)		F0 6 / 8.9	8.1	F0 7 / ℄	0.0 / 5.5	C1 2 / 10	C1 3 / 10.7
			553.9					
553.0	(34.2)	0.0 / 12.5	CO 7 / 10	CO 3 / 3	8.0	CO 9 / ℄	C2 8 / 5	C3 5 / 10	C3 8 / 11.9
			552.6					
551.5	(40.7)	0.0 / 12	C1 2 / 10	9.3	C1 1 / ℄	C3 2 / 6	C4 4 / 10	C4 6 / 12.3
			551.5					
550.0	(34.2)	0.0 / 8.5	C1 2 / 7	10.4	C1 5 / ℄	C1 6 / 5	C4 0 / 10	C4 3 / 12.2
			556.73 H.I.					
			547.7					
547.0	(18.1)	0.0 / 7.0	CO 4 / 6	9.0	CO 7 / ℄	CO 7 / 5	C1 7 / 8	C3 6 / 10	C4 0 / 12.0

	+	H.I.	−	Elev.	
		556.73			
91+00			12.9		
			12.62	544.11	T.P.
	1.13	545.24			
+50			5.2		
92+00			10.3		
+25			11.6		
			12.75	532.49	T.P.
	0.32	532.81			
+50			1.6		
+75			5.6		
93+00			7.8		
+25			9.9		
+50			11.7		
			11.35	521.46	T.P.
	2.04	523.50			
+75			3.0		

8.0 %

8.0 %

Grade	Lt		℄		Rt		
			556.73 H.I.				
543.0	(33.9)	0.0 C0 5 / 9.0 8	543.8 12.9 C0 8 ℄		C1 4 / 4	C3 8 / 8	C4 9 / 10 C5 0 / 12.5
			545.24 H.I.				
539.0	(48.6)	0.0 C1 0 / 11.5 9	540.0 5.2 C1 0 ℄		C1 5 / 4	C4 8 / 7	C5 6 / 10 C6 6 / 13.3
535.0	(20.5)	0.0 C0 4 / 8.0 7	534.9 10.3 F0 1 ℄		0.0 C0 3 ℄	C4 2 / 10	C5 3 / 12.7
533.0	(9.8)	0.0 / 6.0	533.6 11.6 C0 6 ℄		C0 2 / 7	C2 0 / 10	C3 8 / 11.9
			532.81 H.I.				
531.0	(8.7)	0.0 / 6.0	531.2 1.6 C0 2 ℄		0.0 / 5.0	C2 3 / 10	C3 1 / 11.6
529.0	(9.8)		527.2 5.6 F1 8 ℄		F1 4 / 3	0.0 / 5.4	C1 6 / 6 C2 3 / 10 C2 6 / 11.3
527.0	(4.0)		525.0 7.8 F2 0 ℄		0.0 / 5.2	C1 4 / 10	C1 7 / 10.9
525.0	(3.7)		522.9 9.9 F2 1 ℄		0.0 / 7.0	C1 4 / 10	C1 6 / 10.8
523.0	(0.4)		521.1 11.7 F1 3 ℄		0.0 / 9.0	C0 6 / 10	C0 6 / 10.3
			523.50 H.I.				
		+60 = 0.0 −10 Rt					
521.0		F1 3 / 10.0	520.5 3.0 F0 5 ℄		F0 4 / 8.6		

(29)

	+	H.I.	−	Elev.
		523.50		
94+00			4.0	
+25			7.1	
+50			8.9	
+75			9.9	
95+00			11.2	
+25			11.5	
			11.87	511.63 T.P.
	1.95	513.58		
+50			3.3	
+85			4.8	
96+00			6.6	
+25			7.8	
+40			10.5	
+50			11.1	

+6.50 #10

| Grade | Lt. | | ℄ 523.50 H.I. | | |

(30)

	+	H.I.	−	Elev.	
		513.58			
			10.73	502.85	T.P.
	11.52	514.37			
+70			13.8		
97+00 Creek Construct Ford			13.8		
+20			14.0		
+50			11.3		
+75			9.9		
98+00			7.3		
+20			5.0		
+50			4.1		
99+00			1.5		
			0.98	513.39	T.P.
	12.30	525.69			
+50			10.1		
+75			9.3		

−6.50% → +75 → 50' V.C. → +25 → +6.25%

℄ Grade	Lt		℄	Rt
			514.37 H.I.	
501.4			500.6 13.8 FO 8 ℄	0.0 10.0
501.12				
500.3	(6.1)	0.0 10.0	500.6 13.8 CO 3 ℄	CO 6 10 CO 6 10.3
500.8	(0.9)		500.4 14.0 FO 4 ℄	0.0 4.4 CO 3 10 CO 3 10.2
501.06				
502.6	(4.0)	0.0 11.0	503.1 11.3 CO 5 ℄	0.0 7.0 0.0 10
505.1		FO 5 8.7	504.5 9.9 FO 6 ℄	FO 7 9.0
		+85 = 0.0 sec.		
505.7	(27.9)	C1 2 10.6 C1 2 10	507.1 7.3 C1 4 ℄	C1 4 10 C1 4 10.7
507.0	(47.9)	C2 3 11.2 C2 3 10	509.4 5.0 C2 4 ℄	C2 2 10 C2 2 11.0
508.9	(27.9)	C1 4 10.7 C1 4 10	510.3 4.1 C1 4 ℄	C1 2 10 C1 2 10.6
512.0	(15.2)	CO 9 10.5 CO 9 10	512.9 1.5 CO 2 ℄	C1 2 10 C1 4 10.7
			525.69 H.I.	
515.1	(7.6)	0.0 10.0	516.6 10.1 CO 5 ℄	CO 5 10 CO 5 10.3
		+62 = 0.0 sec.		
516.7		FO 5 8.7	516.4 9.3 FO 3 ℄	FO 5 8.7

(31)

	+	H.I. 525.69	−	Elev.	
100+00			7.9		
+25			6.1		
+50			3.4		
+75			1.4		
101+00			0.3		
			1.07	524.62	B.M. #12

B.M. — Spk. in Hub 25' Rt. 101+00

10.47 535.09

+50			8.3		
102+00			6.7		
+50			6.4		
103+00			5.0		
+25			4.6		
+50			4.9		

+6.25% | +2.72% | 150' V.C.

Grade	Lt	℄ 525.69 H.I.	Rt
518.3		FO 6 / 8.9 — 517.8 — 7.9 FO 5 ℄	0.0 / 8.0
519.9		0.0 / 10.0 — 519.6 — 6.1 FO 3 ℄	0.0 / 10
521.4	(22.2) CO 8 / 10.4	CO 8 / 10 — 522.3 — 3.4 CO 9 ℄	C1 2 / 5 — C1 8 / 10 — C1 8 / 10.9
523.0	(25.2) C1 2 / 10.5	C1 0 / 10 — 524.3 — 1.4 C1 3 ℄	C1 3 / 10 — C1 3 / 10.7
524.50	(16.3) CO 8 / 10.4	CO 8 / 10 — 525.4 — 0.3 CO 9 ℄	CO 6 / 10 — CO 6 / 10.3

535.09 H.I.

525.9	(19.1) C1 5 / 10.8	C1 3 / 10 — 526.8 — 8.3 CO 9 ℄	CO 6 / 10 — CO 6 / 10.3
527.2	(26.8) C2 3 / 11.2 — C2 2 / 10	C1 4 / 8 — 528.4 — 6.7 C1 2 ℄	C1 3 / 4 — CO 9 / 10 — CO 8 / 10.5
528.6	(3.5) CO 2 / 10.1	CO 2 / 10 — 528.7 — 6.4 CO 1 ℄	CO 3 / 10 — CO 3 / 10.2
529.95	(1.9) CO 8 / 10.4 — CO 8 / 10	CO 1 / 7 — 530.1 — 5.0 CO 1 ℄	0.0 / 10.0
530.5	(1.4)	FO 8 / 9.2 — 530.5 — 4.6 0.0 ℄	0.0 / 8 — CO 6 / 10 — CO 8 / 10.3
		+40 = 0.0 — 10 Rt.	
530.8		F1 2 / 9.8 — 530.2 — 4.9 FO 6 ℄	FO 5 / 8.7

(32)

	+	H.I. 535.09	−	Elev.	
+75			5.4		150' V.C.
104+00			4.8		
+50			5.9		
105+00			6.6		
+50			7.8		
106+00			10.3		−3.50 %/o
+50			12.3		
			11.56	523.53 TP.	
	0.22	523.75			
+75			1.8		
107+00			3.2		
+50			5.6		50' V.C.
+70			6.2		
108+00			5.9		

℄ Grades	Lt	℄ 535.09 H.I.	Rt
530.8		Fil 9.7 — 529.7 — 5.4 — Fil ℄	FO 7 9.0
		+90 = 0.0 — 10 Rt.	
530.7	(1.5)	FO 8 9.2 — 530.3 — 4.8 — FO 4 ℄	0.0 6.5 — CO 5 10 — CO 6 10.3
529.37		0.0 10 — 529.2 — 5.9 — FO 2 ℄	FO 3 8.5
527.6	(17.9)	CO 6 10.3 — CO 6 10 — 528.5 — 6.6 — CO 9 ℄	C1 1 10 — C1 1 10.6
525.9	(25.6)	C1 2 10.6 — C1 2 10 — 527.3 — 7.8 — C1 4 ℄	C1 0 10 — C1 0 10.5
524.1	(15.2)	C1 1 10.6 — CO 9 10 — 524.8 — 10.3 — CO 7 ℄	CO 5 6 — C1 0 10 — C1 1 10.6
522.4	(8.6)	CO 3 10.2 — CO 7 10 — 522.8 — 12.3 — CO 4 ℄	CO 6 10 — CO 6 10.3
		523.75 H.I.	
521.5	(13.4)	0.0 10 — CO 8 9 — 522.0 — 1.8 — CO 5 ℄	CO 8 5 — CO 8 10 — CO 8 10.4
520.6		0.0 7.0 — 520.6 — 3.2 — 0.0 ℄	0.0 10.0
518.875		Fil 5 10.4 — 518.2 — 5.6 — FO 7 ℄	0.0 10.0
518.4		Fill — 517.6 — 6.2 — FO 8 ℄	0.0 9.0
518.30	(2.3)	Fil 0 9.5 — 517.9 — 5.9 — FO 4 ℄	0.0 6.0 — C1 2 10 — C1 2 10.6

(33)

	+	H.I.	−	Elev.	
		523.75			
			5.03	518.72	T.P.
	5.88	524.60			
+50			5.6		
109+00			4.9		
+50			5.3		
			7.23	517.37	BM. #13

BM - Spk. in Tel. Pole 60' Lt. 109+60

	7.42	524.79		
+85 Sm. Drain			6.7	
110+00			6.5	
+50			5.7	
111+00			5.4	
+50			7.2	
112+00			8.7	
+20 Sm. Drain			8.7	
+50			7.5	

+1.21 %

−1.50 %

50' V. C.

# Grades	Lt	℄	Rt
		524.60 H.I.	
518.9 (11.4)	0.0 CO 5/8 12.6	519.0 5.6 CO 1/8 ℄	CO 7/8 4 C1 2/8 10 C1 3/8 10.7
519.5 (11.5)	CO 6/8 10.3	CO 6/8 10 519.7 4.9 CO 2/8 ℄	C1 2/8 10 C1 2/8 10.6
520.125 (1.0)		FO 5/8 8.7 519.3 5.3 FO 8/8 ℄	0.0 8 CO 8/8 10 CO 8/8 10.4
		524.79 H.I.	
	+70=0.0 −10 Rt.		
519.6		FZ 1/8 11.2 518.1 6.7 F1 5/8 ℄	F1 0/8 9.5
519.4		F1 7/8 10.5 518.3 6.5 F1 1/8 ℄	FO 5/8 8.7
	+10=0.0 −10 Rt.		
518.6 (15.9)	CO 4/8 10.2 CO 2/8 10	CO 8/8 8 519.1 5.7 CO 5/8 ℄	CO 8/8 6 C1 6/8 10 C1 7/8 10.9
517.9 (36.6)	C1 4/8 10.7	C1 5/8 10 519.4 5.4 C1 5/8 ℄	C2 4/8 10 C2 5/8 11.3
517.1 (16.8)	CO 5/8 10.3	CO 5/8 10 517.6 7.2 CO 5/8 ℄	C1 0/8 5 C1 8/8 10 C2 1/8 11.1
516.375 (6.6)		FO 4/8 8.6 516.1 8.7 FO 3/8 ℄	0.0 2.0 C1 5/8 10 C1 6/8 10.8
516.3 (3.8)		FO 2/8 8.3 516.1 8.7 FO 2/8 ℄	0.0 3 C1 0/8 10 C1 0/8 10.5
517.0 (12.5)	CO 5/8 10.3	CO 5/8 10 517.3 7.5 CO 3/8 ℄	C1 0/8 8 C1 5/8 10 C2 0/8 11.0

(34)

	+	H.I. 524.79	−	Elev.	
113+00			5.7		
+50			3.6		
			1.51	523.28	T.P.
	12.03	535.31			
114+00			12.2		
+50			9.8		
115+00			6.8		
+35			5.1		
+50			4.8		
+75			3.4		
116+00			2.5		
+25			3.1		
+50			4.2		
117+00			6.2		

+1.0 S/O

100' H.C.

+75 528.50

Sta. & Grades	Lt	℄ 524.79 H.I.	Rt
519.0 (9.5)	CO² CO² / 10.1 10	0.0 / 7.3 — 519.1 — 5.7 CO¹ ℄	C1⁰ C1⁵ C1⁵ / 6 10 10.8
521.0 (17.3)	0.0 / 10	0.0 / 7.5 — 521.2 — 3.6 CO² ℄	C1⁶ C2⁵ C2⁷ / 5 10 11.4
		535.31 H.I.	
523.0 (12.5)	CO¹ CO¹ / 10.2 10	0.0 / 7.5 — 523.1 — 12.2 CO¹ ℄	C1⁰ C2⁵ C2⁸ / 6 10 11.4
525.0 (18.5)		0.0 / 12 — 525.5 — 9.8 CO⁵ ℄	CO⁹ C1⁸ C2⁷ C2⁶ / 4 6 10 11.3
527.0 (38.1)	C1⁵ C1⁵ / 10.8 10	— 528.5 — 6.8 C1⁵ ℄	C1⁸ C2⁸ C3⁰ / 4 10 11.5
528.4 (49.9)	C1⁶ C2⁰ / 10.8 10	— 530.2 — 5.1 C1⁸ ℄	C2² C3² C3³ C3⁶ / 3 6 10 11.8
529.0 (43.9)	C1⁷ C1⁷ / 10.9 10	— 530.5 — 4.8 C1⁵ ℄	C2¹ C3⁰ C3² / 3 10 11.6
530.0 (36.6)	CO⁷ CO² CO⁶ C1⁰ / 10.4 10 6 3	— 531.9 — 3.4 C1² ℄	C2⁸ C2⁹ / 10 11.5
530.6 (45.6)	C1³ C1⁷ / 10.7 10	— 532.8 — 2.5 C2² ℄	C2⁸ C2⁹ / 10 11.5
530.6 (33.9)	CO⁵ CO⁶ / 10.3 10	— 532.2 — 3.1 C1⁶ ℄	C2⁶ C2⁷ / 10 11.4
529.9 (28.7)	CO⁵ CO⁵ / 10.3 10	— 531.1 — 4.2 C1² ℄	C2⁵ C2⁶ / 10 11.3
526.8 (48.2)	CO⁶ CO⁷ / 10.3 10	— 529.1 — 6.2 C2³ ℄	C3⁶ C3⁹ / 10 12.0

(35)

	+	H.I.	−	Elev.	
		535.31			
+50			10.8		
			11.83	523.48	T.P.
	1.30	524.78			
+75			2.1		
118+00			4.4		
+32			7.4		
+50			10.9		
119+00 Sm. Drain			12.2		
			9.10	515.68	B.M. #14

B.M. - Spk. in Hub 24' Rt. 119+50
1' Out from Fence Line

	0.72	516.40			
+50			5.4		
120+00			8.5		
			8.24	508.16	T.P.
	3.11	511.27			

−7.0 %

+25 — 50' V.C. — +75

−1.50 %

& Grades	Lt	℄ 535.31	Rt
523.3	28.1	0.0 10.8 C1 2 / ℄ 10.0	C2 8 / 10 C3 0 / 11.5
		524.5	
		524.78 H.I.	
		522.7	
521.5	29.1	0.0 2.1 C1 2 / ℄ 6.0	C3 3 / 10 C3 6 / 11.9
		520.4	
519.8	18.2	0.0 4.4 CO 6 / ℄ 3.5	C2 5 / 10 C2 6 / 11.3
		517.4	
517.7	7.7	7.4 FO 3 / ℄	0.0 C1 7 / 2.0 .10 C2 0 / 11.0
		513.9	
514.3	2.2	10.9 F2 2 / ℄	0.0 C0 8 / 5.0 10 C1 0 / 10.5
		512.6	
512.8	1.3	F3 4 / 13.1 12.2 FO 2 / ℄	0.0 C1 0 / 8.0 10 C1 1 / 10.6
		516.40 H.I.	
511.0			
		511.0	
509.6	4.4	0.0 5.4 C1 4 / ℄ 5.2	C1 6 / 10 C1 8 / 10.9
508.875			
		507.9	
508.5	3.9	F3 3 / 13.0 8.5 FO 6 / ℄	0.0 C1 5 / 6.0 10 C2 4 / 11.2

(36)

	+	H.I. 511.27	−	Elev.	
+50			4.3		−11.52 %
121+00			5.2		
+50			5.1		+0.333 %
122+00			4.6		
+25				507.42	
+50			3.4		
+75				506.5	
+80			2.9		
123+00			3.0		
+40 Sm. Drain			6.6		−4.0 %
+50			5.6		
+65			6.9		
+75				502.5	
+88			7.8		
124+00			11.9		
			11.10	500.17	TP.
	4.11	504.28			

Nov. 16-'27
Ward – Notes
Duermit – Inst.
McBain – Rod

	Lt				℄ 511.27 H.I.		Rt		
507.8	(10.5)				4.3	F0 8 ℄	0.0 4.2	C1 4 6	C2 4 10 C2 8 11.4
507.0	(18.3)				5.2	F0 9 ℄	0.0 2.0	C1 5 7	C3 1 10 C3 7 11.8
507.2	(13.9)				5.1	F1 0 ℄	0.0 1.6	C2 7 10	C3 0 11.5
507.3	(15.7)				4.6	F0 6 ℄	0.0 1.0	C1 2 2	C3 2 10 C3 5 11.8
507.2	(15.0)	0.0 10.0	C0 2 2		3.4	C0 7 ℄	C2 1 2	C4 2 10	C4 6 12.3
506.3	(60.8)	C1 2 10.5	C1 2 10	C1 3 2	2.9	C2 1 ℄	C3 7 3	C5 3 10	C6 2 13.1
505.5	(78.2)	C1 3 10.7	C1 3 10	C1 2 3	3.0	C2 8 ℄	C4 7 3	C6 8 10	C7 6 13.8
503.9		Not Needed			6.6	C0 8 ℄			
503.5	(54.2)	0.0 12.0	C0 7 10	C0 8 3	5.6	C2 2 ℄	C5 0 3	C7 3 10	C8 6 14.3
502.9	(79.5)	C1 4 10.7	C1 4 10		6.9	C1 5 ℄	C6 6 7	C7 0 10	C9 0 14.5
502.1	(18.8)				0.0 6	7.8	C1 4 ℄	C1 4 10	C1 5 10.8
501.8					F5 8 16.7	11.9	F2 4 ℄	0.0 9.0	

100' K. C.

(37)

	+	H.I. 504.28	−	Elev.
124 +10			8.1	
+20			10.4	
+25			13.9	
Creek Channel				
+30			13.9	
+36			10.5	
+47			10.7	
+50			8.4	
+70			2.5	
			1.06	503.22 TP
	12.89	516.11		
+85			10.2	
125+00			9.3	
+25			7.9	
+50			6.6	

Grade	Lt	℄ 504.28 H.I.	Rt
501.5		496.2 8.1 F5 ℄	
501.6		493.9 10.4 F7 ℄	
501.6		490.4 13.9 F11 ℄	
501.7		490.4 13.9 F11 ℄	
501.8		493.8 10.5 F8 ℄	
502.0		493.6 10.7 F8 ℄	
502.0		495.9 8.4 F6 ℄	
502.8		501.8 F1 10.1 2.5 F1 ℄	0.0 10.0
		516.11 H.I.	
503.5	(43.0)	CO3 10.2 CO4 10 505.9 10.2 C24 ℄	C32 4 C25 10 C25 11.3
504.3	(43.6)	CO2 10.4 CO2 10 C22 5 506.8 9.3 C25 ℄	C22 10 C18 10.9
505.5	(68.7)	C20 11.0 C24 10 508.2 7.9 C22 ℄	C23 5 C50 10 C72 13.5
506.8	(80.7)	C16 10.8 C20 10 C25 8 509.5 6.6 C22 ℄	C34 5 C66 10 C78 13.9

100' V. C.

+5.0 %

+75 503.0

(38)

	+	H.I. 516.11	−	Elev.
+80			5.7	
126+00			5.0	
+50			2.0	
			0.6.9	515.42 TP
	6.39	521.81		
127+00			4.5	
+25			3.5	
+50			4.1	
128+00			5.0	
+35			4.7	
+50			5.7	
129+00			6.7	
			11.38	510.43 B.M. #15

B.M. – Spk. in Hub 21' Lt. 129+00

7.13 517.56

℄ Grade	Lt	℄ 516.11 H.I.	RT
508.3	(53.9)	0.0 5.7 C2.1 C2.8 C3.5 C6.4 8.0 ℄ 8 10 13.2	
509.25	(31.1)	0.0 5.0 C1.7 C2.8 C4.2 5.0 ℄ 10 12.0	
511.8	(39.3)	0.0 2.0 C2.3 C2.8 C3.2 C3.6 6.0 ℄ 1 10 11.8	
		521.81 H.I.	
514.25	(47.2)	0.0 4.5 C3.2 C3.5 C4.8 7.0 ℄ 10 12.4	
515.3	(52.3)	0.0 C2.8 3.5 C3.2, C3.7 C5.0 8.0 Z ℄ 10 12.5	
515.9	(28.1)	0.0 C1.5 4.1 C1.8 C2.2 C3.4 C4.9 6.0 3 ℄ 8 10 12.5	
516.0	(21.4)	0.0 5.0 C0.8 C1.2 C2.0 C2.7 4.5 ℄ 8 10 11.2	
515.5	(20.6)	0.0 4.7 C1.6 C1.6 5.0 ℄ 10 10.8	
515.25	(25.0)	0.0 5.7 C0.8 C2.6 C2.9 C2.9 4.0 ℄ 6 10 11.5	
514.5	(16.8)	0.0 6.7 C0.6 C2.3 C2.4 3.0 ℄ 10 11.2	

+5.0 %

100' V. C.

−1.50 %

(39)

	+	H.I.	−	Elev.
	517.56			
+50			4.2	
+75			3.1	
130+00			3.3	
130+07.88 E.C.				
130+09.53 P.C.T.	23.35 Dist.			
+25			3.7	
+50			4.8	
131+00			6.6	
+20			6.5	
+50 Sm. Drain			8.2	
132+00			4.5	
+50			0.2	
			1.18	516.38 TP
	12.29	528.67		
133+00			7.1	
+15			5.8	

−1.50 %
−2.07 %
−2.0
100' V. C.
+6.0 %

℄ Grade	Lt		℄ 517.56 H.I.	Rt
513.8	(16.8)		0.0 513.4 4.2 C0.4 ℄ 3.0	C0.5 C2.4 C2.6 ℄ 10 11.3
513.4	(30.5)		0.0 514.5 3.1 C1.5 ℄ 6.5	C3.1 C3.4 10 11.7
513.0	(29.3)		0.0 514.3 3.3 C1.3 ℄ 8.0	C3.2 C3.3 10 11.7
512.5	(31.5)	23.35	0.0 513.9 3.7 C1.4 ℄ 8.0	C3.2 C3.6 10 11.8
512.0	(20.9)		0.0 512.8 4.8 C0.8 3.5	C2.7 C3.0 10 11.5
511.0	(11.2)		511.0 6.6 0.0 ℄	C2.0 C2.3 10 11.2
510.7	(14.6)		0.0 511.1 6.5 C0.4 ℄ 1.5	C2.2 C2.4 10 11.2
511.0	(4.3)		F4.8 509.4 8.2 F1.6 ℄ 15.2	0.0 C0.5 C0.6 7.0 10 10.3
513.0	(14.1)		0.0 513.1 4.5 C0.1 ℄ 1.0	C2.4 C2.6 10 11.3
516.0	(33.8)		0.0 517.4 0.2 C1.4 ℄ 6.0	C3.7 C4.3 10 12.2
			528.67 H.I.	
519.0	(55.8)		0.0 521.6 7.1 C2.6 ℄ 10.8	C4.4 C5.0 10 12.5
519.9	(60.1)	C0.7 10.4	C0.7 522.9 5.8 C3.0 ℄ 10	C4.3 C4.6 10 12.3

(40)

	+	H.I. 528.67	−	Elev	
+50			4.0		
+75			3.2		
134+00			2.6		
+25			2.2		
			1.85	526.82 T.P. on EC Hub	
	5.25	532.07			
+50			4.4		
135+00			3.4		
+25			3.3		
+50			4.4		
136+00			4.3		
+50			5.6		
+78.12 Δ			6.4		
137+00			6.6		

Lt

℄ 528.67 H.I.

RT

Grades								
	522.0	(57.4)	C1.9 10.5	C1.1 10	524.7 4.0	C2.7 ℄	C4.0 10	C4.5 12.3
8% + 6.0	523.5	(42.8)		0.0 12.0	525.5 3.2	C2.0 ℄	C3.5 10	C3.7 11.9
	525.0	(23.5)		0.0 6.8	526.1 2.6	C1.1 ℄	C2.5 10	C2.8 11.4
V. C.	526.3	(12.2)		0.0 1.0	526.5 2.2	C0.2 ℄	C2.0 10	C2.3 11.1
					532.07 H.I.			
100'	527.1	(17.9)		0.0 2.2	527.7 4.4	C0.6 ℄	C2.5 10	C2.8 11.4
	527.5	(28.0)		0.0 4.0	528.1 3.4	C1.2 ℄	C3.3 10	C3.8 11.9
	527.2	(36.4)		0.0 5.0	528.8 3.3	C1.6 ℄	C4.0 10	C4.4 12.2
8% − 1.04	527.0	(24.7)		0.0 3.0	527.7 4.4	C0.7 ℄	C3.4 10	C3.8 11.9
	526.4	(33.9)		0.0 5.3	527.8 4.3	C1.4 ℄	C3.8 10	C4.4 12.2
	525.9	(20.2)		0.0 2.1	526.5 5.6	C0.6 ℄	C2.8 10	C3.6 11.8
	525.6 Offset 2' Rt	(26.6)		0.0 2.5	525.7 6.4	C0.1 ℄	C0.8 ℄ C3.6 10	C4.0 12.0
	525.4	(16.2)		0.0 0.6	525.5 6.6	C0.1 ℄	C2.7 10	C3.2 11.6

(41)

	+	H.I.	−	Elev.
		532.07		
+50			5.6	
138+00			5.7	
+25			5.9	
+50			7.2	
			7.56	524.51 T.P.
	7.70	529.21		
+75			5.2	
139+00			7.2	
+50			11.2	
+65			11.8	
140+00			10.3	
			3.44	525.77 BM #16

BM - Spk. in Hub 20' Rt. 140+00
1.47 527.24

+25			7.2	

1.0 A/O

1.75 A/O

℄ Grades	Lt	℄	Rt
		532.07 H.I.	
524.9	(43.7)	526.5 0.0 5.6 C1.8 ℄ 6.0	C4.8 C5.8 10 12.9
524.4	(51.5)	526.4 0.0 5.7 C2.0 ℄ 8.0	C5.2 C5.7 10 12.9
523.7	(53.4)	526.2 0.0 5.9 C2.5 ℄ 8.5	C4.7 C5.8 10 12.9
523.0	(48.2)	524.9 0.0 7.2 C1.2 ℄ 7.0	C5.0 C5.6 10 12.8
		529.21 H.I.	
522.3	(39.0)	524.0 0.0 5.2 C1.7 ℄ 5.0	C4.2 C5.0 10 12.5
521.6	(21.8)	522.0 0.0 7.2 C0.4 ℄ 1.0	C3.3 C3.8 10 11.9
520.3	(0.1)	518.0 F6.7 11.2 F2.3 ℄ 18.0	0.0 C0.2 9.5 10.1
519.9		517.4 F6.7 11.8 F2.5 ℄ 18.0	F0.3 10.5
518.9	(14.4)	518.9 10.3 0.0 ℄	C2.5 C3.0 10 11.5
		527.24 H.I.	
518.2	(44.2)	520.0 0.0 7.2 C1.8 ℄ 6.0	C4.7 C5.4 10 12.7

42

	+	H.I.	−	Elev.	
		527.24			
+50			7.1		
+70			7.6		
141+00			9.6		
+50			12.4		
			11.85	515.39	T.P.
	1.61	517.00			
142+00			9.7		
+50			5.5		
143+00			5.0		
+50			4.6		
144+00			6.3		
+15			6.8		
+30			10.0		
+42			14.8		
Drain					

— 2.75 %

— 1.50 %

47

℄ Grades

℄

527.24 H.I.

RT

℄ Grades		℄	RT
517.5	(61.5)	0.0 / 9.0 — 7.1 (520.1) C2 e ℄	C5 5 / 10 — C6 8 / 13.4
516.9	(64.2)	0.0 / 9.0 — 7.6 (519.6) C2 7 ℄	C5 8 / 10 — C6 6 / 13.3
516.2	(36.8)	0.0 / 6.0 — 9.6 (517.6) C1 4 ℄	C4 2 / 10 — C5 0 / 12.5
514.8	(12.3)	12.4 (514.8) 0.0 ℄	C2 2 / 10 — C2 4 / 11.2
		517.00 H.I.	
513.4	(2.5)	F3 7 / 13.5 — 4.7 (512.3) F1 1 ℄	0.0 / 5.5 — C0 2 / 10 — C1 e / 10.5
512.0	(5.8)	F1 7 / 10.5 — 5.5 (511.5) F0 5 ℄	0.0 / 2.5 — C1 4 / 10 — C1 6 / 10.8
511.25	(16.4)	0.0 / 10.0 — 5.0 (512.0) C0 7 ℄	C2 e / 10 — C2 1 / 11.1
510.5	(36.1)	0.0 / 7.8 — 4.6 (512.4) C1 9 ℄	C2 7 / 4 — C3 e / 10 — C3 1 / 11.6
509.75	(27.7)	0.0 / 5.0 — 6.3 (510.7) C1 e ℄	C3 4 / 10 — C3 7 / 11.9
509.5	(17.7)	0.0 / 3.5 — 6.8 (510.2) C0 7 ℄	C2 3 / 10 — C2 5 / 11.3
		℄ 25 = 0.0 — 10 RT.	
509.3		10.0 (507.0) F2 3 ℄	
509.1		14.8 (502.2) F6 9 ℄	

(43)

	+	H.I.	−	Elev.	
		517.00			
+50			13.1		
+60			11.0		
145+00			7.3		
+40			4.5		
+50			4.6		
			7.08	509.92	T.P.
	3.96	513.88			
146+00			1.7		
+20			1.7		
+50			3.1		
147+00			4.3		
+50			5.7		
148+00			7.2		
+50			8.0		

+0.66 %

−1.80 %

℄ Grade	Lt		℄	Rt
			517.00 H.I.	
509.0			503.9 F8.0 20.0 — 13.1 F5.1 ℄	F4.0 14.0
509.1			506.0 11.0 F3.1 ℄	F1.9 10.1
		+75 = 0.0 −10 Rt.		
509.3	(14.3)		509.7 0.0 3.0 — 7.3 C0.4 ℄	C2.1 10 — C2.2 11.1
509.6	(58.9)	C0.8 10.4	512.5 C0.8 10 — 4.5 C2.9 ℄	C4.2 10 — C4.4 12.2
509.7	(58.4)	C1.0 10.5	512.4 C1.1 10 — 4.6 C2.7 ℄	C4.2 10 — C4.4 12.2
			513.88 H.I.	
510.0	(45.9)		512.2 0.0 10.8 — 1.7 C2.2 ℄	C3.8 10 — C4.2 12.1
509.6	(51.9)		512.2 0.0 11.0 — 1.7 C2.6 ℄	C4.0 10 — C4.6 12.3
509.1	(43.8)		510.8 0.0 10.0 — 3.1 C1.7 ℄	C4.3 10 — C4.8 12.5
508.2	(35.6)		509.6 0.0 8.0 — 4.3 C1.4 ℄	C3.8 10 — C4.2 12.1
507.3	(22.5)		508.2 0.0 5.2 — 5.7 C0.9 ℄	C2.7 10 — C3.1 11.6
506.4	(11.6)		506.7 0.0 5.0 — 7.2 C0.3 ℄	C1.7 10 — C2.0 11.0
505.5	(18.6)		505.9 0.0 1.0 — 8.0 C0.4 ℄	C3.0 10 — C3.2 11.6

(44)

	+	H.I. 513.88	−	Elev.	
149+00			9.2		
+50			9.8		
150+00			11.0		
			7.89	505.99	B.M. #17

B.M. - Spk. in Hub - 25' Rt 150+00

4.22 510.21

+50			8.9	
151+00			9.1	
+25			10.1	
+50			10.1	
+65			9.4	
152+00			8.9	
+35			8.5	
+50			8.6	

-1.80%

+0.50%

℄ Grade | Lt

℄ 513.88 H.I. | Rt

℄ Grade	Lt			Rt		
504.6	(10.7)	0.0 0.5	504.7 9.2 CO⁻ ℄	C1⁹ 10	C1⁹ 11.0	
503.7	(13.6)	0.0 2.3	504.1 9.8 CO⁺ ℄	C2⁼ 10	C2¹ 11.1	
502.8	(9.3)	0.0 1.0	502.9 11.0 CO⁻ ℄	C1⁶ 10	C1⁷ 10.9	

510.21 H.I.

501.9	(3.2)		501.3 8.9 FO⁶ ℄	0.0 4.3	C1⁼ 10	C1¹ 10.6
501.0	(5.9)	0.0 1.0	501.1 9.1 CO¹ ℄	C1⁼ 10	C1⁼ 10.6	
501.1		F1⁷ 10.5	500.1 10.1 F1⁼ ℄	0.0 10		
501.25	(2.4)	FO⁹ 9.2	500.1 10.1 FO⁼ ℄	0.0 3.5	CO⁷ 10	CO⁸ 10.4
501.3	(0.5)		500.8 9.4 FO⁵ ℄	0.0 7.0	CO³ 10	CO³ 10.2
501.5	(4.3)		501.3 8.9 FO² ℄	0.0 1.0	CO⁹ 10	C1⁹ 10.5
501.7	(4.7)		501.7 8.5 0.0 ℄	CO⁹ 10	C1⁼ 10.5	
501.75	(3.8)		501.6 8.6 FO¹ ℄	0.0 1.0	CO⁸ 10	CO⁸ 10.4

(45)

	+	H.I. 510.21	−	Elev.	
153+00			7.7		
+25			7.5		
+50			6.6		
+70			5.9		
			6.11	504.10	T.P.
	5.85	509.95			
154+00			6.2		
+50			6.3		
155+00			6.6		
+30			5.3		
+50			4.7		
156+00			3.5		
+20			3.5		
+50			1.9		

+ 1.43 %

+ 1.43 %

+25 V.C.

Grade	Lt		℄	Rt	
			510.21 H.I.		
502.0	(14.6)		0.0 502.5 7.7 CO 5 ℄	C2 2 10	C2 2 11.0
502.3	(8.2)		0.0 502.7 7.5 CO 4 ℄	CO 8 10	CO 8 10.4
502.7	(14.8)		0.0 503.6 6.6 CO 2 ℄	C1 1 10	C1 1 10.6
503.0	(20.1)	CO 4 10.2	CO 4 10 504.3 5.9 C1 3 ℄	C1 2 4	C1 2 10	C1 2 10.6
			509.95 H.I.		
503.4	(9.8)	0.0 10.0	0.0 503.8 7.0 6.2 CO 4 ℄	C1 1 7	C1 1 10	C1 1 10.6
504.1	(0.4)		FO 4 503.7 8.6 6.3 FO 4 ℄	0.0 8.0	CO 2 10	CO 2 10.1
		+50=0.0 on Rt.			
504.9			FI 2 503.4 10.9 6.6 FI 5 ℄	FI 3 10.0		
505.4			FI 2 504.1 10.5 5.3 FO 7 ℄	FO 4 8.6		
505.6			FO 7 505.3 9.0 4.7 FO 3 ℄	0.0 10.0		
506.3	(4.8)		0.0 506.5 7.0 3.5 CO 2 ℄	CO 6 10	CO 6 10.3	
506.5	(1.5)		0.0 506.5 7.0 3.5 0.0 ℄	CO 3 10	CO 3 10.2	
506.64						
506.8	(2.2)	CO 3 10.2	CO 3 10 508.1 1.9 C1 3 ℄	C1 6 10	C1 6 10.8	

(46)

	+	H.I. 509.95	−	Elev.	
+70			3.1		50' V.C.
+75			6.63		
157+00			3.3		
+50			3.3		
158+00			3.8		+1.50%
			4.11	505.84	TP. on P.O.T. #66 +19.43
	1.47	507.31			
+25			1.3		
+50			4.4		
+65			7.6		
+85			10.1		
+97			14.4		
159+00 Creek			14.2		Level Br.
+13			12.7		
+20			10.5		
+25			6.63		

℄ Grade		Lt	℄	Rt
			509.95 H.I.	
506.7	(4.6)		0.0 / 5.0 — 3.1 $CO^{3}_{\mathbb{E}}$ (506.9)	CO^{6}_{10} $CO^{6}_{10.3}$
506.25	(8.5)		0.0 / 6.0 — 3.3 $CO^{4}_{\mathbb{E}}$ (506.7)	$C1^{0}_{10}$ $C1^{L}_{10.6}$
505.5	(23.3)	$CO^{4}_{10.2}$	CO^{4}_{10} — 3.3 $C1^{2}_{\mathbb{E}}$ (506.7)	$C1^{7}_{10}$ $C1^{8}_{10.9}$
504.75	(32.2)	$C1^{L}_{10.6}$	$C1^{L}_{10}$ — 3.8 $C1^{3}_{\mathbb{E}}$ (506.2)	$C2^{3}_{10}$ $C2^{4}_{11.2}$
			507.31 H.I.	
504.4	(30.1)	$CO^{8}_{10.4}$	CO^{8}_{10} — 1.3 $C1^{0}_{\mathbb{E}}$ (506.0)	$C1^{8}_{10}$ $C2^{0}_{11.0}$
504.0			$F2^{7}_{12.0}$ — 4.4 $F1^{L}_{\mathbb{E}}$ (502.9)	0.0 / 10.0
504.0			7.6 (499.7)	
504.0			10.1 (497.2)	
504.0			14.4 (492.9)	
504.0			14.2 (493.1)	
504.0			12.7 (494.6)	
504.0			10.5 (496.8)	
504.0				

(47)

	+	H.I. 507.31	−	Elev.	
159+40			5.5		
+50			3.9		
			3.70	503.61	B.M. #18
B.M. - Spk. in Tel. Pole			15' Rt.	159+50	
	11.52	515.13			
+75			8.2		
160+00			6.8		
+30			4.8		
+50			4.5		
161+00			4.4		
+50			5.5		
162+00			6.9		
+50			8.0		
163+00			9.0		

50' V.C. — 100' V.C. — + 4.0 % — − 2.0 %

℄ Grade	Lt	℄ 507.31 H.I.	Rt
504.2		501.8 5.5 F2 ℄	
504.3		0.0 / 12.5 503.4 3.9 FO2 ℄	FO2 9.4
		515.13 H.I.	
505.0	(39.9) C1 11.0	C1 10 506.9 8.2 C1 ℄	C1 10 C1 11.0
506.0	(49.3) C2 11.2	C2 10 508.3 6.8 C2 ℄	C2 10 C2 11.2
507.2	(65.7) C2 11.4	C2 10 510.3 4.8 C3 ℄	C3 10 C3 11.7
508.0	(57.4) C2 11.3	C2 10 510.6 4.5 C2 ℄	C3 10 C3 11.5
509.2	(30.2) C1 10.5	C1 10 510.7 4.4 C1 ℄	C1 10 C1 11.0
509.0	(12.2) CO 10.2	CO 10 509.6 5.5 CO ℄	CO 10 CO 10.4
508.0	(4.0)	0.0 / 10.0 508.2 6.9 CO ℄	CO 10 CO 10.2
507.0	(1.8)	0.0 / 6.0 507.1 8.0 CO ℄	CO 10 CO 10.1
506.0	(2.1)	0.0 / 1.0 506.1 9.0 CO ℄	CO 10 CO 10.2

(48)

	+	H.I. 515.13	−	Elev.	
			9.53	505.60	T.P.
T.P. – Nail in 3x4 Hub & Old Road 15' Lt, 163+15					
	0.92	506.52			
+50			1.5		
164+00			2.5		
+50			3.6		
165+00			5.5		
+50			6.8		
+91			8.6		
166+00			11.0		
Sm. Drain					
+04			7.9		
+15			7.6		
+50			7.3		
			7.31	499.21	T.P.
	6.15	505.36			

℄ Grade	Lt		℄ 506.52 H.I.		Rt	
				505.0		
505.0	(1.5)		0.0 / 10.0	1.5 0.0 ℄	CO 3 / 10	CO 3 / 10.2
				504.0		
504.0	(0.9)		0.0 / 10.0	2.5 0.0 ℄	0.0 / 10.0	
				502.9		
502.5	(9.2)	CO 5 / 10.3	CO 5 / 10	3.6 CO 4 ℄	CO 5 / 10	CO 5 / 10.3
				501.0		
501.0			FO 5 / 8.7	5.5 0.0 ℄	FO 3 / 8.5	
				499.7		
499.50	(0.7)		0.0 / 3.0	6.8 CO 2 ℄	0.0 / 3.5	FO 2 / 8.3
				497.9		
498.6				8.6 FO 7 ℄	0.0 / 10.0	
				495.5		
498.5			F 4 3 / 14.5	11.0 F 3 ℄	0.0 / 3.0	0.0 / 10.0
				498.6		
498.5	(0.5)		0.0 / 0.5	7.9 CO ℄	0.0 / 10.0	
				498.9		
498.4	(4.6)		0.0 / 6.5	7.6 CO 5 ℄	0.0 / 12.0	
				499.2		
498.5	(15.1)	CO 6 / 10.3	CO 6 / 10	7.3 CO 7 ℄	CO 6 / 6	C 1 ℄ / 10	C 1 5 / 10.8

2.0 %
3.0 %
1.0' V. C.
1.0 %

(49)

	+	H.I. 505.36	−	Elev.
167+00			6.6	
+50			5.4	
168+00			4.9	
+50			4.4	
169+00			3.9	
+50			3.6	
170+00			3.3	
			3.24	502.12 BM #19
B.M. - Spk. in Hub 22' Rt. 170+00	5.16	507.28		
+50			5.5	
171+00			6.9	
+50			8.2	
172+00 Sm. Drain			8.8	



℄ Grade	Lt	℄ 505.36 H.I.	Rt
499.0	0.0 / 10.0	0.0 / 1.0 — 498.8 — 6.6 FO^2_{10} ℄	$FO^2_{9.0}$
499.5	(6.2)	0.0 / 6.7 — 500.0 — 5.4 CO^5_{10} ℄	CO^4_{10} $CO^4_{10.2}$
500.0	(9.1)	$CO^5_{10.3}$ — CO^5_{10} — 500.5 — 4.9 CO^5_{10} ℄	CO^3_{10} $CO^3_{10.2}$
500.5	(9.6)	$CO^3_{10.2}$ — CO^3_{10} — 501.0 — 4.4 CO^5_{10} ℄	CO^6_{10} $CO^6_{10.3}$
501.0	(12.8)	$CO^8_{10.4}$ — CO^8_{10} — 501.5 — 3.9 CO^5_{10} ℄	CO^7_{10} $CO^7_{10.4}$
501.5	(5.6)	0.0 / 10.0 — 501.8 — 3.6 CO^3_{10} ℄	CO^5_{10} $CO^5_{10.3}$
501.8	(6.1)	$CO^2_{10.1}$ — CO^2_{10} — 502.1 — 3.3 CO^3_{10} ℄	CO^4_{10} $CO^4_{10.2}$
		507.28 H.I.	
501.0	(9.1)	$CO^8_{10.4}$ — CO^8_{10} — 501.8 — 5.5 CO^8_{10} ℄	CO^8_{10} $CO^8_{10.4}$
500.0	(7.8)	0.0 / 9.0 — 500.4 — 6.9 CO^4_{10} ℄	CO^8_{10} $CO^8_{10.4}$
499.0	(2.6)	0.0 / 2.0 — 499.1 — 8.2 CO^4_{10} ℄	CO^4_{10} $CO^4_{10.2}$
498.7		$FO^3_{8.5}$ — 498.5 — 8.8 FO^2_{10} ℄	0.0 / 9.0

(50)	+	H.I. 507.28	−	Elev.	℄ Grade	Lt.	℄ 507.28 H.I.	Rt.
					V.C.			
+50			6.9		499.75 (9.1)	$CO\frac{3}{10.2}$	$CO\frac{3}{10}$ 500.4 6.9 $CO\frac{6}{℄}$	$CO\frac{3}{10}$ $CO\frac{3}{10.2}$
173+00			5.2		501.5 (10.1)	$CO\frac{5}{10.3}$	$CO\frac{5}{10}$ 502.1 5.2 $CO\frac{6}{℄}$	$CO\frac{3}{10}$ $CO\frac{3}{10.2}$
+50			3.4		+3.50% 503.3 (11.1)	$CO\frac{6}{10.3}$	$CO\frac{6}{10}$ 503.9 3.4 $CO\frac{6}{℄}$	$CO\frac{4}{10}$ $CO\frac{4}{10.2}$
					475 504.12			
174+00			2.6		504.8	$FO\frac{2}{8.3}$	504.7 2.6 $FO\frac{L}{℄}$	0.0 10.0
					50' V.C.			
+20			2.6		505.0	Fill	504.7 2.6 $FO\frac{3}{℄}$	0.0 10
					+25 505.0			
+29			7.5		505.0		499.8 7.5 $F\frac{5}{℄}$	
+37			9.1		505.0		498.2 9.1	
					Level Gr.			
+50			10.0		505.0		497.3 10.0	
Creek								
+57			9.5		505.0		497.8 9.5	
+67			5.8		505.0		501.5 5.8	
					+75 505.0			
+80			3.6		505.0		503.7 3.6 $F1\frac{3}{℄}$	
175+00			2.8		50' V.C. 505.2	$FO\frac{6}{8.9}$	504.5 2.8 $FO\frac{7}{℄}$	$FO\frac{3}{8.5}$
			1.69	505.59 TP.		+10 = 0.0 10 Rt.		
	12.05	517.64						

(51)

	+	H.I. 517.64	−	Elev.
175+25			10.9	
+50			9.8	
+75			9.4	
176+00			8.0	
+15			8.1	
+50			6.1	
+80			6.5	
177+00			7.0	
+25			7.1	
+50			5.7	
+75			4.9	
178+00			5.2	
Place 12" Pipe (Gutter)				
+50			3.8	

Nov. 17-'27
Ward – Notes
Duermit – Inst.
McBain – Rod

	Lt	℄ 517.64 H.I.	Rt
505.75 (18.6)		0.0 / 11.0 — 10.9 C1⁰ ℄ (506.7)	C1⁵/10 C1⁶/10.8
506.5 (26.9)	CO³/10.2	CO³/10 — 9.8 C1³ ℄ (507.8)	C2²/10 C2⁴/11.2
507.3 (21.4)	CO⁶/10.3	CO⁶/10 — 9.4 CO⁹ ℄ (508.2)	C1⁷/10 C1⁸/10.9
508.0 (30.6)	CO⁷/10.4	CO⁷/10 — 8.0 C1⁶ ℄ (509.6)	C2²/10 C2⁰/11.0
508.5 (18.9)	CO⁵/10.3	CO⁵/10 — 8.1 C1⁰ ℄ (509.5)	C1²/10 C1²/10.6
509.5 (36.8)	C1¹/10.6	C1¹/10 — 6.1 C2⁰ ℄ (511.5)	C2⁰/10 C2⁰/11.0
510.4 (16.5)	C1⁰/10.5	C1⁰/10 — 6.5 CO⁷ ℄ (511.1)	CO³/10 CO⁹/10.5
511.0 (1.6)		0.0 / 8.0 — 7.0 FO⁴ ℄ (510.6)	0.0 / 4.0 CO⁵/10 CO⁵/10.3
511.8		F2⁰/11.0 — 7.1 F1³ ℄ (510.5)	0.0 / 12.0
512.50		F1²/9.8 — 5.7 FO⁶ ℄ (511.9)	0.0 / 10.0
512.9 (2.5)		F2⁰/11.0 — 4.9 FO² ℄ (512.7)	0.0 / 2.0 CO⁶/10 CO⁶/10.3
513.2 (3.1)		F2¹/11.2 — 5.2 FO⁸ ℄ (512.4)	0.0 / 7 CO²/10 CO²/10.1
513.9 (3.8)		F1³/10.0 — 3.8 FO¹ ℄ (513.8)	0.0 / 1.0 CO⁸/10 CO⁸/10.4

(52)

	+	H.I. 517.64	−	Elev.
179+00			2.1	
+50			1.2	
			5.55	512.09 B.M. #20
B.M. - Spk. in Hub 25' Lt. 180+00				
	9.88	521.97		
180+00			5.0	
+15			5.0	
+50			5.1	
181+00			5.2	
+25			5.2	
+50			5.3	
+75			4.7	
182+00			5.9	
+25			5.9	

+0.40 +1.50 +0.50 -0.50

℄ Grade	Lt	℄ 517.64 H.I.	RH
514.6	(20.4)	0.0 515.5 2.1 CO9 ℄ 8.0	C2 2 10 C2 4 11.2
515.3	(23.3)	0.0 516.4 1.2 C1 1 ℄ 7.5	C2 4 10 C2 8 11.4
		521.97 H.I.	
516.0	(16.9)	0.0 517.0 5.0 C1 0 ℄ 5.7	C2 8 10 C2 9 11.5
516.1	(23.9)	0.0 517.0 5.0 CO2 ℄ 4.4	C3 0 10 C3 1 11.6
516.3	(14.5)	0.0 516.9 5.1 CO 5 ℄ 3.0	C1 9 10 C2 1 11.1
516.5	(9.4)	0.0 516.8 5.2 CO3 ℄ 3.0	C1 4 10 C1 4 10.7
516.6	(7.0)	0.0 516.8 5.2 CO2 ℄ 1.0	C1 1 10 C1 3 10.7
516.8	(5.1)	516.7 5.3 FO1 ℄	0.0 C1 0 C1 1 0.5 10 10.6
516.9	(7.4)	0.0 517.3 4.7 CO4 ℄ 3.2	CO 9 CO 9 10 10.5
517.0	(0.9)	F2 6 516.1 5.9 FO 9 ℄ 11.9	0.0 CO 4 CO 4 5.5 10 10.2
516.9	(0.3)	F2 3 516.1 5.9 FO 8 ℄ 11.5	0.0 CO 3 CO 4 8.5 10 10.2

(53)

	+	H.I. 521.97	—	Elev.
+50			5.6	
+75			5.6	
183+00			5.0	
+30			5.0	
+50			5.5	
184+00			4.9	
+50			5.1	
+75			6.3	
185+00			5.5	
Place 12" Pipe (Gutter)				
			7.75	514.22 TP.
	8.35	522.57		
+20			5.8	
+50			6.6	
186+00			7.2	

-0.50 %

-0.50 %

Grade	Lt	℄ 521.97 H.I.	Rt	
516.8	(3.6)	516.4 F2 5.6 FO4 ℄ (11.3)	0.0 2.5	CO2 10 CO2 10.5
516.6	(4.7)	516.4 5.6 FO2 ℄	0.0 3.5	C13 10 C15 10.8
516.5	(11.6)	517.0 5.0 CO5 ℄ (4.5)	0.0	C13 10 C14 10.7
516.3	(18.3)	517.0 5.0 CO7 ℄ (3.6)	0.0	C24 10 C26 11.3
516.2	(11.5)	516.5 5.5 CO3 ℄ (0.5)	0.0	C12 6 C18 10 C18 11.0
516.0	(22.1)	517.1 4.9 C14 ℄ (5.5)	0.0	C24 10 C26 11.3
515.7	(23.8)	516.9 5.1 C12 ℄ (5.0)	0.0	C26 10 C28 11.4
515.6	(14.8)	515.7 6.3 CO1 ℄ (1.0)	0.0	C25 10 C27 11.4
515.5	(22.3)	516.5 5.5 C10 ℄ (6.0)	0.0	C25 10 C28 11.4
		522.57 H.I.		
515.4	(26.7)	516.0 5.8 C14 ℄ (6.0)	0.0	C27 10 C29 11.5
515.2	(20.3)	516.0 6.6 CO8 ℄ (5.0)	0.0	C25 10 C27 11.4
515.0	(15.4)	515.4 7.2 CO4 ℄ (2.5)	0.0	C22 10 C25 11.3

(54)

	+	H.I. 522.57	−	Elev.
+25			6.9	
+50			7.0	
187+00			7.6	
+50			7.2	
188+00			6.8	
+15			6.6	
+50			7.0	
189+00			7.6	
+25			5.9	
+50			7.0	
+60			7.6	
+64			8.3	
Creek				
+74			7.5	

− 0.50 %

100' V. C.

+ 2.60 %

50' V. C.

− 3.50

100' V. C.

℄ Grade		Lt	℄ 522.57 H.I.			Rt		
				515.7				
514.9	(16.5)		0.0	6.9	CO 8 ℄	C1 3	C2 1	
			5.0			10	11.1	
				515.6				
514.7	(18.7)		0.0	7.0	CO 9 ℄	C2 1	C2 3	
			5.5			10	11.2	
				515.0				
514.50	(15.8)	CO 2 10.1	CO 2 10	7.6	CO 5 ℄	C1 8	C1 8	
						10	10.9	
				515.4				
514.6	(18.1)		0.0	7.2	CO 8 ℄	C2 1	C2 2	
			6.0			10	11.1	
				515.8				
515.55	(11.0)		0.0	6.8	CO 2 ℄	C1 8	C1 9	
			1.0			10	11.0	
				516.0				
516.0	(7.6)			6.6	0.0 ℄	C1 4	C1 5	
						10	10.8	
				515.6				
516.85	(3.2)		F2 5	7.0	F1 2 ℄	0.0	C1 0	C1 1
			11.7			4.2	10	10.6
				518.0				
516.62	(29.9)		0.0	4.6	C1 4 ℄	C3 0	C3 2	
			7.8			10	11.6	
				516.7				
515.75	(21.8)		0.0	5.9	C1 0 ℄	C2 1	C2 9	
			6.0			10	11.5	
				515.6				
515.1	(9.7)		0.0	7.0	CO 5 ℄	CO 9	CO 9	
			10.0			10	10.5	
				515.0				
514.9	(6.0)		0.0	7.6	CO 1 ℄	C1 0	C1 1	
			4.0			10	10.6	
				514.3				
514.8	(1.7)			8.3	FO 5 ℄	0.0		
						8.0		
				515.1				
514.9	(1.7)		0.0	7.5	CO 2 ℄	0.0		
			7.0			10.0		

(55)

	+	H.I. 522.57	−	Elev.
+85			6.9	
190+00			6.1	
			7.13	515.44 B.M. #21

B.M. - Spk. in Hub 50' Lt 190+00

8.47 523.91

+50			7.1	

Continued Page 57.

191+00			7.2	
+50			7.4	
192+00			7.3	
+50			7.6	
193+00			8.4	
+50			11.4	
193+73.11 ℄ End 1st Line.			12.9	
			9.03	514.88 On USGS B.M.

USGS-B.M. - Plate on Boulder 10' Rt. End of Line

Elev. = 514.887

℄ Grade	Lt		℄ 522.57 H.I.		Rt	
515.0	(17.1)	CO 7 / 10.4	CO 7 / 10	6.9 (515.7)	CO 7 / ℄	C 1 2 / 10	C 1 3 / 10.7
515.2	(24.7)	CO 9 / 10.5	CO 9 / 10	6.1 (516.5)	C 1 3 / ℄	C 1 3 / 10	C 1 3 / 10.7
516.0							

523.91 H.I.

7.1
7.2
7.4
7.3
7.6
8.4
11.4
12.9

(56)

+	H.I.	−	Elev.

LH ℄ RH

(57) From Page 55

	H.I.	−	Elev.
U.S.G.S. BM. - Plate on Boulder			514.89
BM. - U.S.G.S.	12.95	527.84	
190+50		10.7	
191+00		8.7	
+40		6.9	
+50		5.8	
+60		4.9	
192+00		3.7	
+50		0.8	
T.P.		1.07	526.77
	12.85	539.62	
+85		11.5	
193+00 Place 12" Pipe		10.2	
+50		7.2	

+25 × 4.0 %

× 5.33 %

℄ Grade	Lt	℄	Rt
		527.84 H.I.	
516.0			
		517.1	
517.0	1.9	0.0 / 8.0 — 10.7 CO 1 ℄	CO 2 / 10 — CO 2 / 10.1
		519.1	
519.0	8.0	0.0 / 1.0 — 8.7 CO 1 ℄	C 1 4 / 10 — C 1 4 / 10.7
		520.9	
521.2	3.4	6.9 FO 3 ℄	0.0 / 2.0 — CO 8 / 10. — CO 8 / 10.4
		522.0 ℄	
521.7	15.6	0.0 / 3.0 — 5.8 CO 3 ℄	C 1 6 / 10 — C 1 6 / 10.8
		522.9	
522.2	11.7	0.0 / 5.0 — 4.9 CO 2 ℄	C 1 2 / 10 — C 1 3 / 10.7
		524.1	
524.3	3.4	3.7 FO 2 ℄	0.0 / 2.0 — CO 8 / 10 — CO 8 / 10.4
		527.0 ℄	
527.0	4.2	FO 5 / 8.7 — 0.8 0.0 ℄	CO 8 / 10 — CO 8 / 10.4
		539.62 H.I.	
		528.1	
528.9	2.0	11.5 FO 8 ℄	0.0 / 7.0 — CO 1 / 10.1
		529.4	
529.7	2.4	F 1 / 9.5 — 10.2 FO 3 ℄	0.0 / 3.5 — CO 7 / 10 — CO 7 / 10.4
		532.9	
532.3	6.4	0.0 / 1.0 — 7.2 CO 1 ℄	C 1 1 / 10 — C 1 1 / 10.6

	+	H.I.	−	Elev.	
(59)					
		539.62			
193+65			5.8		
194+00			3.8		
+27.29			2.4		
+40			1.4		
+50			1.0		
T.P.			0.27	539.35	T.P.
	11.92	551.27			
195+00			10.5		
+35			9.3		
+50			7.8		
+75			7.3		
196+00			5.7		
+50			3.0		

+5.33 %

+5.33 %

℄ Grade	Lt		℄		Rt	
			539.62 H.I.			
			533.8			
533.1	(15.7)		0.0 5.8 CO 7 ℄		C1 9 10	C2 0 11.0
			535.9			
535.0	(17.0)	CO 4 10.2	CO 4 10	3.8 CO 8 ℄	C1 3 10	C1 4 10.7
			537.2			
536.5	(18.1)		0.0 2.4 CO 7 ℄		C2 0 10	C2 1 11.1
			538.2			
537.2	(26.3)	CO 5 10.3	CO 5 10	C1 3 6 1.4 C1 0 ℄	C1 7 10	C1 7 10.9
			538.6			
537.7	(22.7)	CO 4 10.2	CO 5 10	CO 8 6 1.0 CO 9 ℄	C1 9 10	C2 0 11.0
			551.27 H.I.			
			540.8			
540.3	(16.0)		0.0 10.5 CO 5 ℄		CO 8 5	C1 7 10 C1 8 10.9
			542.0			
542.2	(4.3)	FO 1 8.6	9.3 FO 2 ℄		0.0 2.0	C1 0 10 C1 0 10.5
			543.5			
543.0	(7.3)		0.0 7.8 CO 5 ℄		CO 9 10	CO 9 10.5
			544.0			
544.3	(0.6)		7.3 FO 3 ℄		0.0 7.0	CO 4 10 CO 4 10.2
			545.6			
545.7			5.7 FO 1 ℄		0.0 4.0	0.0 10.0
			548.3			
548.3	(4.7)	F2 5 11.7	3.0 0.0 ℄		CO 9 10	CO 9 10.5

(59)

	+	H.I.	−	Elev.
		551.27		
196+75			1.3	
			1.76	549.51
	12.89	562.40		
197+00			9.9	
+18			7.1	
+50			7.4	
+75			8.6	
198+00			9.1	
+30			7.4	
+50			5.7	
			0.35	562.05 B.M. #22

B.M. #22 - Spike in Hub 25' Rt - 198+25

5.15 567.20

× 5.33 %

× 3.0 %

Grade	Lt		℄ 551.27 H.I.	Rt	
			550.0		
541.7	(13.4)	0.0 2.0	1.3 $CO^{3}_{\text{℄}}$	$C1^{3}_{4}$	$C1^{7}_{10}$ $C1^{9}_{11.0}$
			562.40 H.I.		
			552.5		
551.0	(35.9)	$CO^{6}_{10.3}$	CO^{6}_{10} 9.9 $C1^{5}_{\text{℄}}$	$C3^{8}_{10}$	$C4^{0}_{12.0}$
			555.3		
551.6	(71.6)	$C1^{3}_{10.7}$	$C1^{4}_{10}$ 7.1 $C3^{7}_{\text{℄}}$	$C4^{4}_{10}$	$C4^{5}_{12.3}$
			555.0		
552.5	(49.9)	0.0 11.5	7.4 $C2^{5}_{\text{℄}}$	$C3^{8}_{10}$	$C4^{7}_{12.1}$
			553.8		
553.2	(27.3)	0.0 2.6	8.6 $CO^{6}_{\text{℄}}$	$C3^{8}_{10}$	$C4^{8}_{12.4}$
			553.3		
554.0	(9.3)	$F4^{7}_{15.0}$	9.1 $FO^{7}_{\text{℄}}$	0.0 2.0	$C2^{0}_{10}$ $C2^{5}_{11.3}$
			555.0		
554.9	(15.4)	0.0 1.0	7.4 $CO^{1}_{\text{℄}}$		$C2^{5}_{10}$ $C3^{8}_{11.9}$
			556.7		
555.5	(31.5)	0.0 8.0	5.7 $C1^{2}_{\text{℄}}$	$C3^{5}_{10}$	$C3^{5}_{11.8}$

(60)

	+	H.I.	−	Elev.	
		567.20			
198 + 65			10.2		
199 + 00			8.4		
+ 21 95			7.7		
+ 50			7.8		
200 + 00			10.0		
+ 50			12.9		
T. P.			12.70	554.50	T.P.
	3.68	558.18			
+ 73			6.1		
201 + 00			8.9		
+ 36 42	E.C.		10.8		
+ 50			11.5		
			12.55	545.63	T.P.
	1.54	547.17			

+ 3.0 %

100' V.C.

− 1.0 %

Grade	L.T.		℄ 567.20 H.I.		RT
				557.0	
556.0	(28.0)		0.0 4.0	10.2 C1 = ℄	C3 5 10 C4 0 12.0
				558.8	
557.0	(42.1)	C0 6 10.3	C0 6 10	8.4 C1 8 ℄	C3 5 10 C3 9 12.0
				559.5	
557.4	(49.0)	C0 9 10.5	C1 0 10	7.7 C2 1	C3 8 10 C4 2 12.0
				559.4	
557.2	(54.5)	C1 0 10.5	C1 0 10	7.8 C2 2 ℄	C4 4 10 C4 8 12.4
				557.2	
555.0	(51.9)	C0 7 10.4	C0 7 10	10.0 C2 2 ℄	C4 2 10 C5 0 12.5
				554.3	
551.5	(63.7)	C1 0 10.5	C1 0 10	12.9 C2 8 ℄	C4 8 10 C5 3 12.7
			558.18 H.I.		
				552.1	
549.9	(53.0)	C0 4 10.2	C0 4 10	6.1 C2 2 ℄	C4 6 10 C5 2 12.6
				549.3	
548.0	(32.0)		0.0 3.5	8.9 C1 3 ℄	C3 8 10 C4 9 12.2
				547.4	
545.5	(47.8)		0.0 5.0	10.8 C1 9 ℄	C5 2 10 C5 8 12.9
				546.1	
544.5	(45.4)		0.0 8.5	11.5 C2 2 ℄	C4 7 10 C5 5 12.8

(61)

	+	H.I.	−	Elev.
		547.17		
202+00			3.9	
+25			5.7	
+37			7.3	
+50			8.5	
+75			9.8	
203+00			12.6	
T.P.			11.98	535.19 TP
	1.11	536.30		
+10			2.4	
+35			8.5	
+50			9.7	
+65			9.2	

8% Ascent

−7.0% Descent

100' V. Cr.

Grade	Lt.		℄	Rt
			547.17 H.I.	
541.0	(57.6)	0.0 / 8.0	3.9 (543.3) C2 3 ℄	C5 5 / 10 C6 8 / 13.4
539.2	(60.5)	0.0 / 5.8	5.7 (541.5) C2 3 ℄	C6 2 / 10 C7 0 / 13.5
538.4		Not needed	~~7.3 (539.9) C1 5 ℄~~	
537.5	(33.8)	0.0 / 3.0	8.5 (538.7) C1 2 ℄	C4 2 / 10 C4 8 / 12.4
535.7	(47.9)	0.0 / 6.0	9.8 (537.4) C1 7 ℄	C5 2 / 10 C6 4 / 13.2
534.0	(31.6)	0.0 / 2.5	12.6 (534.6) C0 6 ℄	C4 7 / 10 C5 4 / 12.7
			536.30 H.I.	
533.3	(25.9)	0.0 / 0.5	2.4 (533.9) C0 6 ℄	C3 7 / 10 C4 6 / 12.3
531.5	(10.3)		8.5 (527.8) F3 7 ℄	0.0 / 3.5 C1 5 / 5 C1 8 / 10 C2 0 / 11.0
		+43 = 0.0	−10 Rt.	
530.5		FA 3 / 14.3	9.7 (526.6) F3 9 ℄	F2 4 / 11.6
529.5		F2 9 / 12.4	9.2 (527.1) F2 4 ℄	F1 7 / 9.8
		+70 = 0.0	on Rt.	

(62)	+	H.I.	−	Elev.		Lt.	℄	Rt
							536.80 H.I.	
		536.30						
+75			9.6					
See Page 63 for Continued Line.						528.9 (4.1)	F2½ 11.3 9.6 (526.7) F2½ ℄	0.0 C1½ C1½ 4.8 10 10.7
			0.32	535.98	B.M.#23			
B.M.#23 - 30' Rt.		Sta. 203+74.85						
		R.P. Hub.						
T.P.			11.40	524.90				
	2.50	527.40						
T.P.			9.31	518.09				
	1.35	519.44						
T.P.			5.18	514.26				
	4.16	518.42						
			3.56	514.86				
		See Page 63						

(63)

	+	H.I.	−	Elev.		Grade	Lt	℄	Rt
				535.98 B.M.				536.72 H.I.	
	0.74	536.72							
204+00			9.8		100' V.C.	527.8	(7.8)	FO 8 9.2	526.9 9.8 FO 9 ℄ 0.0 5.5 C 18 7 C 22 10 C 35 11.8
204+21.08 E.C.			9.7			527.2	(6.5)	0.0 5.0 0.0 1.0	527.0 9.7 FO 2 ℄ 0.0 5.0 C 2 10 C 32 11.5
End Line									
+50			9.9			527.0			526.8 9.9
205+00	County Road		10.6			527.0			526.1 10.6
+50			9.8			527.0			526.9 9.8

7-18-39
7.0.

Septic Tank + Sewer Construction at Lower Otay



Flow line of outlet 2.5 below top

B.M.	0.08	104.47		104.39	Nail in tree with R.P. Nail	
S.W. 2' Back			4.47	100.00	100.00	Grade of top.
S.E. Cor.			3.47	101.00	100.00	C - 1.0
N.E. Cor.			2.47	102.00	100.00	C - 2.0
N.W. Cor.			3.47	101.00	100.00	C - 1.0
		102.74				
℄ Switch box	50' S.		5.40	97.34	97.34	Grade of top
				97.34	96.34	C - 1.0 to Flow line of intake
				97.34	95.84	C - 1.5 " " " " Outlet

(66) Diffusion Lines.

sta.	+	H.I.	-	Elev.	Grade	Cut
Upper line "A"		102.74				
0+00 = ℄ switch box			5.40	97.34	95.84	1.5 to Flow line
0+25			5.95	96.79	95.79	1.0 to Flowline ℄ 1.5 to bottom of ditch
0+50			6.00	96.74	95.74	1.0
0+75			6.05	96.69	95.69	1.0
1+00			6.10	96.64	95.64	1.0
1+25			6.15	96.59	95.59	1.0
1+50			6.20	96.54	95.54	1.0
1+75			6.25	96.49	95.49	1.0
2+00 end "A" line			6.30	96.44	95.44	1.0
Middle line "B"						
0+00 = ℄ Switch box					95.84	℄ 1.5
0+25			6.55	96.19	95.19	1.0
0+50			7.50	95.24	94.24	1.0
0+75			7.55	95.19	94.19	1.0
1+00			7.60	95.14	94.14	1.0
1+25			7.65	95.09	94.09	
1+50			7.70	95.04	94.04	
1+75			7.75	94.99	93.99	
2+00 end.			7.80	94.94	93.94	

102.74

	H.I.	-	Elev.	Grade	Cut.
Lower Line "C"	102.74				
0+00 = ℄ Switch box				95.84	
0+25		7.15	95.59	94.59	1.0
0+50		8.58	94.16	94.16	1.0
0+75		8.90	93.84	93.84	1.0
1+00		8.95	93.79		1.0
1+25		9.00	93.74		1.0
1+50		9.05	93.69		1.0
1+75		9.10	93.64		1.0
2+00		9.15			1.0

(68) Settling tank from Fish Tables.

B.M. Nail in Cor. of toilet				97.62	
	2.37	99.99			
℄ Settling box			2.71	97.28	98.28
on stake 2' back			1.71	98.28	98.28
F.L. of outlet tile					96.28
0+25			2.76	97.23	96.23
0+37.5			2.79	97.20	96.20
0+50			2.81	97.18	96.18
0+62.5			2.84	97.15	
0+75			2.86	97.13	
1+00			2.91	97.08	
1+25			2.96	97.03	
1+50			3.01	96.98	
T.P.			3.02	96.97	
	2.48	99.45			
1+75			2.52	96.93	
2+00 End.			2.57	96.88	

Fill 1.0
Grade top of box
C-1.0
1.0
1.0
1.0



Drainage Pipe for Road Construction at Lower Otay.

12" Corrugated Metal Pipe

Sta. 3+35 — 20 ft.
10+00 — 24
19+25 — 18
22+50 — 20
29+50 — 18
54+80 — 20
59+50 — 20
68+20 — 22
93+00 — 22
107+50 — 18
109+85 — 18
121+00 — 20
131+50 — 22
151+50 — 18
155+00 — 20
178+00 — 20
185+00 — 20
193+00 — 20
195+50 — 20

Summary 12" Pipe

5 pcs 18' Long 90 Lin. Ft.
10 " 20' " 200 " "
3 " 22' " 66 " "
1 " 24' " 24 " "
Total = 380 Lin. Ft.

18" Corrugated Metal Pipe

Sta. 44+75 — 20 ft.
51+65 — 20
89+00 — 22
118+80 — 20
139+65 — 26
166+00 — 22
203+50 — 22

Summary 18" Pipe

3 pcs. 20' Long 60 Lin. Ft.
3 " 22' " 66 " "
1 " 26 " 26 " "
Total = 152 Lin. Ft.

24" Corrugated Metal Pipe.

Sta. 25+85 — 24 ft. Total = 24 Lin. Ft.

30" Corrugated Metal Pipe

Sta. 13+92 — 18 ft. Total = 18 Lin. Ft.

36" Corrugated Metal Pipe

Sta 144+45 — 26 ft. Total = 26 Lin. Ft.

Upper Otay Dam.

Crest of Dam	Elev. = 554.74
Crest of Spillway	549.56
Flow of Outlet Pipe	520.86

(80)

Elev. = 992.20 – Roadway on top Lower Otay Dam.

Elev. = 514.887 – U.S.G.S. B.M. Upper end Lake.



IMPROVED TABLES

AND

INFORMATION



194+27.29
190+24.83
402.46

28.39 - 30'