
FWA 2
271-A
W271A

EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and SURVEYING INSTRUMENTS
Chicago New York San Francisco New Orleans Pittsburg Toronto

DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

Roadway 16 feet wide. Side Slopes 1 on 1.

For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.1	8.2	8.3	8.4	8.5	8.6	8.7	8.8	8.9	0
1	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	1
2	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	2
3	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	3
4	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	4
5	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	5
6	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	6
7	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	7
8	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	8
9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	9
10	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	10
11	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	11
12	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	12
13	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	13
14	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	14
15	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	15
16	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	16
17	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	17
18	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	18
19	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	19
20	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	20
21	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	21
22	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	22
23	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	23
24	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	24
25	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	25
26	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	26
27	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	27
28	36 0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	28
29	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	29
30	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	30
31	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	31
32	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	32
33	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	33
34	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	34
35	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	35
36	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	36
37	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	37
38	46.0	46.1	46.2	46.3	46.4	46.5	46.6	46.7	46.8	46.9	38
39	47.0	47.1	47.2	47.3	47.4	47.5	47.6	47.7	47.8	47.9	39
40	48.0	48.1	48.2	48.3	48.4	48.5	48.6	48.7	48.8	48.9	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be 30.6+(20—16)÷2 or 2 ft. added to 30.6 =32.6. For slopes of 1 on 1½ see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

633

256.78
433
761.11

248.99
467
253.66

MICROFILMED
JAN 11 1965

2

30 May 1942

Unit No 2.

Pt Loma Res. - 10,000,000 Gal.



Ross Banks - Bostonia - Jack Shrade, Foreman

Wilcox
Sutliff
Abate
Roads

284.67

49527

175.67 2.244680

284.67 2.454335

31°41 9.790345

2.244697 6

2.454341 7

31°40'43" 9.790355 9

39

156

2.454341 7

9.929734

334.51 2.524407 5

	BS	HI	FS	Rod	Elev
Bm	9.48	259.65			250.17
TP	4.81	262.65	1.81		257.84
Bm				3.505	259.15
BA				2.00	260.65

Spike in Curb S W Cor. Catalina & Karona

Nail on E side Pole S D&SE Co. # 1080

Point on N W Cor Concrete Pediment N W Cor Catalina & Santa Barbara



Range A June 9th point Loma Reservoir

Grids

Sta	B.S.	I	F.S.	Rod	B.M. 250.17
	11.18	261.35			
I.P.			12.74		B.M. Established 248.61
	4.16	252.77		248.61	
0+00			2.6	250.2	
			4.6	248.2	
			6.6	246.2	
			8.4	244.4	
			10.2	242.6	
			11.7	241.1	
			13.2	239.6	
			14.9	237.9	
Range B					
Sta					
0+00			2.5	250.3	
+25			4.3	248.5	
+50			6.0	246.8	
+75			7.5	245.3	
1+00			9.5	243.3	
+25			11.0	241.8	
1+50			12.8	240.0	
1+75.7			14.7	238.1	



Range C

Sta	B S	H I	F S	Elev
		252.77		
Range C			2.0	250.8
			4.2	248.6
			5.8	247.0
			7.6	245.2
			9.3	243.5
			10.9	241.9
			12.6	240.2
			14.5	238.3
R-D				
0+00			1.6	251.2
			3.3	249.5
			5.3	247.5
			7.2	245.6
			8.9	243.9
			10.6	242.2
			12.3	240.5
			14.0	238.8

Range
E

Sta	B.S.	I	F.S.	Elev.
0+00		252.77	1.2	251.6
			3.1	249.7
			5.1	247.6
			6.9	245.9
			8.7	244.1
			10.3	242.5
			12.0	240.8
			13.7	239.1
R-F				
Sta				
0+00			1.0	251.8
			2.8	250.0
			4.5	248.3
			6.6	246.2
			8.3	244.5
			10.1	242.7
			12.0	240.8
			14.0	238.8

TR-G

Sta	B.S	Δ	F S	
S		252.77		
0+00			1.0	251.8
			2.7	250.1
			4.5	248.3
			6.5	246.3
			8.1	244.7
			9.9	242.9
			11.7	241.1
			13.8	239.0
TR-H				
0+00			0.8	252.0
			2.6	250.2
			4.3	248.5
			6.0	246.8
			7.7	245.1
			9.2	243.6
			10.8	242.0
			12.4	240.4

TR-K

Sta	B.S.	I	F.S.	
		252.77		
0+00			0.6	252.2
			2.4	250.4
			4.0	248.8
			5.6	247.2
			7.2	245.6
			8.6	244.2
			10.2	242.6
			11.7	241.1

TR-L

0+00			0.7	252.1
			2.3	250.5
			3.8	249.0
			5.3	247.5
			6.8	246.0
			8.2	244.6
			9.6	243.2
			11.2	241.6

Range
777

Sta	B.S.	I	F.S.	
		252.77		
			0.8	252.0
			1.9	250.9
			3.5	249.3
			5.0	247.8
			6.5	246.3
			7.8	245.0
			9.2	243.6
			11.3	241.5

Range (M) — Elevs of Stakes

Sta	B.S.	Δ	F.S.	Elev.	
	2.46	257.07		248.61	
0+00					
+25			0.20	250.87	
+50			1.71		
+75			3.34		
1+00			4.83		
+25			6.09		
+50			7.49		
1+75.67			9.50		
T.P.	4.35	255.22		250.87 = Sta 0+25	
			3.05	252.17 = Sta 0+00	

Range-M
offset
slope

Sta	B.S.	Δ	F.S.	Elev

Range-A

Sta	B.S.	Δ	F.S.	Elev

Range A
offset slope

Sta	B.S.	I	F.S.	Elev

West Side

Ranges

	B.S.	I	F.S.	E/E.V
A	6.60	255.21		248.61
B				
A = 0+00			5.03	250.18
B =			5.05	250.16
C			4.48	250.73
D			4.17	
E			3.73	
F			3.45	
G			3.40	
H			3.16	
K			3.01	
L			3.03	
M				

North Line of TOG

Sta	B.S.	H.I.	F.S.	Rod	Elev
	10.46	260.63			250.17
	1.62	249.50	12.75		247.88
N 0+50	on Line			4.63	
1+00	"			7.66	241.84
1+50				10.50	239.00
N.E. Cor 1+75				11.28	238.22
(1+50)	1.77	243.61			241.84
1+50	Inner			4.97	238.64
"	Outer			5.68	237.93
"	Toe 32.10			5.73	237.88
	" 42.10			5.82	237.79
N.E. Cor 1				7.32	236.29
	Outer 16'			7.74	235.87
2				8.16	235.45



Line-C = Inlet 16" Pipe ℄ 3-0" west N-E

Sta	B.S.	Π	F.S.	Grad	Elev
	1.59	238.81			237.22
0+00				2.57	
+50				3.56	
1+00				4.52	
1+44				7.13	
1+50				7.36	
1+60				7.72	

Line-D = 11- west of N-E Cor- starting from ℄ of sump 148.33 S

0+00					
+50 22	1.59	238.81		0.77	237.22
1+00 22				0.82	
1+48 55				1.34	
1+85 41				1.78	
2+00				2.02	
+50				3.12	
3+00				4.07	
3+08 39				4.62	



Overflow Line 7' offset

Sta	B.S.	I	F.S.	Rod	Stake Elev
	6.29	248.13			Sta 1+00 on line 241.84
0+00				2.64	
0+50				2.88	
0+88				2.10	
1+00				3.79	
+50				7.32	
2+00				11.21	
	1.59	238.81			N.E. Hub 237.22 =
2+50				5.70	
3+00				8.61	
3+24				8.39	

Sta 0+00 = Toe of Reservoir



Tile Drain Pipe Profile and Cuts } stakes
{Call Pipe - A

sta	B.S.	H	F.S.	rod	Elev
	4.63	241.85			= Stake 77,55. 237.22 Cut
0+00				4.30	237.55
TP	4.77	241.99			237.22
0+43				7.85	
+83				10.35	231.64
+86				10.43	231.56

Cut	Fill	flowline
7.55		230.0
4.91		229.23
3.14		228.80
5.12		226.44 = Sub grade of Box North side



Levels for Top of inside cut

sta	B.S	I	F.S.	Rod	Elev
	13.06	254.90			241.84
nr c to o				6.44	248.46
45° Δ				5.04	249.86
				3.59	250.31
	below = 50' offsets for Road & toe of 2:1 slope				
	9.96	260.13			250.17

Cut	Fill	From Toe Dist. out	
14.79	5.54	22.39	= N & S Line
16.19	4.14	24.26	
16.64	3.69	26.47	= E & W-Line



14 June 42

Levels & Cuts Inlet Line

	BS	HI	FS	Rod	
1+00	0.24	242.08			241.84
(1+50)				3.07	239.01
3+26				4.82	237.26
2+00				5.67	238.41
2+50				5.93	236.15
2+00				8.13	233.95
1+50				10.87	231.21

Outlet Pipe

N.E. Con.	5.83	244.05			238.22
4+72	Ends			7.68	236.37
+50				6.97	237.08
				4.69	239.36
4+00				4.73	240.32
3+50				5.42	238.63
3+00				5.92	238.13
+90.27				6.02	238.03
2+50				6.73	237.32
2+00				7.64	236.41
1+50				9.55	234.50
1+00					
0+50					
0+28					

Trench Cuts

Grade

Sa/p 12

234.50	2.76
234.50	1.91
233.30	2.85
231.80	2.65
229.30	1.91
231.00	5.37 / 6.08
230.94	8.42
230.80	9.52
230.65	7.98
230.50	7.63
230.34	7.69
229.70	7.62
228.90	7.51
228.10	6.40
227.30	
226.50	
226.14	

Sa/p 12

272 | 436 (1.60
272
1640
1632
800

172 | 500 (.291
344
1560

0262
.1734

4036 -
272
1605

32
16
492
32
810

3.01
172

142.33

14 June 1942

Lines from Drain Box

Sta	B.S	H.I	B.S	F.S	Elev
Bm	.153	239.75			238.22
4 Pipes ℄				389	235.86
" Ⓣ				1 22	238.53
0+43				461	235.14
0+81 Ent 4 Drain Ⓣ				710	232.65
" ℄ Box Ⓣ				718	232.57
Box Cen				783	231.92
℄ Valve Box				798	231.77
16" Drain Line 0+0					
" 0+81 Ⓣ				791	231.84
" ℄					
0+00 Ⓣ				268	237.07
" ℄				365	236.10

p.12

230.00	5.86
"	8.53
229.28	5.89
228.50	4.15
227.0	-5.57
227.0	-4.92
227.0	-4.77
227.75	4.09
228.00	9.07
228.00	8.10

Outlet Line

Overflow pipe & Box

June-14-1942

sta	B.S.	I	F.S.	Rod	Elev	
(1400)	8.81	250.61			241.84	
0+00				4.91	245.70	
"					"	
"					"	
0+50				4.34	246.27	
0+63				4.54	246.07	
	June 26-1942 - Whiles					
	1.35	258.13			256.78	BM
T.P			12.36		245.77	
"	2.52	248.29			245.77 = sta 1+50	
0+63				6.12	242.17	
1+00				5.57	242.72	
1+50				9.46	238.83	
T.P.	1.26	240.09			238.83	
2+00				5.18	234.91	
2+50				7.27	232.82	
2+88				8.46	231.63	

sta 4+00 = 230.4

21

Grade cut

up 12		
242.80 -	2.9	flow line
242.3 -	3.4	Bottom Box
241.3 -	4.4	Subgrade Box
242.0 -	4.27	
240.95 ✓	5.12	

7.73
13
2319
773
100.49 11.60 = 7.73
150

242.00
230.40
11.60

Valve flange on water meter

241.90	0.27
238.13	4.59
234.27	4.56
230.40	4.51
227.81	5.01
226.00	5.63

• Cuts on West Line 5' & 25' offsets

Sta	BS	H.I	FS	Rod	Elev
BM	4.58	263.73			259.15 ✓
0+0				5.39	258.34
0+30				5.13	258.60
0+60				5.61	258.12
0+90				5.29	258 44
1+26				4.83	258.90
1+42 33				4.95	258.78
1+64 67				5.00	258.73
1+94 67				5.91	257 82
2+24 67				6.90	256.83
2+54 67				7.20	256.53
2+84 67				7.23	256.50
T.P	12.91				250.82 = Sta 4+
		256.83	6.01		

263 7/3 / 4.95 — 263 7/3 / 5.61 — 263 9 3 / 5.13 — 258.78 — 258.12 — 263 7/3 / 4.83 — 258 60 — 258 90

Cut

Sta	
P3	
254.0	4.34
254.0	4.60
254.0	4.12
"	4.44
	4.90
	4.78
	4.73
	3.82
	2.83
	2.53
	2.50

Wood 0+82 0+90 0+106



West Line of Reservoir
= Line-A-on-Print

Sta	B.S.	π	F.S.	Rod	Elev = 0+90-A Line
T.P.	6.01				250.82
0+00				4.76	253.07
correction				2.12	254.71
	5.28	256.10			250.82
0+00				4.02	252.08
out 27.61					
0+30				5.59	250.51

sub.G.	Cut	Fill G.	Fill	Dist. out
233.67				
	21.04			(31.56) not used
	18.41			27.61
			1.82	2.39
233.52	16.99			25.48
			3.49	

South line of Reservoir
sta 0+00 to 1+75.67

Sta	B.S	H.I	F.S.	Rod	Elev
	2.90	254.98			sta-0+00 B.M. 252.08 =
0+00				2.90	252.08
Dividing line = D.L.				3.17	251.81
50' & 60' out				3.17	251.81
0+50				6.81	248.17
D.L.				6.21	248.77
50'-out				6.21	248.77
outside toe of slope				6.21	248.77
1+00				9.31	245.67
50' out				9.05	245.93
outside Toe				9.82	245.16
1+50				11.80	243.18
				11.12	243.86
				10.40	244.58
TP	3.06	246.24			= sta 1+50 243.18
1+75.67 = D.L. also				4.49	241.75
50' out				3.30	242.94
outside Toe				3.26	242.98
Correction from new HI 250.41				7.40	~~243.01~~

Toe of inside cut Dividing Line & toe of outside slope

24

cut	Fill	Dist. out
18.41		27.61
	1.92	2.39
	2.19	50.0
	2.19	60.0
14.50		21.75
	5.83	82.5
	5.23	50'0'
		60.56 = Toe of Slope
12.00		18.00
	8.33	12.00 check this?
	8.07	50.0
	8.84	69.68 T.S.
9.51	10.82	14.26
	10.14	50'0
		71.72 = T.S.
8.08		12.12
	12.25	17.88
	11.06	50'0
		72.12 = T.S.
	19.99	71.98 = T.S.

CTC - 22°-30' Intervals
of S.E Corner

Sta	B.S.	H	F.S.	Rod	Elev
	4.40	246.15			= Sta A75 69 241.75
22°-30' = D.L.				4.40	241.75
50'-out				4.14	242.01
Outside Toe.				4.14	242.01
45°-00' = D.L.				4.40	241.75
50' out				4.99	241.16
outside toe				5.00	241.15
67°-30' = D.L.				4.40	241.75
50-out				5.62	240.53
outside Toe				6.24	239.91
90°00' = sta 0+00-on, East Line				4.40	241.75
50-out				6.16	239.99
Outside Toe				7.30	238.85

from south line left

Cut	Fill	out
8.08	11.99	12.12 50.0 73.98 = T.S.
8.08	11.99 12.84 12.85	12.12 50.0 75.68 = T.S.
8.08	11.99 11.98 13.47 14.09	12.12 12.98 50.0 78.18 = T.S.
8.08	11.99 14.01 15.15	12.12 12.88 50.0' 80.30



East Side Line of Reservoir

Sta	B.S.	I	F.S.	Rod	Elev
	4.40	246.15			241.75
0+30				5.13	241.02
				6.24	239.91
				7.58	238.57
0+60				5.88	240.27
				7.03	239.12
				8.09	238.06
0+90				6.44	239.71
			Cor.	7.00	239.15
				7.89	238.26
				7.90	238.25
1+20				7.47	238.68
			Cor.	7.60	238.55
				9.41	236.74
				10.95	235.20
1+64.67				7.60	238.65
			Cor.	8.37	237.78
				10.90	235.25
				12.10	234.05
1+94.67				8.29	237.86
				9.54	236.61
				11.74	234.41
2+24.67				8.23	237.92
				9.55	236.60
				11.10	235.05

Cut	Fill	Out	Sub Grade
			233.52
7.50	12.98	11.25	
	14.09	50.0'	
	15.43	89.86 = T.S.	
			233.37
6.90		10.35	
	13.73	19.65	
	14.88	50.0'	
	15.94	81.88 = T.S.	
			233.22
6.49			
5.93	14.85	8.84	
	15.74	50.0	
	15.75	81.48	
			1+20 = 233.07
5.61			
5.48	15.45	8.22	
	17.26	50.0	
	18.80	90.0 = T.S.	
			233.07
5.58			
4.71	16.23	7.06	
	18.75	50.0'	
	19.95	89.90	
			233.22
4.64	16.14	6.96	
	17.39	50.0	
	19.59	89.18	
4.55	16.08	6.82	233.37
		50.0	
	17.40	27.70	
	18.95	88.90	

Cont from page - 26

Sta	B.S	H	FS	Rod	Elev
2+54 [67]		246.15		8.31	237.84
				9.75	236.40
				10.66	235.49
2+84 [67]	Check		7.96		
2+24 [67]	10.06	247.98			237.92 = B.M
2+54 [67]		247.98	10.14 ←	9.77 Check →	238.21
2+84 [67]				9.79	238.19
			Correction	11.24	236.74
T.P				11.75	236.23
	4.70	242.89			238.19
				10.87	232.02
22°-30' = to Left				7.83	235.06
				9.72	233.17
45°-00'				5.68	237.41
				7.82	235.04
				9.40	233.49
67°-30'				7.55	235.34
				8.20	234.69
90°-00' = Sta 1+75 [67] m-Line				5.58	
				6.92	235.97
				7.90	234.99

Cut	Fill	Out	Grade
		6.48	233.52
4.32	16.16		
		50.00'	
	17.60		
		87.02 = T.S.	
	18.57		
4.52			
		4.90	
3.27	17.06	25.10	
		50.00	
	17.77		
	21.98	93.96 = T.S.	
	18.94	50.00	
	20.83	91.66 = T.S.	
3.74	16.59	5.61	
	18.96	50.00	
	20.51	91.02	
	18.66	50.00'	
	19.31	88.62	
3.24		5.61	
	18.03	50.00	
	19.01	88.02	

North side toe of inside slope
Dividing line & Toe of outside slope

Sta	B.S.	H.I.	F.S.	Rod on ℄-Line	Elev
T.P.		242.89	1.46 = sta 1+00		241.43
	8.95	250.38			2
0+00				0.25	250.13
				2.10	248.38
0+50				6.17	244.21
				5.60	244.78
				5.79	244.59
				6.15	244.23
1+00				8.95	241.43
				8.95	241.43
				9.26	241.12
				9.26	241.12
1+50				11.43	238.95
				11.80	238.58
				12.20	238.18
				12.50	237.88

Cut	Fill	Out
16.46		
	5.62	50.0'
		61.24 = T.S. Check?
10.54		
11.11	9.22	16.66
10	10.92	50.00
	9.87	69.54 = T.S.
7.76		
7.76	12.57	11.64
	12.88	50.0
	12.88	74.76 = T.S.
5.28		
4.91	15.12	7.36 ✓
	15.82	50.0
	16.12	82.24 = T.S.

2 4 4.00
2 3 7.88
1 4 12

8 2
2 5 4.00
2 3 7.88
1 4 12

2 4 4.00
2 4 1.12
1 2 8 8

4 9 1
2 4 1
7 3 2

5 2 8
4 9 1
1 4 1 2
9 7 2

Shoulder of East side of 20'-Road = 30' out from west Ring toe

Sta	B.S.	I	F.S.	Rod	Elev
	3.94	263.09			Polo #080 259.15
0+00				8.59	254.50
+30				8.54	254.55
+60				8.92	254.17
+90				8.94	254.15
1+20				9.06	254.03
1+42 33				9.21	253.88
1+64 67				9.35	253.74
1+94 67				9.69	253.40
2+24 67				9.74	253.35
2+54 67				9.60	253.49
2+84 65				9.56	253.53

= T.C. for shoulder

29

Cut	Fill	Cut	Grade
20.83		0.50	233.67
21.03		0.56	233.52
20.80		0.17	233.37
20.93		0.15	233.22
20.96		0.03	233.07
20.92	0.22		232.96
19.67	0.26		233.07
20.15	0.60		233.22
19.98	0.65		233.39
19.79	0.51		233.52
19.86	0.47		233.67

West Line Toe Elevs & Cuts.

Sta	B.S.	H.I.	F.S.	Rod	Elev.
	4.68	258.85			254.17
0+00					
0+30				8.35	250.50
+60				8.18	250.67
+90				8.03	250.82
1+20				8.60	250.25
1+42 33				8.83	250.02
1+64 47				8.72	250.13
1+94 47				8.85	250.00
2+24 47				9.50	249.35
2+54 47				9.52	249.33
2+84 47				8.74	250.11

Grade	Cut	Fill
233.52	16.98	
233.37	17.30	
233.22	17.60	
233.07	17.18	
232.96	17.06	
233.07	17.06	
233.22	16.78	
233.37	16.98	
233.52	15.81	
233.67	16.44	

Whiles

25 June - 1942

Sta	B S	H.I.	F. S	Rod	Elev
B.M	4.11	~~263.26~~			259.15
				2.67	260.59
BM	11.31	261.48			250.17
B.M				4.70	256.78
T.P.	4.84	258.67	7.65		253.83
0+00				4.67	254.0
0+99.88				4.67	254.0
1+89.80				4.67	254.0
2+84.67				4.67	254.0

= 8.0 offset from inside face of Wall

Below = Record of Elevs & Cuts & north & south

	1.43	258.21		256.78
	1.31	246.79	12.73	245.48
0+00			0.09	246.70
+60			5.86	240.93
1+42.03			9.25	237.54
2+24.66			9.34	237.45
2+84.67			8.79	238.00

In Pot 1080. See p 3 on C

Nail at Varona p 3
On Flange between Valve & Water Meter

261.48
2.67
7.48

= Valve flange as above

Cut	Grade
13.03	233.67
7.56	233.37
4.74	233.07
4.08	233.37
4.33	233.67



Stakes set on line of Toe slope

East line Elevs & Cuts set for Contractor

Sta	B.S.	H.I.	F.S.	Rod	Elev
	8.53	246.07			237.54
0+00				7.22	238.85
0+60				5.91	240.16
1+42 33				9.34	236.73
2+24 66				10.03	236.04
2+84 67	Was	taken	out.		

South side Toe line from west to East

		246.07			
0+00				4.84	241.23
0+27 83				1.83	244.24

West line Toe line south to north

		246.07			
0+60				5.47	240.60
1+42 33				6.93	239.14
2+24 66				7.13	238.94
0+60	3.52	243.68			240.16 BM
Check to	4.83	243.68			238.85 BM
	6.94				
2+84 67	West line	Toe cut		4.29	239.39
	6.40	243.13			236.73
	2.98	243.14			240.16
				0.05	

June 25-1942 - Whiles

32

Grade Sta-142 33	Cut	Dist-out	cut for slope
	℄ of Res - north & South		
		7.77	
233.47	5.18		
233.37	6.79	10.18	
233.07	3.66	5.49	
233.37	2.67	4.00	
233.67	7.56	11.34	
" "	10.57	15.85	
233.37	7.27	10.91	
233.07	6.07	9.11	
233.37	5.57	8.35	
= Sta 8 on East line June 26 - 1942			
233.67	5.72	8.58	
note at this point had to be cut to the slope		8.58	3.69 = to slope

Note - Stakes were set to Grade on slope in places where Ground was to hard Cut to slope. Was given Whiles

North Line

tp		243.14		7.35	235.79
				2.24	
				5.91	237.23
				3.57	239.57

Below = 1 to 1½ Shoulder

from S.W. Cor using West Toe slope

sta	B.S.	A	FS	Rod	254
	6.62				254.00
0+00				2.11	253.51
				2.46	253.16
				5.93	254.69
clear				5.16	255.46
				5.57	255.05
				5.84	254.78
				6.75	253.87
				8.59	252.05

Grade	cut	Fill	out	cut to slope
	2.12		3.16	
	3.56		5.34	
	5.90		5.34	2.34

as Sta - 0+00

252.00		0.49		
		0.84		
	0.69			
	1.46			
	1.05			
	0.78			
		0.13		
		1.95		

June 30 - 1942

Sta	BS	H.I.	F.S.	Rod	Elev
BM	10.90	261.07			250.17
BM				4.32	256.75
	4.33	261.11			256.78
			12.12		248.99
	4.67	253.66			
			12.68		240.98
	0.59	241.57			
				4.35	237.22
				5.56	236.01
				7.92	
				8.08	
	10.40	246.41			236.01
			0.01		246.40
	11.88				258.28
			1.50		256.78
					~~256.78~~
	2.25	238.26			236.01

Spike at Corner on Flange to Meter } See p 31

Use at 256.78

B.M. on flange of Meter

Top of 16" Pipe NE Cor Res Inlet Pipe

← Check

10.96
256.78
43.2
214.6

R. 6.63
5.90
6.73
4.75
5.48

6.65
5.92
6.73

23.400
.33 Sub Grade
233.67

℄ - 233.28
— .33 Sub
232.95 = Grade

232.73 ℄ both ways

3' offset Line E side from N to So.

Sta	B.S.	H.I.	F.S.	Rod	Elv.
0	2.02	258.80			256.78
33'				4.80	
30'				4.80	
60'				4.80	
E & W ℄				4.80	
33'				4.80	
30'				4.80	
60'				4.80	

Grade = 2.54%

BM on Meter Flange Ft. Loma Res

3 July 1944



Wilcox
McComb
Banks
Johnson

36

1946.00
86.92
280.92
19.08
30.00
330.00

87.02 + 2°41
.10
86.92
87.07
.00 11
8702
87 02
.0075722

℄ = 1+03

142.33
30
172.33
167.83
63
230.83

142.33
72.62
214.95

℄ = 1+03
2 3083
2.3383

3 July

Levels on Drainage Line E of Reservoir

1+00 = Elbow out from Valve Chamber

Sta	B.S	H.I	F.S	Rod	Elev
B.M	2.69	259.47			256.78
TP	0.98	248.83	11.62		247.85
T.P	1.80	237.88 ✓	12.25		236.58
1+00 ⓣ				4.90	232.98
℄				4.35	
1+63 ⓣ				5.10	232.78
℄				4.31	
1+12 ⓣ				4.93	232.95
℄				4.09	
1+50 ⓣ				5.07	232.81
℄				4.02	
2+00 ⓣ				5.60	232.28
℄				4.23	
2+50 ⓣ				6.06	231.82
℄				5.63	
3+00 ⓣ				6.13	231.75
℄				4.71	
3+35 ⓣ				6.34	231.54
℄				7.77	
3+50 ⓣ				6.45	231.43
℄				6.67	

256.78
4.97
261.75
23.57
237.88

Grade	Cut	
		on Valve deep 34
227.45	5.53	
227.44	5.34	
227.00	5.95	
226.83	5.98	
226.61	5.67	
226.38	5.44	
226.16	5.59	
		on Rear Fill
226.00	5.54	
		on Cut
225.66	5.77	

Sta	BS	HI	FS	Rod	Elev
		237.88			
4+00 ℄				7.54	230.34
℄				7.53	
4+50 ℄				12.34	225.54
℄				11.73	
BM				7.06	230.82
T.P	3.40	228.95	12.33		225.55
5+0 ℄				7.61	221.34
℄				6.89	
5+50 ℄				9.29	219.66
℄				8.40	
BM	6.62	263.40			256.78
Hub				9.40	254.00
	6.22	263.00			256.78
			8.99		254.01
	5.12	259.13			
				5.13	
				5.13	
				5.13	

Grade	Cut
224.50	5.84
221.13	4.41
217.75	3.59
214.38	5.28

Stake

= Old Blue Top

B.M. on Meter Flange

3' offset on Inside of Rear So End.
3' do on ℄ N&S.
3' do on SW Cor on Tool Line

16" Pipe Line
Pt. Loma Res.

Keeler
39
July 9-42



16" Pipe Line
Pt. Loma Res.

July 10-42



Levels on Drainage Line Pt. Loma Res — July 10-42 — Keeler

Sta	B.S.	H.I.	F.S.	Rod	Elv.
	4.25	254.42	12.84		250.17
	1.08	242.66	12.85		241.58
	1.07	230.88	10.26		229.81
	0.82	220.44			219.62'
5+50 ℄				0.82	219.62
7'				0.72	219.72
6+00 ℄				6.56	213.88
7'				6.35	214.09
6+50 ℄				12.44	208.00
7'				12.09	208.35
T.P. 7'	0.35	208.70	12.09		208.35
7+00 ℄				5.41	203.29
7'				5.58	203.12
7+50 ℄				10.26	197.44
7'				10.30	198.40
T.P. 7'	1.04	199.44	10.30		198.40
8+00 ℄				6.88	192.56
7'				7.05	192.39
8+50 ℄				11.60	187.84
7'				11.79	187.65
T.P. 7'	0.59	188.24	11.79		187.65
9+00 ℄				7.13	181.11
7'				7.46	180.78
9+25 ℄				11.33	176.91
7'				11.78	176.46



Sta	BS	HI	FS	Rod	Elv
		188.24			
9+25 T.P 7'	0.80	177.26	11.78		176.46
9+50 ℄				6.69	170.57
7'				6.92	170.34
9+75 ℄				11.16	166.10
7'				11.31	165.95
9+85 ℄				12.83	164.43
7'				13.00	164.26
T.P. 7'			12.99	12.99	164.27
	0.49	164.76			
10+00 ℄				2.97	161.79
7'				2.47	161.29
10+40 ℄				7.65	157.11
7'				7.29	157.47
10+50 ℄				7.52	157.24
7'				7.15	157.61
T.P. nail on 7' Appox 10+80	1.63	158.92	7.47		157.29
11+40 ℄				8.79	150.13
7'				8.69	150.23
	12.01	169.14	1.79		157.13
	12.61	181.48	0.27		168.87
	11.96	193.07	0.37		181.11
	12.29	204.84	0.52		192.55
	12.92	217.46	0.30		204.54
	12.72	230.07	0.11		217.35



Sta	B.S.	H I	F S	Rod	Elv
		230.07			
	12.92	241.30	1.69		228.38
	12.87	253.80	0.37		240.93
			3.65		250.15

B.M. S.W. Cor Catalina & Verona Elv 250.17 = Error 0.02

Pt Lomo
Pipe Line Unit #6

Keeler
July 14-42

44



Levels on Pipe Line Pt Loma Res Unit #6

Sta	B.S.	HI	F.S.	Rod	Elv.
	3.88	254.05	9.17		250.17
	1.68	246.56			244.88
0+00 ℄				2.31	244.25
6'				2.24	244.32
+50 ℄				4.60	241.96
6'				3.81	242.75
+75 ℄				4.75	241.81
6'				3.99	242.57
1+00 ℄				6.26	240.30
6'				4.61	241.95
T.P.	1.37	235.14	12.79		233.77
1+50 ℄				5.87	229.27
6'				5.12	230.02
1+57 ℄				6.54	228.60
6'				6.32	228.82
1+67 ℄				7.60	227.54
6'				7.45	227.69
1+75 ℄				8.15	226.99
6'				8.06	227.08
T.P.	1.38	223.89 ✓	12.63		222.51
2+00 ℄					~~225.59~~ 223.96
6'				1.23	222.66
2+25 ℄				2.79	221.10
6'				3.16	220.73
	8.31		34.59		

Keeler July 14-42

45

Grade	Cut
240.40	3.92
236.47	6.28 ✓
234.50	8.07 ✓
232.13	9.82 ✓
227.4	2.62 ✓
226.14	2.68 ✓
224.34	3.35 ✓
222.90	~~4.18~~ ~~5.18~~ ✓ ?
219.00	3.66 ✓
216.50	4.23 ✓

246.56
8.31
254.87
34.59
220.28

250.17
8.31
258.48
34.59
223.89

Hand Level shot 1.30' high

Sta	B.S.	H I	F S	Rod	Elv.
		223.89 ✓			
2+50 ℄				4.34	219.55
6'				4.62	219.27
3+00 ℄				8.15	215.74
6'				8.15	215.74
—	1.96	213.13	12.72		211.17 ✓
3+50 ℄				3.17	209.96
6'				3.55	209.58
4+00 ℄				7.93	205.20
6'				8.01	205.12
4+50 ℄				12.50	200.63
6'				12.53	200.60
T.P. 6'	1.22	201.82	12.53		200.60 ✓
5+00 ℄				5.83	195.99
6'				5.78	196.04
5+50 ℄				12.48	189.34
6'				12.82	189.00
	0.59	189.59 ✓	12.82	~~12.82~~	189.00 ✓
5+75 ℄				2.60	187.00
6'				2.70	186.89
6+00 ℄				4.00	185.59
6'				4.25	185.34
6+25 ℄				9.13	180.46
6'				10.24	179.35
	3.77		38.07		

Grade	Cut
	B.S.
214.67	4.60 ✓
211.00	4.74 ✓
206.37	3.71 ✓
201.25	3.87 ✓
196.38	4.22 ✓
191.50	4.54 ✓
185.50	4.50 ✓
183.50	3.39 ✓
180.60	4.74 ✓
176.20	3.15 ✓

223.89
3.77
227.66
38.07
189.59

Sta	BS.	H.I.	F.S.	Rod	Elv.
		189.59			
	0.88	177.96	12.51	~~12.51~~	177.08 ✓
6+50 ℄				2.79	175.17
6'				1.99	175.97
6+75 ℄				7.70	170.26
6'				6.72	171.24
	1.27	166.57	12.66		165.30 ✓
7+00 ℄				3.86	162.71
6'				3.23	163.34
7+20 ℄				7.90	158.67
6'				8.30	158.27
7+38 ℄				12.05	154.52
6'				12.30	154.27
				10.02	156.55

Grade	Cut.
171.00	4.97 ✓
158.50	4.84 ✓
155.00	3.27 ✓
152.50	4.05 ✓

BS	FS
2.15	35.19
3.77	38.07
8.31	34.59
14.73	107.85

BM 250.17
− 107.85
142.32
+ 14.23
✓ 156.55

Wilkes
Bench set by Staff
157.01 — Diff = 0.46'

Levels & Cuts Pipe Line Unit #6
Harbor Drv.

Keeler
July 18-42

Sta	BS	HI	FS	Rod	Elv.
	3.22	253.39 ✓	~~3.22~~		250.17
	1.34	242.47	12.26		241.13
1+50 ℄				12.77	
6'				12.50	229.97
	0.60	230.57	12.50		229.97
1+75 ℄				3.50	
6'				3.62	226.95
2+00 ℄				5.97	
6'				7.26	223.31
2+25 ℄				9.50	
6'				9.87	220.70
2+50 ℄				10.85	
6'				11.33	219.24
	1.03	219.17	12.43		218.14
3+00 ℄				3.78	
6'				3.68	215.49
3+50 ℄				9.32	
6'				9.46	209.71
	0.70	208.72 ✓	11.15		208.02
4+00 ℄				3.62	
6'				3.71	205.01
4+50 ℄				8.65	
6'				8.80	199.92
			10.28		198.44
	4.89		58.62		

227.40		2.57 ✓
222.90		4.05 ✓
219.00		4.31 ✓
216.50		4.26 ✓
214.67		4.57 ✓
211.00		4.49 ✓
206.37		3.34 ✓
201.25		3.76 ✓
196.38		3.54 ✓

Sta	B.S.	H I	F S	Rod	Elv
	0.60	199.04			198.44
5+00 ℄				3.90	
6'				3.62	195.42
5+50 ℄				10.18	
6'				10.24	188.80
5+75 ℄				12.94	
6'				12.98	186.06
	0.01	186.07	12.98		186.06
6+00 ℄				3.25	
6'				3.46	182.61
6+25 ℄				6.65	
6'				6.71	180.36
6+50 ℄				11.46	
6'				11.33	174.74
	0.13	174.87	11.33		174.74
7+00 ℄				10.40	164.47
6'				10.72	164.15
	1.22	165.52	10.57		164.30
7+20 ℄				4.62	
6'				4.93	160.59
7+38 ℄				7.30	
6'				7.48	158.04
			9.00	9.00	156.52
	1.76				
	~~8.85~~		43.88		

	BS 8.85	FS 102.50
		250.17
		− 102.50
		147.67
		+ 8.85
		156.52
191.50	3.92 ✓	
185.50	3.30 ✓	
183.50	2.56 ✓	
180.60	2.01 ✓	
176.70	4.16 ✓	
171.00	3.74 ✓	
158.50	5.60 ✓	
155.00	5.59 ✓	
152.50	5.54 ✓	

Lorrel & Rosecrans St Ties



82/407 (4
32 8

35
14.72
20

10437.45
10314.47
22

104+37.45
103 30 32
10 7. 13

50 x 814 . 4070
820 820

30.32
1968 - 1.294025
9996810
1.290835.
19.54

50 1698970
9996810
1.695780 -
49.63 = 50-L

13.95 - 1.144574
9996810
1385 - 1.141387

R 814, ∂R 1628 - 3.211654
6 784346 -
4. 685575
- 1.473921 29.78
1290835
2.764756 - 582"

814 2.910624
2 913814
9.996810



Profile Levels on Lowell East to Harbor Drv. from Rosecrans

Sta	B.S.	H.I.	F.S.	
Offset Rod = 814				
	TR	1628		
			3.211654	
			6.788346	
			4.685575	
			2.102771	126.7
			2.263944	
			4.366715	
			3.556303	
			0.810412	6.462
				27.72

183.63
.23270"
36
3600

7-29-1942

Whiles

53



7-29-1942 - Whiles

Sta	B.S.	I	F.S.	Red	Elev
	5.71	6.45			B.M. 0.74
south #1			5.32	-	1.13 =
" #2		on Crnd of curb	4.07		2.38
" #3					
		Top of Temp pier	1.51		4.94
North side #1			1.72		4.73
" #2			1.80		4.65
" #3			2.33		4.12
			7.86		- 1.41 BM



7-30-1942 — Whites

Angle	Value	Line	Length	Bearing
P.I.	from B.S. on ℄ of Highway to sta. B.			
	Ref = 14°-07'-45" / 467°-56'	B-PI	202.94	
B-PI-A	116°-59'-00"	B.A.	369.21	



7-30-1942 Whites

Angle	Value	Line	Length	Bearing
		E.C.	97.05'	
	445°-11'			
C.E.D	111°-17'-45"	C.D.	235.15'	
	254°-47'			
C.D.B.	63°-41'-45"			
	154°-37'			
C.B.A.	38°-39'-15"	B.A.	369.21'	
	367°-05'			
D.B.C.	91°-45'-00"			
	140°-21'			
D.B.A.	35°-05'-15"			
	370°-54'			
B.A.D.	92°-43'-30"			
	118°-12'-00"			
B.C.D	24°-33'-00"			
	272°-40'			
B.A.C.	68°-10'-00"			
	292°-40'			
A.C.B.	73°-10'			
	208°-43'			
A.D.B	52°-10'-45"			
	83°-56'			
A.C.D.	20°-59'-00"			
	125°-53'			
11-11-11	20°-58'-50"			



Aug-5-1942

Elevs Grades on Unit #6 from from FWA # 179

Sta	B.S.	I	F.S.	Rod	Elev
		6.80			
149+00 ℄				4.47	2.33
⑥				4.35	2.45
149+50 ℄				4.73	2.07
⑥				4.90	1.90
150+00 ℄				4.88	1.92
⑥				4.95	1.85
150+50 ℄				4.67	2.13
⑥				4.67	2.13
151+00 ℄				4.97	1.82
⑥				4.97	1.83
151+50 ℄				4.45	2.35
⑥				4.58	2.22
151+96.23 ℄				4.47	2.33
152+00. ⑥				4.57	2.23
T.P.	4.76	6.99	4.57		2.23
152+00 ℄				4.62	2.37
⑥				4.71	2.28
152+50 ℄				4.40	2.59
⑥				4.50	2.49
153+00 ℄				4.61	2.38
⑥				4.70	2.29
153+50 ℄				5.02	1.97
⑥				4.82	2.17
154+00 ℄				4.95	2.04
⑥				4.83	2.06

H.I. of 6.80 carried as from F.W.A Book Units 1 to 6 Page #79

Grade Cut



Sta	B.S.	I	F.S.	Rod	Elev
		6.99			
154+50 ℄				4.93	2.06
⑥				5.36	1.63
155+00 ℄				4.97	2.02
⑥				4.32	2.67
155+50 ℄				4.93	2.06
⑥				4.72	2.27
156+00 ℄				5.40	1.59
⑥				5.38	1.61
156+50 ℄				5.40	1.59
⑥				5.37	1.62
157+00 ℄				5.74	1.25
⑥				5.43	1.56
T.P.	6.94	8.50	5.43		1.56
157+50 ℄				7.12	1.38
⑥				6.94	1.56
158+00 ℄				7.05	1.45
⑥				6.85	1.65
				7.82	= B.M. 0.68
158+50 ℄				6.24	2.26
⑥				5.65	2.85
159+00 ℄				6.04	2.46
⑥				5.92	2.58
159+50 ℄				5.30	3.20
⑥				5.31	3.19

Grade Cut

		6.99
		5.43
		1.56
		6.94
		8.50
-2.72		
	4.35 <	
-2.66		
	5.33 <	
-2.61		
	4.88 <	
-2.55		
	4.16 <	
-2.50		
	4.12 <	
-3.00		
	4.56 <	
-3.50		
	5.06 <	Last station marked
-3.25		
	4.90 <	

Check on B.M. Should be 0.67

-3.00	
	5.95 <
-2.96	
	5.54 <
-2.92	
	6.11 <

Sta	B.S.	H.I. 850	F.S.	Rod	Elev
160+00 ℄				4.56	3.94
ⓛ				4.83	3.67
160+50 ℄				4.94	3.56
ⓛ				5.03	3.47
161+00 ℄				5.77	2.73
ⓛ				5.14	3.36
161+50 ℄				5.81	2.69
ⓛ				5.85	2.65
162+00 ℄				5.73	2.77
ⓛ				5.80	2.70
	4.82	7.52	5.80		2.70
162+50 ℄				4.85	2.67
ⓛ				5.03	2.49
163+00 ℄				4.95	2.77
ⓛ				4.90	2.62
163+50 ℄				5.52	2.00
ⓛ				5.37	2.15
164+00 ℄				5.34	2.18
ⓛ				5.38	2.14
164+50 ℄				5.43	2.09
ⓛ				5.42	2.10
165+00 ℄				5.59	1.93
ⓛ				5.54	1.98

Grade Cut

	8 5 0
	5 8 0
	2 7 0
+	9 8 2
	7 5 2

-2.88 6.55 <

-2.85 6.32 <

-2.81 6.27 < 6.17

-2.77 5.42 <

-2.73 5.43 <

-2.70 5.19 <

-2.66 5.28 <

-2.62 4.97 <

-2.58 4.72 <

-2.54 4.64 <

-2.50 4.48 <

Sta	B.S.	H	F.S.	Rod	Elev
		7.52			
165+50 ℄				5.75	1.77
ⓒ				5.45	2.07
166+00 ℄				5.95	1.57
ⓒ				5.60	1.92
166+50 ℄				5.79	1.73
ⓒ				5.34	2.18
167+00 ℄				5.45	2.07
ⓒ				4.69	2.83
T.P.	4.41	7.24	4.69		2.83
167+50 ℄				5.42	1.82
ⓒ				4.87	2.37
168+00 ℄				5.43	1.81
ⓒ				4.72	2.52
168+50 ℄				5.24	2.00
ⓒ				4.97	2.27
169+00 ℄				5.37	1.87
ⓒ				5.24	2.00
169+50 ℄				5.26	1.98
ⓒ				4.96	2.28
170+00 ℄				5.21	1.97
ⓒ				4.99	2.25
170+50 ℄				5.46	1.78
ⓒ				5.00	2.24

Grade cut

-3.67	5.74 ←
-4.84	6.76 ←
-6.00	8.18 ←
-5.00	7.83 ←
-4.00	6.37 ←
-3.00	5.52 ←
-2.93	5.20 ←
-2.86	4.86 ←
-2.79	5.07 ←
-2.71	4.96 ←
-2.64	4.88 ←

7.52
4.69
2.83
4.41
7.24

Sta	B.S.	I.A.	F.S.	Rod	Elev
171+00 ℄		7.24		4.58	2.66
ⓒ				4.44	2.80
171+50 ℄				4.55	2.69
ⓒ				3.83	3.41
172+00 ℄				4.47	2.77
ⓒ				3.99	3.25
T.P.	4.99	8.24	3.99		3.25
172+50 ℄				5.17	3.07
ⓒ				4.92	3.32
173+00 ℄				5.16	3.08
ⓒ				5.04	3.20
173+50 ℄				4.97	3.27
ⓒ				4.73	3.51
174+00 ℄				4.98	3.26
ⓒ				4.87	3.37
174+50 ℄				4.95	3.29
ⓒ				4.77	3.47
175+00 ℄				4.74	3.50
ⓒ				4.56	3.68
175+50 ℄				4.86	3.38
ⓒ				4.74	3.50
176+00 ℄				4.90	3.34
ⓒ				4.82	3.42
176+50 ℄				4.71	3.53
ⓒ				4.61	3.63
				6.11	2.13

Grade	Cut
-2.57	
	5.37
-2.50	
	5.91
-2.43	
	5.68
-2.36	
	5.68
-2.28	
	5.48
-2.21	
	5.72
-2.14	
	5.51
-2.07	
	5.54
-2.00	
	5.47
-2.50	
	5.87
-3.00	
	6.25
-2.50	
	6.13

7.24
3.99
3.25
4.99
8.24

Check-on B.M.

Sta	B.S.	H.I.	F.S.	Rod	Elev
		8.24			
177+00 ℄				4.74	3.50
⑥				4.64	3.60
T.P.	5.02	8.62	4.64		3.60
177+50 ℄				5.28	3.34
⑥				5.13	3.49
178+00 ℄				5.10	3.52
⑥				4.98	3.64
178+50 ℄				5.01	3.61
⑥				4.40	4.22
179+00 ℄				5.16	3.46
⑥				5.00	3.62
179+50 ℄				4.78	3.84
⑥				4.84	3.78
180+00 ℄				4.62	4.00
⑥				4.51	4.11
180+50 ℄				4.11	4.51
⑥				4.05	4.57
181+00 ℄				4.42	4.20
⑥				4.45	4.17
181+50 ℄				4.81	3.81
⑥				4.66	3.96
182+00 ℄				4.76	3.86
⑥				4.65	3.97
T.P.	4.71	8.68	4.65		3.97

Grade	Cut
-2.00	5.60
-1.50	4.99
-1.54	5.18
-1.58	5.80
-1.62	5.24
-1.66	5.44
-1.71	5.92
-1.75	6.32
-1.79	5.96
-1.84	5.80
-1.88	5.85



Sta	B.S.	H.I.	F.S.	Rod	Elev
		8.68		-	
182+50 ℄				3.97	4.71
ⓒ				3.91	4.77
183+00 ℄				3.83	4.85
ⓒ				3.68	4.82 ~~5.00~~
183+50 ℄				4.44	4.09
ⓒ				4.20	4.15 ~~4.18~~
184+00 ℄				4.18	4.50
ⓒ				3.58	4.78 ~~5.18~~
184+50 ℄				4.41	4.27
ⓒ				4.35	4.33 ~~1.26~~
184+88 ℄				4.86	= B.C. 3.83
ⓒ				4.78	3.90
185+00 ℄				4.86	3.82
ⓒ				4.64	4.04
185+50 ℄				5.02	3.66
ⓒ				5.07	3.61
	5.97	9.58	5.07		3.61
186+00 ℄				5.82	3.76
ⓒ				5.88	3.70
186+50 ℄				6.30	3.28
ⓒ				6.36	3.28
187+00 ℄				6.39	3.19
ⓒ				6.38	3.20
187+50 ℄				6.91	2.67
ⓒ				6.83	2.75

Grade	Cut
-1.92	6.69
-1.96	6.78
-2.00	6.86
-3.00	7.78
-4.00	8.26
-2.76	6.79
-1.50	5.14
-1.55	5.25
-1.61	4.89
-1.66	4.86
-1.72	4.47

8.54 - HI

8 6 8
5 0 7
3 6 1
- 9 7
2 6 4

3.72 = .82

4.39 - 4.15

3.76 - 4.78

4.28 - 4.26

Sta	B.S.	I	F.S.	Rod	
		9.58			
188+00 ℄				6.76	2.82
(L)				6.73	2.85
188+09.06 ℄				6.97	2.61
(L)				7.05	2.53
			7.25		2.33
	7.25	9.28			2.03 BM
185+50	5.75	9.08	5.95		3.33
182+00	4.70	8.39	5.39		3.69
177+00	4.62	7.95	5.06		3.33
				6.18	1.77
172+00			5.10		2.85

August 6th - 1942

Sta	B.S.	I	F.S.	Rod	Fler
	6.06	8.09	~~4.75~~		2.03 B.M.
185+56	5.75	9.09	4.75		3.34
182+06	4.69	8.39	5.39		3.70
177+00	4.53	7.89	5.03		3.36
		7.89	6.00		1.89
172+00	4.02	7.04	4.87		3.02
167+00	4.31	6.91	4.44		2.60
162+00	5.50	7.96	4.45		2.46
158.0021		7.96	7.51		0.45
157+00	5.42	6.77	6.61		1.35
~~157+46.00~~ ~~152+00~~			5.45		1.32

Grade Cut

2.19
6.35
8.54
4.95
1.59

9.58
7.25
2.33

1.77

4.62

1.83

Should be 2.03 deducting to first circuit

note if B.M. taken as 2.19 this checks on closure

4.75	2.19
5.39	6.06
5.03	5.75
4.87	4.69
4.44	4.53
4.45	4.02
6.61	4.31
4.69	5.50
5.97	5.42
5.65	4.91
4.88	5.26
2.90	5.03
3.55	4.96
63.18	5.41
	68.04
	63.18
	4.86

Check on B.M. at Sta 172+50

B.M.

August 6 1942

Sta	B.S.	⊼	F.S.	Rod	Elev
~~152+00~~		6.77			
152+00	4.91	6.99	4.69		2,08
147+00	5.26	6.28	5.97		1,02
142+00	5.03	5.66	5.65		0,63
137+00	4.96	5.74	4.88		0,78
132+00	5.41	8.25	2.90		2,84
			3.55		4.70 BM
	3.54	8.40			4,86
132+00	3.41	6.41	5.40		3.00
137+00	5.31	6.26	5.46		0,95
142+00	5.62	6.41	5.47		0,79
147+00	5.88	7.07	5.22		1,19
152+00	4.70	6.96	4.81		2,26
151+96 03		6.96	5.46		1.50 BM
157+00					
156+00	6.79	8.31	5.44		1.52
158+00 21	6		7.70		0.61 BM
162+00	4.61	7.22	5.70		2.61
167+00	4.29	7.01	4.50		2.72
172+00	5.08	8.23	3.86		3.15
176+50			6.21		2.02 BM
177+00	5.02	8.52	4.73		3.50
182+00	5.61	9.46	4.67		3.85
185+50	4.87	8.36	5.97		3.49
			6.17		2.19

Note this circuit

2.19

should be 4.86 the starting point
should have been 2.19

5.40	
5.46	
5.47	
5.22	
4.81	
5.44	
5.70	
4.50	
3.86	
4.73	
4.67	
5.97	
6.17	
-67.40	

B.M.	4.86
	3.54
	3.41
	5.31
	5.62
	5.88
	4.70
	6.79
	4.61
	4.29
	5.08
	5.02
	5.61
	4.87
+69.59	
67.40	
	2.19

100 off

2.03
4.15
8.18
6.04
2.14

Hwy

Sta	B.S.	I	F.S.	Rod	Elev
	6.31	7.89			1.58 1.53 B.M
			5.73		2.11 B.M
188+50 ℄				5.19	2.70
(II)				5.22	2.67
189+00 ℄				5.39	2.50
(II)				5.06	2.83
189+50 ℄				5.40	2.49
(II)				5.32	2.57
190+00 ℄				3.82	4.07
(II)				3.65	4.24
190+50 ℄				2.77	5.12
(II)				2.78	5.11
T P	4.37	9.48	2.78		5.11
191+00 ℄				5.40	4.08
(II)				5.13	4.35
191+50 ℄				5.53	3.95
(II)				5.21	4.27
192+00 ℄				5.52	3.96
(II)				4.68	4.80
192+50 ℄				4.80	4.18
(II)				4.75	4.73
193+00 ℄				4.73	4.75
(II)				4.72	4.76
193+50 ℄				4.69	4.79
(II)				4.71	4.77

Grad — Cut

Should Be Elev 1.58 ✓ Correct

Note this B.M. not correct

State at 100 offset southside = to our Sta 184+84.88

State ~~P.I.~~ ℄ Hwy Sta 389+40.40

Was taken as Elev 2.19

-1.83	4.50 ←	
-1.88	4.71 ←	
-1.94	4.51 ←	
-2.00	6.24 ←	
-2.75	7.86 ←	
-3.56	7.85 ←	
-2.50	6.77 ←	
-1.50	6.30 ←	
-1.52	6.25 ←	
-1.54	6.30 ←	
-1.56	6.33 ←	

1.53
6.31
4.37
+ 2.21
- 2.78
9.43
- 5.73

Sta	B.S.	I	F.S.	Rod	Elev
194+00 ℄		9.48		4.92	4.56
(11)				4.41	5.07
194+50 ℄				4.85	4.63
(11)				4.60	4.88
195+00 ℄				4.72	4.76
(11)				4.33	5.15
T.P.	3.48	8.63	4.33		5.15
195+50 ℄				3.36	5.27
(11)				3.15	5.48
196+00 ℄				2.98	5.65
(11)				2.71	5.92
196+50 ℄				3.80	4.83
(11)				3.67	4.96
197+00 ℄				4.61	4.02
(11)				4.56	4.07
197+50 ℄				4.92	3.71
(11)				4.83	3.80
198+00 ℄				4.79	3.84
(11)				4.84	3.79
198+50 ℄				4.78	3.85
(11)				4.80	3.83
199+00 ℄				4.41	4.22
(11)				4.47	4.16
199+50 ℄				4.16	4.47
				3.96	4.67



Sta	B.S.	I	F.S.	Rod	Elev
200+00 ℄		8.63		3.83	4.80
⑪				3.69	4.94
T.P.	3.77	8.71	3.69		4.94
200+50 ℄				4.67	4.04
⑥				4.67	4.04
201+00 ℄				5.44	3.27
⑥				5.42	3.29
201+50 ℄				6.07	2.64
⑥				6.14	2.57
202+00 ℄				5.17	3.54
⑥				5.50	3.21
202+50 ℄				5.18	3.53
⑥				5.26	3.45
203+00 ℄				5.36	3.35
⑥				5.30	3.41
203+50 ℄				5.22	3.49
⑥				5.32	3.39
204+00 ℄				5.02	3.69
6				4.82	4.89 3.89
				7.12	1.59
204+50 ℄				5.13	3.58
⑥				4.95	3.76
	4.38	8.14	4.95		3.76
205+00				5.12	3.02
⑥				4.98	3.16

Grade Cut

-1.82 — 6.76

-1.84 — 5.88

-1.86 — 5.15

-1.88 — 4.45

-1.90 — 5.11

-1.92 — 5.37

-1.94 — 5.56

-1.96 — 5.35

-1.98 — 6.87 — X 3.87

-2.00 — 5.76

-2.25 — 5.41

1 2.21
3.48
3.77
4.38
4.67
+28.51
21.34
7.17
225

-2.78
4.33
3.69
4.95
5.59
21.34

28.56
21.34
7.22

Sta	B.S.	H.I.	F.S.	Rod	Elev.
205+50 ℄		8.14		4.94	3.20
ⓛ				5.12	3.02
206+00 ℄				4.63	3.51
ⓛ				4.51	3.63
206+50 ℄				5.23	2.91
ⓛ				5.08	3.06
207+00 ℄				4.91	3.23
ⓛ				4.79	3.35
207+50 ℄				5.22	2.92
ⓛ				5.07	3.07
208+00 ℄				5.38	2.76
ⓛ				5.03	3.11
208+50 ℄				5.14	3.00
ⓛ				5.17	2.97
209+00 ℄				5.69	2.45
ⓛ				5.33	2.81
209+50 ℄				5.78	2.36
ⓛ				5.59	2.55
	4.67	7.22	5.59		2.55
				5.63	1.595 B.M. 1.59
210+00 ℄				5.02	2.20
ⓛ				4.59	2.63
210+50 ℄				4.78	2.44
ⓛ				4.35	2.87

Grade cut

-2.50	
	5.52 ←
-2.43	
	6.06 ←
-2.36	
	5.42 ←
-2.29	
	5.64 ←
-2.22	
	5.29 ←
-2.14	
	5.25 ←
-2.07	
	5.04 ←
-2.00	
	4.81 ←
-1.93	
	5.05 ←

= 2.44 B.M. as there are 2 B.M. of same Elev

-3.00	
	5.63 ←
-2.94	
	5.81 ←

7.17
5.63
1.54

7.117
1.59
5.58

7.22
5.63
1.59

Sta	B.S.	I	F.S.	Rod	Elev
211+00 ℄		7.22		4.81	2.41
⑥				4.72	2.50
211+50 ℄				5.83	1.39
⑥				5.83	1.39
212+00 ℄				4.71	2.51
⑥				5.11	2.11
212+50 ℄				4.41	2.81
⑥				4.32	2.90
213+00 ℄				4.98	2.24
⑥				4.66	2.56
213+50 ℄				4.95	2.27
⑥				4.81	2.41
213+95 ℄				4.86	2.36
⑥				4.82	2.40
214+42 ℄				4.66	2.56
(7.09)				4.44	2.78
214+89 ℄				5.05	2.17
(8.18)				4.69	2.53
209+74				7.02	+0.20

Grade	cut
2.87	5.37
2.80	4.19 = 4.19
2.73	4.84
2.66	5.56
2.58	5.14
2.51	4.92
2.42	4.82
2.37	5.15
2.30	4.83

2.90

7.25
5.63
1.62

Note ground level here is at edge of telephone ditch
16" pipe which we tie to is open

= Elev of a 12" water line pipe is cast iron

8-22-1942 Whiles & Banks

These Elevs are City Datum

Sta	B.S.	H.I.	F.S.	Rod	Elev
	7.70	6.29			-1.41 B.M.
				6.29	0.00
				2.48	3.81

See Page 54-

40D Nail Drove into piling S.E. Cor of pier

top of 3/4" Bolt on S.E. Cor of pier this Bolt is on top of the Board Around top of pier 162.0' to pier 3rd Bent out from shore line

Note in addition to above Work placed Alignement flags for Dredge on ℄ of pipe

1+57 Cent of Outlet T 226.14'
1+67 do Inlet T 224.34

E to W Grade ℄ Res. 233.29 - 0.33

224.34
1+67 = ~~224.34~~ ~~226.14~~

1+57 = ~~224.34~~ 226.14
4.80

228.38
226.14
2.24

IMPROVED TABLES
AND
INFORMATION

B.M. 250.17
11.18
241.05
12.74
248.61
4.16
252.77

248.67
142.33

248.61
+ 2.46
251.07
- 9.50
241.57 = B.M. S.E. Cor of toe.

3 80
233 - 22
58. 20. 32
31 39 32
37 01 -

248.61
1.60
255.21

End of Work = Hwy Sta 211+65.39

We are now at 384+62.09
211+65.39
17296.70

214+89.5
213+95.6
83.9

DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

Roadway 16 feet wide. Side Slopes 1 on 1½

For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.2	8.3	8.5	8.6	8.8	8.9	9.1	9.2	9.4	0
1	9.5	9.7	9.8	10.0	10.1	10.3	10.4	10.6	10.7	10.9	1
2	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.1	12.2	12.4	2
3	12.5	12.7	12.8	13.0	13.1	13.3	13.4	13.6	13.7	13.9	3
4	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	4
5	15.5	15.7	15.8	16.0	16.1	16.3	16.4	16.6	16.7	16.9	5
6	17.0	17.2	17.3	17.5	17.6	17.8	17.9	18.1	18.2	18.4	6
7	18.5	18.7	18.8	19.0	19.1	19.3	19.4	19.6	19.7	19.9	7
8	20.0	20.2	20.3	20.5	20.6	20.8	20.9	21.1	21.2	21.4	8
9	21.5	21.7	21.8	22.0	22.1	22.3	22.4	22.6	22.7	22.9	9
10	23.0	23.2	23.3	23.5	23.6	23.8	23.9	24.1	24.2	24.4	10
11	24.5	24.7	24.8	25.0	25.1	25.3	25.4	25.6	25.7	25.9	11
12	26.0	25.2	26.3	26.5	26.6	26.8	26.9	27.1	27.2	27.4	12
13	27.5	27.7	27.8	28.0	28.1	28.3	28.4	28.6	28.7	28.9	13
14	29.0	29.2	29.3	29.5	29.6	29.8	29.9	30.1	30.2	30.4	14
15	30.5	30.7	30.8	31.0	31.1	31.3	31.4	31.6	31.7	31.9	15
16	32.0	32.2	32.3	32.5	32.6	32.8	32.9	33.1	33.2	33.4	16
17	33.5	33.7	33.8	34.0	34.1	34.3	34.4	34.6	34.7	34.9	17
18	35.0	35.2	35.3	35.5	35.6	35.8	35.9	36.1	36.2	36.4	18
19	36.5	36.7	36.8	37.0	37.1	37.3	37.4	37.6	37.7	37.9	19
20	38.0	38.2	38.3	38.5	38.6	38.8	38.9	39.1	39.2	39.4	20
21	39.5	39.7	39.8	40.0	40.1	40.3	40.4	40.6	40.7	40.9	21
22	41.0	41.2	41.3	41.5	41.6	41.8	41.9	42.1	42.2	42.4	22
23	42.5	42.7	42.8	43.0	43.1	43.3	43.4	43.6	43.7	43.9	23
24	44.0	44.2	44.3	44.5	44.6	44.8	44.9	45.1	45.2	45.4	24
25	45.5	45.7	45.8	46.0	46.1	46.3	46.4	46.6	46.7	46.9	25
26	47.0	47.2	47.3	47.5	47.6	47.8	47.9	48.1	48.2	48.4	26
27	48.5	48.7	48.8	49.0	49.1	49.3	49.4	49.6	49.7	49.9	27
28	50.0	50.2	50.3	50.5	50.6	50.8	50.9	51.1	51.2	51.4	28
29	51.5	51.7	51.8	52.0	52.1	52.3	52.4	52.6	52.7	52.9	29
30	53.0	53.2	53.3	53.5	53.6	53.8	53.9	54.1	54.2	54.4	30
31	54.5	54.7	54.8	55.0	55.1	55.3	55.4	55.6	55.7	55.9	31
32	56.0	56.2	56.3	56.5	56.6	56.8	56.9	57.1	57.2	57.4	32
33	57.5	57.7	57.8	58.0	58.1	58.3	58.4	58.6	58.7	58.9	33
34	59.0	59.2	59.3	59.5	59.6	59.8	59.9	60.1	60.2	60.4	34
35	60.5	60.7	60.8	61.0	61.1	61.3	61.4	61.6	61.7	61.9	35
36	62.0	62.2	62.3	62.5	62.6	62.8	62.9	63.1	63.2	63.4	36
37	63.5	63.7	63.8	64.0	64.1	64.3	64.4	64.6	64.7	64.9	37
38	65.0	65.2	65.3	65.5	65.6	65.8	65.9	66.1	66.2	66.4	38
39	66.5	66.7	66.8	67.0	67.1	67.3	67.4	67.6	67.7	67.9	39
40	68.0	68.2	68.3	68.5	68.6	68.8	68.9	69.1	69.2	69.4	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be 41.9+(20—16)÷2 or 2 ft. added to 41.9 =43.9. For slopes of 1 on 1 see inside of front cover.

Copyright, 1914, by Eugene Dietzgen Co.