

W458

FIELD BOOK

No. 385

8.35
6.25 6.5
5.75
14.60 12.2

~~MICROFILMED~~

~~DEC 10 1964~~

458

Our Leather Bound Engineers Note Books are carried in the following rulings:

- No. 380 LEVEL BOOK. Left and Right Hand Page the same as Left Hand Page of this Book.
- No. 382 FIELD BOOK. Left Hand Page as in this Book, Right Hand Page 4 x 4 to the inch, Center Line Red.
- No. 384 MINING TRANSIT BOOK. Left Hand Page as in this Book, Right Hand Page 8x8 to the inch, Center Line Red.
- No. 385 FIELD BOOK. Left Hand Page as in this Book, Right Hand Page 8 vertical and 4 horizontal lines to the inch, Center Line Red.

We also carry the Note Books listed above, bound in extra strong Fabri-Hide (otherwise the same quality of book), which can be furnished at a somewhat lower price.

In ordering Fabri-Hide covered books, add the letter "F" to catalog number.

THE FREDERICK POST CO.
ENGINEERING and DRAFTING SUPPLIES
IRVING PARK STATION
CHICAGO, ILL.

P. 36 indexed 10/1/46 mcd
 P 38 " 4/1/47 mcd
 P 48 " 12/8/47 mcd
 49 " 1/13/48 mcd

Warning
 There are two
 FB's numbered
458

SAN DIEGUITO DAM FINAL CROSS-SECTIONS
 UPSTREAM FACE AFTER BACKFILL
 Indexed 3/24/48

84-91

HODGES DAM April-1-1936

C.B. Hough

Ground elev's of diagonals - 1-18
 X-sec's for diagonal excav. - 19-24
 " April est. red. reinf. excav. - 25-28
 Elev's in vert. reinf. footings - 29-31
 Trench width - diagonal excav. 32
 City steel inventory 33
 Equip. inventory 34
 Transit points set on dam 35
 Level Notes Flaggin 395 + 375' Contour vicinity
 Lake Hodges Recreational Area 36 ✓
 Levels for Water Tank - to Contour 395 - Bernardo Bridge 38
 Profiles + alignment of ditch 43 ✓
 + Pipelines at Dieguito Reservoir
 X-section of upstream side of
 San Dieguito Reservoir (BEFORE EXC.) 46-49 ✓
 83
 DEFLECTION OF BASE LINE L & T'S - SAN DIEGUITO DAM - 43
 X-SECTIONS UPST. SIDE SAN DIEGUITO DAM (AFTER EXC.) - 50-54
 (12 1/2' stations)
 PROFILE OF TOP OF FOOTING (CUTOFF) SAN DIEGUITO DAM - 55-65
 X-SECTIONS UPST. SIDE SAN DIEGUITO DAM,
 AFTER EXC (6.25' STATIONS) 66 & 68 - 78 & 82
 ELEV OF BASE LINE L & T'S - SAN DIEGUITO DAM - 67, 92 & 93
 SAN DIEGUITO DAM SPILLWAY ELEV. 79
 SAN DIEGUITO DAM COUNTERFORTS - GROUND
 SURFACE & BOTTOM ELEVATIONS 80 & 81

#1	Diag. Ht. arch	Elev.	April-13-36	6'-6" Ht. angle to Arch
#9 W	247.0	233		
E	232.8	-		
#10 W	230.1	223		
E	222.5		219.93	
#11 W	217.9	215		
E	214.5		216.91	
#12 W	2121	212		
E	212.5			
#13 W	212.3	209	Marked 214.00 213.97	
E	208.8			
#14 W	208.8	207	212.09	
E	206.7			
#15 W	204.3	204	209.16	
E	201.6			
#16 W	203.1	208	Jack 207.00 207.13	
E	208.2			
#17 W	208.2	208	206.17	
E	202.2			
#18 W	200.9	204		
E	205.0			
#19 W	205.0	205	211.12	
E	209.4			
#20 W	209.4	209	Blk 220.00 221.15	
E	212.3		225.12	
#21 W	221.3	221		
E	232.7			

Elev. Measured Down from Walkway

#22 = 207
 #23 = 208
 #24 = 209
 #25 = 210
 #26 = 211
 #27 = 212
 #28 = 213
 #29 = 214
 #30 = 215

#2	Diag. Ht. arch	Elev.	April-14-1936
W #10	Elev. over Arch Walkway		238.00 - 1.78 236.22
E #10		5.29	230.93
E #11		5.31	230.91
W #13		5.25	230.97
W #14		5.13	231.09
W #15		5.06	231.16
W #16		5.09	231.13
W #17		5.05	231.17
W #18	Red-water	5.02	231.17
W #19		5.10	231.12
W #20		5.07	231.15
E #20		5.10	231.12
E #19	Red. T.P.	5.10	231.12
HI 208.68 - 6'6" Ranges 2.68 = 206.00 4.00 = 202.2 To Wall 5.4 #17 W = 208.0 ground = 202.2 To Wall 5.4 #16 E = 208.0 stairway = 202.2 To Wall 5.5 #16 W = 208.0 = 203.9 Water 204.3 #15 E = 204.0 = 203.8 loose Rock #15 W = 204.0 = 203.0 loose R. Water 205.5 #14 E = 207.0 = 206.5 loose Rock #17 E = 208.0 Water 202.45 #18 W (20 x 2) 202. #18 E = 204. 209.1 R. Rock 204.5 Water #19 W = 205. 209.5 R. Rock 204.5 Water			

#3

April - 14 - 36

Cont. from Page - 2 -

#19 E	205	210.0 LR	Water 209.1
#20 W	209	209.6 LR	209.08 W
#20 E	209	LR 210.0	Water 221.6
#21 W	221	LR 224.2	Water 221.6
#14 W	207	LR 203.0	✓ 208.9
#13 E	209	LR 208.2	✓ 208.9
#13 W	209	LR 211.8	
#12 E	212	LR 212.7	
#12 W	212	LR 213.1	Water 212.2
#11 E	215	LR 213.0	
#11 W	215		
#10 E	223		
#10 W	223		

#4

#5

#9 E

6'-6"

9.19

232

229


247

#9 W

232

229

#6



#7

#10 E

222.5

220.4

El. 220

217

230.1

#10 W

El. 220

217

#11 E

214.5

212.4

212

212


#11 W

217.9




217

El. 215




#8






#9




#11





#15



X. Sec. for Diagonal Exc. 4/25-36

9-E. El. 2320	232.0	232.0	232.2	235.0	235.5	235.5
Arch	00	15	4.0	4.0	6.0	8.0
see page 23 for 9W	232.8	232.9	232.9	233.8	234.9	234.7
Arch	00	20	3.0	4.0	4.0	8.0
10-W El. 220.0	222.1	222.0	225.6	225.5		
Arch	00	15	7.0	8.0		
water 224.3	222.8	223.0	223.8	225.9	229.0	
Arch	00	15	2.0	5.0	8.0	
C-1.0	220.4	221.0	221.8	222.8	223.2	
Arch	00	1.5	2.0	4.5	6.0	
10-E. El. 220	222.5	222.4	222.5	223.2	223.5	
Arch	00	1.5	3.0	6.0	8.0	
C-3.0	217.0	217.2	218.6	219.4	220.4	
Arch	00	1.5	2.6	4.0	6.0	
+5.5 Break	218.1	218.0	219.0	219.4	221.0	
Arch	00	1.5	3.0	4.0	6.0	
Arch	217.9	218.6	218.8	219.3	219.3	
	00	1.5	3.0	4.0	4.8	
	221.4	221.7	222.5			
	5.0	6	8			
11-E El. 215	212.4	212.4	215	214.7	215.5	215.5
Arch	00	1.0	1.5	4.0	6.0	6.0
5' Break	215.5	216.0	217.5	219.1		
Arch	00	1.5	3.0	6.0		
Arch	214.5	215.0	217.4	217.9		
	00	1.5	3.0	6.0		
12 W. El. 211.0	213.2	213.0	214.0	214.3	217.7	218.0
Arch	00	1.5	3	4.6	6.5	8.0
+8.0 Break	214.6	214.1	216.5	217.5		
Arch	00	1.5	6.5	8.0		
Arch	212.1	212.1	213.9	215.9	216.7	
	00	1.5	4.0	6	8.	

Hough Brickman X Sec. Diagonal Exc. 4/1-27-36

12 E. El. 211.0	212.7	213.8	215.4	216.2		
Arch	00	1.5	6.0	9.0		
+4.0 Break	214.1	214.3	214.3	216.1	216.7	
Arch	00	1.5	2.5	6.0	9.0	
Arch	212.5	212.5	213.3	215.3	216.3	216.5
	00	1.5	3.0	4.0	6.0	8.0
13 W El. 207.0	211.0	211.0	212.0	215.0	215.2	215.5
Arch	00	1.5	2.8	3.0	6	8
+6.5 Break	213.0	213.6	216.0			
Arch	00	1.5	8.0			
Arch	211.2	212.6	213.9			
	00	1.5	8.0			
13 E. El. 207.0	208.2	208.5	208.9	210.0	210.0	212.2
Arch	00	1.5	2.6	2.6	4.0	5.0
+8.0 Break	207.4	207.4	212.4	212.9		
Arch	00	2.0	3.0	8.0		
Arch	207.9	208.2	208.9	209.5	210.7	211.1
	00	1.5	2.0	2.0	4	8
14 W El. 208.0	208.4	208.4	208.9	211.1	211.9	213.4
Arch	00	1.5	3.0	2.6	5.0	8.0
Arch	208.4	208.9	210.9	211.7	212.2	211.9
	00	1.5	4	5	7	8
14 E. El. 208.0	206.7	208.0	208.0	209.6		
Arch	00	1.5	2.0	5		
Arch	206.2	206.7	208.3	210.5		
	00	1.5	4.0	7		
15 W El. 203.0	202.6	203.5	203.5	207.3	207.0	208.5
Arch	00	1.5	3.0	4.0	4.8	8
Arch	202.1	204.6	205.5	206.4	209.3	209.7
	00	1.5	3.0	3.0	6.6	8.5

15 E. Ele. 2030
 Arch

203.7	2038	2040	2088	2094
00	15	35	50	70
2019	2019	2008	2038	2041
0	15	20	26	60
				70

16 W. El. 203
 Arch

203.4	203.4	2038	2050	2060	2067
00	10	15	20	60	80
204.4	204.4	2059	2055	2057	
00	20	26	60	80	

16 E. 203.0

17 W 2030

17 E. 203.00

18 W 204.0
200.8

change.

18 E. 202.0
200.5

208.7	209.5	209.5	209.7	209.8	210.1
00	15	20	20	60	80

+5' Break


209.0	209.5	209.8	210.8	212.8
00	15	30	60	80

Arch
 IN
 Toe

203.7	203.9	204.2	204.6	209.4	209.3
00	15	20	40	40	80

19 W. Ele. 205.0
 +6' Break

2090	2088	2088	2090
00	15	20	80
2080	2080	212.7	212.7
0	60	46	50
			8



Arch

203.9	204.0	2037	2065	208.7	2090
0	15	20	60	65	80

19 E. Ele. 205.0
 +4' Break

211.3	211.5	211.8	211.7
0	40	60	80
211.2	211.5	212.0	212.5
0	20	40	60
			80

Arch.

208.1	208.3	208.7	209.8	212.3	212.7
00	20	30	40	60	80

20 W. Ele. 208.0

210.0	211.7	214.8
00	15	75

Arch

208.1	208.1	210.7	213.1
00	20	25	80

20 E. Ele. 208.0
 approx - 11' Water Ele. 221.6

210.0	210.0
00	60

Arch

212.3	212.5
00	7

21 W. Ele. 221.0

224.0	224.0	223.4	223.4
00	30	60	80

Arch.

221.1	221.6	222.0	222.1	221.8
00	20	40	50	70

21 E. Ele. 221.0 Water Ele. 240.75

239.2	240.0
00	6

Arch =

237.9	240.0
0	7

#23

22 W.	239.0	$\frac{236.8}{.00}$	$\frac{36.8}{1.5}$	$\frac{40.7}{1.5}$	$\frac{42.6}{3.0}$	$\frac{42.1}{5.0}$	$\frac{42.0}{6.0}$	$\frac{240.7}{9.0}$	Water.
-------	-------	---------------------	--------------------	--------------------	--------------------	--------------------	--------------------	---------------------	--------

Arch.		$\frac{236.0}{.00}$	$\frac{236.5}{1.5}$	$\frac{240.5}{6.0}$	$\frac{239.0}{8}$			
-------	--	---------------------	---------------------	---------------------	-------------------	--	--	--

22 E.	239.0		water 261.8	$\frac{258.0}{.00}$	$\frac{258.0}{5}$	$\frac{258.5}{8}$			Arch same
-------	-------	--	-------------	---------------------	-------------------	-------------------	--	--	-----------

23 W.	$\frac{272.0}{277.0}$	$\frac{270.5}{.00}$	$\frac{270.5}{1.2}$	$\frac{272.5}{1.5}$	$\frac{272.9}{3.0}$	$\frac{270.5}{5.0}$			
-------	-----------------------	---------------------	---------------------	---------------------	---------------------	---------------------	--	--	--

Arch		$\frac{268.5}{.00}$	$\frac{268.5}{1.2}$	$\frac{270.5}{1.5}$	$\frac{270.9}{3.0}$	$\frac{268.5}{5.0}$	cont Slope to E.C. 261.8		
------	--	---------------------	---------------------	---------------------	---------------------	---------------------	--------------------------	--	--

9 W.	232	$\frac{247.2}{.00}$	$\frac{247.4}{1.5}$	$\frac{248.0}{8.0}$				
------	-----	---------------------	---------------------	---------------------	--	--	--	--

+ 0.5 to Break same
Arch in a hole

23 E	272.0	$\frac{294.0}{0.0}$	$\frac{294.6}{5}$	$\frac{293.4}{5}$				
------	-------	---------------------	-------------------	-------------------	--	--	--	--

+ 3.5 top of slope
Arch + 6.4

Note: - all $\frac{1}{2}$ from Buttrass No. are Level Dist.

See page 32 for excav. widths.

Hough
Brackman

Set B

4/1-27-36

#24

Buttrasses # 5 to 6


Ele 264.00 + 36.8 = 300.7 = Top Walk

#5 East Ele 12.0

#6 W-17.0 = Ele. 283.7

0+00 = E-Face #5	Ele 287.2	285.5	$\frac{286.4}{2}$	287.0
+06	285.0	286.4	285.7	$\frac{284.1}{2}$
+13.4	281.3	284.9	283.1	280.5
+16.5	279.3	284.0	281.3	278.8
+22.4 W-Face #6	277.2	281.4	279.6	275.3

Looking across stream
upstream
Down stream
Stair steps



Xsec. Vert. re-int. footings
for April estimate

B.M. 0.00 219.00 219.00

Bot. 19-20

Set A

215.0
4.0
20

210.4
8.6
15

210.5
8.5
5

207.0
12.0
0

Set B

212.5
6.5
20

211.0
8.0
14

210.4
8.6
5

210.4
8.6
0

Set C 5 c. vds

Set D 0.0 219.00 219.00

Bot. 15-16

211.0
8.0
across

A 1.3 208.3 207.0

202.6
5.7
0

202.7
5.6
10

202.4
5.9
20

B 2.3 209.3 207.0

202.8
6.5
20

202.3
7.0
10

203.0
6.3
0

C 2 4

D 3 "

April estimate xsec's (cont.)

But. 13-14

Set A 4' x 1.3' x 20'

Set B 4' x 1' x 20'

" C 4' x 2.2' x 20'

" D 4' x 1.5' x 20'

Diag. W side of 14 - 1 c. yd.

But. 11-12

A 4' x 3' x 20'

B 4' x 3.5' x 20'

C 4' x 2.5' x 20'

D 3 c. yd.

Diag. E side " 11 1 c. yd.

" W " " 11 1 "

But. 9-10

A 4' x 3' x 20'

B 4' x 2' x 20'

C 4' x 2.5' x 20'

D 4' x 5' x 20'

Diag. 1 c. yd. E side " 9

#27

Elev for Rock May-7-1936 Hough
 Struts Taken with Handlevel.

Buttress

#20

#7.

← 23.5



Elev. 264.0

9 + 10	Set A	E. Face.	231. + 04	228. &	227. W.F	220.
	B		232.		229.	225
	C		230.		228.5	225
	D		233. + 03	230.	230.	227.5
11 + 12	A		209.		208.5	209.5
	B		211.		210.5	212.
	C		212		211	210.5
	D		210		209.	210.
13 + 14	A		206		204.5	205
	B		208.5		207.	207.5
	C		207.		208.	208.
	D		207.5		207	207.5
15 + 16	A		200.		201	200.
	B		200.5		200.5	201.
	C		202.		202.	202
	D		202.		200	202.
17 + 18	A		198.5 + 6 = 199.5		201. -	200
	B		198		199	199
	C		199		199.5	199.3
	D		original			
19 + 20	A		209.5		210	212.5
	B		209.5		209	214
	C		211.5		original ^{Rock}	213.0
	D		orig.		210.4	210.8



Buttress #8

Elev. 250.5

May-7-1936

#31

Final Cross Sections

Excavation Struts

Original Section's

FB
535

#32

Width of trench at diagonal Excav.

~~10/2/36~~
10/2/36
F.E.B.

width
Buttress W. side E. side


9	6.0	6.7	Allow 1' hor. under diagonal add. excav. on west
10	4.0	7.2	" 1' " " " " " " "
11	4.0	7.3	
12	4.0	7.5	
13	3.0	7.7	
14	4.0	7.7	
15	4.0	7.7	
16	4.0	-	
17	-	-	
18	-	2.5	
19	7.7	4.0	
20	6.0	4.0	
21	5.0	4.0	Allow 1' hor. under diagonal add. excav.
22	5.0	4.0	" 1' " " " " " "
23	-	4.0	" 1' " " " " " "

12-28-36.


Sutherland Steel left at Hodges Dam

1) Near Engineer's Office


13-1" □
 26-1" □
 36-1" □
 38-1" □
 45-1" □
 49-1" □
 207-1" □ 32'
 to 34'




5-1" □ 6'
 55-3/4 □ 31.4
 40-3/4 □ 31.4
 95




5-1" □ 6"
 2-1" □ 8'
 2-1/8 □ 40'
 7-1" □ 40'




48-3/4 □ 31.3
 35-3/4 □ 31.3
 83



163-1" □ 8'
 147-1" □ 8'
 310



271-5/8 □ 8'
 26
 297



2) Below the Dam

13-1" □ 8' ← 8' →

8-1" □ 8'
 2-1" □ 5'
 1-3/4 □ 4'
 1-3/4 □ 6.5'
 6-3/4 □ 2.5'
 1-1" □ 6' ← 6' →
 1-3/4 □ 18' + 18'
 1-1/8 □ 6'
 13-1/4 □ 4'
 1-1/8 □ 8'


30-1/4 □ 16' 1/2 1/2

3) 500 ft south of Spillway

26-1" □ 12.2' →

1-1" □ 22'
 3-3/4 □ 20'
 2-7/8 □ 20'
 2-3/4 □ 16'
 1-1" □ 8'
 1-1" □ 5'
 10 3/4 □ 8'
 4-5/8 □ 5'
 1-5/8 □ 18'
 5-1/8 □ 8'
 11-1/8 □ 20'


straight
Bar



66-3/4 □ 31'

This record is only approximately correct. See yellow sheets for weight records. B.

273-3/4 □ 8'
 1" □ 6'



12-29-36

34

Inventory Engineers Office Latta Hodges Dam

- | | |
|-------------------------------------|------------------------------------|
| Scale (box) 3 Weights | 1 Level A. Liety (10279) |
| Set of Sand-Screens (6) | 1 Transit A. Liety (10280) |
| Set of Rock Screens (10) | 3 Punched, crosslined yellow Pad |
| 8 pan with 5 screens | 3 Chain |
| 2 Pans for drying ^{slides} | 2 stools |
| Material | 2 drafting tables with horses |
| 1 Wood stake & 6 Section | 1 Remington Standard Typewriter |
| of stovepipe | 2 Level rods |
| Waterpails: 2 | 2 50 ft Cloth tapes |
| 1 Cylinder for stumpdest | 1 50 ft Steel tape |
| 15 yds 7 3/8" Detail Paper | 3 6 ft Rulers |
| 1 Flashlight | 2 new Plumb-Bob. |
| 12 1/2 yds Cross-Section Paper | 1 old Plumb-Bob. |
| 1 Coal oil stove | 3 new Pencils |
| 1 Hammer | 1 First-Aid Cabinet (11) |
| 1 Tube of paste | 5 new Field Books 537-538, 539 |
| 25 yds Plumb-Bob cord | Books 543, 544 |
| Carbon paper | 1 Marvel-Puncher |
| 1 Roll white Cloth | 1 (Bostich) Clipping Machine |
| 1 Roll red Cloth | 1 Canvas Boot-sock |
| 3 Columbia Files | 1 Stake-Bag |
| 1 Broom | 6 (No. 12) Lockarch Transfer Cases |
| 1 Wire-Letter-Basket | 1 Pencil sharpener |
| 1 Padlock & 2 Keys | 2 Sandpaper Pencil-sharpener |
| 2 Loose I. P. Leaf | 3 Precer blue & red Crayons |
| Ring-Binder | 3 " red |
| 1000+ Daily Report Forms | 5 Field (Inspectors Report) Books |
| 1 Straight-Edge | 458, 535 |
| 1 Table broom | 518, 519, 536 |
| 1 Kodak Triobad | 3 Diary-Books |
| 1 100 ft Steel Tape | 5-D, L-H Telephone Directory |
| | 1 Set of Hodges Dam Plans |
| | 1 200 ft Steel Tape |

Levels for the Flagging of the
395 + 375 Contours in the vicinity
of Bernardo Bridge Lake Hodges

B.M.	8.70	336.30		327.60	Brass
T.P.	14.02	350.05	0.27	336.03	
T.P.	13.94	363.29	0.68	349.35	
T.P.	13.20	375.86	6.63	362.66	
T.P.	12.88	388.73	0.01	375.85	
T.P.	13.56	401.24	1.05	387.68	
T.P.	12.08	409.88	3.44	397.80	
T.P.	1.55	403.63	7.80	402.08	
T.P.	4.27	398.82	9.08	394.55	
T.P.	10.15	402.42	6.55	392.27	
T.P.	7.50	400.49	2.43	392.99	
T.P.	0.94	389.08	12.35	388.14	
T.P.	2.55	381.05	10.58	378.50	
T.P.	6.03	379.36	7.72	373.33	
T.P.	2.38	383.95	4.79	374.57	
T.P.	6.66	385.32	5.29	378.66	
T.P.	13.00	385.52	12.80	372.52	
T.P.	3.77	383.17	6.12	379.40	
T.P.	9.54	387.38	5.33	377.84	
Set B.M.	7.74	383.30	11.82	375.56	✓
T.P.	2.14	382.22	3.22	380.08	
T.P.	7.80	383.69	6.33	375.89	
T.P.	5.23	382.62	6.30	377.39	
T.P.	2.35	379.42	12.55	370.07	✓
T.P.	10.86	385.31	4.97	374.45	

Bliss Notes # 36
Davis
Phillips Sept 23/46
cap. Set in South End of the Bernardo
Bridge U.S.G.S.

		T 38531			
TP	770	382.58	10.43	374.88	
T.p.	7.67	387.19	3.06	379.52	
TP	7.38	385.82	8.75	378.44	
TP	2.78	379.73	8.87	376.95	✓
TP	11.40	379.98	11.15	368.58	
TP ⁴	12.10	387.37	4.71	375.27	Top of Boulder Near End of line
TP	11.25	387.62	11.70	375.67	
TP	0.66	385.91	2.37	385.25	✓
TP	12.90	398.15	0.66	385.25	on Corrugated iron culvert on Daley Road. South of Lake Hodges. Recreation Area.
TP	11.37	409.40	0.12	398.03	
TP	5.20	414.18	0.92	408.98	
TP	1.76	403.64	12.30	401.88	
Check out			8.5	395.14	on 395 contour

3-31-47
King
Leonard
Nei Now

38

Levels to 395' Contour for Water Tank - Bernardo Store

6.61	339.21		327.60
12.46	345.06	1.41	332.60
12.60	357.28	370.38	344.68
12.81	369.99	0.10	357.18
12.24	381.81	0.42	369.57
11.64	392.86	0.59	381.22
9.19	400.03	2.02	390.84

Set - 395' Contour 5.03 395.00

0.21	389.75	10.49	389.54
0.11	376.84	13.02	376.73
0.61	365.52	11.93	364.91
0.06	352.67	12.91	352.61
0.50	340.37	12.80	339.27
2.39	333.04	9.72	330.65
		5.43	327.61

U.S. C & G.S. B.M. So. End Bernardo Bridge

San Diequito Ditch
Realignment + Referencing
Cont. from F.B. 561 P 28, 29, 30

10+25 16°53' Lt



5+10 12°22' Rt

0+10

Rainey Dec. 15, 1947
King
Niernow

39


Note: All points
Referenced 30° off
back tangent except
0+10



40

2nd to last
line pt. 30.80

line pt. 20.80



11.34

241.1

10.9

247.4

248.2

247.2

Dec. 22, 1947 Rainey
Niemon

253.44

11

S.W. Abut. Conc. Bridge 253.26

3.80 257.06

10.13 246.93


4.18 256.11

2.64 248.47

3.87 252.34

4.95 247.39

4.50 251.89



8' offset line to E. S.
for open Ditch

42

0+00 open Ditch on Bank of exist.
Ditch

5+53⁰⁰ Δ Pt 17°51' Rt. Ex = 40

6+97¹⁰ Δ Pt 6°00' Lt. No ex.

10+92¹⁰ Δ Pt 23°47' Lt. Ex = 6'

13+95⁰⁰ Δ Pt 92°32' Rt. Ex = 120

17+60⁰⁰ Δ Pt 04°11' Rt. No ex

19+41⁰⁰ Δ Pt. 04°37' Rt. No ex.

21+57⁰⁰ 08°04' Lt. No ex

23+27⁰⁰

Rainey
King
Nichols 12/17/47

Cuts
0+00

Profile for 30" line

0+00	at Dam 243.2				
0+32	2 Pt.	2.2	241.0	238.5	25
0+41		3.1	240.1	238.4	17
0+82		3.8	239.4	237.7	17
0+94		6.5	236.7	237.1	10.4
1+20		5.5	237.7	235.8	1.9
1+32		6.7	236.5	235.2	1.3
1+45	end	8.2	235.0	234.5	0.5



H.I.
243.2

Rt.

Sec. 0+32 $\frac{+17.7}{75'}$ $\frac{+12.7}{25'}$ $\frac{+8.8}{24'}$ $\frac{+7.8}{50'}$ $\frac{-2.2}{11'}$ $\frac{-4.5}{32'}$ $\frac{-5.9}{32'}$

Sec. 0+82 $\frac{+16.3}{75'}$ $\frac{+15}{46'}$ $\frac{+10}{43}$ $\frac{+11-17}{20' 13'}$ $\frac{-3.8}{2'}$ $\frac{-4.3}{2'}$ $\frac{-10.2}{17'}$

Sec. 1+45 $\frac{+135}{75'}$ $\frac{+50}{44'}$ $\frac{-09}{21}$ $\frac{-4.7}{9}$ $\frac{-6.9}{7}$ $\frac{-8.2}{17}$ $\frac{-14.1}{27}$ $\frac{13.3}{27}$



Profile on Guirass E
for Diequito Ditch

From Butt #12 el. 240
400' el. 241
Cont. 241

45

Cuts

BM. Butterass #13		250.00			
4.95	254.35				
0+00					
0+50	5.6	248.8	240.12	8.7	
1+00	6.2	248.2	240.3	7.9	
1+50	5.4	249.0	240.4	8.6	
2+00	4.5	249.9	240.5	9.4	
2+50	4.5	249.9	240.6	9.3	
3+00	5.0	249.4	240.8	8.6	
3+50	7.3	247.1	240.9	6.2	
4+00	7.1	247.3	241.0	6.3	
4+50	6.7	247.7	241.0	6.7	
5+00	7.9	246.5	241.0	5.5	

SAN DIEGUITO DAM

BM. L&T Arch # 6 250.26

1.27 252.73

0+00 L&T on Buttrass #1

0+25

0+50

0+75

1+00

1P#1

0.76 242.55

1+25

1+50

1+62.50

1+75

1P#2

0.38 228.75

12.94 233.79

12.18 228.37

Jan. 9, 1948 X-sections
CROSS-SECTIONS PRIOR
TO EXCAVATION
P. 46 - 49 incl.

also p. 83

535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Ramsey.
King
Nienow 46

252.7

249.6 250.2 50.2
3.1 2.5 2.5
28' 49'

46.9 47.5 48.2 47.9
5.3 5.2 4.5 4.8
24' 30' 35'

44.6 45.1 45.0
8.1 7.6 7.7
37 49'

42.2 42.7
10.5 10.0
35'

40.3 39.8 40.7 40.7 39.7 39.7
2.4 12.4 12.0 12.0 13.0 13.0
25' 32' 36 40 49

240.6

236.8 36.6
3.8 4.0
25'

32.4 32.8 33.7 33.5 34.4 34.0
8.2 7.8 6.9 7.1 6.2 6.6
28 37 37 36 30

30.3 30.9 29.8 29.7
10.3 9.7 10.8 10.9
26 30 36

28.2 27.6 29.0 27.9 27.8
12.4 13.0 11.6 12.7 12.8
17' 24 27 33

128.75

1787²

2+00

2+21

2+25

2+29

T.P.

0.21

219.23

9.73

219.02

2+32

Nature Set BM.

5.10

214.13

2+39

2+44

2+50

47

228.8

26.3 26.3 24.7 25.8 25.3 25.3

2.5 2.5 4.1 3.0 3.5 3.5
6. 15 24 29 35

23.5 22.3 23.6 22.8 25.8

5.3 4.5 5.2 6.0 3.0
19 27 37 47.5

220.8

19.4 17.5 18.8

8.0 9.4 11.3 10.0

14 22 27

20.0

18.4 16.5 17.8

8.8 10.4 12.3 11.0

14 22 26

18.8

17.2 14.3 16.7

10.0 11.6 14.5 12.1

14 21 26

219.7

15.5 16.1 12.9 11.3 16.7

3.7 3.1 6.3 2.9 2.5

8 17 18 27

S.A. Cox. Handwritten Note

14.8 12.9 11.5 11.5 13.7 12.4

4.4 6.3 7.7 7.7 5.5 4.4

15 17 20 23 25

16.4 14.2 11.2 11.2 13.0 19.2

2.8 5.0 5.0 3.0 6.2 0.0

14 16 19 22 35

12.7 12.9 11.0 11.0 11.9 22.2

4.5 6.3 8.2 8.2 7.3 13.0

14 16 19 21 47

San Diegoito
X sections cont.

2+64

48

B.M. L+T Butress #13		250.00
1.63	251.63	
T.P. #1	11.22	240.41
1.57	241.98	
T.P. #2	12.15	229.83
0.96	230.79	
	11.16	219.63
2.55	222.31	

Note! From 2+64 to 3+25 sections same as 3+25 except at Butress or arch where it is same as ground. distance out practically same as section 3+25 and other odd sections

3+25

222.3		
12.1	12.3	15.3
10.2	10.0	7.0
	16	25

3+37.5

13.4	15.5	16.7	16.7	18.3
8.9	4.8	5.6	5.6	7.0
	14	19	25	30

3+50

17.3	20.0	19.1	19.0	23.3
5.0	2.3	3.2	3.3	+1.0
	28	30	38	47

4 62.5

17.4	18.6	19.5	20.7
4.9	3.7	7.5	1.6
	17	24	35

4 75

19.4	23.3
2.9	+1.0
	30

T.P.

0.58 221.73

1037 232.70

+ 87.5

222.1

21.5	(22.8)	23.8	23.3	25.0
10.6	0.3	8.3	8.8	7.1
	16	21	28	34

232.10 ✓

4700

4712.5

4725

4750

4775

T.P.

5700

5712.5

5725

T.P.

5767

11.23 243.06 ✓

0.27 231.83 ✓

9.74 252.02 ✓

0.80 242.26 ✓

2.03 249.99 250 ✓

251.0

232.10

22.0 ✓	24.0 ✓	26.5 ✓	25.7 ✓	24.7 ✓	27.8 ✓
9.5	8.1	5.1	6.3	7.4	4.3
	17	25	28	42	49

23.4 ✓	24.8 ✓	26.1 ✓	25.8 ✓	24.9 ✓	26.9 ✓
8.5	2.3	6.0	6.3	5.2	5.2
	19	24	33	35	38

24.8 ✓	25.4 ✓	26.9 ✓	27.0 ✓	27.3 ✓
7.3	6.7	5.2	5.1	4.8
	17	22	31	37

27.3 ✓	27.5 ✓	29.6 ✓	28.3 ✓	28.4 ✓	232.1 ✓
4.8	4.6	2.5	3.8	3.7	0.0
	22	33	37	44	51

29.1 ✓	29.7 ✓	332.1 ✓	30.5 ✓	29.8 ✓
5.0	2.4	0.0	1.6	2.3
	15	25	30	34

243.1 ✓

31.5 ✓	33.5 ✓	34.8 ✓	32.9 ✓	33.0 ✓
11.6	9.6	8.3	10.2	10.1
	29	35	40	51

33.0 ✓	33.4 ✓	35.0 ✓	35.5 ✓
10.1	9.7	8.1	7.6
	8	18	39

34.4 ✓	35.6 ✓	35.8 ✓	37.0 ✓
8.7	7.5	7.3	6.1
	10	32	36

REDUCED
GRS 1/16/48

251.0	49.7	47.7	47.8
45.4	1.3	1.8	3.3
5.6	14	22	35
			40

CHECKED OK 3.22.48

*Sections of
San Diego to Reservoir
Prior to Converting
(AFTER EXC.) (12 1/2 stations) p.50 654 Lude

JAN 29, 1948

Randy
King
Newman

50

B.M. 147 Arch # 6 250.26

3.05 254.01

TP #1 11.36 242.65

4.62 247.27

0+37.5

0+50

0+62.5

0+75

0+87.5

TP #2

3.04 239.84

10.47 236.80

1+00

1+12.5

1+25

From 0+00 to 0+25 No excavation

247.3

45.7	46.0	44.7	44.1	44.1	44.5	44.7
1.6	1.8	2.6	3.2	3.2	3.8	2.6
	35	38	30.5	39.7	39.7	39.2

44.6	44.3	44.7	41.7
2.7	3.0	2.6	5.2
	20	36	40

43.9	43.6	41.3	39.8	40.0	39.6	39.6	40.3	40.4
3.9	3.7	6.0	7.5	7.3	7.7	7.2	7.0	6.2
	20	22	29	31.2	31.8	33.5	32.3	33.2

41.9	41.4	39.6	38.3	36.2	36.3	36.7	39.1	39.2
------	------	------	------	------	------	------	------	------

5.1	5.9	7.7	9.0	11.1	10.6	8.3	8.1
	20	22	26	28	35.8	32.3	31.7

41.7	39.6	37.5	37.7	37.3	37.3	38.1	38.1
------	------	------	------	------	------	------	------

1.6	2.7	3.3	3.6	4.0	4.0	4.2	4.2
	14	24	34.5	40	40.3	41	41.6

REDUCED 93.9. 1/27/48

239.8

39.2	37.8	37.1	36.0	38.3	35.5	35.5	36.5	36.5
40.6	2.0	2.7	3.8	1.5	4.2	4.8	3.3	3.3
	14	21	34	41	42	50	50	50

38.2	36.0	34.3	33.7	33.7	33.7	34.2
1.6	3.8	5.3	6.1	6.1	6.1	5.6
	31	36	38	38.2	39.2	39.2

35.2	34.7	33.1	33.1	33.3	33.4
1.6	5.1	6.7	6.7	6.5	6.8
	26	30	33.3	35.7	36.0

	+		
↓ 1+375		239.84	
1+50			
TP#3			10.88 228.96
↓ 1+675	2.78	231.74	
1+75			
1+875			
2+00			
TP#4			12.05 219.69
	3.62	223.31	
			9.15 214.16
	4.77	218.93	
√ 2+125			
2+25			

289.8									
32.8	32.7	31.6	31.0	31.5	31.0	30.6	30.6	30.3	31.0
70	71	8.2	8.5	8.3	8.8	9.2	9.2	8.8	8.8
	82	29	33	35	38	38	38	39	39
30.1	30.8	30.1	29.3	28.3	28.3	28.8	28.8	28.8	
9.7	9.0	9.7	10.0	11.5	11.5	11.0	11.0	11.0	
	30	40	45	46	47	47	47	49.5	

231.7							
27.7	28.7	28.3	26.2	26.2	26.8	26.8	
4.0	3.0	3.4	5.0	5.5	4.9	4.9	
	27	22	34	35	35	32.7	
24.4	23.5	25.0	25.0	24.1	24.7	24.7	
7.3	8.2	6.7	6.7	9.6	7.0	7.0	
	19	21	26	30	30	30.8	
22.3	21.5	22.4	23.1	23.1			
9.4	10.2	9.3	8.6	8.6			
	19	32	32	33.3			
19.5	22.1	22.3	20.8	20.9	21.4	21.4	
12.2	9.6	9.4	10.9	10.8	10.3	10.3	
	7	24	23	41	41	44	

218.9						
16.7	17.4	15.9	16.1	14.6	14.2	
2.2	1.5	3.0	2.8	4.3	4.7	No feeding
	12	17	21	25	25.8	
15.6	15.9	12.9	12.1	12.6	13.1	
3.3	3.0	6.0	6.8	6.3	5.8	
	7	16	22	22	22.3	

H.I.

218.93

2+375

2+50

2+625

2+75

2+875

3+00

3+125

3+25

3+375

3+50

3+50

218.9

14.8 14.6 9.4 8.8 9.3 9.6

4.1 4.3 9.5 10.1 9.6 7.3
10 17 23 23 24

14.2 14.5 10.1 6.2 6.1 6.8 6.8

4.7 4.4 9.2 12.7 12.8 12.1 12.1
5 18 20 32 32 35

12.4 7.8 5.5 5.2 5.5 5.9

6.5 11.1 13.4 13.7 13.4 13.0
11.5 13.5 20 20 20.7

10.4 5.3 4.9 5.6 5.8

8.0 13.6 11.0 14.8 15.1
11 16.5 16.5 17.3

9.5 6.0 7.5 5.5 5.5

9.4 12.9 14.4 13.4 13.4
8 19.5 19.5 20.2

7.3 7.0 5.1 4.9 6.2 6.3

11.2 11.8 13.8 14.0 12.7 12.6
9 11 32 32 32.8

8.8 8.7 10.0 10.0

10.1 10.2 8.9 8.9
23.5 23.5 25

11.9 12.8 11.1 10.9 12.0 12.1

7.0 6.1 2.8 8.0 6.9 6.8
11 15 22.5 20.5 22

13.3 14.2 15.0 15.1

5.6 4.7 3.9 3.8
27 27 28.5

5.2 5.9 5.9

13 17

223.6

15.1 15.0 16.0 18.1 16.6 17.1 17.1

8.5 8.6 7.6 5.5 7.0 6.5 6.5
? 20 36 39 39 43

2.15

223.58

221.43

223.5B

3+625

3+75

3+625

3+875

4+00

4+12.5

T.P.

1.64 221.94

9.36 231.30

4+25

4+375

4+50

4+62.5

223.6

16.2	16.1	18.1	17.7	18.3	18.5
24	7.5	5.5	5.9	5.3	5.1
	16	16	29	29	30.2

18.2	17.9	19.3	18.5	19.1	19.3
5.4	5.7	4.3	5.1	4.5	4.3
	15	16	26	26	27

19.6	20.9	20.0	20.4	20.5
4.0	2.7	3.6	3.2	3.1
	31	29.7	29.7	30.5

21.2	22.4	21.2	21.6	21.6
2.4	1.2	2.4	2.0	2.0
	18	41.5	41.5	42.5

22.4	23.5	21.6	22.1	22.2
1.2	0.1	2.0	1.5	1.4
	27	33.5	33.5	34.2

231.3

23.5	25.0	22.5	22.6	23.1	23.2
7.8	6.8	8.8	8.7	8.2	8.1
	21	25	28.5	28.5	29.3

25.2	25.6	23.7	23.5	23.9	24.0
6.1	5.7	7.6	7.8	7.4	7.3
	23	27	32	32	33.2

26.1	27.7	24.8	25.4	25.4
5.2	3.6	6.5	5.9	5.9
	24	44.5	44.5	47.5

27.2	27.5	29.6	26.4	25.8	26.4	26.5
4.1	3.8	1.7	4.9	5.5	4.9	4.8
	18	24	30	34.2	34.2	35.4

JAN. 26, 1948

Rainey
King
Nelson

54

231.30

4475

T.P.

11.05

230.36

1.39

229.31

44875

5400

54125

5425

54375

5450

T.P.

12.84

251.57

1.65

238.71

L+T But #13

1.57

250.00

231.3

28.3	28.8	30.5	27.5	26.7	25.2	26.2
3.0	2.5	0.8	3.2	4.6	4.1	4.1
	17	20	27	32.5	32.5	32.9

240.4

29.5	29.7	32.1	29.4	27.6	28.2	28.3
10.9	10.7	8.3	11.0	12.8	12.2	12.1
	14	19	24	37	37	37.5
31.0	31.8	34.3	30.8	28.8	28.6	29.1
2.7	3.0	6.1	2.6	11.6	11.8	11.3
	15	20	2.8	4.5	5.0	5.0
32.0	32.4	36.1	32.8	31.6	31.5	32.1
8.4	7.5	4.3	7.6	8.3	8.9	8.3
	15	25	30	38	39	39
33.4	34.1	36.5	33.9	33.9		
7.0	6.3	3.9	6.5	6.5		
	11	22	25	36.5		
35.6	37.2	35.1	35.3	36.0	36.0	
4.8	3.2	5.3	5.1	4.4	4.4	
	26	38	40	40	40.4	
37.5	43.6	36.2	36.7	37.3	37.3	
2.9	4.2	4.2	3.7	3.1	3.1	
	31	45	49	50	52	

Checked JK 3.18.48

Profile of Footings (CUTOFF)
 San Dieguito Reservoir
 Note: chained on curve

p. 55 to 65
 incl.

Jan 28, 1948

Rainey
 City
 Nierow

55

		250.96
2.18	253.14	
BM. Set Arch #1	2.18	251.02
	12.99	240.15
0.82	240.97	
	11.59	229.38
3.92	233.30	

0+00 Butt #4

0+05

0+10

0+15

0+20

0+25

0+30

0+35

0+40

Start Buttrass #4 Start of arch #4

233.3

ground	top	back
28.8	28.9	29.1
4.5	4.4	4.2
		2.6
28.3	28.6	28.6
5.0	4.7	4.7
		1.0
27.3	27.7	27.7
6.0	5.6	5.6
		0.5
26.6	27.2	27.2
6.7	6.1	6.1
		0.7
25.8	26.4	26.4
7.5	6.9	6.9
		1.0
25.2	25.6	25.6
8.1	7.7	7.7
		0.8
24.5	25.1	25.1
8.8	8.2	8.2
		0.7
23.6	24.6	24.6
9.7	8.7	8.7
		0.7
23.3	23.8	23.8
10.0	9.5	9.5
		0.7

233.3

22.5	23.1	23.1
10.8	10.2	10.2
		1.1

224.0

22.1	22.6	22.6
1.9	1.4	1.4
		1.4

21.4	21.9	21.9
2.6	2.1	2.1
		1.5

20.8	21.4	21.4
3.2	2.6	2.6
		1.5

20.8	21.5	21.7
3.2	2.5	2.3
		3.0

0745 233.30
10.96 222.34
1.70 224.04

0750

0755

0760

0765⁵⁵ Grain

Set T.B.M. on Rock 2.61 221.43
0.60 222.03

0790 At Grain

Start Buttress #8 Arch #8

222.0

16.5	17.2	17.3
5.5	4.8	4.7
		3.5

16.6	17.2	17.2
5.4	4.8	4.8
		1.1

16.7	17.3	17.3
5.1	4.7	4.7
		0.7

17.3	18.0	18.0
4.7	4.0	4.0
		0.7

17.7	18.4	18.4
4.3	3.6	3.6
		0.7

222.03

Grnd.	Foot	Back
222.0		
18.0	18.6	18.6
4.0	3.4	3.4
		0.7
18.5	19.1	19.1
3.5	2.9	2.9
		0.8
19.0	19.5	19.5
3.0	2.5	2.5
		0.5
19.6	20.1	20.1
2.4	1.9	1.9
		1.0
20.1	20.6	20.6
1.9	1.4	1.4
		1.0
20.7	21.1	21.1
1.3	0.9	0.9
		0.6
21.0	21.5	21.5
1.0	0.5	0.5
		1.0

221.43

1.00 222.43

0+00

From 0+05 to 0+35

0+05

Gunited

0+10

Start Arch #5. Buttress #5

222.4

20.6	21.4	21.4
1.8	1.0	1.0
		3.9

20.0	20.8	20.8
2.4	1.6	1.6
		1.5

19.2		
3.2		Gunited

Grnd. bot Back

222.43

222.4

0+35

12.6 13.2
2.8 2.2 no foot

0+40

11.9 12.0 12.4
11.0 10.7 10.4
0.8

0+45 blew off

0+50

8.7 9.1 19.3
13.7 13.3 13.1
0.9

2.5 Jump in footing

T.P.

10.55 211.88

4.98 216.86

216.9

0+55

7.5 8.1 9.9 9.9
7.9 8.8 7.0 7.0
0.5

0+60

6.4 8.3 8.8
10.5 8.6 8.6
0.5

0+65

6.1 6.7 6.7
10.8 10.2 10.2
0.5

0+67.0

Groin

6.2
10.7

Start Arch #6

0+05

5.7 6.1 6.1
11.2 10.8 10.8
0.3

0+10

5.8 5.8 5.8
11.1 11.1 11.1
0.3

0+15

5.1 5.2 5.2
11.8 11.7 11.7
0.3

216.86

0+20

Wind	Foot	Back
216.9		
5.0	6.3	6.3
11.9	10.6	10.6
		0.4

0+25

4.9	5.3	5.3
12.0	11.6	11.6
		1.2

0+30

4.9	5.2	5.4
12.0	11.7	11.5
		1.2

0+35

4.9	5.3	5.5
12.0	11.6	11.4
		1.3

0+40

4.8	5.3	5.4
12.1	11.6	11.5
		1.0

0+45

4.9	5.5	5.7
12.0	11.4	11.2
		0.8

0+50

4.8	5.6	5.7
12.1	11.3	11.2
		0.5

0+55

4.9	5.6	5.7
12.0	11.3	11.2
		0.3

0+60

4.9	5.4	5.7
12.0	11.3	11.2
		0.4

0+65

5.6	6.3	6.4
11.3	10.6	10.5
		0.7

0+67

5.8	6.3	6.5
11.1	10.6	10.4
		3.0

216.86

0+05

0+10

0+15

0+20

0+25

0+30

0+35

0+40

0+45

0+50

0+55

Grnd

Foot

Back

Start Arch #7
216.9

5.8 7.0 7.2

11 8.9 9.7
0.6

6.7 8.3 8.4

10.2 8.6 8.5
0.8

8.7 9.6 9.8

8.2 7.3 7.1
0.8

9.4 10.7 10.8

7.5 6.2 6.1
1.0

10.2 11.1 11.3

6.7 5.8 5.6
1.0

11.0 11.8 11.9

5.9 5.1 5.0
1.1

12.1 12.9 13.0

4.8 4.0 3.9
1.0

13.4 13.9 14.1

3.5 3.0 2.8
1.1

14.2 14.9 15.1

2.7 2.0 1.8
1.0

14.6 15.1 15.2

2.3 1.8 1.7
1.0

15.2 15.7 15.7

1.7 1.2 1.2
1.0

60

216.86

0+60

0+65

0+67 = Butt #8 see Arch #8

T.P.

3.25 213.61

9.93 223.54

T.P.

1.92 221.62

6.24 227.86

0+00 = 0+64 Arch #8

0+05

0+10

0+15

0+20

0+25

216.9

15.8 16.3 16.3

1.1 0.6 0.6
2.8

16.3 14.9 16.9

0.6 0.0 0.0
0.9

Start Arch #9
227.9

21.2 21.8 21.8
6.7 6.1 6.1
3.0

21.3 21.8 21.8
6.6 6.1 6.1
1.0

21.5 22.1 22.1
6.4 5.8 5.8
0.8

21.7 22.3 22.1
6.2 5.6 5.8
0.8

21.8 22.5 22.4
6.1 5.4 5.4
0.6

22.2 22.7 22.7
5.7 5.2 5.2
0.7

227.86

0+30

0+35

0+40

0+45

0+50

0+55

0+60

0+60 = 0+64 Arch #5

T.P.

6.16 232.75

1.27 226.59

0+05

0+10

gnd	Box	Rock
227.9		
22.6	23.0	23.0
5.3	4.9	4.9
		0.6
23.0	23.6	23.6
4.9	4.3	4.3
		0.8
23.5	24.0	24.0
4.4	3.9	3.9
		0.7
24.0	24.5	24.5
3.9	3.4	3.4
		1.0
24.2	24.8	24.8
3.7	3.1	3.1
		1.0
24.4	25.1	25.1
3.5	2.8	2.8
		0.7
24.9	25.3	25.3
3.0	2.6	2.6
		1.1

Start Arch #10

24.9	25.3	25.3
3.0	2.6	2.6
		3.0

232.8

25.1	25.8	25.8
7.7	7.0	7.0
		1.1

25.5	26.0	26.0
7.8	6.8	6.8
		1.0

232.75

0+15

0+20

0+25

0+30

0+35

0+40

0+45

0+50

0+55

0+60

0+63 Groin = 0+00

Grain	Foot	Deck
232.8		
25.6	26.1	26.1
7.2	6.7	6.7
		1.0
25.8	26.4	26.4
7.0	6.4	6.4
		0.9
26.1	26.6	26.6
6.7	6.2	6.2
		0.4
26.7	27.1	27.1
6.1	5.7	5.7
		0.5
27.0	27.5	27.5
5.8	5.3	5.3
		0.5
27.3	27.7	27.7
5.5	5.1	5.1
		0.5
27.7	28.3	28.3
5.1	4.5	4.5
		0.6
28.1	28.7	28.7
4.7	4.1	4.1
		0.5
28.3	28.8	28.8
4.5	4.0	4.0
		0.6
28.5	29.0	29.0
4.3	3.8	3.8
		0.4
28.7	29.2	29.2
4.1	3.6	3.6
		0.1

Start Arch #11

0+05	232.75		
T.P.	0.67	232.08	
0+10	8.94	241.02	
0+15			
0+20			
0+25			
0+30			
0+35			
0+40			
0+45			
0+50			
0+55			

Grnd	Box	Back
232.8		
29.8	30.7	30.7
3.0	2.1	2.1
		0.3
241.0		
30.4	31.1	31.1
10.6	9.9	9.9
		0.6
31.3	31.6	31.6
9.7	9.4	9.4
		0.4
31.8	32.3	32.3
9.2	8.7	8.7
		0.5
32.4	33.0	33.0
8.6	8.0	8.0
		0.6
33.9	33.9	33.9
7.1	7.1	7.1
33.9	34.5	34.5
7.1	6.5	6.5
		0.4
34.4	35.2	35.2
6.6	5.8	5.8
		0.5
35.2	35.9	35.1
5.8	5.1	5.1
		0.4
35.5	36.3	36.3
5.5	4.7	4.7
		0.4
36.1	36.8	36.8
4.9	4.2	4.2
		0.3

241.02

0+60

0+62 BuH #12

5+375

5.5 235.6

241.0

36.8	37.1	37.1
7.2	3.9	3.9
		0.4

36.7	37.3	37.5
4.3	3.7	3.5
		2.0

REDUCED

JWA 1/27/48

X Sections of San Dieguito
Derr

(AFTER EXCAVATION)
(6.25' stations)

From L+T Butress #1 to Start of
Guniting 34.95'

Arch #5
55' from L+Ts on Buttresses

66

p. 66 to 78
incl.
except p. 67
also p. 82

	H.I.		
		221.43	
0+25	0.17	221.60	
0+31.25			
0+TP		9.29	212.31
	2.42	214.79	
0+50			

HI	Length of Slope
221.60	
212.78	25.10
211.49	24.81
214.73	
206.52	35.1

Pooling

8.92
23.07

10.11
23.06

8.21
33.78

ELEV OF BASE
LINE LET'S

Elev L+Ts

Lake Drained
Quitting in Progress

JAN 29, 1948

67

L+T Butt #13		250.00
5.15	255.15	
Butt #12	5.07	250.08
" 11	5.00	250.15
" #10	5.02	250.13
" 9	5.08	250.07
Arch #8	4.15	251.00
Butt #8	5.13	250.02
Arch #7	4.18	250.97
Butt #7	5.10	250.05
Arch #6	4.20	250.95
Butt #6	5.08	250.07
" 5	5.13	250.02
" 4	5.05	250.10
" 3	4.98	250.17
" 2	5.02	250.13
" 1	5.00	250.15

Arch #6

Rainey
King Jan. 31, 1948
Harrow

68

Length of Slope

HI 214.73

206.11 [✓] *curited*8.62
24.79*curited at toe*

33.70

HI 215.17

205.68 [✓] *curited*8.49
20.75

33.60

205.62 [✓] *curited*9.55
17.55

33.50

205.65 [✓] *curited*9.52
17.05

33.85

05.86

27.8

205.63 [✓]9.54
17.81

33.75

204.60 [✓]10.57
19.70

34.65

204.94 [✓]10.23
24.40

34.33

205.71 [✓]9.46
34.72

32.90

214.73

0+6.25

214.13

1.04 215.17 [✓]

0+12.50

0+18.25

0+25

0+31.25

0+37.50

0+43.75

0+50

Length of slope

HI 215.17

207.46 ✓
curved at top7.71
25.23

31.45

curved 25' below footing

211.08 ✓

4.09

23.48

26.68

211.78 ✓ curved 2' below top of footing

3.35

213.6

26.41

curved 1.5' below footing

213.23 ✓

1.94

22.48

24.27

curved at top

219.07 ✓

1.10

24.10

23.22

219.90 ✓

0.27

28.40

21.46

HI 223.48

215.81 ✓

7.67

33.35

20.35

217.19 ✓

6.29

42.35

18.75

215.17

0+625

0+125

0+1825

0+25

0+3125

0+3750

IR#1

8.47

223.48 ✓

0.16

215.01 ✓

0+4325

0+50

	223.48 ✓		
0+0625			
0+1250			
0+1875			
0+25			
0+3125			
0+3750			
0+3750			
0+4375			
0+50			
TP		2.08	221.40 ✓
9.16	230.56 ✓		

HI	223.48	Length of Slope
	217.58 ✓	
	5.90	
	34.52	18.20
	218.16 ✓	
	5.32	
	50.00	18.00
	218.59 ✓	
	4.89	
	27.72	17.58
	219.07 ✓	
	4.41	
	27.06	17.10
	219.62 ✓	
	3.86	
	27.77	16.50
	220.43 ✓	
	5.05	
	31.18	15.55
	221.19 ✓	
	2.33	
	31.50	14.65
	222.72 221.72	
	1.76	
	45.00	14.00

230.56 ✓

0+12.50

0+18.75

0+25

0+31.25

0+37.50

0+43.75

0+50

Arch #9

71

Length of
Slope

HI 230.56

222.26 ✓

5.30
32.48

12.99

~~222.69~~ 222.59

7.97
30.23

12.79

222.93 ✓

7.63
29.60

12.36

223.48 ✓

7.08
31.03

14.36

224.16 ✓

6.40
34.54

10.27

224.63 ✓

5.93
40.03

9.75

225.35 ✓

5.21
47.64

9.52

0+06.25

0+12.50

0+18.75

0+25

TP

0+31.25

0+37.50

0+43.75

4+00

0+50

230.56 ✓

236.17 ✓

1.44

229.12 ✓

Arch = 10

72

Length
of
Steps

HI 230.56 ✓

225.91 ✓

4.65

39.54

8.72

226.38 ✓

4.18

35.37

7.80

226.47 ✓

4.09

33.24

7.85

227.09 ✓

3.47

32.67

7.24

HI 236.17

227.46 ✓

8.71

33.78

6.72

228.01 ✓

8.16

37.35

5.80

228.63 ✓

7.54

42.42

4.90

229.24 ✓

6.93

50.52

4.80

236.17 ✓

0+0625

0+1250

0+1875

T.P.#1

6.05

②

241.30

241.30

0+25

0+3125

0+3750

0+4375

0+50

0.92 235.25 ✓

Arch #11

HI 236.17

231.14 ✓

5.03

44.00

232.08 ✓

4.09

39.03

232.85 ✓

3.32

37.87

HI 241.30

233.80 ✓

7.50

36.72

234.64 ✓

6.66

37.43

235.73 ✓

5.57

40.00

236.35 ✓

4.95

44.43

237.45 ✓

3.85

37.28

REDUCED

U.H.A. 2/2/48

Checked JK 2.26.48

out of
Arch Area
(No. 1)ARCH 12
P. 82

Arch #1

HI 251.51

Gumited

246.22

5.25

38.15

Gumited

245.18

6.33

38.76

244.40

2.11

42.98

241.94

9.57

46.68

JK

B.M. Arch #1

0.49

251.51

251.02

0+34

0+37E

0+43ZS

0+50

251.51
 0+06 25
 0+12 50
 T.P.#1
 4.44 2.44.28 ✓ 11.67 239.84 ✓
 0+18 25
 0+25
 0+31 25
 0+37 50
 0+43 25
 0+50

HI 251.51

291.30 ✓

10.21

43.24

240.04 ✓

11.47

38.82

HI 244.28

6.50

238.91 ✓

5.37

36.50

237.17 ✓

7.11

35.24 ✓

236.28

8.00

34.40

~~237.41~~ 237.50

6.28

38.74 ✓

237.73

6.53

42.71

236.44 ✓

7.84

53.10

All
Gummed

Gummed at top

JK

244.28 ✓

0+06.25

0+12.50

0+18.75

0+25

0+31.25

0+37.50

T.P.

0+40

1.36

234.53

0+43.75

0+50

1111

233.17 ✓

HI Arch #3

244.28

235.77 ✓

8.57

43.33

235.36 ✓

8.97

38.80

233.81 ✓

10.47

36.55

233.47 ✓

10.81

33.57 Arch

232.91 ✓

11.87 Arch

33.07

230.98 ✓

13.30

33.51

HI 234.53

230.08 ✓

4.45

42.73

228.67 ✓

5.36

53.12

Quitted at face

All
Quitted

on structure
9.28
35.66
face of
arch
entered
9.21
36.44
face of
arch

2.15

JK

Arch #4

HI

234.53

Length of Slope

228.10 ✓

6.43

6.75

~~39.95~~

227.27 ✓

7.26

7.25

~~34.99~~

226.03 ✓

8.50

8.75

31.40

224.92 ✓

9.61

10.00

~~30.05~~

224.07 ✓

10.46

11.00

~~30.63~~

223.55 ✓

10.98

12.10

33

222.74 ✓

11.79

12.50

~~27.50~~

222.23 ✓

12.30

13.20

40.93

234.53

0+06.25

0+12.50

0+18.75

0+25

0+31.25

0+37.50

0+43.75

0+50

IP

0.13 222.55 ✓

12.11 222.42 ✓

All
GaugedGauged
at Top

JK

cont.

Length of Slope

222.55

0+065

HI 222.55

219.07 ✓

3.48
34.10

17.27

0+1250

216.79 ✓

5.76
28.01

20.00

0+1825

214.90 ✓

7.65
23.92

22.62

T.B.M. on Rock

118

221.37 ✓

corr.
221.43

JK

Spillway elevs.

SAN DIEGUITO DAM

79

	HI	ELEV.
B.M. Lat. Butt. #13		250.00
5.06	255.06	
	-4.05	251.01
-2.83	248.18	
S Lip (HOOD)	+1.86	250.04
S Spillway invert	+1.79	249.97
T.P.	+1.86	250.04
-1.89	248.15	
Middle Spillway	+1.83	249.98
" Lip (HOOD)	+1.88	250.03
N Spillway	+1.85	250.00
" Lip (HOOD)	+1.90	250.05

Checked JK 3-24-48

Counterforts
(SAN DIEGUITO DAM)
GROUND SURFACE & BOTTOM
ELEVATIONS

Feb. 13, 1948

Rainey
Baker
Chipman

244.5

Butt #12S

242.0

Butt #12N

240.0

Butt #11S

235.0

Butt #11N

232.0

Butt #10S

231.0

Butt #10N

231.0

Butt #9S

228.0

Butt #9N

228.0

Butt #8S

222.0

Butt #8N

222.0

Butt #7S

213.0

Butt #7N

213.0

Butt #6S

At face

242.7

242.8

1.8

1.7

10'

239.2

238.1

2.8

3.9

10'

233.8

232.6

229

6.2

7.4

9'

232.1

231.3

230

2.9

3.7

10'

228.3

228.4

224

3.5

3.6

10'

227.9

227.1

223

3.1

3.9

12'

224.6

224.8

219.5

6.4

6.2

12'

224.0

223.5

218

4.0

4.5

12'

219.2

219.3

215.5

8.8

8.7

12'

218.1

216.1

214.5

3.9

5.9

15'

209.3

211.7

206

12.7

10.3

15'

208.4

207.0

204

4.6

6.0

10'

207.9

206.4

200.5

5.1

6.6

15'

MEAN BOTTOM
OF EXC. (ELEV.)
9K 3.1.1748

80

Counterports cont.

Butt #4N	215.0	209.5	212.0	204
		5.5	3.0	
			14	
Butt #5S	222.0	221.2	220.8	217.3
		0.8	1.2	4.7
			7	15
Butt #5N	225.0	222.0	223.3	217.5
		7.0	5.7	
			12	
Butt #4S	232.0	231.0	230.3	227
		1.0	1.7	
			11	
Butt #4N	236.0	232.8	233.3	228
		3.7	2.7	
			10	
Butt #3S	242.0	239.3	238.5	233
		2.7	3.5	
			9	
Butt #3N	243.0	239.8	239.9	234
		3.2	3.1	
			10	
Butt #2S	247.0	249.0	243.2	—
		3.0	3.8	
			18	
Butt #2N	247.0	244.3	244.6	—
		2.7	2.4	
			8	

REDUCED J.N.A. 2/16/48

Checked JF 3.23.48

MEMO BY T.Y.O. P.
OF EXC. (ELEV.)
JL 3.15.48

Rainey
Baker
Shipman

2.17.48

D+I Butt #13

250.00

1.25 251.25

0+0625

0+1250

0+1825

0+25 (= 5+75)

See p. 166

Arch #12 (AFTER EXCAVATION)

82

face of Arch	Edge of post	Grp'd
HI 251.25		
240.33 ✓	240.33	239.59
10.92	10.92	11.66
44.00	43.21	43.20
241.83 ✓	241.83	240.80
9.42	9.02	10.45
39.72	39.10	39.25
243.11 ✓	243.11	241.75
8.14	8.14	8.50
37.38	36.72	36.88
244.38 ✓	244.38	244.38
6.87	6.87	6.87
36.72	35.60	35.60

REDUCED J.N.A. 2/17/48

checked JK 3.23.48

KEYSOR
ANDREWS

2-17-98

see p. 46.

ARCH # 12 (BEFORE EXCAVATION)

83

249

0+06²⁵

0+12⁵⁰

0+18⁷⁵

0+25 (= 5+75)

249.

2420

70

440

2435

5.5

39.72

2450

4.0

37.38

2445

4.5

36.72

Final^(?) Sections
San Dieguito DAM
(after backfill)

BM Arch #2		251.02
	0.27	251.29
T.P. #1		12.71 238.58
	1.60	240.18
T.P. #2		12.41 227.77
	1.12	228.89
T.P. #3		11.93 216.96
	3.13	220.09
2+25		
2+50		
2+75		
3+00		
3+25		
3+91.25		
3+37.50		
3+43.75		

p. 84 to 91
incl.

231.25
Feb 19, 1948

Raimy
Baker
Chipman

84

228.32

220.1

215.9 ✓
4.2

211.1 ✓
9.0

211.1 ✓
9.0

210.1 ✓
10.0

212.6 ✓
7.5

213.6 ✓
6.5

215.9 ✓
4.2

216.5 ✓
3.6

Face at each

212.8 ✓
7.3
21.7

210.6 ✓
9.5

211.8 ✓
8.3

212.7 ✓
7.4

214.6 ✓
5.5
25.0

216.4 ✓
3.7
27.1

217.1 ✓
3.0
30.3

218.6 ✓
1.5
36.6

220.09 ✓

3+50

3+56 25

2+16 25

2+12 50

2+06 25

2+00

J.P. 22

11.41

231.42 ✓

0.08 220.01 ✓

1+93 25

1+87 50

1+81 25

1+75

220.1 ✓

216.9 ✓

3.2

217.4 ✓

2.7

216.8 ✓

3.3

17.6 ✓

2.5

218.4 ✓

1.7

219.6 ✓

0.5

231.4

220.7 ✓

10.7

222.0 ✓

9.4

~~23.2~~
~~222.5~~

8.2

224.7 ✓

6.7

227.55

71.81

239.34

face of arch

219.0 ✓

1.1

39.3

18.6

1.5

31.95

16.5

3.6

25.9

219.0 ✓

1.1

29.7

221.4 ✓

1.3

36.2

223.1 ✓

13.0

41.9

223.5 ✓

7.9

37.4

224.0 ✓

7.4

32.5

224.8 ✓

6.6

31.10

225.7 ✓

5.7

30.80

85

239.34

240.8
240.4
2

231.42

1+68.75

1+62.50

1+56.25

1+50

T.P. #5

11.57 242.10

0.89

230.53

1+43.75

1+37.50

1+31.25

1+25

1+18.75

1+12.50

231.4

~~225.3~~
26.3

5.1

227.4

4.0

228.7

2.7

229.8

1.6

242.1

231.1

11.0

232.2

9.9

233.4

8.7

234.3

7.8

234.2

6.9

236.2

5.9

228.1

3.3

34.1

229.9

1.5

37.9

230.9

0.5

41.9

231.4

0.0

43.5

232.6

9.5

41.2

233.3

8.8

38.25

234.5

7.6

36.1

235.4

6.7

35.5

236.2

5.9

36.2

237.4

4.7

39.4

242.10 ✓

1+06.25

1+00

T.P. #6

1021 250.88 ✓

1.43

240.67 ✓

0+99.75

0+87.50

0+81.25

0+75.00

0+67.25

0+62.50

0+56.25

0+50

242.1

237.2 ✓

4.9

238.1 ✓

4.0

250.9

239.1 ✓

11.8

240.2 ✓

10.7

241.0 ✓

9.9

241.8 ✓

9.1

242.5 ✓

8.4

243.3 ✓

7.6

243.7 ✓

7.2

244.4 ✓

6.5

face starch

87

238.8 ✓

3.3

43.4

239.3 ✓

2.8

48.9

239.8 ✓

11.1

43.0

240.4 ✓

10.5

39.4

241.0 ✓

9.9

36.2

241.9 ✓

9.0

35.5

242.5 ✓

8.4

36.0

243.4 ✓

7.5

38.9

244.2 ✓

6.7

43.0

244.4 ✓

6.5

46.6

250.88[✓]

0+4325

0+3750

0+3125

0+25

0+00

on paper
Terned to

226.02

7.P#7

4.75

221.27[✓]

8.63 229.90[✓]

3+6250

3+6825

3+75

3+8125

3+8750

3+9325

250.9[✓]

245.1[✓]

5.8

245.6[✓]

5.3

246.1[✓]

4.8

246.7[✓]

4.3

249.6[✓]

1.3

245.4[✓]

5.5

42.9

246.3[✓]

4.6

38.5

246.8[✓]

4.1

38.3

247.8[✓]

3.1

36.4

250.5[✓]

0.4

51

229.9

218.0[✓]

11.9

218.8[✓]

11.1

219.2[✓]

10.7

220.2[✓]

9.7

220.8[✓]

9.1

221.4[✓]

8.5

19.1[✓]

10.8

28.6

220.1[✓]

9.8

27.8

221.5[✓]

8.4

27.8

222.8[✓]

7.1

29.7

223.6[✓]

6.3

32.9

224.3[✓]

5.6

30.2

✓
229.90

4+00

4+06 25

4+12 50

4+18 75

4+25

4+31 25

4+37 50

4+43 25

4+50

T.P.

8.77 236.90

✓
1.77 228.13

4+56 25

4+62 50

4+68 25

229.9

222.0 ✓

7.9

222.6 ✓

7.3

223.3 ✓

6.6

223.7 ✓

6.2

224.3 ✓

5.6

225.1 ✓

4.8

225.6 ✓

4.3

226.2 ✓

3.7

226.8 ✓

3.1

236.9

227.4 ✓

9.5

227.9 ✓

9.0

228.5 ✓

8.4

225.1 ✓

4.8

43.1

224.8 ✓

5.1

34.50

224.9 ✓

5.0

33.3

225.2 ✓

4.7

39.0

225.7 ✓

4.2

30.1

226.7 ✓

3.2

32.9

227.2 ✓

2.7

37.0

227.8 ✓

2.1

40.80

228.1 ✓

1.8

45.0

228.4 ✓

8.5

38.2

228.6 ✓

8.3

36.2

229.0 ✓

7.9

33.7

236.90

4+75

4+81²⁵4+87⁵⁰4+93⁷⁵

5+00

T.P.

8.89 244.17

1.62 235.28

5+06²⁵5+12⁵⁰5+18⁷⁵

5+25

5+31²⁵5+37⁵⁰5+43⁷⁵

236.9

229.0 ✓

7.9

229.6 ✓

7.3

230.1 ✓

6.8

230.8 ✓

6.1

231.5 ✓

5.4

244.2

232.3 ✓

11.9

233.1 ✓

11.2

233.9 ✓

10.3

234.9 ✓

9.3

235.9 ✓

8.3

236.8 ✓

7.4

237.7 ✓

6.5

229.7 ✓

7.2

230.2 ✓

6.7

231.7 ✓

5.2

232.4 ✓

4.5

233.2 ✓

43.2

233.2 ✓

37

233.2 ✓

10.3

233.2 ✓

11.0

233.9 ✓

43.2

234.4 ✓

39.2

234.4 ✓

9.8

234.8 ✓

36.6

234.8 ✓

9.4

236.7 ✓

35.9

236.7 ✓

7.5

238.7 ✓

36.9

238.7 ✓

5.0

240.0 ✓

37.7

240.0 ✓

4.2

240.0 ✓

14.0

✓
244.17

5450

J.P.

2.20 241.97 ✓

8.84 250.81 ✓

5456.25

5462.50

5468.75

5475

244.2

238.4 ✓

5.8

240.9 ✓

3.3

45.8

250.8

239.6 ✓

11.2

242.2 ✓

8.6

42.

241.9 ✓

8.9

245.2 ✓

5.7

243.5 ✓

7.3

243.1 ✓

7.7

13.1

17.2

39.2

243.8 ✓

7.0

248.3 ✓

2.5

244.9 ✓

5.9

244.5 ✓

6.3

12.3

18.3

37.2

246.7 ✓

4.1

248.6 ✓

2.2

246.1 ✓

4.7

245.7 ✓

5.1

7.7

16.4

37.2

REDUCED - ANDREWS
checked JK 3-20-48

ELEV BASE LINE L&T'S - SAN DIEGUITO DAM

check elev.

uniting of face
comp.

W.S. 216±

L&T Butt #13		250.00
	5.00	255.00
Butt #12	4.91	250.09
Butt #11	4.86	250.14
Butt #10	4.88	250.12
Butt #9	4.92	250.08
Arch #8	3.99	251.07
Butt #8	4.97	250.03
Arch #7	4.02	250.98
Butt #7	4.95	250.05
Arch #6	4.05	250.95
Butt #6	4.92	250.08
" #5	4.98	250.02
" #4	4.90	250.10
" #3	4.84	250.16
" #2	4.86	250.14
" #1	4.84	250.16

Feb. 19, 1948

92

3.5.48

Plus the water Elev. -		238.8
L&T Butt #13		250.00
	+ 5.09	- 255.09
Butt #12	5.01	250.08
Butt #11	4.95	250.14
Butt #10	4.98	250.11
Butt #9	5.02	250.07
Arch #8	4.09	251.00
Butt #8	5.07	250.02
Arch #7	4.12	250.97
Butt #7	5.06	250.03
Arch #6	4.15	250.94
Butt #6	5.03	250.06
" #5	5.08	250.01
" #4	4.99	250.10
" #3	4.94	250.15
" #2	4.96	250.13
" #1	4.94	250.15

ELEV BASE LINE L&T'S - SAN DIEGUITO DAM

Check elev.

Water level 233.5

Feb. 27, 1948

Ramey
Baker
Shipman

93

Butt #13 250.00
5.02 255.02

0.33

250.33

12.39 237.99

Butt #12 4.94 250.08

Elev. Top Water Crest

237.99

" #11 4.88 250.14

" #10 4.91 250.11

" #9 4.96 250.06

255.98

" #8 5.01 250.01

5.19 249.89

" #7 4.99 250.03

" #6 4.99 250.03

#5 5.02 250.00

" #4 4.94 250.08

#3 4.88 250.14

#2 4.90 250.12

#1 4.88 250.14

Arch #8 4.02 251.00

#7 4.06 250.96

#0 4.09 250.93

Struts May-6-36

Elev. of Buttress bottom openings

9-10	240 225.	240 229	240 229	229.
11-12	240 215	240 216.	240 216.	240 216.
13-14	220 209	220 -	220 -	220
15-16	220 203	220 204	220 -	220 -
17-18	220 202	220 202	220 202	220 202
19-20	240 213	240 213	240 213	240 213
21-22	242	260 242	260 242	

Hough
Brackman

#9 E. Set ✓

4-18-36

10 W. C-12.5

16 E C 1.0

17 W. C 1.0

19 W C 4.0

18 E. C 9.0

19 E. C 7.0

20 W. C 4.0

20 E C 13.6 from Water 4-25-36

21. W. C 3.0

16 W. C 1.0 is .8 above water

15 E. C 1.0

15 W C 3.7 below water

14 E. (OK Set) Fred raise 7' 10" to 00 6-6"
Red Blue center is 2068

14 W C 1.0 0.1 above water

13 E C 2.0 0.1 ✓ ✓

13 W C 6.0

12 E C 2.0

12 W C 3.0 water 2127

11 E Set.

11 W. C 3.0

10 E. C 1.0

21 E. water Ab. 240.75 C @ Water 19.75

22 W ✓ ✓ ✓ C @ 0.8

22 E.

Constant Diagonals
Diff. Elev. 1.414 = Dist

2.5
60
1500
27/14 52.0 54
30 10

TABLE No. 2
211.1
200.5
10.6
9.0
211.12
210.9
211.7
2200
83
211.7
8
3.7

IMPROVED TABLES

AND

INFORMATION

TABLE No. 2
To find Tangent and External for curve of any other degree, divide by degree of curve and add correction found in column of corrections. Degree of curve with a given T may be found by dividing tangent (or external) opposite T by given tangent (or external).
The distance from a point on the tangent to the curve is very nearly the square of the tangent length divided by twice the radius.

A. LIETZ Co.

San Francisco U.S.A. 10268

Level - City # W - 5247 -

A. LIETZ Co.

San Francisco U.S.A. 10278

Transit - City # W - 6867



401.24	403.63
<u>395.</u>	<u>95</u>
6.2	8.6

13	26.5
<u>75</u>	<u>67</u>
205	21.19
<u>167</u>	<u>135</u>
2.17	67

398.8	402.42
<u>95</u>	<u>95</u>
38	7.4

381.05	379.4	383.95
<u>75</u>	<u>75</u>	<u>75</u>
6.0	44	9.00

385.32	385.52	383.17	387.85
<u>76</u>	<u>75</u>	<u>75</u>	<u>75</u>
10.3	10.5	82	12.4

30.4

Water 21.67 Below starting BM

246.78

246.78

11.82

234.96

50
<u>5.14</u>
200
50
<u>150</u>
15700
72.00