

Distances from Side Stakes for Cross-Sectioning

Slope 1 to 1. Roadway of Any Width

	0	.1	.2	.3	.4	.5	.6	.7	.8	9	
0	0.00	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	0
1	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.70	1.80	1.90	1
2	2.00	2.10	2.20	2.30	2.40	2.50	2.60	2.70	2.80	2.90	2
3	3.00	3.10	3.20	3.30	3.40	3.50	3.60	3.70	3.80	3.90	3
4	4.00	4.10	4.20	4.30	4.40	4.50	4.60	4.70	4.80	4.90	4
5	5.00	5.10	5.20	5.30	5.40	5.50	5.60	5.70	5.80	5.90	5
6	6.00	6.10	6.20	6.30	6.40	6.50	6.60	6.70	6.80	6.90	6
7	7.00	7.10	7.20	7.30	7.40	7.50	7.60	7.70	7.80	7.90	7
8	8.00	8.10	8.20	8.30	8.40	8.50	8.60	8.70	8.80	8.90	8
9	9.00	9.10	9.20	9.30	9.40	9.50	9.60	9.70	9.80	9.90	9
10	10.00	10.10	10.20	10.30	10.40	10.50	10.60	10.70	10.80	10.90	10
11	11.00	11.10	11.20	11.30	11.40	11.50	11.60	11.70	11.80	11.90	11
12	12.00	12.10	12.20	12.30	12.40	12.50	12.60	12.70	12.80	12.90	12
13	13.00	13.10	13.20	13.30	13.40	13.50	13.60	13.70	13.80	13.90	13
14	14.00	14.10	14.20	14.30	14.40	14.50	14.60	14.70	14.80	14.90	14
15	15.00	15.10	15.20	15.30	15.40	15.50	15.60	15.70	15.80	15.90	15
16	16.00	16.10	16.20	16.30	16.40	16.50	16.60	16.70	16.80	16.90	16
17	17.00	17.10	17.20	17.30	17.40	17.50	17.60	17.70	17.80	17.90	17
18	18.00	18.10	18.20	18.30	18.40	18.50	18.60	18.70	18.80	18.90	18
19	19.00	19.10	19.20	19.30	19.40	19.50	19.60	19.70	19.80	19.90	19
20	20.00	20.10	20.20	20.30	20.40	20.50	20.60	20.70	20.80	20.90	20
21	21.00	21.10	21.20	21.30	21.40	21.50	21.60	21.70	21.80	21.90	21
22	22.00	22.10	22.20	22.30	22.40	22.50	22.60	22.70	22.80	22.90	22
23	23.00	23.10	23.20	23.30	23.40	23.50	23.60	23.70	23.80	23.90	23
24	24.00	24.10	24.20	24.30	24.40	24.50	24.60	24.70	24.80	24.90	24
25	25.00	25.10	25.20	25.30	25.40	25.50	25.60	25.70	25.80	25.90	25
26	26.00	26.10	26.20	26.30	26.40	26.50	26.60	26.70	26.80	26.90	26
27	27.00	27.10	27.20	27.30	27.40	27.50	27.60	27.70	27.80	27.90	27
28	28.00	28.10	28.20	28.30	28.40	28.50	28.60	28.70	28.80	28.90	28
29	29.00	29.10	29.20	29.30	29.40	29.50	29.60	29.70	29.80	29.90	29
30	30.00	30.10	30.20	30.30	30.40	30.50	30.60	30.70	30.80	30.90	30
31	31.00	31.10	31.20	31.30	31.40	31.50	31.60	31.70	31.80	31.90	31
32	32.00	32.10	32.20	32.30	32.40	32.50	32.60	32.70	32.80	32.90	32
33	33.00	33.10	33.20	33.30	33.40	33.50	33.60	33.70	33.80	33.90	33
34	34.00	34.10	34.20	34.30	34.40	34.50	34.60	34.70	34.80	34.90	34
35	35.00	35.10	35.20	35.30	35.40	35.50	35.60	35.70	35.80	35.90	35
36	36.00	36.10	36.20	36.30	36.40	36.50	36.60	36.70	36.80	36.90	36
37	37.00	37.10	37.20	37.30	37.40	37.50	37.60	37.70	37.80	37.90	37
38	38.00	38.10	38.20	38.30	38.40	38.50	38.60	38.70	38.80	38.90	38
39	39.00	39.10	39.20	39.30	39.40	39.50	39.60	39.70	39.80	39.90	39
40	40.00	40.10	40.20	40.30	40.40	40.50	40.60	40.70	40.80	40.90	40
41	41.00	41.10	41.20	41.30	41.40	41.50	41.60	41.70	41.80	41.90	41
42	42.00	42.10	42.20	42.30	42.40	42.50	42.60	42.70	42.80	42.90	42
43	43.00	43.10	43.20	43.30	43.40	43.50	43.60	43.70	43.80	43.90	43
44	44.00	44.10	44.20	44.30	44.40	44.50	44.60	44.70	44.80	44.90	44
45	45.00	45.10	45.20	45.30	45.40	45.50	45.60	45.70	45.80	45.90	45
46	46.00	46.10	46.20	46.30	46.40	46.50	46.60	46.70	46.80	46.90	46
47	47.00	47.10	47.20	47.30	47.40	47.50	47.60	47.70	47.80	47.90	47
48	48.00	48.10	48.20	48.30	48.40	48.50	48.60	48.70	48.80	48.90	48
49	49.00	49.10	49.20	49.30	49.40	49.50	49.60	49.70	49.80	49.90	49
50	50.00	50.10	50.20	50.30	50.40	50.50	50.60	50.70	50.80	50.90	50

Distance of slope stake from side or shoulder stake for any width roadway, slope 1 to 1. If ground is nearly level, the cut or fill at side stake is located by the double entry method in left column and top row. The number in body of table in same row and column gives distance from side stake to slope stake. If ground is not level estimate the difference in elevation between the side stake and slope stake, lower target by this amount if cut, elevate if fill. Add this amount to cut or fill and find distance in table. Set up rod at this point, and line of sight should cut target. If it does not make the slight adjustment necessary.

75
75
75
730

TABLE XIII—CORRECTIONS FOR TANGENTS AND EXTERNALS

These corrections are to be added to the approximate values, found by dividing the tangent, or external, for a 1° curve (Table VIII) by the degree of curve, in order to obtain the true tangents, or externals. Intermediate values may be obtained by interpolation.

FOR TANGENTS ADD

Central Angle	Degree of Curve													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	03	.06	09	13	16	19	.22	.25	.28	.31	.34	38	42	.46
15°	04	10	14	19	24	.29	.34	.39	45	.51	.53	58	.63	.68
20°	06	.13	19	.26	.32	.39	.45	.51	.58	.65	.72	79	.84	.90
25°	.08	16	24	.33	40	49	.58	67	.75	.83	90	.99	1.06	1.14
30°	10	19	.29	39	49	.59	.69	79	.89	.99	1.09	1.20	1.29	1.39
35°	11	22	.34	47	.58	.69	.70	.81	.92	1.04	1.29	1.42	1.54	1.66
40°	13	.26	.40	.53	.67	.80	.93	1.06	1.20	1.34	1.49	1.64	1.79	1.94
45°	15	.30	44	60	76	91	1.06	1.21	1.37	1.52	1.70	1.87	2.04	2.21
50°	17	.34	.51	.68	.85	1.02	1.19	1.36	1.54	1.72	1.91	2.10	2.29	2.48
55°	19	38	.57	76	.95	1.14	1.32	1.52	1.72	1.92	2.14	2.35	2.56	2.77
60°	.21	42	.63	.84	1.05	1.27	1.49	1.71	1.94	2.17	2.38	2.60	2.83	3.07
65°	23	46	.69	.93	1.16	1 40	1.64	1.88	2.13	2.38	2.63	2.88	3.13	3.39
70°	25	.51	76	1.02	1.28	1.54	1.80	2.06	2.33	2.60	2.88	3.16	3.44	3.72
75°	.27	.56	.83	1.12	1.40	1.69	1.98	2.27	2.57	2.87	3.16	3.47	3.78	4.09
80°	30	.61	.91	1.22	1.53	1.84	2.15	2.46	2 78	3.10	3.44	3.78	4.12	4.46
85°	33	66	1.00	1.33	1.68	2.02	2.36	2 70	3.05	3.40	3.77	4.14	4.55	4 89
90°	36	.72	1.09	1.45	1.83	2.20	2.57	2.94	3.32	3.70	4.10	4.50	4.91	5.32
95°	39	79	1.19	1.55	2.00	2.40	2.80	3.20	3.61	4.02	4.40	4.98	5.38	5.83
100°	43	.86	1.30	1.74	2.18	2.62	3.06	3.50	3.95	4.40	4.88	5.37	5.85	6.34
110°	51	1.03	1.56	2.08	2.61	3.14	3.67	4.21	4 76	5.31	5 86	6.43	7 01	7 60
120°	62	1.25	1 93	2.52	3.16	3.81	4 45	5.11	5.77	6 44	7 12	7.80	8.50	9 22

FOR EXTERNALS ADD

Central Angle	Degree of Curve													
	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
10°	.001	.003	.004	.006	.007	.008	.009	.011	.012	.014	.015	.017	.018	.020
15°	.003	.007	.010	.014	.018	.023	.027	.029	.032	.035	.039	.043	.047	.051
20°	.006	.011	.017	.022	.028	.034	.038	.045	.051	.057	.063	.070	.076	.083
25°	.009	.018	.027	036	.046	.056	.065	.074	.083	.093	.106	120	127	135
30°	.013	.025	.038	.051	.065	.078	.090	.103	.116	.129	.149	.170	.179	.188
35°	.018	.035	.054	.072	.086	.109	.131	.153	.175	.197	.213	.230	.247	.264
40°	.023	.046	.070	.093	.117	.141	.172	.203	.234	.265	.277	.290	.315	.341
45°	.030	.060	.093	.119	.153	.184	.216	.254	.289	.325	.351	.378	.411	.445
50°	.037	.075	.116	.151	.189	.227	.266	.305	.345	.384	.425	.467	.508	.550
55°	.046	.093	.142	.188	.236	.283	.332	.381	.420	.479	.530	.582	.641	.700
60°	.056	.112	.168	.225	.283	.340	.398	.457	.516	.575	.636	.697	.774	.851
65°	.067	.135	.204	.273	.343	.412	.483	.554	.625	.697	.711	.845	.922	1.01
70°	.080	.159	.240	.321	.403	.485	.568	.652	.735	.819	.906	.994	1.08	1.17
75°	.095	.182	.286	.383	.480	.578	.678	.777	.877	.977	1.07	1.18	1.29	1.39
80°	.110	.220	.332	.445	.558	.671	.787	.903	1.02	1.13	1.25	1.38	1.50	1.62
85°	.128	.259	.391	.524	.657	.790	.926	1.06	1.20	1.34	1.47	1.62	1.76	1.91
90°	.149	.299	.450	.603	.756	.910	1.07	1.22	1.38	1.54	1.70	1.87	2.03	2.20
95°	.174	.350	.522	.706	.985	1.06	1.25	1.43	1.62	1.80	1.99	2.18	2.38	2.58
100°	.200	.401	.604	.809	1.01	1.22	1.43	1.64	1.85	2.06	2.28	2.50	2.73	2.96
110°	.268	.536	.806	1.08	1.35	1.63	1.91	2.20	2.48	2.76	3.05	3.35	3.66	3.96
120°	.360	.721	1.08	1.45	1.82	2.19	2.57	2.95	3.33	3.72	4.11	4.50	4.91	5.32

INDEX

WERT
KEMP
ALEXANDER
HOLAHAN

1

3-16-55

Profile ℄ of Proposed Water Line
Ronaro Dr. Country Club Pump House
to La Jolla View Reservoir

See Map 1975
See Book 17



Note: ⊞ = hub
△ = ℄ ST.

Sec A

Detail paving & drain on left

Note: All measurements on curves are radial
" " " tangents are right angle


See Map 1975
& Book 17
86.3+25.03
PIPE FINDER LOCATION
8" C.I. WAT. 7/20/53
0± LT 3+50
1± LT 4+00
4± LT 4+50
1± LT 4+97
Δ = 45° 11' 10"
R = 217.01
Δ = 17° 03' 50"
R = 696.08
L = 207.31
2+75 ? Questionable
18" RT 6+00
6" RT 6+50
5" RT 7+00
6" RT 7+50
Pomeroy Drive
25' @ 2+50
GV. 2' RT 5+62
GV. 25' RT 5+70
GV. 5' RT 5+96
9 FH. 13' RT
GV. 9' RT
Limits of 6" con. paving Shown


Drive
Romero
6' 9+00
6' 8+50
6' RT. 8+00
GV. 21' LT. 7+71
7+70.26
PIPE FINDER LOCATION 4" C.I. 7/20/55
6' RT 7+50
Romero
Sec "B"
B.C. 9+22.95
Drive
Romero
6' RT 12+00
8' RT 11+75
8' RT 11+50
9' RT 11+00
8' RT 10+75
7' RT 10+50
5' RT 10+00
5' RT 7+50
6' RT B.C.
B.C. 9+22.95
5
9'
9'
5'
cable slant gutter
Sec "B"
6" con paving
12+47.32
Proj. Int Sta.
℄ℓ = 254.51
Δ = 73° 31'
℄L = ~~324.31~~ 326.56


Pipe Finder Location a" Cl.
7/20/55
8' RT 15+94
3' RT 15+50
on ℄ 15+13
15 E. prop.
15+93.98
N 78°
Way
14+90 3' LT
FH 13' RT 14+90
GV 6' RT 14+90
3' LT 14+50
Δ = 73° 01' 20"
℄ R = 195.23
℄ L = 248.82
on ℄ 14+25
5° 22' 46" W
Romero Dr. developed
12' RT 13+50
Romero Drive
B.C. 13+45.15
Δ = 118 29 10
℄ R = 45
℄ L = 93.06
12+49.51
9' RT 12+50
9' RT 12+75
10' RT 13+25 in cobble stone gutter
Δ = 11° 29' 46"
R = 25.63
L = 5.12
B.C. 13+42.57

See page 26

Romero Drive Cont.

		435.33
		436.10
	435.47	
0.14	436.24	
		425.96
9.51	426.73	
	426.44	
0.48	427.21	
		413.42
13.02	414.19	
	414.27	
0.85	415.04	
		400.95
13.32	401.72	
	401.27	
0.32	402.04	
		387.94
13.33	388.71	
	389.47	
1.53	390.24	
		380.46
9.01	381.23	
	380.75	
0.29	381.52	
0+00		
	11.7	
0+39		

Where from?

L.E.T., common B.C. Country Club Dr. & Carrizo

Note B.M. marked 436.10 was found to b 0.77 in error. Corrections in red.

? see p9 #5

Note: All x sec. & distance measured radial on curves & 90° on tangents

TBM LET Sta 1+00 B.C.

LL	℄	RL
11.9 / 9	11.7 / 8	12.0 / 9

20' GL

		380 .75		
		381.52		
0+50			6.0	
0+51				
1+00	B.C.		0.30	380.4
				380.23
	T.P.		0.52	381.00
		393.15		
	12.92	393.92		
1+09				
1+25			9.9	
1+39			8.2	
1+39				
1+[illegible]			7.0	
1+50			7.0	
1+66			5.05	

Reduced by J. Gray 4-11-55

	Lt	℄	Rt
	6.1 / 9	6.0 / 0	6.7 / 9
			G.V. Wat. MH. Air V.
	0.4 / 9	0.3 / 0	0.9 / 9
			20 R. Water G.V.
	10.0 / 9	9.9 / 0	10.0 / 9
	8.5 / 9	8.2 / 0	8.7 / 9 radial
	Elect. cross		
	Elect MH. 35' ℄, cut 2.5 top 2" cable		
	7.1 / 9	7.0 / 0	7.1 / 9
	Water MH. 7' Rt, G.V. 10' Rt.		

Romero Dr. Cont.

	393.15 393.92		
1+75		4.1	
1+82		3.2	
1+89			
2+00		1.2	
			393.09
T.P.		0.06	393.86
	405.84		
12.75	406.61		
2+25		11.0	
2+50		8.1	
2+80.03 EC.		4.6	5.4 = 400.74
3+00		2.4	2.8 = 403.04
			405.60
		0.24	406.37
	418.06		
12.46	418.83		

1+	℄		RC
4.2/9	4.1/0	4.3/9	16" wat. cross @ 9' Rt.
3.2/0	16" water cross @ ℄		
16" water cross @ 2.5/9			
1.3/9	1.2/0	1.3/9	
11.1/9	11.0/0	11.1/9	
9.0/9	8.1/0	9.0/9	
6.2/9	4.6/0	6.0/9	
3.2/9	2.4/0	3.5/9	

Romero Dr. Cont

	418.06		
	418.83		
3+25.83 BC.		11.7	
3+50		8.9	
3+75		6.0	
3+98			
4+00		3.2	
4+05			
4+15			
4+25		0.4	
4+25			417.92
T.R.		0.14	418.69
	431.09		
13.17	431.86		

Lt	℄	Rt
11.9 / 9	11.7 / 0	11.7 / 9
9.0 / 9	8.9 / 0	9.0 / 9
6.2 / 9	6.0 / 0	6.0 / 9
	cable cross. 9' Rt.	
3.2 / 9	3.7 / 0	3.5 / 9
	cable cross @ ℄	
cable cross. 9' Lt., begin standard curb, left only		
0.5 / 9	0.4 / 0	0.9 / 9
	Elect cross. @ 9' Rt.	

Romero Dr. Cont

431.09
431.86

4+50	11.1
4+50	
4+75	8.7
4+77	8.03
4+95	
4+96.97 PCC.	6.5
4+97.	6.5
4+99	
5+00	
5+25	3.6
5+50	1.0

LT	℄	RT
		11.3/9 — 11.1/0 — 12.0/16 So. gutter
	Elect crossing ℄	
		9.0/9 — 8.7/0 — 8.8/7 Elect cross. — 9.2/13 ℄ County Club Dr.
Gas MH. 12' LT		
	Elect MH. 9' LT	
		6.7/9 — 6.5/0 — 7.5/23 ℄ County Club Dr.
	Gas cross ℄	
	Tele cross ℄	
	Tele MH. 11' RT	
		9 — 3.6/0 — 5.7/23 — 6.1/39 ℄ County Club Dr.
		1.0/9 — 1.0/0 — 1.4/9 — 2.2/18

Romero Dr. Cont.

		431.09		
		431.86		
			430.38	
		0.71	431.15	
		443.46		
	13.08	444.23		
5+62				
5+70.5				
5+70.5				
5+75		10.3		
5+86				
5+91				
5+96				
6+00		7.3		
6+07				
6+25		4.4		
6+50		1.4		

Lt	℄	Rt
		Water GV. 2' Rt
		Water GV. 28' Rt
		Sewer line 38' Rt
	10.6/9 10.3/6	10.9/9 12.4/31 curb face
	Sewer line @ ℄	
Sewer line @ 9' Lt.		
		Water GV. 5' Rt
	7.7/9 7.3/6	7.8/9 8.0/13' curb face
		Water GV. 9' Rt, FH. 13' Rt
	4.6/9 4.4/6	4.8/12 curb line
	1.7/9 1.4/6	1.8/12

Ponce Dr. Cont.

		443.46			
		444.23			
				442.97	
			0.49	443.74	
		456.17			
	13.20	456.94			
6+72.5					
6+75			11.3		
7+04.20	E.C.		8.0		
7+50			2.9		
7+60			1.07		
7+65			0.62		
7+71					
				456.16	
T.P.			0.01	456.93	
		469.27			
	13.11	470.04			

Lt	&	Rt
End St. curd on Lt Begin rubble gutter, Rt & Lt		
11.6 / 9	11.3 / 0	11.4 / 9
8.1 / 9	8.0 / 0	8.2 / 9
2.5 / 9	2.4 / 0	2.6 / 9
Tel. MH. 1' Lt		
Gas MH. 3' Lt		
Water GV. 21' Lt		

Romero Dr. Con't

	469.27		
	470.04		
8+00		9.6	
8+50		3.8	
T.P.		0.16	469.88
	482.35		469.11
13.24	483.12		
9+00		10.9	
9+22.95		8.7	
9+52.95		4.1	
T.P.		0.21	482.91
	494.92		482.14
12.28	495.19		
9+82.95		11.9	
10+12.95		7.6	
10+12.95		7.58	
10+19		6.73	

Lt	℄	Rt		
9.7 / 9	9.6 / 0	10.0 / 9		
3.8 / 9	3.8 / 0	4.1 / 9		
11.1 / 9	10.9 / 0	11.1 / 9		
8.3 / 9	8.2 / 0	8.4 / 9		
4.2 / 9	4.1 / 0	4.2 / 9		
12.2 / 9	11.9 / 0	12.0 / 9		
7.8 / 9	7.6 / 0	7.8 / 9	7.5 / 12 back curb	8.2 / 17

Gas & Elect. M.H. 4' Lt

Tele. M.H. 2' Lt

Romero Dr. Cont.

				LT.		RT.		
	494.92							
	495.19							
10+42.95		3.4		3.6/9	3.4/0	3.6/9	3.3/12 back curb	3.4/17
T.P.		0.31	494.88					
	506.95							
12.84	507.72							
10+72.95		11.7		12.1/9	11.7/0	11.8/9	11.7/12 back curb	11.8/17
11+02.95		7.7		7.8/9	7.7/0	7.7/9	7.7/12 back curb	7.8/17
11+32.95		3.4		3.5/9	3.4/0	3.7/9		
T.P.		0.08	507.64					
	519.88							
13.01	520.65							
11+62.95		12.2		12.3/9	12.2/0	12.5/9		
11+92.95		7.8		7.9/9	7.8/0	8.1/9		
12+22.95		3.6		3.7/9	3.6/0	3.8/9		
12+49.51 P.R.C.		0.4		+0.8/17	0.0/12	0.6/9	0.4/0	0.5/9

Romero Dr. Cont

519.88
520.65

519.44
520.21

T.P. 0.44

532.60
533.37
13.16

		Lt	℄	Rt
12+64	12.08			Tele. MH. 2' Rt
12+67	11.36	Gas & Elect MH. 2' Lt		
12+75	10.7	8.3/25 10.7/21 10.6/19 back curb 11.2/9	10.7/0	10.4/9
13+00	9.0	6.4/26 8.8/21 9.0/12 back curb 9.5/9	9.0/0	8.7/9
13+25	7.2	4.9/27 7.2/22 7.8/12 back curb 7.8/9	7.2/0	6.9/9
13+42.57 E.C.	5.8	6.1/9	5.8/0	5.6/9
13+45.15 B.C.	5.6	3.0/20 5.1/19 7.2/12 5.8/9	5.6/0	5.6/9
13+75	1.9	2.3/9	1.9/0	1.7/18 gutter

Romero Dr. Cont

		532.60					
		533.37		532.59			
T.P.			0.01	533.36			
		545.43					
	12.84	546.20					
14+00			11.2				
14+07			9.80				
14+12			9.04				
14+25			7.6				
14+50			4.2	541.23			
14+75			.09				
14+90				545.36			
T.P.			0.07	546.13			
		558.70					
	13.34	559.47					
15+00			10.7				

Lt.	℄	Rt.
11.9 / 9	11.2 / 0	10.7 / 30 gutter

Gas & Elect. MH. 19' Rt.

Tele. MH. 29' Rt.

7.9 / 9	7.6 / 0	cable cross 7.2 / 15	6.4 / 46.5 Gutter	4.5 / 50 Sewer M.H.	Cut 5.7 ± FL.
4.7 / 9	4.2 / 0 cable cross.		2.6 / 32 sewer cross.	2.4 / 42	1.7 / 52
cable cross. 1.1 / 9	0.9 / 0	0.7 Gutter / 15			

Water GV. 6' Rt. & F.H. 13' Rt.

11.0 / 9	10.7 / 0	10.7 / 9

Romero Dr. Cont

	558.70		
	559.47		
15+25		7.2	
15+50		3.7	
			558.53
T.P.		0.17	559.30
	571.35		
12.82	572.12		
15+75		12.5	
15+93.98 P.R.C.		9.6	
16+00		8.7	
16+25		5.0	
16+50		1.2	
			571.14
		0.21	571.91
	583.92		
12.78	584.69		
16+75		10.1	
16+85		7.02	

Lt	℄	Rt
7.4 / 9	7.2 / 0	7.2 / 9
3.9 / 9	3.7 / 0	3.7 / 9
12.6 / 9	12.5 / 0	12.6 / 9
9.7 / 9	9.6 / 0	9.6 / 9
9.0 / 9	8.7 / 0	8.9 / 9
5.3 / 9	5.0 / 0	5.2 / 9
1.6 / 9	1.2 / 0	1.3 / 9
10.4 / 9	10.1 / 0	10.2 / 9

Sewer MH. 15' Rt

Pomero Dr. Cont

	583.92		
	584.69		
17+00		6.3	
17+30		2.0	
17+30.41 E.C.		2.0	
17+41.5		0.14	
			583.85
T.P.		0.07	584.62
	596.76		
12.91	597.53		
17+47		12.16	
17+50		11.7	
18+00		4.5	
			596.74
T.P.		0.02	597.51
	609.45		
12.71	610.22		
18+50		9.9	
19+00		2.7	

	LL.	℄	RL
	6.5 / 9	6.3 / 0	6.5 / 9
Storm Dr. Grate	2.85 / 9	2.0 / 0	2.17 / 9 Storm Dr. Grate
	2.8 / 9	2.0 / 0	2.2 / 9
Tele MH. 4' LL			
Gas & Elect MH. 6' LL.			
	11.9 / 9	11.7 / 0	11.7 / 9
	4.7 / 9	4.5 / 0	4.5 / 9
	10.2 / 9	9.9 / 0	9.9 / 9
	3.0 / 9	2.7 / 0	2.6 / 9

Romero Dr. Cont

	609.45		
	610.22		
		609.37	
T.P.		0.08	610.14
	622.34		
12.97	623.11		
19+50		8.2	
20+00		1.0	
20+01.5		0.86	
		622.29	
T.P.		0.05	623.06
	635.44		
13.15	636.21		
20+50		7.0	
		635.31	
T.P.		0.13	636.08
	648.34		
13.03	649.11		
21+00		12.6	
21+15.04 B.C.		10.4	
21+25		8.9	
21+42			

Lt	℄	Rt
8.6 / 9	8.2 / 0	8.3 / 9
1.4 / 9	1.0 / 0	1.0 / 9
Gas & Elect MH. 4' Lt.		
7.3 / 9	7.0 / 0	7.0 / 9
12.9 / 9	12.6 / 0	12.5 / 9
10.6 / 9	10.4 / 0	10.5 / 9
9.0 / 9	8.9 / 0	9.2 / 9
Water G.V. 1' Lt		

Romero Dr. Cont

	648.34		
	649.11		
21+50		5.2	
21+75		2.5	
21+86			
21+95		0.9	
21+97.5		0.5	
22+00		0.4	
22+04		0.08	
			648.10
T.P.		0.24	648.87
	660.93		
12.83	661.70		
22+04		11.25	
22+25		10.7	
22+50		8.2	

Lt.	℄	Rt
5.1/9	5.2/0	5.4/9 4.9/12 4.4/18
1.9/9	2.5/0	3.1/9 2.5/12 2.0/18
Gas cross 1.5/9		
	0.9/0 Gas cross	
Gas & Elect MH. 4'		
0.4/9	0.4/0	0.5/4 Gas cross 0.7/9 0.1/12 +0.6/18
Tele. MH. 2' Lt.		
Sewer MH. 21' Lt		cut 5.0 to ft.
10.7/9	10.7/0	10.7/9 10.4/12 10.0/18 9.1/22
8.2/9	8.2/0	8.1/9

Romero Dr. Cont

	660.93		
	661.70		
22+55.23 E.C.		7.6	
22+75		5.1	
23+00		1.9	
			660.87
T.P.		0.06	661.64
	674.11		
13.24	674.88		
23+25		11.9	
23+33.45		10.9	
23+50		8.9	
24+00		2.5	
			673.99
T.P.		0.12	674.76
	682.07		
8.08	682.84		
24+50		5.9	

Lt.	℄	Rt
7.6 / 9	7.6 / 0	7.6 / 9
5.1 / 9	5.1 / 0	5.1 / 9
2.0 / 9	1.9 / 0	2.1 / 9
12.0 / 9	11.9 / 0	12.2 / 9
10.9 / 9	10.9 / 0	11.1 / 9
8.9 / 9	8.9 / 0	9.1 / 9
2.5 / 9	2.5 / 0	2.7 / 9
5.9 / 9	5.9 / 0	6.0 / 9

Romero Dr. Cont.

682.07
682.84

25+00	4.2	
25+01	4.30	677.76
25+07	4.11	677.96
25+50	3.4	
25+57	3.41	678.66
25+59.12 P.R.C.	3.3	
25+65		
25+75	3.0	
25+87		
26+00	2.6	
26+25	2.2	

L.E.	℄	R.E.
	4.2 / 9	4.2 / 6 — 4.3 / 9
	Tele. MH. 9' DE	
	6.5' E. MH. 8' RE	
	3.6 / 9	3.4 / 6 — 3.7 / 9
	Sewer M.H. 16' RE	
2.3 / 20 — 2.7 / 12	3.4 / 9	3.3 / 6 — 3.6 / 9
	cut 6.8 left.	3.5 / 9 Sewer cross
	3.1 / 9	3.0 / 6 Sewer cross — 3.3 / 9
2.9 / Sewer cross 9		
1.0 / 27 — 2.0 / 12	2.7 / 9	2.6 / 6 — 2.9 / 9
	2.4 / 9	2.2 / 6 — 2.4 / 9

Romero Dr. Cont.

		682.07		680.45	
		682.84			
T.P.			1.62	681.22	
		686.24			
	5.79	687.01			
26+50			5.9		
26+75			5.5		
P.R.C.					
26+84.78			5.3		
26+87					
27+00			5.0		
27+07					
27+25			4.7		
27+50			4.4		

	Lt	℄	Rt
	4.7 / 20 (end con. wall)	5.1 / 12	6.0 / 9 — 5.9 / 0 — 6.1 / 9
		5.6 / 9	5.5 / 0 — 5.7 / 9
		5.4 / 9	5.3 / 0 — 5.5 / 9
Sewer Co.		5.4 / 9	
	5.1 / 9	5.1 / 8 (Sewer cross)	5.0 / 0 — 5.3 / 9
			6" MH 14' Rt
	4.7 / 9	4.7 / 6 (Sewer cross)	4.7 / 8 — 4.9 / 9
	4.4 / 9	4.4 / 5 (Sewer cross)	4.4 / 0 — 4.6 / 9

Romero Drive Court

			Lt.	℄	Rt.
	686.24		4.3 / 9	4.3 / 8 Sewer chars	4.5 / 0 — 4.6 / 9 — 4.6 / 10 water G.V.
9355 27+64.30 P.I. 2925	687.01	4.5			
27+66			water GV. on line		
27+79		4.2	edge pavc. 4.1 / 7'	4.2 / 0 Sewer cross.	4.5 / 6 G.V. — 5.1 / 24.5 edge conc. pave.
27+93.55		2.9	con. wall 1.8 / 8	2.8 / 2 rock wall & flower bed	2.9 / 0 — 3.4 / 8
28+00		2.2	1.2 / 8 con wall	2.2 / 1.5 rock wall	2.2 / 0 — 2.7 / 7 edge con. pave.
	663.86				
	2.38	684.63			
	696.96				
13.10	697.73				
28+06			Sewer MH. 11.5' Rt., Flow Ln.		
28+08			F.H. 23' Rt.		
28+33		10.1	9.3 / 7'	10.1 / 8 rock wall cross	

Romero Drive Cont

				LC	℄	RC
	696.96					
	697.73					
28+50		7.7		6.3 / 8 con wall	7.7 / 0	7.6 / 7 Top rock wall; 8.3 / 11 Bottom rock wall; 8.8 / 8 ℄ AC.; 8.6 / 15 edge of p.
29+00		2.5		1.6 / 8 con wall	2.5 / 0	2.6 Top rock wall; 3.0 / 7 Bottom rock wall; 3.7 / 10 ℄ AC.; 3.3 / 17 edge of AC.
29+07		1.9		East end rock wall & flower bed, L 1.9 Top wall; 2.2 Bottom wall		
T.P.		0.90	697.40 698.17			
	710.96					
	13.06 711.23					
29+37.06 APL.	(45°)	13.5		Back line 13.2 / 10	13.5 / 0	14.1 / 7 — 13.9 / 19
29+37+06 APL	(45°)	13.5		Line ahead 13.8 / 13	13.5 / 0	13.4 / 15 — 13.0 / 26 face rock wall
29+67.06 APL		11.5		Line ahead 12.0 / 10 face of rock wall	11.5 / 0	10.0 / 1 — 10.2 / 10 flower bed
29+78				G&E MH. 3.5 LC.		

Romero Drive Cont.

		710.46		
		711.23		
30+00		9.4		
30+50		4.8		
30+75		1.4		
	T.P.	1.30	709.16	
			709.93	
		719.61		
	10.45	720.38		
31+01.32	Δ PL	6.6		
30+92		2.1		
			713.87	
	T.P.	5.74	714.64	
		724.66		
	10.79	725.43		
			721.10	
		3.56	721.87	

	LL			RL	
	9.3/10	9.4/0	9.3/6	8.0/7	8.0/10
			face rock wall		
	9.6/10	4.8/0	4.8/1	3.7/1.5	3.7/10
			face rock wall		
	1.8/10	1.9/7.5	1.0/7	1.4/0	1.1/10
			face rock wall		
back line	6.3/10	6.6/0		7.0/10	

Ground line next to pump house

USGS Δ Sba 721.10

Note: This level circuit closed within 0.01

?

Romero Drive Cont

△ = L.P.T. Found



Romero Drive Cont



Romero Drive Court

409.0
N-16° 37' W

Fd. 1/2" pipe

Seepage 29 for details

See Map 2977-B for Reservoir easement

Set nail

Concrete wall N-75° 12' 52" E

5' RT 29+37

13°39'32"

6' RT 29+00

4" AC PAVT

45 RT 28+00

Set nail

6" Rubble Curb 1E LT 28+00 See profile for details

9 GV on ℄ 4° 27+66

X in pave. Set by intersec.

9 GV

28+42

1.7' RT

Δ = 60° 02'
℄ R = 192.41

P.C. 28+84.29

30° 01'

P.C. 27+89.53

ENCALIA

95' RT 27+50

95' RT 27+25

5' RT 27+00

Δ = 90° 00'
℄ R = 80.00
L = 125.66

P.C. 26+84.78

5' RT 26+75

3' RT 2-C 5.0

PIPE FINDER LOCATION 24" C.I. 7/20/55

Δ = 30° 01'
℄ R = 190.41
L = 99.75

Romero Drive Cont



Hart
Kemp
Holahan
Alexander

4-6-55

Profile & Proposed Water Line
"C" St. 34th to 35th

0+00 W/L of 34th

0+60 E/L of 34th

6+59.95 W/L of 35th

7+19.95 E/L of 35th St.



WEST
KEMP
HOLAHAN &
ALEXANDER JT

		137.88	
	0.68	138.56	
0+00	12.9		125.66
+18	11.3		127.26
+37			
+50	9.0		129.56
+50			
+62	8.4		130.16
+85	6.9		131.66
1+00	7.6		130.96
T.P.	12.82	125.74	
	0.13	125.87	
1+50	2.5		123.37
+89	10.1		115.77
2+00	10.1		115.77
+12	9.9		115.97

Reduced by J Gray 5-6-55

NEMON. 34TH & C

WATER GATE

E.H. 36'R

	125.87			
2+50		2.2	123.67	
T.P.		0.87	125.00	
	3.85	128.85		
2+69		1.9	126.95	
+86		0.6	128.25	
3+00		1.3	127.55	
+35		4.9	123.95	P.O.T.
+50		8.0	120.85	
T.P.		12.86	115.99	
	0.35	116.34		
4+00		7.0	109.34	
T.P.		12.69	103.65	
	0.79	104.44		
4+47		7.2	97.24	TOP SLOPE
+55				10" GUM TREE
+71				" & 8" GUM TREE
+76				" " "

	104.44			
4+81				6" GUM TREE
+86				" " "
+91				" " "
+96				2" " "
T.P.		12.75	91.69	
	0.53	92.22		
T.P.		13.09	79.13	
	0.27	79.40		
4+93		5.7	73.70	
5+03.37		9.7	69.70	BOTTOM SLOPE
+41		14.5	64.90	
+46		12.5	66.90	
+50		12.6	66.80	
+68		12.4	67.0	
+77		10.3	69.1	
+78		9.79	68.61	TOP DWL BLEM W. SIDE A.C. ACCESS RD.
		7.37	72.03	B.M. on Guard rail & produced

Wert
Kemp
Holahan
Alexander

4-29-55

Profile & Proposed Water Line

Boston St, 39th to 40th



PROFILE & PROPOSED WATER LINE

BOSTON ST., 39TH TO 40TH

		20.31	
	11.12	31.43	
T.P.		0.23	31.20
	10.41	41.61	
0+00		5.9	35.7
T.P.		1.64	39.97
	8.94	48.91	
0+41		1.9	47.0
0+50		1.3	47.6
0+60		2.6	46.3
T.P.		12.59	36.32
	1.96	37.78	
1+00		5.8	32.0
1+18		11.9	26.9
T.P.		12.65	25.13
	0.92	26.05	

℄ WATER

15' RIGHT

SPK. IN POLE

WEST LINE 39TH	8.5	5.9	
T.B.M.			
CON. MON.			
	5.9	43.0	1.9
	5.4	43.5	1.3
	6.2	42.7	2.6
	8.2	29.58	5.8
	13.8	24.0	11.9

				℄	
	26.05			15' RIGHT	WATER
1+28		2.8	23.2	4.2 21.8	2.8
1+50		4.7	21.3	5.8 20.2	4.7
2+00		6.6	19.4	7.1 18.9	6.6
2+50		7.6	18.4	8.0 18.0	7.6
3+00		7.9	18.1	7.8 18.2	7.9
T.P.		7.91	18.14		
	5.62 23.76				
3+50		5.6	18.2	5.4 18.36	5.6
4+00		5.5	18.3	5.1 18.66	5.5
4+50		5.1	5	4.8 19.0	5.1
5+00		5.0		4.7 19.1	5.0
5+50		5.3		4.9 18.9	5.3
6+00		4.5		4.4 19.4	4.5
6+50		4.3		4.5 19.3	4.3
7+00		4.0		4.5 19.3	4.0
7+24.5.5		3.8		3.9 19.9	3.8
T.P.		3.72	20.04		
	3.94 23.98				

SPK IN POLE 10' SO. COM. MON.

	23.98			
T. P.		5.48	18.50	
	3.03	21.53		
T. P.		1.26	20.27 = 20.31	SPK. IN POLE

5-16-55

Profile of Proposed Water Line
Alley Blk 58, No. of Monroe E of 32nd

382.39 S.E.B.M. Monroe & 32nd

2.95 385.34

0+00	5.0	380.34	S/L of Monroe
0+12	5.2	380.14	So. curb
0+32	4.6	380.74	& Monroe
0+38	5.0	380.34	No curb line
0+50	5.0	380.34	
0+60	4.8	380.54	N/L of Monroe
0+80	2.6	382.74	
1+00	2.2	383.14	
1+50	1.8	383.54	
2+00	1.4	383.94	
T.P.	1.86	383.48	

Profile of Proposed 6" C.I. Water Main

4.97 388.45

2+50	4.0	384.45	
3+00	5.4	383.05	
3+50	5.1	383.35	

	Left	Right
	384.0	383.8
	4.5 / 10.5 383.7	4.7 / 4.5
	4.8 / 10.5 383.6	5.0 / 4.5 383.5
	4.9 / 10.5 383.6	4.7 / 4.5 383.8

	Left	Right
	381.0	
N/L of Monroe	1.3 / 10.5 383.0	1.4 / 4.5 380.9
	2.3 / 10.5 383.7	2.4 / 4.5 382.9
	1.6 / 10.5 383.7	2.0 / 4.5 383.3
	1.6 / 10.5 383.9	1.6 / 4.5 383.7
	1.4 / 10.5 383.9	1.4 / 4.5 383.9

	388.95		
4+00		4.9	383.55
4+50		4.8	383.65
5+00		5.0	383.45
5+50		5.0	383.45
6+00		5.1	383.35
6+50		5.1	383.35
T.P.		4.55	383.90
	3.11 387.01		
7+00.36		4.8	382.21
7+12.36		5.3	381.71
7+32.36		4.6	382.41
7+48.36		4.9	382.11
7+60.36		4.6	382.41
		5.89	381.12

Left		Right	
	384.1		
4.1 / 10.5	383.7	4.9 / 4.5	383.6
4.8 / 10.5	383.7	4.8 / 4.5	383.7
4.8 / 10.5	383.7	5.0 / 4.5	383.5
4.9 / 10.5	383.6	5.0 / 4.5	383.5
5.3 / 10.5	383.2	5.0 / 4.5	383.5
4.9 / 10.5	383.6	5.0 / 4.5	383.5

S/L of Madison

So. curb

℄

No. curb

N/L to Madison

SEBP Bancroft & Madison 381.01

Alley Blk 58 Cont.

7+60.36 N/L of Madison

7+00.36 S/L of Madison

6+60 N/L of Monroe

6+00 S/L of Monroe



West
Kemp
Holahan
Hexander

6-6-55

Profile & Proposed Water Line
Malden St, Collingwood to Lamont

0+00 W/L at Collingwood



Malden St. Cont

9+11.19	Angle point	89° 58' Def LT.
9+45.09	Angle point	89° 58' Def RT



Malden St. Court

14+90.40 W/L of Lamont

15+70.40 E/L of Lamont



Malden St. Cont

			209.80	NW. 2" pipe Jewell & Collingwood
	12.83	222.63		
P		0.10	222.53	
	12.43	234.96		
P		0.17	234.79	
	13.20	247.99		
P		9.36	238.63	Set TBM. SE. cor. mon. Collingwood & Malden
	9.64	248.27		
0+00		10.0	238.3	
0+18		9.3	239.0	
0+20		9.8	238.5	
0+43		9.7	238.6	
0+50		8.6	239.7	
1+00		5.2	243.1	
1+50		3.5	244.8	
1+75		3.0	245.3	
2+00		3.8	244.5	

Malden Cont

	248.27		
2+50		6.9	241.4
3+00		10.4	237.9
3+39			
P		13.09	235.18
	0.02	235.20	
3+50		0.5	234.7
3+59			
3+77			
4+00		3.0	232.2
4+11			
4+29			
4+50		4.0	231.2
4+51			
4+58		4.2	231.0
5+00		4.8	230.4
5+50		7.2	228.0
6+00		9.4	225.8

12" pepper tree 6' Rt

12" pepper tree 7' Rt

12" " " 7' Rt

24" " " 7' Rt

12" " " 6' Rt

12" " " 5' Rt

Power pole (P-1699) 7' Rt

Malden Cont

	235.20		
6+50		10.8	224.4
P		11.59	223.61
	3.95	221.56	
7+00		9.3	218.3
7+50		8.4	219.2
8+00		8.4	219.2
8+50		9.0	218.6
9+00		10.9	216.7
9+11.19		11.1	216.5
9+23			
9+45.09		6.6	221.0
9+50		6.6	221.0
P		5.96	221.60
	0.18	221.78	
10+00		2.7	219.1
10+50		7.3	214.5
11+00		11.4	210.4

Angle point in line

Water GV. 3' RT & FH. 6' RT

Angle point in line

Malden Cont

	221.78		
		13.33	208.45
	0.36	208.81	
11+50		1.9	206.9
12+00		6.0	202.8
12+50		8.9	199.9
13+00		8.9	199.9
13+50		8.2	200.6
14+00		7.1	201.7
14+50		6.5	202.3
14+90.4		6.24	202.1
15+00		6.7	202.1
15+10.4		7.1	201.7
15+20.		6.8	202.0
15+30.4		6.7	202.1
15+50		6.0	202.8
15+66		6.4	202.4
15+70.4		5.6	203.2

Begin 6" con. pave. & W/L of Lamont

W curb line produced

Gas x ing

& Lamont

& gutter & 6" curb

E/L of Lamont

Malden Cont

208.81

6.36 202.45

SW. Cor. Malden & Lamont

6-21-55

50

Profile & Proposed Water Line

Springfield St., Swan To Oriole St.

0+00 E/L Swan St

1760.54 &

1+00

1+61.88

5+67.02 W/L Oriole St.



SPRINGFIELD ST. CONT.

		406.78	
	0.31	407.09	
0+00		3.4	
0+17			
0+32		4.6	
0+50		6.5	400.6
T.P.		12.79	394.30
	0.56	394.86	
1+00		4.2	390.7
1+25		10.0	
T.P.		12.89	381.97
	0.51	382.48	
1+50		2.0	
1+60.54		3.6	
2+00		9.3	373.2
T.P.		13.08	369.40
	1.00	370.40	
2+50		5.3	

(SEE DRAWING 6)

NE 3/4" I.P. SWAN & SPRINGFIELD F.B. 896 P. 20

E/L SWAN ST

WATER G.V. ON LINE

4

SPRINGFIELD ST. CONT.

	370.40		
2+75		2.4	
3+00		12.2	
T.P.		13.22	357.18
	0.30	357.48	
3+50		8.4	
T.P.		12.64	344.84
	1.09	345.93	
4+00		7.7	
4+25		13.3	
T.P.		12.87	333.06
	2.05	335.11	
4+50		9.1	
4+76		11.2	
4+87		10.6	
4+93		8.8	BEGIN UNIMPROVED DRIVEWAY
5+00		8.7	
5+13		8.0	END " "
5+17			F.H. 52' ET

SPRINGFIELD ST. CONT.

	335.11		
5+50		4.1	
5+67.02		20	
		0.68	334.43 = 334.14

W/L ORIOLE ST, END PROFILE
& 2x2 HUB ORIOLE & N/L SPRINGFIELD
ADJUSTED ELEV. TO 334.43

KEMP
HOLAHAN &
ALEXANDER

6-22-55

54

PROFILE & PROPOSED WATER

UPLAND ST., WEAVER TO 360' WEST

0+60	SET SPK. FOR CONTROL
4+50	END PROFILE

WEAVER ST.

NO. SUPERIOR

FD OLD PK. IN STUB OF 2" PIPE

SET SPK. & WATER STA. 0+60

544.46' TO CON. MON.

B.C. WEAVER ST. 49.90' N. OF N/L UPPER ST.

89°59'

UPPER ST.

19'

UPLAND ST. & PROPOSED WATER

NO. SUPERIOR

30' 30'

SET NAIL STA. 4+50

UPLAND St. CONT.

		366.17
	2.35	368.52
T.P.		10.79 357.73
	0.07	357.80
0+00		5.4 352.4
0+15		8.1 349.7
T.P.		12.47 345.33
	0.59	345.92
0+22		1.4 344.5
0+46		3.8 342.1
0+50		4.3 341.6
0+60		7.9 338.0
T.P.		13.17 332.75
	0.06	332.81
1+00		2.1 330.7
1+50		9.5 323.3
T.P.		13.07 319.74
	0.04	319.78

B.M.
CON. MON. E.C. WEAVER 40' S. OF TOOLEY, F.B. 852 P. 9

T.B.M.
TOP 9 x 9 MARKER OTAY LINE STA. 730+00

E. EDGE UNIMPROVED ROAD - WEAVER
W " " " "

UPLAND ST. CONT.

	319.78	
2+00	3.1	316.7
2+25	7.0	312.8
2+50	10.3	309.5
T.P.	12.47	307.31
	0.59	307.90
3+00	8.1	299.8
T.P.	12.42	295.48
	4.37	299.88
3+50	8.8	291.1
4+00	14.4	285.5
4+50	17.0	282.9
T.P.	0.96	299.39
	13.04	312.43
T.P.	0.14	312.29
	12.64	324.93
T.P.	0.29	324.64
	12.88	337.52

UPLAND ST. CONT.

	337.52		
T.P.		0.77	336.75
	11.93		348.68
T.P.		0.02	348.66
	10.17		358.83
T.P.		1.09	357.74
	10.57		368.31
		2.13	366.18 = 366.17

B.M.
STARTING B.M.

SEA BREEZE DR - POTAMAC ST TO
250' N'LY ALLEGHANY

PLAN & PROFILE & PROPOSED WATER

3+56.66 FD 3/4" PIPE IN 3" PIPE ℄ ALLEGHANY & SEA BREEZE

3+37 S'LY CURB LINE

0+60 N.LY CURB LINE

0+20 S'LY CURB LINE

0+00 S'LY PROP LINE OF POTOMAC



SEA BREEZE DR

CONT

			274.49	BM SWBP ALLEGHANY & SEA BREEZE
	2.45	276.94		
3 TP		8.96	267.98	
	8.77	276.75		
0-12				FH 15' RT
0+00		8.24	268.51	BEG 6" A.C PAVE
0+20		7.96	268.79	S'LY CURB LINE POTOMAC
0+25				G.V. 5' RT
0+30				GV 30 L
0+41.5		7.70	269.05	SEWER CROSSING
0+41.5		7.88	268.87	E'LY RIM SEWER MH 5'LT 5.9' FLOW
0+50		7.69	269.06	
0+60		7.76	268.99	N'LY CURB LINE POTOMAC
0+81		7.85	268.90	END 6" AC PAVE
1+00		7.4	269.35	
1+02				TEL MH 26' LT
1+50		6.1	270.65	
2+00		5.0	271.75	
2+50		3.8	272.95	

Reduced by J. Gray 7-5-56

SEA BREEZE DR

		CON	
	276.75		
3+00	2.7	274.05	
3+25	1.86	274.89	BEG 6" AC PAVE
3+35			FH 46' RT
3+37	1.55	275.20	S'LY CURB LINE ALLEGHANY
3+46			2 G V 4.5' & 5.5' LFT
3+50	1.30	275.45	
3+56.66	1.30	275.45	℄ ALLEGHANY
3+59	1.30	275.45	15" SEWER CROSSING 20' TO FLOW
3+59	1.12	275.63	W'LY RIM SEWER MH 6' RT DROP FROM EAST 6.2' TO FLOW
3+67			GAS CROSSING & GAS MH 20' RT
3+74	1.55	275.20	BEG PCC GUTTER ARXON
3+76.5	1.60	275.15	℄ " " "
3+79	1.52	275.23	END " "
TP	0.93	275.80	
	5.96 281.76		
4+00	4.64	277.12	
4+50	1.83		

SEA BREEZE DR (CONT)

	281.76		
5+00	1.53		
5+50	1.37		
5+97.5	1.25		SEWER MH. 4' RT 25' FLOW
6+00	1.14		
6+10	1.14		
	7.25	274.51 = 274.49	SWBP ALLEGHANY & SEABREEZE

CALLE TOCON

FROM CALLE AGUA DULCE 210 E'LY

PLAN + PROFILE & PROPOSED WATER

0+00 W'LY PROP LINE OF AGUA DULCE

6-29-55 62

ALEXANDER
HOLAHAN
KELLHOFER



CALLE TOCON

CONT

BM			278.15	
	11.72	289.87		
TP		0.73	289.14	
	12.64	301.78		
TP		0.46	301.32	
	13.01	314.33		
TP		3.58	310.75	
	8.50	319.25		
0+00		10.1	309.15	
0+08				
0+50		7.9	311.35	
1+00		5.1	314.15	
1+12		4.6	314.65	
1+50		4.1	315.15	
2+00		4.3	314.95	
2+50		1.8	314.45	

Reduced by J. Grey 6-30-55

NW BP IN ROLL CURB CUMBERLAND & CALLE SERENA

¾ IP RE 6560 STA 0+75 30' LEFT

POWER POLE 5' LEFT

LEFT			RIGHT
		9.6/10	7.0/10
		10/10	3/2
		7.1/10	6.9/7
		6.4/10	6.9/6
5.7/10	5.6/3	4.3/3	3.3/10
		6.1/10	6.0/1
			4.2/10

CALLE TOCON (CONT)

	319.25			
TP		13.07	306.18	
	0.65	306.83		
TP		12.70	294.13	
	0.39	294.52		
TP		9.92	284.60	
	2.55	287.15		
CK BM		9.06	278.09 = 278.15	NWBP CUMBERLAND & CALLE SERENA

Country Club Res
to Encelia Dr



29+19.75 Top edge of Curb on Res

5' off on Line 2 prop pipes S 16° 37' E

28+41.12 Δ 35° 00' Lt.

27+76.78 POT Hub & Tack

6.05' off prop Line See Dist

27+38.46 AH Δ 10° 54' 40" Rt

27+43.40 BK

108.30
Rechecked

26+35.10 Δ 102° 45' Lt from PRC to 6' Prop Line
with prolongation of 6' off prop Line

26+35.10 POC intersection of ℄ Curve

Δ = 54° 25'
R = 80'
L = 75.98

25+59.12 PRC 27° 12' 30" Lt



Country Club Res
Cont

	6.12	684.78		678.66
26+35.18			4.74	680.04
26+46.50			4.76	680.02
+48.6			4.72	680.06
+48.7			4.13	680.65
+50			4.0	680.78
26+60			3.3	681.48
26+69			3.5	681.28
TP	12.88	696.86	0.80	683.98
26+67				
+71				
+75			11.1	685.76
+78				
+83				
27+00			5.5	691.36
	11.15	707.85	0.16	696.70
27+38.46			5.9	702.0
27+43.40				
+50			4.0	703.9
+56				

25+50 See page 21

TBM East Rim Sewer MH 16' Rt 678.66
6.12
691.78
2.03
677.75 Gutter

Edge of Conc paving Begin Rock Cement
butt of Gutter

Top Rock cement Curb 8" wide

4" Flowering Acacia Tree on ℄
6' Rt begin 4' High Conc Ret wall

End of Conc retaining Wall 6.3' Rt

8' Lt 3/4" Acacia Tree

11.8 / 6' Lt — 10.3 / 6' Rt

8' Rt 6" Dia Flowering Acacia Tree

4' Rt 1/2" Dia Cuc Tree

6.4 / 6' Lt — 4.6 / 6' Rt

5.6 / 6' Lt — 5.6 / 6' Rt

4.1 / 6' Lt — 3.8 / 6' Rt

4' Rt 6" Dia Acacia Tree

	707.85		
11.60	716.43	3.02	704.83
27+76		6.7	709.73
+78			
+85			
+90			
+94			
28+00		4.7	711.73
+03			
+13			
+16		4.55	711.88
+41.12		4.52	711.91
+41.13			
+44			
+50		4.30	712.13
+95		2.11	714.32
+96		1.42	715.01
+98			
29+00		0.8	715.63
8.80	725.20	0.03	716.40

6.8 / 6' Lt — 6.9 / 6' Rt — 8' Rt to Cone Wall

6' Rt Small Ornamental Scrub

4' Rt 1" Dia Acacia Tree

6' Lt 1/2" Dia Oleander Bush

3.5' Rt 2" Dia Acacia — 2.3 Rt 5" Dia Acacia

1.27 / 8' Lt edge AC pave — 4.7 / 6' Rt

5' Lt Ornamental Bush — 4' Rt 1" Dia Acacia

2' Rt 1" Dia peach Tree — 8' Rt 12' long Ornamental Bush

Begin AC pave 6" Rock wall border

5' Rt to Rock wall border

6' Rt to Clump ornamental Bush

7' Rt to 12" Dia Overhanging Tree evergreen Tree

End of AC paving face of 6" Rock border

Top of Rock border

2' Rt to Native calif bush 3/4 Dia

0.6 / 6' Lt — 1.3 / 6' Rt

	725.20		
29+03			
+16		5.3	719.90
+19.75		5.0	720.2
+19.8		3.9	721.3
		18.9 ±	
		4.13	721.07 = 721.1

5.6
13.3
18.9

6' Lt 7" Dia Acacia Tree

7' High Cyclone Fence

edge Conc wall edge Res

Top Wooden Roof of Res

Bottom of Res

O S & S Mon see page 25

Country Club Res. Feeder Main.

Stks For 12" A.C.

T.B.M.	11.83	690.49		678.66
26+50			10.2	680.3 676.1
+62			7.8	682.7 677.4
+75			3.9	686.6 681.7
T.P.	12.04	702.11	0.42	690.07
27+00			10.2	691.9 687.8
T.P.	11.74	713.37	0.48	701.63
27+43.40 BK				
27+38.46 AH			11.2	702.2 698.1
27+50			9.2	704.2 699.9
28+00			1.8	711.6 707.2
+12			1.5	711.9 707.8
28+41 12			1.4	712.0 708.0
28+50			1.3	712.1 708.1
T.P.	5.86	718.93	0.30	713.07
28+88			5.2	713.7 709.8
29+00			3.1	715.8 711.6
29+09			1.0	717.9 714.0
Check			6.76	712.17=712.13

West
Williams
Varonfakis X
Kellhofer |

11/22/55 Sunny

East Rim Sewer M.H 16' Rt (See Page 21)

C4 2
C5 3
C4 9
C4 1
C4 1
C4 3
C4 4
C4 1
C4 0
C4 0
C3 9
C4 2
C3 9

End Work

Sta 28+50 Page 67

Country Club Di-
12" AC Feeder Main

26+30	4' Lt to CI Pipe
26+20	4' " " " "
26+10	4' " " " "
26+00	4' Lt " " "
25+90	4' Lt " " "
25+80	4' Lt " " "
25+70	5' Lt " " "
25+59 12	5½ Lt " " "
25+50	5½ Lt " " "
25+25	3½ Lt " " "
25+00	1½ Lt " " "
24+75	2½ Lt " " "
24+50	2½ Lt " " "
24+25	2½ Lt " " "
24+00	2½ Lt " " "
23+75	3' Lt " " "
23+50	3' Lt " " "
23+00	3½ Lt " " "

22+55.23				4° Lt Kalpapa
22+50				4⁵ Lt " " "
22+40				4⁶ Lt " " "
22+30				4⁵ Lt " " "
22+20				4⁴ Lt " " "
22+10				4³ Lt " " "
22+00				4³ Lt " " "
21+90				4⁵ Lt " " "
21+80				4⁶ Lt " " "
21+70				4⁸ Lt " " "
21+60				5° Lt " " "
21+50				5° Lt " " "
21+40				5° Lt " " "
21+30				5⁵ Lt " " "
21+20				5⁵ Lt " " "
21+15.01 EC				5' Lt " " "

COUNTRY CLUB DR.
12" A.C. FEEDER MAIN

T.B.M.	11.09	391.55		380.46
T.P.	7.43	397.40	1.58	389.97
0+00			9.90	387.50
0+00 (P)			3.5	393.9 386.8
0+22 45° BEND			5.6	391.8 385.2
0+30			6.7	390.7 385.0
0+40 (L)			8.9	388.5 384.6
0+48 45° BEND			10.0	387.9 384.3
0+58 45° BEND			9.3	388.1 384.5
1+75			8.3	389.1
	2.93	388.56	11.77	385.63
			8.10	380.46 = 380.4

WEST
WILLIAMS &
VARONFAKIS
KELLHOFER &

12/7/55 WINDY & COLD

L & T. STA. 1700 B.C. (PAGE 5)

Top of 8" Jct

C7	1	H. 397.40	
C6	6	6.7	= 390.7
C5	7	7.7	389.7
C3	9	9.4	388.0
C3	1	10.6	386.8
C3	6	9.4	388.0

& ST

WATER METERS

4+22	RT.	
7+58	RT.	7354
9+25	RT.	7330
10+03	LT.	
10+71	RT.	7308
13+29	RT.	7260
14+25	RT.	7258 } NOT HIGHLINED
14+60	RT.	7252
15+30	LT.	
15+63	RT	
16+91	LT.	7330
16+95	RT	
17+68	LT.	
18+16	RT.	
18+55	RT.	

WATERS METERS (CONT.)

19+05	RT.
19+95	RT. & LT.
21+05	RT.
22+00	RT.
22+55	RT.
23+04	LT.
24+20	LT.
25+15	LT.
25+97	LT.
26+74	LT.

ASH ST.
31ST TO FERN ST.

BM 2.18	237.25	235.07		NWBP ASH & 31th
0+35 G.V. By City			231.2	
0+50			231.2	
0+75			231.2	
1+00			230.4	
1+50			228.9	
2+00			227.1	
2+50			226.2	
2+75			225.5	
3+00			224.7	
3+10 8"x6" CROSS By City			224.4	± NOT MK'D
3+10 5' Sa. G.V. By City				
3+20			224.0	
3+50			226.0	
4+00			226.9	
4+50			227.7	4+83.50
				5+02.50
5+00			228.8	
5+50			229.8	
5+53 E.H.TEE			229.8	
5+85 G.V. By City			229.6	
5+90 16"x8" REDUCER END WOEC			229.5	± NOT MK'D
			1233.01	

Lower OTAY Lake
Transit Traverse for Topo Survey

WEST
WILLIAMS
VARONFAKIS
KELLHOFER

12/29/55

1+61.25 = 42+75	109° 34' 50" Rt	To 2+39.85 ✗	
25+95 ✗	108° 53' 20" Rt.	Set Hub & Tack R.H. NAIL	30' S.E. FROM S.E. CORNER HOUSE # 1548
22+00 ✗	55° 35' 15" Rt	Set Hub & Tack R.H. NAIL	STATION ON TREE 16.5 OFF 35' S.E. FROM S.E. CORNER HOUSE # 1538
18+30 ✗	9/19/62 CAW Set PK in ℄ AC Road		
17+29 ✗	45° 41' 50" Lt	Set Hub & Tack R.H. NAIL	
15+60 ✗	67° 00' 45" Rt	Set Hub & Tack R.H. NAIL	32.7 No OF LIGHT POST Lt SIDE OIL TOP RD
11+36 ✗	DAM Dec 28, 60 (57° 28' 05") 57° 27' 20" Rt	Set Hub & Tack R.H. NAIL	13.5 Lt P.P. 181501
5+46.85 ✗	62° 21' 10" Lt	Set Hub & Tack R.H. NAIL	RC Set 2" x 2" Redwood 12,3360, CAW N. SIDE DIRT RD (6) TREE STUMP 2' DIA.
2+39.85 ✗	69° 30' 40" Rt	Lt To	℄ DAM 6' OUT FROM OTAY DAM NAME PLATE
1+61.25 ✗	11° 49' 10" Lt	Lt T	℄ Dam B.C. of Curve
0+00	East End Dam Wall West Side		Spillway Lt T Top of Wall

75

15+60
11 3C
A 24

12+29
15+60
T 29

LEVELS AT LOWER OTAY
(FOR TOPOGRAPHY)

1-19-56
SHOREY
KEMP
SMITH

BM	4.80	502.82		498.02	CHISEL MK. ON 6" I. BEAM AT LEVEL GAUGE ON DAM
TP	12.24	510.53	4.53	498.29	
TP	8.83	518.43	0.93	509.60	
TP	2.38	517.19	3.62	514.81	
TP	6.42	516.01	7.60	509.59	
TP	10.27	525.82	0.46	515.55	
TP	11.66	536.74	0.74	525.08	
CK BM	4.93	537.14	4.53	532.21	BRASS TABLET U.S.C.&G.S. SURVEY BM H-891 - 1955 IN 1" DIA. CONC. MON.
TP	0.03	524.25	12.92	524.22	
TP	3.33	516.67	10.91	513.34	
TP	0.03	504.90	11.80	504.87	
TP	0.34	492.01	13.23	491.67	
TP	0.21	479.80	12.42	479.59	
TP	0.02	466.70	13.12	466.68	
TP	0.02	453.65	13.07	453.63	
TP	0.08	440.45	13.28	440.37	
TP	0.20	427.72	12.93	427.52	
TP	0.24	414.67	13.29	414.43	
TP	0.25	401.73	13.19	401.48	
TP	2.74	395.56	9.11	392.62	

		395.56		
CK. BM			7.13	388.43 = 387.25
BM	5.27	502.11		496.84 ✓
TBM	12.02	508.53	5.60	496.51
TP	13.15	521.14	0.54	507.99
TP	13.17	534.19	0.12	521.02
TP	6.76	540.92	0.03	534.16
TBM	0.36	540.76	0.52	540.40
TP	3.36	537.23	6.89	533.87
TBM	0.69	529.73	8.19	529.04
TBM	4.72	527.12	7.33	522.40
TP	13.03	540.04	0.11	527.01
TP	8.04	547.48	0.60	539.44
TBM	6.18	549.69	3.97	543.51
TBM	3.48	542.06	11.11	538.58
CK. BM			11.01	531.05 = 531.03

1-20-56
SHOREY
KEMP
SMITH

NOTE: See Also pg 79 FOR check Levels

U.S.C.&G.S. BM. { 27' S.W. ROAD - 30' S. GATE & FENCE COR. & APPROX. 800' S.E. FILTRATION PLANT H-90 - 388

CHIS'L MK. ON 6" I. BEAM GAUGE ON DAM (ADJ. ELEV. 1.18)

HUB STA. 5+46 85 Δ PT.

HUB STA. 11+36 Δ PT.

HUB STA. 15+60 Δ PT.

HUB STA. 17+29 Δ PT.

HUB STA. 22+00 Δ PT.

HUB. STA. 25+25 Δ PT.

U.S.C.&G.S. SURVEY BM - H891 - 1955 { ADJUSTED ELEV. CORR. 1.18 SEE PG. 76
70' N. HOUSE Nº 1072½ CROWELL RD. &
30' W. OILED RD.

TIES TO TRAVERSE AT OTAY DAM LOCATION



37+05.10

34+45 △ PT. 00° 12' RT.

31+45 △ PT. 16° 48' RT.

25+95 △ PT. 7° 40' LT.

SEE PAGE 75 FOR TRAVERSE

22+00 △ PT.

MOUND WITH 4"X4" POST INTERSECTION OTAY RANCH FENCE LINE

NE COR OTAY RANCH.

April 26 1956 BEATTY SMITH

See 3150 pg 11 FB 932

△ SOUTH DAM

NAIL IN 3X3" RW POST 0.6

POST IN CONC MON SW COR JANAL RANCH

2°59'30"

33°02'20"

34+45 △ PT. 0°12' RT

TO So. DAM

CHECK LEVELS
OTAY RES
USGS BM to DAM

Beatty
West
4/23/57

BM	11.16	398.41		387.253
TP	11.17	409.38	0.20	398.21
SET TBM	1.14	408.44	2.08	407.30
CK TBM	7.72	408.44	7.72	400.72 = 400.58
TBM	13.14	420.44	1.14	407.30
TP	12.74	432.89	0.29	420.15
TP	13.07	445.91	0.05	432.84
TP	12.39	457.97	0.33	445.58
TP	13.29	471.17	0.09	457.88
TP	13.02	483.93	0.26	470.91
TP	13.05	496.77	0.21	483.72
TBM	12.89	508.50	1.16	495.61
TP	12.97	521.28	0.19	508.31
TP	12.66	533.13	0.81	520 47
TP	11.10	541.18	3.05	530.08
TP	0.48	541.46	0.20	540.98
TP	0.12	528.68	12.90	528.56
TP	0.01	515.64	13.05	515.63
TP	5.80	508.48	12.96	502.68
CK BM on Dam.			11.72	496.76 = 498.02

496.81 FB 281-69
496.84 pg. 77

USGS BM H 80 - 388 - 1938

— P.P. 81011 Junct. of roads Spike in Pole
— CH13 □ NE Cor CHLOR LOADING PLATFORM FB 281-74

— NW Cor Conc Stove platform

= 531.35 (Mike)
= 542.26 (Mike)

498.02
496.76
diff 1.26

496.36
5.61
.75



DISTANCES FROM SIDE STAKES FOR CROSS-SECTIONING.

SLOPE 1½ TO 1. ROADWAY OF ANY WIDTH.

	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	
0	0.00	0.15	0.30	0.45	0.60	0.75	0.90	1.05	1.20	1.35	0
1	1.50	1.65	1.80	1.95	2.10	2.25	2.40	2.55	2.70	2.85	1
2	3.00	3.15	3.30	3.45	3.60	3.75	3.90	4.05	4.20	4.35	2
3	4.50	4.65	4.80	4.95	5.10	5.25	5.40	5.55	5.70	5.85	3
4	6.00	6.15	6.30	6.45	6.60	6.75	6.90	7.05	7.20	7.35	4
5	7.50	7.65	7.80	7.95	8.10	8.25	8.40	8.55	8.70	8.85	5
6	9.00	9.15	9.30	9.45	9.60	9.75	9.90	10.05	10.20	10.35	6
7	10.50	10.65	10.80	10.95	11.10	11.25	11.40	11.55	11.70	11.85	7
8	12.00	12.15	12.30	12.45	12.60	12.75	12.90	13.05	13.20	13.35	8
9	13.50	13.65	13.80	13.95	14.10	14.25	14.40	14.55	14.70	14.85	9
10	15.00	15.15	15.30	15.45	15.60	15.75	15.90	16.05	16.20	16.35	10
11	16.50	16.65	16.80	16.95	17.10	17.25	17.40	17.55	17.70	17.85	11
12	18.00	18.15	18.30	18.45	18.60	18.75	18.90	19.05	19.20	19.35	12
13	19.50	19.65	19.80	19.95	20.10	20.25	20.40	20.55	20.70	20.85	13
14	21.00	21.15	21.30	21.45	21.60	21.75	21.90	22.05	22.20	22.35	14
15	22.50	22.65	22.80	22.95	23.10	23.25	23.40	23.55	23.70	23.85	15
16	24.00	24.15	24.30	24.45	24.60	24.75	24.90	25.05	25.20	25.35	16
17	25.50	25.65	25.80	25.95	26.10	26.25	26.40	26.55	26.70	26.85	17
18	27.00	27.15	27.30	27.45	27.60	27.75	27.90	28.05	28.20	28.35	18
19	28.50	28.65	28.80	28.95	29.10	29.25	29.40	29.55	29.70	29.85	19
20	30.00	30.15	30.30	30.45	30.60	30.75	30.90	31.05	31.20	31.35	20
21	31.50	31.65	31.80	31.95	32.10	32.25	32.40	32.55	32.70	32.85	21
22	33.00	33.15	33.30	33.45	33.60	33.75	33.90	34.05	34.20	34.35	22
23	34.50	34.65	34.80	34.95	35.10	35.25	35.40	35.55	35.70	35.85	23
24	36.00	36.15	36.30	36.45	36.60	36.75	36.90	37.05	37.20	37.35	24
25	37.50	37.65	37.80	37.95	38.10	38.25	38.40	38.55	38.70	38.85	25
26	39.00	39.15	39.30	39.45	39.60	39.75	39.90	40.05	40.20	40.35	26
27	40.50	40.65	40.80	40.95	41.10	41.25	41.40	41.55	41.70	41.85	27
28	42.00	42.15	42.30	42.45	42.60	42.75	42.90	43.05	43.20	43.35	28
29	43.50	43.65	43.80	43.95	44.10	44.25	44.40	44.55	44.70	44.85	29
30	45.00	45.15	45.30	45.45	45.60	45.75	45.90	46.05	46.20	46.35	30
31	46.50	46.65	46.80	46.95	47.10	47.25	47.40	47.55	47.70	47.85	31
32	48.00	48.15	48.30	48.45	48.60	48.75	48.90	49.05	49.20	49.35	32
33	49.50	49.65	49.80	49.95	50.10	50.25	50.40	50.55	50.70	50.85	33
34	51.00	51.15	51.30	51.45	51.60	51.75	51.90	52.05	52.20	52.35	34
35	52.50	52.65	52.80	52.95	53.10	53.25	53.40	53.55	53.70	53.85	35
36	54.00	54.15	54.30	54.45	54.60	54.75	54.90	55.05	55.20	55.35	36
37	55.50	55.65	55.80	55.95	56.10	56.25	56.40	56.55	56.70	56.85	37
38	57.00	57.15	57.30	57.45	57.60	57.75	57.90	58.05	58.20	58.35	38
39	58.50	58.65	58.80	58.95	59.10	59.25	59.40	59.55	59.70	59.85	39
40	60.00	60.15	60.30	60.45	60.60	60.75	60.90	61.05	61.20	61.35	40
41	61.50	61.65	61.80	61.95	62.10	62.25	62.40	62.55	62.70	62.85	41
42	63.00	63.15	63.30	63.45	63.60	63.75	63.90	64.05	64.20	64.35	42
43	64.50	64.65	64.80	64.95	65.10	65.25	65.40	65.55	65.70	65.85	43
44	66.00	66.15	66.30	66.45	66.60	66.75	66.90	67.05	67.20	67.35	44
45	67.50	67.65	67.80	67.95	68.10	68.25	68.40	68.55	68.70	68.85	45
46	69.00	69.15	69.30	69.45	69.60	69.75	69.90	70.05	70.20	70.35	46
47	70.50	70.65	70.80	70.95	71.10	71.20	71.40	71.55	71.70	71.85	47
48	72.00	72.15	72.30	72.45	72.60	72.75	72.90	73.05	73.20	73.35	48
49	73.50	73.65	73.80	73.95	74.10	74.25	74.40	74.55	74.70	74.85	49
50	75.00	75.15	75.30	75.45	75.60	75.75	75.90	76.05	76.20	76.35	50

THE NATIONAL BLANK BOOK COMPANY
HOLYOKE MASSACHUSETTS
NEW YORK CHICAGO BOSTON SAN FRANCISCO